From measured attenuation to a wet-antenna law

Research log: what has been implemented, where we stand, and what comes next

Yonatan Haber and Yehonatan Tsitseluk

CellEnMon lab, final-year electrical engineering project

Data-driven discovery of rain-induced and wet-antenna attenuation laws in commercial microwave links

12 October 2026

Abstract

This report describes the research part of the project at the level of ideas: what each step does, why it is done that way, and what it found. It contains no code. Two things are finished and frozen. First, a *baseline* for every link and rain event, which turns the raw signal levels into the attenuation $A(t)$; it is unbiased, accurate to about ± 0.2 dB per event, and it does not absorb the drying of the antenna after rain. Second, a fixed set of *drying tails*: 429 stretches of $A(t)$ after the rain has stopped on a link, in which the remaining attenuation is mostly wet-antenna attenuation (WAA). A third piece is finished for the drying law: the tools were tested on simulated tails whose true law is known. A fit of one tail at a time cannot tell the candidate laws apart; a fit of all tails together can. SINDy applied directly to the tails failed: it returned a linear law for almost every truth. It was replaced by two jumps. The pooled fit first draws a free drying curve from all tails, and sparse regression then names the equation of that clean curve. On simulated data this recovers an exponential and a quadratic law for W above 0.35 dB in the first hour, and the result was confirmed on fresh data with the rule fixed in advance. Three additions failed their tests and will not be used: a curve that may contain a step, a choice between laws by held-out likelihood, and an uncertainty band from resampling one data set. The tools that passed were then applied to the real tails for the first time. They did *not* identify a drying law: the drying rate per dB of water falls as W grows, a shape that none of the candidate laws has, because about one tail in five stays flat or rises after the rain has stopped. Without the events in which this is common, the tails are close to an exponential with a time constant of about 15 minutes. Which tails count as drying has to be decided before the next step. Still to come are the drying law itself, the wetting law from very short links, the verification on unseen events, and then the two later stages of the project: the path law $f(L, \bar{R}, Z)$ and the rain estimate.

Contents

1 Scope and status at a glance **4**

1.1 What this report covers 4

1.2 Status 4

2 The problem in equations **5**

2.1 What a link measures 5

2.2 Rain along the path 5

2.3 Wet-antenna attenuation, and why it comes first 6

2.4 Three rules that shape every step 6

3 What the data layer provides **6**

4 Step 1: the baseline and $A(t)$ (done, frozen) **7**

4.1 The idea and the main risk . . . 7
4.2 The method . . . 7
4.3 How a baseline is validated when the truth is unknown . . . 8
4.4 Does the baseline absorb the drying? . . . 8
4.5 What disturbs the signal in dry weather . . . 9
4.6 What the baseline hands to the next step . . . 9

5 Stage 1, part 1: the drying tails (done, frozen) **10**

5.1 The idea . . . 10
5.2 Extracting every tail, with no selection . . . 10
5.3 Selection by rules fixed in advance . . . 11
5.4 A lesson: the "fast drop" . . . 11
5.5 The frozen tail set v1 . . . 11
5.6 What the tails look like . . . 12

6 Stage 1, part 2: testing the tools on simulated tails (done for drying) **13**

6.1 Why simulate . . . 13
6.2 The candidate drying laws . . . 14
6.3 The simulator . . . 15
6.4 Fitting one tail at a time: not enough . . . 16
6.5 Fitting all tails together: works on simulated data . . . 18
6.6 Stress test of the pooled fit: partly passed . . . 19
6.7 SINDy directly on the tails: failed . . . 20
6.8 Two jumps: draw the drying curve, then name it . . . 21
6.9 The rest of the method, and a false step . . . 22

7 The first fit of the real tails **23**

7.1 What was done . . . 23
7.2 What was found . . . 23
7.3 How we read it . . . 24

8 Where we stand **25**

9 What comes next **26**

9.1 The target of Stage 1 . . . 26
9.2 The steps . . . 26

9.3 After Stage 1 27
9.4 Open questions 27

References **28**

A Glossary **29**

B Where the details are **29**

1 Scope and status at a glance

1.1 What this report covers

The report covers the research folder of the repository as it stood on 12 October 2026: the baseline module and the WAA module. The data layer below it (the pipeline that turns the raw OpenMRG files into a verified data set) has its own technical report and is summarised here in one page (Section 3). Every number in this report is taken from the documents the two modules keep: their method descriptions, their decision logs and their step reports (Appendix B). Unless stated otherwise, the numbers are for the *training* events and *training* links only; the validation set is built by the same rules but has not been looked at, and the test set has not been touched.

References in square brackets are those of the project proposal and are listed at the end.

1.2 Status

Figure 1 shows the whole project and Table 1 the steps inside it.




Figure 1: The project, and the inside of Stage 1. Thick solid border with grey fill: done. Thick dashed border: in progress. Dotted border: planned.

Table 1: Steps of the research part and their state on 12 October 2026.

Step	What it is	State	Section
Baseline	Dry-weather level per (event, sub-link); $A(t)$	done, frozen 7 Oct	4
WAA 0–1	Inventory; extract every drying tail (20 355)	done	5
WAA 2, 2b, 2c	Selection by fixed rules; frozen tail set v1 (429 train, 123 validation)	done, frozen 8 Oct	5
WAA 3a	Simulator of tails, calibrated to the real set	done	6.3
WAA 3b-1	Fit one tail at a time, on simulated tails	done: not enough	6.4
WAA 3b-1b	Fit all tails together, on simulated tails	done: works	6.5
WAA 3b-1c	Stress test of that fit	done: partly passed	6.6
WAA 3b-2	SINDy directly on simulated tails	done: failed	6.7
WAA 3b-3, 3b-3b	Two jumps: draw the drying curve, then name its equation	done: partly passed	6.8
WAA 3b-3c, 3b-4	The rest of the discovery method; the cause of a false step	done: partly passed	6.9
WAA 4	Drying law $h(W)$ on the real tails, first fit	done: no law identified	7
WAA 6	What the drying depends on	not started	9
WAA 3c, 7	Simulator of whole events; wetting law $g(R, W)$ from very short links	not started	9
WAA 8–9	Verification; final WAA equation	not started	9
Stage 2	Path law $f(L, \bar{R}, Z)$ with symbolic regression	not started	9
Evaluation	Rain estimate, comparison with the literature	not started	9

2 The problem in equations

2.1 What a link measures

A commercial microwave link (CML) sends a signal from one mast to another. The network records the transmitted signal level (TSL) and the received signal level (RSL). Their difference is the total loss $\mathrm{TL}(t) = \mathrm{TSL}(t) - \mathrm{RSL}(t)$. Most of it is always there (free-space loss, cables, antennas). What is always there is called the *baseline*, and the *attenuation* is what is left above it:

$$A(t) \;=\; \mathrm{TSL}(t) - \mathrm{RSL}(t) - \mathrm{baseline} \;=\; A_{\mathrm{rain}}(t) + \delta(t). \tag{1}$$

A_{rain} is the loss caused by rain along the path. $\delta(t)$ collects everything else, mainly wet-antenna attenuation and whatever error is left in the baseline.

2.2 Rain along the path

Every short piece dx of the path attenuates the signal by $a\,R(x,t)^b\,dx$, where $R(x,t)$ is the local rain rate and a, b depend on the frequency and polarisation. The link sums all pieces:

$$A_{\mathrm{rain}}(t) \;=\; \int_0^L a\,R(x,t)^b\,dx \;\approx\; a\,\bar{R}(t)^b\,L, \tag{2}$$

with L the path length and $\bar{R}$ the mean rain rate along the path. The approximation is exact only when the rain is uniform along the path. The project replaces it by a more general form,

$$A_{\mathrm{rain}}(t) \;=\; a\,\bar{R}(t)^b\,f(L, \bar{R}, Z), \tag{3}$$

where f is a correction function to be found from data and Z stands for properties of the path and the link (non-uniform rain, frequency, polarisation, time resolution). Uniform rain gives $f = L$.

2.3 Wet-antenna attenuation, and why it comes first

Water collects on the antenna covers during rain and dries afterwards. This adds an attenuation $W(t)$, the WAA. It differs from A_{rain} in two ways: it is local (it happens at the two antennas, so it does not grow with L), and it has memory (it stays after the rain has stopped).

WAA has to be removed before f is learned. Suppose the WAA were a constant W. Then

$$A = a\bar{R}^b L + W \quad \Longrightarrow \quad \frac{A}{a\bar{R}^b} = L + \underbrace{\frac{W}{a\bar{R}^b}}_{L_0}, \tag{4}$$

so a constant WAA looks exactly like a path that is longer by L_0. A method that learns f from A would return $f = L + L_0$ and report a length dependence that is not there. This fixes the order of the work (Figure 2): baseline, then WAA, then f.




Figure 2: The order of the work. An error in an early block is passed on to every later block, which is why each block is validated and frozen before the next one starts.

2.4 Three rules that shape every step

1. **No circular selection.** Links or events are never chosen by how well a model fits them. Choosing the links where the power law works, and then concluding that the power law works, would prove nothing. Every selection rule in this report is fixed before the result is seen and never looks at the shape of the curve.
2. **Readable equations.** The aim is an explicit law that can be checked against the physics (a *gray-box* model), not only a good prediction. A neural network [11] is used later only as a reference for performance.
3. **Rain is defined by the references, never by the link.** Whether it rains on a link is decided from the weather radar along the path and from the rain gauges. The link's own signal is never used for that, because the signal is the thing being explained.

3 What the data layer provides

The research uses the OpenMRG data set [13]: three summer months (June to August 2015) of 364 two-way links (728 sub-links, one per direction) around Gothenburg, with ten city rain gauges, one national gauge with weather data, and a weather-radar composite. The points that matter for the research are these.

- **Resolution.** The links are sampled every 10 s. RSL is recorded in steps of 0.3 dB and TSL in steps of 1 dB. This *quantization* is the size of the effects studied here, so it appears in almost every section.

- **Rain reference.** The radar gives the rain rate every 5 minutes on a 2 km grid; the data layer averages it along each link path to get $\bar{R}$. The radar is preferred over a single gauge because it sees the whole path.
- **Rain events.** 89 rain events and 62 long dry periods are defined from the radar and the gauges only.
- **Reference state of each link.** Every 5 minutes each link is labelled *wet* (radar on the path or a gauge within 1 km shows at least 0.1 mm/h), *dry* (no rain at all on the path in that bin and for 30 minutes on either side), or *unknown* (anything in between, or radar missing). Unknown never counts as dry.
- **Split.** Events are divided into training, validation and test sets (60 / 20 / 20 %), and links into training and test (80 / 20 %). The split is frozen. The training set has 283 links (566 sub-links).

4 Step 1: the baseline and $A(t)$ (done, frozen)

4.1 The idea and the main risk

The baseline is the total loss a sub-link would show if it were not raining. It cannot be measured during rain, so it has to be estimated from dry time. The main risk is specific to this project. After the rain stops, the antenna is still wet and the signal returns slowly. If the baseline is estimated from that period, or is allowed to move during the event, it follows the slow return and the wet-antenna attenuation disappears into the baseline, which is exactly the signal Stage 1 needs. The baseline must therefore be blind to everything that happens after the event starts.

4.2 The method

For each pair of a rain event e and a sub-link s, the baseline is one number: the median of the total loss over the usable dry time in the 24 hours before the event starts,

$$\begin{aligned} B_{e,s} &= \operatorname{median}\{\, \mathrm{TL}_s(t) \;:\; t \in [\, t_{\mathrm{start}}(e) - 24\,\mathrm{h},\; t_{\mathrm{start}}(e)\,),\; t \text{ usable} \,\}, \\ A_s(t) &= \mathrm{TL}_s(t) - B_{e,s}. \end{aligned} \tag{5}$$

A 5-minute slot is *usable* if the link's reference state is dry and at least one hour has passed since the link was last wet (so that the drying of an earlier shower is kept out). If the 24-hour window holds less than one hour of usable time, a 48-hour window is used; if that fails too, the pair gets no baseline rather than a guess. This happens for 2.9 % of the pairs, almost all of them in the first events of the season, which have no history before them. Figure 3 shows the construction.




Figure 3: The baseline of one event on one sub-link. Only dry time before the event is used, so the baseline cannot follow the drying tail. Hatched: rain according to the references.

A first version of the method (v1) used the mean over 6 hours before the event, and in some cases a sloping line from the level before the event to the level after it. The frozen version (v2) differs in three choices, each one decided by the validation below: a longer window (24 h), the median instead of the mean, and a flat baseline only. The sloping line was dropped because the cases where it applied did not look like drying; they looked like changes of level that have nothing to do with the rain.

4.3 How a baseline is validated when the truth is unknown

There is no "true" baseline to compare with during rain. The idea of the validation is to create cases where the truth *is* known. In certified dry weather the attenuation is zero by definition. So we place *fake events* in dry periods: we pretend that an event of duration D starts at a random dry moment, compute the baseline exactly as for a real event, and measure what the method reports during the fake event. Anything other than zero is baseline error. The error of one fake event is its *offset*,

$$\text{offset} \;=\; \frac{1}{D}\int_{\text{fake event}} \big(\text{TL}(t) - B\big)\, dt, \qquad \text{truth} = 0. \tag{6}$$

This was done for 513 good training sub-links, six durations from 1 to 40 hours and 20 fake events each: 61 560 fake events. Table 2 gives the result.

Table 2: Baseline error on fake events in dry weather (truth: zero). "90 % within" is the 90th percentile of |offset|. The summer median is the simplest possible baseline (one number per sub-link for the whole season).

	Duration D of the fake event					
90 % of offsets within (dB)	1 h	3 h	6 h	12 h	24 h	40 h
Summer median	0.43		0.40		0.34	
v1: 6 h mean before the event	0.29	0.31	0.34	0.36	0.30	0.38
v2: 24 h median before the event	0.33	0.32	0.31	0.28	0.28	0.29
v2: median offset	0.00	0.00	0.00	0.00	+0.02	+0.05

What the table says:

- The baseline is **unbiased**: the median offset is zero.
- Its **spread is about** ±0.2 dB (10th to 90th percentile), and 90 % of the errors are below about 0.3 dB. That is one RSL quantization step: the baseline is about as accurate as the instrument allows.
- The short window (v1) is slightly better for events of 1 to 3 hours, the long window (v2) is better from 6 hours on. Real significant events last several hours, so v2 was chosen.

4.4 Does the baseline absorb the drying?

This is the check the proposal asks for. After each real event we measure how far the signal is above the baseline k hours after the link's last wet moment, and compare with the same quantity after fake events (the control, where nothing dries). If the baseline had swallowed the drying, the real and the control curves would be equal at all k. Figure 4 shows a small excess after real rain (+0.04 dB above the control one hour after the rain) that shrinks to zero by 12 hours. The drying signal stays in $A(t)$, as intended. The excess is small in the median because most (event, sub-link) pairs have little rain; the strong cases are selected in Section 5.




Figure 4: Level after the rain minus the baseline, against the time since the link's last wet moment. Circles, solid line: real events. Squares, dashed line: control (fake events in dry weather). Bands: 10th to 90th percentile.

4.5 What disturbs the signal in dry weather

The validation also showed what the baseline cannot remove, because it happens with no rain at all:

- **A daily cycle.** The dry-weather loss of a sub-link moves over the day, by 0.15 dB for the median sub-link but by more than 0.4 dB for 14 % of them. Those sub-links have about twice the baseline error.
- **Dew.** Jumps of 1 dB or more in dry weather happen mostly at night in humid air (a third of them at relative humidity $\geq 90\,\%$, against 5 % of all dry time), usually in both directions of a link and on neighbouring links at once. This is most likely dew on the antennas: wet-antenna attenuation without rain. An hour is marked "at dew risk" when the humidity is at least 90 % or the air is within 2 °C of its dew point.

These are not corrected. Instead each (event, sub-link) pair carries *flags* (baseline far from the usual dry level, large daily cycle, dew risk, degraded link), and the pairs with a serious flag are left out of the main WAA analysis. One tested idea was rejected by a rule fixed before the run: leaving the dew-risk hours out of the baseline window did not improve the error, so it was not adopted.

4.6 What the baseline hands to the next step

- One baseline per (event, sub-link), for training and validation events on training links, with its flags. $A(t)$ follows from Eq. (5).
- One number per sub-link, σ_{off}: the spread of its baseline error on fake events. It says how far $A(t)$ of that sub-link may sit from zero for no physical reason, and it is used later as prior knowledge when laws are fitted (Section 6.5).

In short. The baseline is the median dry level of the 24 hours before each event, held flat. It is unbiased, accurate to about one quantization step, and blind to the drying after the rain. Frozen on 7 October 2026.

5 Stage 1, part 1: the drying tails (done, frozen)

5.1 The idea

During rain, $A(t)$ is the sum of two unknowns, $A_{\text{rain}}(t)$ and $W(t)$, and they cannot be separated without assuming a model for one of them. After the rain has stopped on a link, the path term is zero:

$$R(x,t) = 0 \text{ on the path} \implies A_{\text{rain}}(t) = 0 \implies A(t) = W(t) + \text{baseline error} + \text{noise}. \quad (7)$$

The stretch of $A(t)$ after the rain is called a *drying tail*. In it we observe the WAA almost directly, with no assumption about the power law. Figure 5 shows the picture. The tails show only how the antenna *dries*; how it *gets wet* has to be learned later from data during the rain (Section 9).




Figure 5: Sketch of one event on one link (not real data). During the rain the measured attenuation is the sum of the path term and the hidden WAA. After the last trace of rain, at t_{trace}, only the WAA is left and it decays as the antenna dries. Hatched bar: rain on the path according to the references. Dotted bar: only a trace of rain, below the threshold that makes a bin wet.

5.2 Extracting every tail, with no selection

The first step cuts one tail for every (event, sub-link) pair that has a baseline and had rain, using the reference state of the link only:

- **Start** t_0: the end of the link's last wet bin in the event.
- **End**: the first of (a) the next wet bin of the link, (b) a gap of 15 minutes or more in the data, (c) $t_0 + 12$ hours. The end never looks at the value of A, so a tail is not forced to reach zero.

This gives 20 355 tails on 566 sub-links from 69 events (15 370 from training events). Nothing is selected and nothing is fitted at this point. A first descriptive result already shows that the memory exists: of the tails that start above 2 dB, only 25 % are back at their dry level after 10 minutes and 79 % after 3 hours, while tails that start below 0.5 dB are back within 10 minutes in 94 % of the cases.

5.3 Selection by rules fixed in advance

Most of the 20 355 tails are too weak or too disturbed to say anything about drying. The selection uses only rules that are fixed before the result is seen and that never look at the shape of the decay:

- **Exclude** pairs with a flagged baseline, sub-links that are not of good quality, sub-links whose dry-weather baseline error σ_{off} exceeds 0.3 dB (one RSL step), and tails with more than 10 % of missing minutes.
- **Shorten** a tail when something other than drying starts: a step in the transmitted power, or a sustained rise of A (below).
- **Main set**: the tail starts at $A_{\text{start}} \geq 1$ dB and has at least 60 usable minutes. A larger *alternative set* uses $A_{\text{start}} \geq 0.6$ dB and serves as a sensitivity check.
- **Control set**: tails that start below 0.5 dB. They show what a tail looks like when there is nothing to dry, and are used to measure the noise (Section 6.3).

5.4 A lesson: the "fast drop"

The first selection produced 959 main tails, and they showed a striking feature: within the first half hour (the margin between the last wet bin and the first certified dry bin) the attenuation fell by a median of 1.1 dB, which is 83 % of its starting value. It was tempting to read this as a fast drying of the antenna. Two checks said otherwise.

- The drop did not grow with the link length L, which would point to the antenna and not to the path. But the comparison quantity, the attenuation during the rain, barely grew with L either (rank correlation 0.13), so this test had little power to decide.
- Looking at the references more closely showed that in this margin the radar or a gauge often still reported a *trace* of rain, below the threshold that makes a bin "wet". When the start of the tail was moved to the end of the last trace, 381 of the 959 tails no longer started above 1 dB.

So much of the fast drop was light rain ending, not the antenna drying. The consequence is the stricter start used from then on, and a clear statement of what is and is not shown: the tails are a clean place to study drying, but the proof that what dries is the antenna and not residual path rain is left to the test with very short links (Section 9), where the contrast in L is large enough.

5.5 The frozen tail set v1

The final rules are:

- **Start** t_{trace}: the end of the last 5-minute bin with any trace of rain (radar above zero on the path, a gauge within 1 km above zero, or radar missing, which counts as "unknown, so possibly rain"). A_{start} is the mean of A over the first 5 minutes from t_{trace}.
- **End**: the first of the ends listed above, the first new trace of rain, and the *rise cut*: if A (smoothed over 10 minutes) rises 0.6 dB above its lowest value so far and stays there for 10 minutes, the tail ends just before the rise began. A drying antenna does not get wetter, so a sustained rise means something else has started.

Figure 6 shows how many tails each stage leaves, and Table 3 the frozen set.




Figure 6: From all tails to the frozen set. No stage looks at how the tail decays.

Table 3: The frozen tail set v1 (8 October 2026).

Set	Tails	Sub-links	Links	Events
Main, training	429	249	159	24
Main, validation (not looked at)	123	96	76	9
Alternative ($A_{\mathrm{start}} \geq 0.6\,\mathrm{dB}$), training	1 155	368	212	34
Alternative, validation (not looked at)	458	263	170	12

5.6 What the tails look like

Figure 7 shows the median of the 429 tails. It starts near 1.5 dB, loses half of its value in about 15 minutes, is at about a quarter after 30 minutes, and then slows down: about 14 % is left after one hour and 5 % after three hours. The control tails stay at zero. The shape is *fast at first, slow later*, and the central question of the next section is what kind of law produces it.




Figure 7: Median of the drying tails, each aligned at its own start. Solid: frozen set v1. Dashed: the set before the last two rules. Dash-dot: control tails. Top: linear scale; bottom: logarithmic scale, on which a single exponential would be a straight line.

Two properties of the set limit what can be concluded from it and are carried into every later step:

- **Three events hold 246 of the 429 tails.** Tails of one event share the same weather, so they are not independent. All uncertainties are therefore computed by resampling whole *events*, not single tails.
- **Some rises are unexplained.** In one night event the attenuation rises by 0.5 to 1 dB right after the rain with no trace in radar or gauges, then decays. It may be drizzle below the radar beam or condensation on the wet covers. The humidity record is missing for those hours, so the data cannot decide; the rise cut removes these stretches, and nine such events are flagged so that results can be recomputed without them.

In short. 429 drying tails, selected by rules that never look at the decay, are the frozen input of the WAA model. The median tail halves in about 15 minutes and then has a slow remainder lasting hours. Whether the fast early part is the antenna or the last light rain is not settled by the tails alone.

6 Stage 1, part 2: testing the tools on simulated tails (done for drying)

6.1 Why simulate

The law itself will be learned from real measurements only. But before a fitting method is trusted on real tails, we need to know what it can and cannot tell us. On real data that question has no answer, because the true law is unknown. On simulated data it has: we generate tails from a law we choose, pass them through the same distortions as the real measurements, apply the method,

and see whether it returns the law we put in. This is the same idea as the fake events of the baseline: build a case where the truth is known.

The simulated tails are not invented from scratch. Each one copies a real tail of the frozen set: the same sub-link, the same event, the same length, the same starting level, the same missing minutes. Only the decay and the noise are generated.

6.2 The candidate drying laws

Five laws are used, each a different physical picture of how the water leaves the antenna (Table 4, Figure 8). All start from $W(0) = A_{\text{start}}$ at the start of the tail.

Table 4: The candidate drying laws. W in dB, t in minutes since the start of the tail. The label mn is used when the law generates data (the truth) and Fn when it is fitted to data (the candidate).

Law	Equation	Picture
m1 / F1	$\dfrac{dW}{dt} = -\dfrac{W}{\tau}$	One time constant: exponential drying, the form used in the literature.
m3 / F3	$\dfrac{dW}{dt} = -c\,W^n$	Drying speeds up when the antenna is wetter ($n > 1$); $n = 2$ as truth.
m4 / F4	$W = W_f + W_s,\quad \dfrac{dW_f}{dt} = -\dfrac{W_f}{\tau_f},\quad \dfrac{dW_s}{dt} = -\dfrac{W_s}{\tau_s}$	Two layers of water: a fast one and a slow one that holds a share φ at the start.
m5 / F5	$\dfrac{dW}{dt} = -a\,W - b\,W^2$	A linear and a quadratic term together.
m6 / F6	$\dfrac{dW}{dt} = \begin{cases} -k_{\text{run}}(W - A_c) - k_{\text{evap}}W, & W > A_c \\ -k_{\text{evap}}W, & W \le A_c \end{cases}$	A switch: above a film level A_c water runs off quickly; below it only slow evaporation is left.




Figure 8: The five laws with the parameters calibrated to the real median tail, for a tail that starts at 1.5 dB, before any tail-to-tail spread or noise is added. On this logarithmic scale the exponential is a straight line; the others bend, and they lie almost on top of each other, which is why they are hard to tell apart. The laws were calibrated together with a spread (Section 6.3), so a single curve is not expected to match the real median by itself.

6.3 The simulator

Tail-to-tail spread

Real tails do not all dry at the same speed: antennas differ, and so do wind, sun and temperature. The simulator gives each tail its own speed by stretching time,

$$W_i(t) = W\left(\frac{t}{f_i}\right), \qquad f_i = e^{\,s\,z_i}, \qquad z_i = \tfrac{1}{\sqrt{2}}\,z_{\text{link}} + \tfrac{1}{\sqrt{2}}\,z_{\text{tail}}, \quad z \sim \mathcal{N}(0,1), \tag{8}$$

so half of the variation belongs to the link (it is the same in all its tails) and half to the single tail. The width s is set so that the band between the 10th and 90th percentile of the simulated tails matches the real band; this gives $s = 1.25$ for every law, i.e. individual tails dry between 5 times faster and 5 times slower than the median.

The measurement chain

A real tail is not $W(t)$; it is $W(t)$ seen through the instrument. The simulator applies the same chain (Figure 9):

$$x(t) = W_i(t) + c_i + n_{\text{slow}}(t) + \sigma_w\,\varepsilon(t), \qquad A(t) = \text{1-minute mean of } \; Q_{0.3\,\text{dB}}\big[x(t)\big], \tag{9}$$

with $c_i \sim \mathcal{N}(0, \sigma^2_{\text{off}})$ a constant baseline error of that tail (from the baseline validation), n_{slow} a slowly wandering noise, ε white noise on the 10-second samples, and Q the rounding of RSL to steps of 0.3 dB.




Figure 9: The simulator: a known law seen through the measurement chain. Each block can be switched off to see which distortion hides what.

Getting the noise right

The first version of the simulator had only white noise. Compared with the real control tails (which contain noise and no drying), it was far too quiet over a whole tail: the spread within a tail was 0.05 dB simulated against 0.14 dB real. Real dry-weather noise is correlated in time: it wanders. A simulator without that would have made the laws look much easier to tell apart than they are. The noise model was therefore extended with a slow component (a first-order autoregressive process with its own strength and correlation time), fitted per sub-link to five properties of its control tails. After the change all five agree (Table 5).

Table 5: Real dry-weather noise against the simulated noise (medians over sub-links). The typical fitted noise is a white part of 0.09 dB, a slow part of 0.15 dB and a correlation time of 80 minutes.

Property of a control tail	Real	Simulated
Spread within the tail (dB)	0.141	0.134
Share of minutes exactly on a 0.3 dB level	0.25	0.27
Correlation between minutes 1 minute apart	0.80	0.80
Correlation between minutes 10 minutes apart	0.57	0.63
Correlation between minutes 60 minutes apart	0.22	0.23

Calibrating the laws, and a second lesson

Each law's parameters were set so that its simulated median tail matches the real one (Table 6, Figure 10).

Table 6: Calibrated laws (times in minutes) and how far the simulated median and band are from the real ones (root mean square difference of A/A_{start} over the first 6 hours, after the full measurement chain).

Law	Calibrated parameters	Misfit of the median	Misfit of the band
m1 exponential	$\tau = 29.8$	0.026	0.062
m3 power	$c = 0.053$, $n = 2$	0.044	0.072
m4 two layers	$\tau_f = 18.7$, $\tau_s = 193$, $\varphi = 0.17$	0.033	0.062
m5 linear + quadratic	$a = 0.0030$, $b = 0.045$	0.038	0.069

The important result is in the first row of the table. Before the spread was added, the plain exponential could not produce the slow remainder of the real median, and two layers fitted best; it looked as if the data asked for two layers. With the spread, the noise, the offsets and the real tail lengths included, **a plain exponential reproduces the slow remainder as well as two layers do**. A population of antennas that each dry exponentially but at different speeds looks, in the median, like one antenna with a fast and a slow layer. The shape of the median curve therefore cannot decide between the laws; the decision has to come from the individual tails.

6.4 Fitting one tail at a time: not enough

The natural first method fits every candidate to every tail separately, each with its own start and its own constant offset, and picks the candidate with the best score. The score is the Bayesian information criterion (BIC), which rewards a good fit and charges for every extra parameter. Because the noise wanders, neighbouring minutes are not independent, and a tail of n minutes carries less information than n independent values. This is accounted for by an effective sample size:

$$n_{\mathrm{eff}} = n\,\frac{1-\rho}{1+\rho}, \qquad \mathrm{BIC} = n_{\mathrm{eff}}\,\ln\frac{\mathrm{RSS}}{n} + k\,\ln n_{\mathrm{eff}}, \tag{10}$$

where ρ is the correlation between neighbouring residuals, RSS the sum of squared residuals and k the number of parameters. A typical tail has $n = 210$ minutes but only $n_{\mathrm{eff}} \approx 64$.

Applied to simulated data sets with each of the five laws as the truth (ten data sets per law), the result was negative, and clearly so:

- **Per tail, nothing can be identified.** The exponential wins 60 to 80 % of the tails whatever the true law is. One noisy, quantized tail that starts near 1.5 dB does not contain enough information.
- **Per data set** (scores summed over all tails), only one question can be answered: *single exponential or not.* When the truth is exponential, the exponential wins every time. When the truth is any of the other four laws, the two-layer candidate wins. So if two layers won on real data, it would mean "not a single exponential", and not "two layers".
- The slow time constant of the two-layer law cannot be recovered: the fit trades it against the free offset.
- Switching the distortions off one at a time showed that no single one is to blame. Noise alone, or quantization alone, is enough to hide the small slow layer.




Figure 10: Real tails against simulated tails, one row per law (m1, m3, m4, m5). Solid line and hatched band: real median and 10–90 % band. Dashed and dotted lines: the same for the simulated tails. Columns: first 90 minutes (linear, logarithmic), first 6 hours (linear, logarithmic). All four laws reproduce the real median and band about equally well.

6.5 Fitting all tails together: works on simulated data

The weakness of the per-tail fit is that every tail gets its own free parameters and no tail informs another. But the question is not "what is the law of this tail"; it is "what is the one law that all antennas follow". The second method asks exactly that. One candidate law with one set of parameters θ is fitted to the whole data set at once:

$$A_i(t) \;=\; W\!\left(\frac{t}{f_i};\ \theta,\ W_{0,i}\right) + c_i + e_i(t). \tag{11}$$

The pieces, and what each one fixes compared with the per-tail fit:

- θ: the law's parameters, **shared by all tails**. This is where the information is pooled.
- $W_{0,i}$: the start of tail i, free.
- $f_i = e^{\,s(u_{\text{link}}+v_{\text{tail}})}$: the speed of tail i, as in Eq. (8). It is not fitted per tail. It is treated as a random quantity with a width s that is fitted, and the likelihood is *averaged* over all the speeds a tail could have. This is what separates "many exponentials with different speeds" from "two layers".
- c_i: the offset of tail i, no longer free. It has the prior $c_i \sim \mathcal{N}(0, \sigma_{\text{off}}^2)$, with σ_{off} the baseline error of that sub-link measured in dry weather. The offset can no longer absorb a slow layer for free.
- $e_i(t)$: the noise, with the white and the slow part of that sub-link measured on its control tails. The likelihood uses this correlated-noise model directly, instead of correcting for it afterwards.

Schematically, the quantity that is maximised over θ and s is

$$\mathcal{L}(\theta, s) \;=\; \prod_{\text{links}} \int du\ p(u) \prod_{i\,\in\,\text{link}} \int dv\ p(v)\ \max_{W_{0,i},\,c_i}\ p(A_i \,|\, \theta, W_{0,i}, c_i, f_i)\, p(c_i), \tag{12}$$

and the candidates are compared by $\text{BIC} = -2\ln\mathcal{L} + k\ln N$, where N counts the independent units (a link in an event), not the minutes and not the tails.

The test and its result

The test data follow the structure of the real set. Ten data sets per true law were built by an *event bootstrap*: 24 events are drawn with replacement from the 24 real ones, with all their tails, so that the dominance of a few events is part of the test. A rule for success was written down before the run: the method is useful if the true law's own candidate wins in at least 80 % of the data sets for the exponential, two-layer, linear + quadratic and switch laws, and the main parameters are recovered within ±30 %.

The rule was met, using the first 60 minutes of each tail, the first 6 hours, or the whole tail (Figure 11):

- The right law wins in 80 to 100 % of the data sets for the four laws in the rule.
- The parameters come back within about ±15 % (median), including the slow time constant and the share of the slow layer, which the per-tail fit could not recover.
- One confusion remains: the pure power law (m3) is taken for the linear + quadratic law (F5) in 20 to 40 % of its data sets. The two are close relatives, and F5 contains a quadratic term.




Figure 11: Pooled fit on simulated data. Rows: the law that generated the data. Columns: the candidate chosen. Each cell is the share of the ten data sets; a perfect method would have 1.0 on the diagonal (dashed boxes). Panels: first 60 minutes, first 6 hours, whole tail.

What this does and does not show

On the real tails, the pooled fit will be able to say which of the five forms describes the drying best, with its parameters and an uncertainty from resampling events. It will not prove a mechanism: the true law may be none of the five, and the winner is then only the best approximation among them. And the test above was run under friendly conditions, which is why the next step was added:

- the fit used the same noise model that generated the data, while the real noise has more than one time scale;
- the search started from the calibrated parameters of each law;
- the real tails decay faster in the first hour than every calibrated law (real median A/A_{start} at 30 minutes is 0.23; the simulated laws give 0.28 or more). This is a hint, not a result: the uncertainty of the real value is wide (0.16 to 0.56).

6.6 Stress test of the pooled fit: partly passed

The stress test tries to break the pooled fit by removing the three friendly conditions one at a time, again on simulated data and again with a rule for success fixed before the run (per test and per true law: the law's own candidate wins in at least 4 of 5 data sets, and its main parameters come back within $\pm 30\,\%$). It uses the first 60 minutes of each tail and four true laws: exponential, two layers, linear + quadratic, and the switch.

T1, wrong noise model.
The data are generated with two slow noise components (correlation times of 20 and 300 minutes), but the fit still assumes one. Slow noise that the fit does not model could be mistaken for a slow layer and favour the more flexible laws.

T2, honest starting points.
The search starts from four generic values, the same for every true law, instead of from the right answer; the best of the four is kept.

T3, faster truths.
Every law is recalibrated to the real median at 10, 30 and 60 minutes, so that the test data dry as fast as the real tails do. The exponential and the two-layer law are also tested with a wider spread of drying speeds ($s = 1.5$).

Table 7: Stress test of the pooled fit on simulated data: 12 of the 14 cases pass. "Pass" means the rule fixed before the run is met.

True law	T1: wrong noise	T2: honest starts	T3: faster truths
m1 exponential	pass	pass	pass (also with the wider spread)
m4 two layers	pass	pass	pass (also with the wider spread)
m6 switch	pass	pass	pass
m5 linear + quadratic	**fail**: the power law wins 5 of 5	pass	**fail**: wins 4 of 5, but its linear rate comes back at 0.65 of the truth

What the result means:

- **The method holds for three of the four laws.** The exponential, the two-layer law and the switch are recognised under noise the fit does not know, from generic starting points, and when they dry as fast as the real tails. The fear that unmodelled slow noise would be mistaken for a slow layer did not come true in this test.
- **The two nonlinear laws are one family.** Both failures belong to the linear + quadratic law, and both have the same cause: with the calibrated parameters its linear term is small, so it is almost a pure quadratic, which the power law copies. The margins are tiny (about 2 BIC units, in either direction). On real tails the two will be read together as "drying that speeds up when the antenna is wetter", and the linear rate will not be interpreted from the first hour.
- **Starting points matter, most of all for the switch law.** From different starting points the switch candidate reached clearly different solutions in all 20 data sets of the test, the other candidates in about a fifth to a half of them. The winner still was the same as with the ideal start in 19 of 20 data sets. Every candidate will therefore be fitted from several starting points on the real tails.
- **Two layers against the switch needs a clear margin.** In one two-layer data set the switch won from a generic start by about 4 BIC units; a difference below about 10 units between these two will not be called a decision.

One limit of the test itself: when the slow laws were recalibrated to the fast early decay with all parameters free, their slow part ran off to a constant floor, so the slow parameters were kept at their earlier values. This choice was made before any fit of T3 and is still to be confirmed by us.

6.7 SINDy directly on the tails: failed

The second tool of the proposal is weak-form SINDy [10]. It writes dA/dt as a sum of terms from a library (here $1, A, A^2, A^3$ and switch terms $\max(A - A_c, 0)$), keeps only the terms it needs, and avoids differentiating the noisy signal by integrating it against smooth test functions over windows of 21 minutes. It was run on the simulated data sets of the stress test, with the rule for success fixed before the run. It failed all four questions asked of it.

- **It returns "A" for almost every truth.** In the first hour, with the spread of drying speeds, the quadratic and the linear + quadratic truths give the linear law in 5 of 5 data sets, with no A^2 term. The switch truth gives the linear law with no switch term. The exponential truth keeps its term but gets a false A^2 term in 3 of 5 data sets and a rate 1.8 times too high.

- **A hidden second state is not noticed.** The two-layer truth returns a clean single-variable law in 5 of 5 data sets, which would be read as a finding.
- **It disagrees with the pooled fit.** The two tools name the same family of law in 1 of 20 data sets; the pooled fit is right in 19 of 20.

The reason is the two things the pooled fit models and SINDy on raw tails does not: the baseline offset of each tail and the spread of drying speeds. With the true offset given and no spread, SINDy does find A^2 in 5 of 5. The spread alone creates the *mixing trap*: exponential tails of different speeds, put into one regression, look like a nonlinear law (a false A^2 in 3 of 5 data sets with the spread, in none without it). So SINDy will not be run on the raw real tails as first planned.

6.8 Two jumps: draw the drying curve, then name it

Discovery was kept but split in two (Figure 12).

Jump 1, draw the curve.
The pooled fit of Eq. (11) is used again, but the menu of laws is replaced by a free smooth curve $k(W)$, the drying rate per dB of water:

$$\frac{dW}{dt} \;=\; -f_i\, W\, k(W), \tag{13}$$

with f_i the speed factor of tail i. The curve is a spline with five knots, and how smooth it must be is chosen by leaving out half of the events. A flat k is exponential drying; k proportional to W is quadratic drying. On a log-log plot the slope of k is therefore 0 for the exponential law and 1 for the quadratic one.

Jump 2, name it.
Sparse regression is applied to the clean curve $h(W) = W\,k(W)$ with the library W, W^2, W^3 and switch terms. Offsets, spread and noise were dealt with in jump 1, so the mixing trap should not appear.




Figure 12: The two jumps that replace SINDy on raw tails.

First run. By the rule fixed before the run the result was only partial. The curve is badly determined at low W: for the exponential truth its lowest point came out 2 to 4 times too high in 9 of 10 fits. Looking at the results afterwards, the curve and its equation were right above about 0.35 dB. A finding made after seeing the results is not a result, so it was tested again.

Confirmation run. New simulated data, the first 60 minutes, and a judged range fixed in advance: from 0.35 dB up to the highest level with enough data (2 to 3.5 dB). Nothing below 0.35 dB is judged or named. Table 8 gives the result.

Table 8: Confirmation run of the two jumps on fresh simulated data (5 data sets per law, first 60 minutes, W above 0.35 dB). "Slope" is the slope of $\log k$ against $\log W$.

True law	Slope: true	Slope: found	Equation found (coefficient / truth)
m1 exponential	0	−0.01 to 0.05	W (×0.99), one term in 5 of 5: pass
m3 quadratic	1	0.99 to 1.12	W^2 (×0.97), one term in 5 of 5: pass
m5 linear + quadratic	0.92	0.93 to 1.03	W^2 (×1.13), one term in 5 of 5: pass
m6 switch at 0.16 dB	0.23	0.20 to 0.32	three terms, not a law (not judged: the switch is below the range)
m4 two layers	–	0.36 to 0.47	three terms; the warning sign fired in 2 of 5: fail

For the three single-curve laws the true curve lies inside the band of the five fits over the whole judged range, and the mixing trap does not appear. Two limits remain. A switch below the range and a two-layer law both give a *mildly rising* curve (slope 0.2 to 0.5) with a many-term equation, and the curve cannot say which of the two it is. And the hoped-for warning sign for two layers (the free curve fits clearly worse than the two-layer candidate) fired in only 2 of 5 data sets, so it is not used as a check.

6.9 The rest of the method, and a false step

Four additions were tested on the same simulated data, each with its own rule fixed before the run (Table 9).

Table 9: Tests of the remaining parts of the discovery method, on simulated data.

Part	What happened	Used on real tails?
Naming alone: the true curve plus 2 to 5 % noise	Sparse regression repeated on resampled points names exactly the true terms in 20 of 20 draws for all four laws, the switch included. Symbolic regression (PySR [7]) does so in 20, 20 and 18 of 20 for the exponential, quadratic and linear + quadratic laws; it cannot write a switch. Choosing the best subset of terms by BIC adds one extra term in 3 to 8 of 20 draws.	yes
A curve that may contain a step (to find a switch)	A step is kept in 5 of 5 data sets for *every* truth, also the pure exponential.	no
Choosing between candidate laws by the likelihood of left-out events	The law with the false step wins in 18 of 20 data sets. Comparing only the five named laws by BIC on the whole data set still names the right family in 4 or 5 of 5.	no; BIC of the named laws instead
An uncertainty band from resampling the events of one data set	The band is ±1 to 6 % wide and contains the true curve on 0 to 78 % of the range (rule: 80 %). It is about three times too narrow: the level of a fit is off by −7 to +23 %. The slope is steadier, within 0.01 to 0.11 of the truth.	shown, with this warning

Is the quantization the cause of the false step? The first explanation was that RSL is recorded in steps of 0.3 dB, which the simulator copies but the noise model of the fit does not describe. This was tested directly: exponential data were simulated three times with the same random numbers, with no rounding, with 0.3 dB and with 0.1 dB. The step is kept in 5 of 5 data sets in all three cases, also with no rounding at all. So the quantization is *not* the cause, and adding it to the fit is not expected to help. The test showed one more thing: in 15 of 15 fits the step stays where the search started it, so its position carries no information either. The cause is

open.

What can be said on real tails, as a result. For W between 0.35 dB and the top of the data, in the first hour after rain: how the drying rate per dB of water changes with W, as a slope known to about ± 0.1; whether that stretch is a one-term law (exponential or quadratic); the level of the rate to about $\pm 20\,\%$; and which of the named laws the data prefer by BIC. Nothing can be said below 0.35 dB, and nothing about a switch level: a step found there would mean nothing.

In short. A simulator that copies the real tails and their noise shows that the median curve cannot decide between the laws, and that fitting single tails cannot either. Fitting all tails together, with a shared law, a random speed per tail, a bounded offset and a correlated-noise model, recovers the right law and its parameters on simulated data. SINDy on the raw tails does not. Drawing a free drying curve with the pooled fit and then naming its equation does, for W above 0.35 dB in the first hour. A step in the curve, a choice by held-out likelihood and a resampling band failed their tests. All of this is on simulated data; the first fit of the real tails is the next section.

7 The first fit of the real tails

7.1 What was done

This is the first step that fits a law to real data. It uses the frozen tail set, training events only: 429 tails from 24 events on 159 links. The 123 validation tails were not read. Only the tools that passed on simulated data were used, with their settings unchanged, and the rule for reading the result was written down before the run:

- the five named laws, each fitted to all tails together from four starting points and compared by BIC;
- the free drying curve $k(W)$ of Eq. (13), drawn from the first 60 minutes of the tails and read between 0.35 dB and 2.83 dB (the top of the data), with a band from 20 refits on resampled events;
- the naming of that curve by sparse regression, with symbolic regression as a cross-check.

Every result was repeated on other versions of the set: without the events flagged for many rising tails, without the tails with a level flag, on the alternative set with weaker tails, and with each of the three largest events left out in turn.

7.2 What was found

No drying law is identified. The free curve *falls* as W grows: the slope of $\log k$ against $\log W$ is -0.87 on the main set (-1.43 to -0.82 over the resampled refits). In words, a wetter antenna would dry *more slowly* per dB of water: the time constant $1/k$ is 6 minutes at 0.35 dB, 33 minutes at 1 dB and 71 minutes at 2.83 dB. None of the simulated truths has this shape: an exponential gives slope 0, and the nonlinear laws give a rising curve. A direct look at the measured rate of decrease, with no model, shows the same trend, so it is in the data and not made by the fit.

Where it comes from. Many tails do not decay at first. Ten minutes after the tail starts, 21 % of the tails are still at 90 % or more of their starting level. In the events that had been flagged for many rising tails this share is 38 %; in the other events it is 11 %. A tail that stays flat at a high level tells the fit that strong attenuation dries slowly. Table 10 shows how much the result depends on which tails are included.

Table 10: Slope of the free drying curve on the real tails, for different versions of the tail set. Slope 0 means an exponential law.

Tails used	**Slope of** $\log k$ **against** $\log W$
Main set (429 tails)	-0.87
Without the events flagged for many rising tails	-0.05
Without the tails with a level flag	-0.79
Alternative set (weaker tails included)	-0.69
One of the three largest events left out, in turn	-0.60, -1.60, -0.46

Without the flagged events the curve is flat, which is the exponential law, with a time constant of about 15 minutes. So the answer depends on a choice that has not been made: which tails count as drying.

The curve is badly determined. The four starting points of the fit end far apart (800 to 1700 units of the fit's cost; on simulated data the difference was about 8), and the resampling band is $\pm 94\,\%$ wide. A dip near 0.9 dB moves when a knot of the curve is moved, so it is not read.

No equation. Sparse regression keeps all five terms of its library, which means it finds no short formula. The best formula with one term misses the curve by 61 % (root mean square), and the simplest formula from symbolic regression is a constant rate, which misses it by 49 %.

The named laws, and a fault in the comparison. As run, the exponential law wins by BIC, with a time constant of 25.2 minutes. Looking into this found a fault in our own tool: for the exponential and the two-layer law the starting level of a tail may be fitted as negative, while the other laws and the free curve keep it positive. Three rising tails with a negative start account for the whole advantage of the exponential over the power law with exponent 1, which is the same law. Compared like for like, the switch law is ahead of the exponential by 21.5 BIC on the main set; over the other versions of the set this ranges from the exponential ahead by 0.9 to the switch ahead by 216. This is not decisive either. The residuals of the fit have 4.1 times the variance that the dry-weather noise model allows, so every BIC difference is overstated, and the switch law depends on its starting point. One thing is stable in all seven versions of the set: the power law ends at exponent 1 and the linear + quadratic law ends with no quadratic term. A drying rate that *rises* with W is therefore not supported in the first hour.

Shape of the real tails. The median of A/A_{start} is 0.568, 0.229 and 0.142 at 10, 30 and 60 minutes.

Literature. The comparison with a published drying time constant could not be made: neither the proposal nor the other documents of the project quote one, and none was invented. The values have to be read from [1] and [9].

7.3 How we read it

The model that was tested, $dW/dt = -h(W)$ with one curve for all tails and a random speed per tail, does not describe the first hour of the real tails. A tail that stays flat or rises after the last trace of rain points to something the model leaves out: water still arriving (light rain or drizzle below what the references see, or condensation), which belongs to the wetting term $g(R, W)$ of Eq. (14), or a tail that starts too early. The exponential with a time constant of 15 to 28 minutes is a placeholder, not a discovered law.

Three decisions are open before the next step: (a) which tails define drying (all of the frozen set; the set without the flagged events; or tails restarted where the decay begins, which would be a new frozen set); (b) repairing the fault in the starting level and repeating the tests on simulated

data, this time with some rising tails among them; (c) a larger noise level, or a fitted one, for drying tails.

In short. The first fit of the real tails did not find a drying law. The drying rate falls with W (slope -0.87), because about one tail in five stays flat or rises after the rain. Without the events where this is common the tails are close to an exponential with a time constant of about 15 minutes. No short equation fits the curve, the comparison of the named laws is not decisive, and a fault in that comparison was found. A drying rate that rises with W is not supported.

8 Where we stand

Table 11: What is established, and what is not, on 12 October 2026.

Established	**Not established yet**
$A(t)$ exists for every training and validation event on the training links, with a baseline that is unbiased and accurate to about one quantization step.	Baselines for the test events and test links (needed for the final held-out check).
The baseline does not absorb the drying after rain.	Whether the attenuation at the start of a tail is the antenna or residual light rain on the path.
A memory after rain exists: strong tails take hours to return to the dry level.	The form of the drying law. The first fit of the real tails did not identify one (Section 7).
A frozen, non-circular set of 429 drying tails (and 123 validation tails not yet looked at).	What the unexplained night-time rises are (drizzle or condensation).
The median tail halves in about 15 minutes and has a slow remainder.	Whether the slow remainder is a second process or only the spread of drying speeds between antennas.
The median curve and single-tail fits cannot identify the law; a pooled fit can, on simulated data, also under a wrong noise model and from generic starting points (exponential, two layers, switch).	Whether a trustworthy uncertainty band can be made from one data set (resampling events gave a band about three times too narrow).
SINDy on the raw tails does not recover a known law on simulated data. In two jumps (a free drying curve, then sparse regression) an exponential and a quadratic law are recovered for W above 0.35 dB in the first hour, also on fresh data.	Anything below 0.35 dB, a switch level included, and why the fit prefers a false step there (it is not the 0.3 dB quantization).
On simulated data the power law and the linear + quadratic law cannot be told apart.	Which law the real tails follow. The real residuals have 4.1 times the variance of the noise model, so the real noise is *not* close enough to it.
Dry-weather noise is correlated over tens of minutes; dew produces WAA-like jumps at night.	The wetting law, the path law f, and the rain estimate: not started.
On the real tails, a drying rate that rises with W is not supported in the first hour; about one tail in five stays flat or rises after the rain.	Which tails count as drying, and what keeps the others flat or rising (rain below the references, condensation, or a tail that starts too early).

Two methodological habits have carried the work so far and will continue. The first is to *build a case with a known truth* before trusting a method: fake events for the baseline, simulated tails for the fitting. The second is to *fix the decision rule before the run*: the rejected humidity rule, the tail selection, and the success rules of the fitting tests were all written down before their results were seen. Twice this prevented a wrong conclusion that looked attractive: that the fast drop is antenna drying (Section 5.4) and that the data ask for two layers (Section 6.3). The stress test adds a third case of the same kind: a win of the linear + quadratic law over the power law, or

the reverse, will not be read as a finding. The latest steps added two more habits. A finding made after seeing the results is tested again on fresh data before it is used (the range above 0.35 dB). And our own explanation of a failure is tested before it is acted on: the quantization was the suspected cause of the false step, and the test said no.

9 What comes next

9.1 The target of Stage 1

The goal is one dynamic equation for the WAA with rain as its input,

$$\frac{dW}{dt} = \underbrace{g(R, W)}_{\text{wetting}} - \underbrace{h(W)}_{\text{drying}}, \tag{14}$$

where h is learned from the drying tails ($R = 0$, so $dW/dt = -h(W)$) and g from whole events on very short links, where the path term is small. Figure 13 shows the route.




Figure 13: The remaining route of Stage 1. Grey fill: done. Dashed border: in progress. Dotted border: planned.

9.2 The steps

1. **The drying law on real tails (first fit done, no law yet).** The first fit (Section 7) did not identify a law. Before it is repeated, three things are decided and repaired: which tails define drying; the fault in the starting level of a tail, followed by a repeat of the tests on simulated data with some rising tails among them; and the noise level used for drying tails. The drying time constants of the literature [1], [9] are read from the papers, so that the comparison can be made with numbers.
2. **What drying depends on.** Relate the drying speed to frequency, antenna size, time of day, temperature, wind and humidity.
3. **The wetting law, from very short links.** On links shorter than about 0.6 km the path term is small, so $A(t)$ during the rain is mostly WAA. That the path term is small must be shown without assuming the power law: among short links, the attenuation during rain must not grow with L, and the two directions of a link must agree. First the simulator is extended from tails to whole events (real radar rain, a wetting law, a small path term that grows with L), and the tool for this step is chosen by testing on that simulated data, as was done for drying. With $h(W)$ kept fixed from the tails, $g(R, W)$ is then learned with the radar rain along the path as input, and compared with the model of Schleiss et al. [1]. This step is also the real test of whether what we call WAA belongs to the antenna (Section 5.4).

4. **Verification.** On data not used so far: drying on the validation events; the full law on unseen events; agreement between the drying time read from the free curve and the one fitted directly; agreement between the two directions of a link; and whether dew events, which wet the antenna without rain, dry by the same $h(W)$. The decisive check is the transfer to longer links: after the predicted WAA is subtracted, the remaining attenuation should grow with L with no constant offset. That is the test of Eq. (4), and it is the handover to Stage 2.

9.3 After Stage 1

- **Stage 2, the path law.** With the WAA removed, learn $f(L, \bar{R}, Z)$ of Eq. (3) by symbolic regression (PySR [7]), with the radar rain along the path as the reference, and see how the dependence on the length differs from $f = L$.
- **Rain estimate and evaluation.** Invert the combined model (path law and WAA) to get rain from attenuation, on events that were not used for training. Measures: normalised bias and normalised RMSE against gauges and radar, by link length; the amount of false rain after the end of events; comparison with the plain power law, the WAA models of the literature [1], [9] and a neural-network reference [11]; and the stability of the learned terms under resampling.

9.4 Open questions

- Why does the fit prefer a false step at low W on simulated data? It is not the quantization. What is left to test: whether the fit without a step had simply not searched long enough, the bound on the baseline offset, and the very narrow shape of the step.
- Which tails define drying: all of the frozen set, the set without the events with many rising tails, or tails restarted where the decay begins?
- What keeps the attenuation flat or rising after the last trace of rain in about one tail in five: rain or drizzle below what the references see, re-wetting, condensation, or attenuation along the path? The answer decides whether those minutes belong to the drying term or to the wetting term.
- The residuals of the real tails have 4.1 times the variance of the dry-weather noise model. Should the noise level of drying tails be larger, or fitted?
- Which is wrong in the resampling band: the resampling itself, or the short search each refit was given?
- Are the night-time rises after rain drizzle that the radar misses, or condensation? The humidity record has gaps exactly there.
- Should light rain after the first dry moment end a tail (as now), or be given to the model as input?
- The spread of drying speeds was calibrated after the noise was fixed, so any noise the model still misses ends up in the spread. How much of $s = 1.25$ is real variation between antennas?
- The literature form for exponential drying is named in the working plan after Minda and Nakamura; that reference is not in the proposal's list and has to be checked and added before it is cited.

References

The numbers are those of the project proposal; only the references used in this report are listed.

[1] Schleiss, M., Rieckermann, J., & Berne, A. (2013). Quantification and modeling of wet-antenna attenuation for commercial microwave links. *IEEE Geoscience and Remote Sensing Letters*, 10(5), 1195–1199.

[7] Cranmer, M. (2023). Interpretable machine learning for science with PySR and SymbolicRegression.jl. arXiv:2305.01582.

[8] Ostrometzky, J., & Messer, H. (2018). Dynamic determination of the baseline level in microwave links for rain monitoring from minimum attenuation values. *IEEE Journal of Selected Topics in Applied Earth Observations and Remote Sensing*.

[9] Pastorek, J., Fencl, M., Rieckermann, J., & Bareš, V. (2021). Precipitation estimates from commercial microwave links: practical approaches to wet-antenna correction. *IEEE Transactions on Geoscience and Remote Sensing*.

[10] Messenger, D. A., & Bortz, D. M. (2021). Weak SINDy: Galerkin-based data-driven model selection. *Multiscale Modeling & Simulation*, 19(3), 1474–1497.

[11] Habi, H. V., & Messer, H. (2020). Recurrent neural network for rain estimation using commercial microwave links. *IEEE Transactions on Geoscience and Remote Sensing*.

[13] Andersson, J. C. M., Olsson, J., van de Beek, R., & Hansryd, J. (2022). OpenMRG: open data from microwave links, radar, and gauges for rainfall quantification in Gothenburg, Sweden. *Earth System Science Data*, 14, 5411–5426.

A Glossary

Term	Meaning
$A(t)$	Attenuation: total loss minus baseline, Eq. (1).
A_{rain}, $\delta(t)$	The part of A caused by rain along the path; everything else.
$W(t)$	Wet-antenna attenuation (WAA), in dB.
$\bar{R}$, L	Mean rain rate along the path; path length.
$f(L, \bar{R}, Z)$	The path-law correction to be learned in Stage 2; uniform rain gives $f = L$.
Sub-link	One direction of a two-way link.
Baseline	The total loss of a sub-link without rain; here one number per (event, sub-link).
Fake event	A pretended event placed in certified dry weather, where the true attenuation is zero.
Offset, σ_{off}	The baseline error of one (fake) event; its spread for a sub-link.
Drying tail	The stretch of $A(t)$ after the rain has stopped on a link.
t_0, t_{trace}	End of the link's last wet bin; end of the last bin with any trace of rain (the tail start).
A_{start}	Mean of A over the first 5 minutes of the tail.
Control tails	Tails that start below 0.5 dB: noise without drying.
Tail set v1	The frozen set of 429 training tails (123 validation).
m1 ... m6, F1 ... F6	A drying law used as the truth of a simulation; the same law used as a candidate in a fit.
Spread s	Width of the tail-to-tail variation of the drying speed, Eq. (8).
BIC	Bayesian information criterion: goodness of fit with a charge per parameter; lower is better.
Pooled fit	One law with shared parameters fitted to all tails at once, Eq. (11).
Event bootstrap	Resampling whole events with replacement, to measure uncertainty.
SINDy	Sparse identification of nonlinear dynamics: finds a short equation for dW/dt from a library of terms.
Free curve $k(W)$	The drying rate per dB of water, drawn by the pooled fit without assuming a law, Eq. (13).
Jump 1, jump 2	Drawing the free curve from all tails; naming its equation by sparse regression.
Mixing trap	Exponential tails of different speeds, analysed together, look like a nonlinear law.

B Where the details are

This report gives the ideas. The exact rules, thresholds and numbers are in the documents of each module, inside the research folder.

Topic	Document
Baseline method, flags, accuracy, decisions	`baseline/METHOD.md`
Baseline validation	`R1_validation.md` and `R1b_validation.md`, in the reports folder of `baseline`
Tail definitions, rules of set v1, what each WAA step decided	`wet_antenna/METHOD.md`
Frozen tail set	`freeze_tail_set.md`, in the reports folder of `wet_antenna`
Simulator and its calibration	`calibrate_simulator.md`, same folder
Pooled fit on simulated tails	`check_pooled_fit.md`, same folder
SINDy on simulated tails	`check_sindy.md`, same folder
The two jumps and their confirmation	`check_free_curve.md` and `confirm_free_curve.md`, same folder
The rest of the method; the false step	`check_discovery_method.md` and `check_quantization.md`, same folder
The first fit of the real tails	`fit_real_drying.md`, same folder
The plan, and how to rerun every step	`docs/ROADMAP.md` and `docs/REPRODUCE.md`
The data layer	`docs/pipeline_log.pdf` (next to this report)