Project structure

Which folders and files the repository has, and what each one is for

Yonatan Haber and Yehonatan Tsitseluk

CellEnMon lab, final-year electrical engineering project

Data-driven discovery of rain-induced and wet-antenna attenuation laws in commercial microwave links

12 October 2026

In short. The repository has three parts that depend on each other in one direction. `pipeline/` turns the raw OpenMRG files into a clean data release. `research/` reads that release and does the science. `docs/` explains both. The data itself is in `data/`, which is not in git.

Contents

1 The parts and how they connect 1

2 Top level 2

3 `docs/`: project documents 2

4 `pipeline/`: the data layer 2

5 `research/`: the science 4

6 `data/`: not in git 6

1 The parts and how they connect




Figure 1: How the parts connect. Thick solid border with grey fill: code. Thick dashed border: data (not in git). Dotted border: documents and results (in git).

The dependency goes one way only: research reads the data through one door (`cmlpipe.api`), and nothing in `pipeline/` uses `research/`. A test checks this.

2 Top level

File	What it is
`README.md`	Front page: what the project is and where to start.
`CLAUDE.md`	Instructions and rules for Claude (notation, layout, what is protected or frozen).
`LICENSE`	MIT licence for the code.
`.gitignore`	The only ignore file: keeps the data, the caches and a few big output files out of git.
`.gitattributes`	Git settings for line endings and binary files.
`environment.yml`	The conda environment to install.
`environment.lock.yml`	The same environment with exact versions.
`.github/workflows/check.yml`	Runs the fast tests on GitHub on every push.
`.claude/commands/updatedocs.md`	The `/updatedocs` command: updates the research log, this document and the reproduce page.

3 `docs/`: project documents

File	What it is
`README.md`	Index of this folder.
`proposal.md`, `proposal.docx`	The project proposal (Hebrew); `media/` holds its figure.
`ROADMAP.md`	The only roadmap: a checklist, then the detailed WAA plan.
`REPRODUCE.md`	How to rerun everything, step by step. Its step table is generated from `research/steps.yaml`.
`research_log.tex`, `.pdf`	The research report at the level of ideas: what was done, what it found, what comes next.
`project_structure.tex`, `.pdf`	This document.
`build_research_log.py`	Builds either PDF from its `.tex` with pdflatex.
`pipeline_log.pdf`	The report on how the data pipeline was built.
`sindy_intro_report_2026-03.pdf`	Our earlier report "Introduction to SINDy".
`papers/`	The OpenMRG dataset paper.

4 `pipeline/`: the data layer

The pipeline is the Python package `cmlpipe`. It takes the raw data through three levels and then makes a release: **L1** is the raw data in a standard format (one file per day), **L2** adds quality flags, **L3** is the data reduced to coarser time steps, and the **release** is the read-only data set that the research reads.

4.1 Files at the top of the folder

File	What it is
`README.md`	Overview of the pipeline and its stages.
`pyproject.toml`	The single list of Python dependencies.
`get_data.py`	Downloads OpenMRG from Zenodo into `data/raw` and runs the pipeline.
`get_caches.py`	Downloads the saved fits (about 9 hours of fitting), so they need not be repeated.
`configs/openmrg.yaml`	All pipeline settings.
`start_explorer.bat`	Starts the data explorer on Windows.
`LICENSE-DATA.md`	The licence of the data (CC BY-SA, from OpenMRG).

4.2 The code: `src/cmlpipe/`

One folder per job. Most folders have a `core.py` (the calculations only) and a `stage.py` (reads files, calls the core, writes files).

Folder or file	What it does
`io/`	Reads the raw files and writes L1. `openmrg.py`: the CML data. `openmrg_reference.py`: gauges, weather and radar. `schema.py`: defines and checks the L1 format. `netcdf.py`: the one place that reads NetCDF. `ingest.py`: the stages.
`qc/`	Quality control: flags bad samples without fixing them. `flags.py`: the flag bits. `rules.py`: the rules. `stage.py`: the stages.
`geometry/`	Where links, gauges and radar pixels are, and which radar pixels lie along each link.
`aggregate/`	Reduces the 10 s data to coarser time steps (L3), for CML, gauges and radar.
`events/`	Finds rain events and dry periods from the references only (never from the CML), and makes the frozen train / test split. `link_state.py`: wet, dry or unknown per link every 5 min.
`inventory/`	Which events are significant, how complete each link is, a quality status per sub-link.
`release/`	Builds the release. `build.py`: the stage. `cmlstores.py`, `zarrstore.py`: write the time series as Zarr. `metadata.py`: the list of every product. `guide.py`: writes the data guide.
`api/`	The only door the research uses to read data. `cmldata.py`: the `CMLData` class. `access.py`: one link with everything on one time axis. `explore.py`: find and plot helpers.
`viz/`	Figures. `explorer.py`: plots for the explorer. `quicklooks.py`: one image per event. `link_cards.py`: one page per link. `inventory_figures.py`, `run_report.py` (an HTML summary), `style.py`.
`cli.py`, `__main__.py`	The `python -m cmlpipe` commands.
`config.py`	Loads the settings file and computes its hash.
`provenance.py`	Stamps each output with what produced it.
`parallel.py`	Runs the per-day work on several processes.
`logging_utils.py`	One log file per run.

4.3 The other folders

Folder	What is in it
`apps/explorer/`	The data explorer (a Streamlit page). `app.py`: the interface. `data.py`: loads the data. `smoke.py`: checks it without a browser.
`tests/`	One test file per part of the pipeline (`test_qc.py`, `test_events.py`, ...). Most use a tiny synthetic data set built in `conftest.py`. `test_real_openmrg.py` and `test_api.py` need the real data. `test_boundaries.py` checks that the pipeline never uses the research code. `test_research_steps.py` checks that the step list and the reproduce page match the scripts.
`tools/`	`check_boundaries.py`: the checker behind that boundary rule.
`examples/`	`quickstart.ipynb`: a short notebook that shows how to read the data.
`docs/`	`DATA_GUIDE.md` and `data_dictionary.md`: written by the release stage, not edited by hand. `howto_access.md`: reading data from code. `methods.md`: what each stage does and why. `openmrg_summary.md`: summary of the dataset. `reference/`: a CML libraries how-to and the OpenSense example notebook.

5 `research/`: the science

5.1 Shared files

File or folder	What it is
`README.md`	Overview of the research code.
`config.yaml`	Every research setting, one section per module.
`steps.yaml`	Every step in run order: what it does, what it needs, how long it takes.
`__main__.py`	The `python -m research` menu, with `run`, `compare` and `docs`.
`common/`	Small helpers used everywhere. `save.py`: save an output. `report.py`: tables for the reports. `plotting.py`: a figure style that does not rely on colour. `config.py`: reads the settings.

5.2 What every module has, and the local folders

Each module below has the same shape: `README.md` (what, status, how to run), `METHOD.md` (the method and the decisions, with numbers), `paths.py` (the only place with file locations) and an `outputs/` folder. Everything in `outputs/` is in git, and every file name starts with the name of the script that made it.

Folder	What is in it
`outputs/products/`	Data that later steps read, for example `baselines.csv`, `tails_index.csv` and the simulated tails.
`outputs/tables/`	Results as CSV tables.
`outputs/figures/`	Figures (PNG).
`outputs/reports/`	One Markdown report per script.
`explorations/`	The playground. Local only; just its `README.md` is in git.
`.cache/`	Saved fits and logs per script. Local only. It holds the 9 hours of fitting: do not delete.
`.vibe-wise/`	Plugin notes. Local only: never commit, move or delete.

5.3 `baseline/`: computing $A(t)$

$A(t) = \mathrm{TSL}(t) - \mathrm{RSL}(t) - \text{baseline}$. This module estimates the baseline.

File	What it does
`baseline.py`	The baseline method itself (functions only).
`run_sample.py`	Runs the method on a sample of events and sub-links: v1 (two windows, kept for comparison) or v2 (pre-event window, the current method).
`make_dew_products.py`	The hourly dew risk and the list of dry-weather jumps.
`make_baseline_table.py`	The frozen baseline v2: one baseline per event and sub-link, with its uncertainty.
In the folder `validation/`*: the checks of the baseline*	
`c1_fake_events.py`	Fake events in dry weather, where the truth is $A = 0$.
`c2_after_window.py`	Does the window after the rain carry a drying signal?
`c3_daily_cycle.py`	The daily cycle in dry weather.
`c4_jumps.py`	What the dry-day jumps are.
`c5_flagged.py`	The flagged cases of the v1 run.
`c6_sensitivity.py`	Sensitivity to the window length and to mean or median.
`r1b_event_level.py`	The final pass or fail of baseline v2.
`common.py`, `run_all.py`	Shared code of the checks, and the script that runs them all in order.

5.4 `wet_antenna/`: the WAA drying law

Table 1: The scripts that are run, in run order.

Step	Script	What it does
0	`inventory.py`	What data there is for WAA; no analysis.
1	`extract_tails.py`	Cuts out every drying tail after every rain event, with no selection.
2	`select_tails.py`	Selects usable tails by rules fixed in advance; tests the "fast drop".
2b	`refine_selection.py`	Fixes after looking at the selected tails.
2c	`freeze_tail_set.py`	Last fixes, then freezes tail set v1 that all modelling uses.
3a	`calibrate_simulator.py`	A simulator of tails with known drying laws and realistic noise.
3b-1	`check_per_tail_fit.py`	Fit one tail at a time on simulated tails (cannot find the true law).
3b-1b	`check_pooled_fit.py`	Fit all tails together.
3b-1c	`stress_pooled_fit.py`	Stress test of the pooled fit.
3b-2	`check_sindy.py`	Weak-form SINDy directly on simulated tails (failed).
3b-3	`check_free_curve.py`	Learn a free drying curve $k(W)$ from all tails, then name its equation.
3b-3b	`confirm_free_curve.py`	Confirms that on fresh simulated tails, with the rule written first.
3b-3c	`check_discovery_method.py`	The rest of the discovery method (model choice, bootstrap band).
3b-4	`check_quantization.py`	Is the 0.3 dB quantization of RSL the cause of the false step? (no)
4	`fit_real_drying.py`	The first fit on the real tails, train events only.

Table 2: The libraries: used by the scripts above, not run on their own.

File	What is in it
`simulator.py`	The drying laws and the noise model.
`per_tail_fit.py`	The candidate models and the fit of single tails.
`pooled_fit.py`	The fit of all tails together.
`free_curve.py`	The free curve and the naming of its equation.
`sindy.py`	A minimal weak-form SINDy, written with numpy only.
`tails.py`	Small helpers for the selection steps.
`datasets.py`	The noise tables, the tail sets on disk and the bootstraps.
`fit_jobs.py`	The long fitting jobs; they save their progress, so an interrupted run continues.

6 `data/`: not in git

Folder	What is in it
`raw/openmrg/`	The original download: `cml/`, `gauges/`, `radar/` and the Torslanda case study. Never modified.
`work/openmrg/`	What the pipeline writes: `L1_standard/`, `L2_qc/`, `L3_products/`, `tables/` (with the frozen `events.csv` and the split files), `reports/`, `logs/`.
`release/openmrg_v1/`	The read-only release that the research reads: `tables/`, `timeseries/` (Zarr), `catalog.json`, `DATA_GUIDE.md`, `DATA_DICTIONARY.md`, `verification.json`.