
Table of Contents

.....	1
3 Lab: FIR Filters	1
3.1 Deconvolution Experiment for 1-D Filters	1
3.1.1 Restoration Filter	2
3.1.2 Worst Case Error	5
3.1.3 An Echo Filter	5
3.2.1 Overall Impulse Response	6
3.2.2 Distorting and Restoring Images	7
3.2.3 A Second Restoration Experiment	8
worst case error (wce)	12

```
%{  
Yonatan Carver  
ECES 352 - Lab 7  
  
%}  
clear; clc; close all  
  
load lab6dat % as x1, xtv, x2, h1, h2
```

3 Lab: FIR Filters

3.1 Deconvolution Experiment for 1-D Filters

```
xx = 256 * (rem(0:100, 30) > 10); % x[n]  
bb = [1 -0.92]; % impulse response  
  
ww = firfilt(bb, xx);  
  
first = 1;  
last = length(xx);  
nn = first:last;  
  
figure('Name', '3.1 - Deconvolution Experiment for 1-D Filters')  
subplot(2,1,1)  
% stem(nn-1, xx(nn))  
stem(xx)  
grid on  
xlim([0 90])  
title('Input Waveform: x[n]')  
xlabel('Time Index (n)')  
  
subplot(2,1,2)  
% stem(nn-1, w(nn), 'filled')  
stem(ww, 'filled')  
grid on  
xlim([0 90])  
title('Output Waveform: w[n] = x[n] - 0.92x[n-1]')
```


```

xlabel('Time Index [n]')

sgtitle('3.1 Deconvolution Experiment for 1-D Filters')

%{
The length of x[n] is 101.
The length of w[n] is 102.
If h = 2 elements (n+2-1)
%}

```



```

% l=1;
% for n = 1:1:length(xx)
%   ww(n) = xx(n) - 0.92*xx(n-1);
% end
%
% stem(ww)

```

3.1.1 Restoration Filter

```

r = 0.92;
M = 15;
cc = r.^[0:M];
yy = conv(cc,ww);
error = immse(yy(1:91),xx(1:91)); % 2.0984e+03

figure('Name', '3.1.1 - Restoration Filter')

```

```
subplot(2,1,1)
stem(ww)
grid on
xlim([0 90])
title('w[n]')
xlabel('Time Index (n)')

subplot(2,1,2)
stem(yy, 'filled')
grid on
xlim([0 90])
title('y[n]')
xlabel('Time Index (n)')

sgtitle('3.1.1 Restoration Filter')


% (c)
figure('Name', '3.1.1 (c)')
subplot(3,1,1)
stem(xx)
grid on
xlim([0 90])
title('w[n]')
xlabel('Time Index (n)')

subplot(3,1,2)
stem(yy, 'filled')
grid on
xlim([0 90])
title('y[n]')
xlabel('Time Index (n)')


subplot(3,1,3)
stem(error, 'filled')
grid on
xlim([0 90])
title('Error')
xlabel('Time Index (n)')

sgtitle('3.1.1 (c) Restoration Filter')
```

3.1.1 Restoration Filter



3.1.1 (c) Restoration Filter




3.1.2 Worst Case Error

```
diff = max(immse(yy(1:101), xx(1:101)));

figure('Name', '3.1.2 - Worst Case Error')
stem(diff)
hold on; grid on
% stem(yy(1:90))
% stem(xx(1:90))
legend('Difference')%, 'y[n]', 'x[n]')
title('3.1.2 - Worst Case Error')

%{
Error plot & worst case error tells us that it is more difficult to
reproduce
the original signal.
%}
```



3.1.3 An Echo Filter

```
fs = 8000;
time_delay = 0.2 * fs;
r = 0.9; % 90% of original signal
P = 2000;
```

```

yln = [1 zeros(1,time_delay-2) r];
x22 = conv(x2, yln);

% soundsc(yln)
% soundsc(x2)
soundsc(x22) % new sound with echo

%{
time_delay is 1600 because fs = 8000
magnitude of signal is 90% of original

Coefficients of FIR filter should be r = 0.90.

Convolve the echo filter with the input signal.
%}

```

3.2.1 Overall Impulse Response

```

yn = conv(cc, ww);
hh = conv(bb, cc);

figure('Name', '3.2.1 - Overall Impulse Response')
subplot(3,1,1)
stem(bb)
grid on
xlim([0 15])
title('bb')
xlabel('Time Index (n)')


subplot(3,1,2)
stem(cc)
grid on
xlim([0 15])
title('cc')
xlabel('Time Index (n)')

subplot(3,1,3)
stem(error, 'filled')
grid on
xlim([0 15])
title('Impulse Response')
xlabel('Time Index (n)')

sgtitle('3.2.1 Overall Impulse Response')

```

3.2.1 Overall Impulse Response



3.2.2 Distorting and Restoring Images

```
load echart

% figure('Name', '(a) Show Image: echart')
% imshow(echart)
% title('echart: Original Image')

bb1 = zeros(1,16);
q = 0.92;

for n = 0:15
    bb1(n+1) = q^n;
end

[row, height] = size(echart);
ech92 = zeros(row, height);

for i = 1:row
    w = conv(echart(i,:), bb);
    ech92(i,:) = w(1:height);
end
for i = 1:height
    w = conv(ech92(:,i), bb);
    ech92(:,i) = w(1:row);
end
```

```

end

reconstructed = zeros(row, height);
for i = 1:row
    w = conv(ech92(i,:), bb1);
    reconstructed(i,:) = w(1:height);
end
for i = 1:height
    w = conv(reconstructed(:,i), bb1);
    reconstructed(:,i) = w(1:row);
end

figure('Name', '3.2.2 - Distorting and Restoring Images', ...
    'units','normalized', 'outerposition', [0 0.50 1 0.5])
subplot(1,3,1)
imshow(echart)
title('Original Image')

subplot(1,3,2)
imshow(ech92)
title('ech92')

subplot(1,3,3)
imshow(reconstructed)
title('Reconstructed echart')

%{
Small "delay" in the image - called: ghosting.
%}

```

Original Image	ech92	Reconstructed echart
E W S X	E W S X	E W S X
E W S X M	E W S X M	E W S X M
E W S X M P	E W S X M P	E W S X M P

3.2.3 A Second Restoration Experiment

```

% 10
=====
bb2 = zeros(1,11);

for n = 0:10
    bb2(n+1) = q^n;
end

ech92_10 = zeros(row, height);

for i = 1:row
    w = conv(echart(i,:), bb);

```

```

    ech92_10(i,:) = w(1:height);
end
for i = 1:height
    w = conv(ech92_10(:,i), bb);
    ech92_10(:,i) = w(1:row);
end

reconstructed_10 = zeros(row, height);
for i = 1:row
    w = conv(ech92_10(i,:), bb2);
    reconstructed_10(i,:) = w(1:height);
end
for i = 1:height
    w = conv(reconstructed_10(:,i), bb2);
    reconstructed_10(:,i) = w(1:row);
end

figure('Name', '3.2.2 - Distorting and Restoring Images: 10', ...
    'units','normalized', 'outerposition', [0 0.50 1 0.5])
subplot(1,3,1)
imshow(echart)
title('Original Image')

subplot(1,3,2)
imshow(ech92_10)
title('ech92\_10')

subplot(1,3,3)
imshow(reconstructed_10)
title('Reconstructed echart\_10')

% 15
=====

bb3 = zeros(1,16);

for n = 0:15
    bb3(n+1) = q^n;
end

ech92_15 = zeros(row, height);

for i = 1:row
    w = conv(echart(i,:), bb);
    ech92_15(i,:) = w(1:height);
end
for i = 1:height
    w = conv(ech92_15(:,i), bb);
    ech92_15(:,i) = w(1:row);
end

reconstructed_15 = zeros(row, height);
for i = 1:row
    w = conv(ech92_15(i,:), bb3);

```

```

    reconstructed_15(i,:) = w(1:height);
end
for i = 1:height
    w = conv(reconstructed_15(:,i), bb3);
    reconstructed_15(:,i) = w(1:row);
end

figure('Name', '3.2.2 - Distorting and Restoring Images: 15', ...
    'units','normalized', 'outerposition', [0 0.50 1 0.5])
subplot(1,3,1)
imshow(echart)
title('Original Image')

subplot(1,3,2)
imshow(ech92_15)
title('ech92\_15')

subplot(1,3,3)
imshow(reconstructed_15)
title('Reconstructed echart\_15')

% 30
=====

bb4 = zeros(1,31);

for n = 0:30
    bb4(n+1) = q^n;
end

ech92_30 = zeros(row, height);

for i = 1:row
    w = conv(echart(i,:), bb);
    ech92_30(i,:) = w(1:height);
end
for i = 1:height
    w = conv(ech92_30(:,i), bb);
    ech92_30(:,i) = w(1:row);
end

reconstructed_30 = zeros(row, height);
for i = 1:row
    w = conv(ech92_30(i,:), bb4);
    reconstructed_30(i,:) = w(1:height);
end
for i = 1:height
    w = conv(reconstructed_30(:,i), bb4);
    reconstructed_30(:,i) = w(1:row);
end

figure('Name', '3.2.2 - Distorting and Restoring Images: 30', ...
    'units','normalized', 'outerposition', [0 0.50 1 0.5])
subplot(1,3,1)

```

```

imshow(echart)
title('Original Image')

subplot(1,3,2)
imshow(ech92_30)
title('ech92\_30')

subplot(1,3,3)
imshow(reconstructed_30)
title('Reconstructed echart\_30')

% 1000
=====

bb5 = zeros(1,1001);

for n = 0:1000
    bb5(n+1) = q^n;
end

ech92_1000 = zeros(row, height);

for i = 1:row
    w = conv(echart(i,:), bb);
    ech92_1000(i,:) = w(1:height);
end
for i = 1:height
    w = conv(ech92_1000(:,i), bb);
    ech92_1000(:,i) = w(1:row);
end

reconstructed_1000 = zeros(row, height);
for i = 1:row
    w = conv(ech92_1000(i,:), bb5);
    reconstructed_1000(i,:) = w(1:height);
end
for i = 1:height
    w = conv(reconstructed_1000(:,i), bb5);
    reconstructed_1000(:,i) = w(1:row);
end


figure('Name', '3.2.2 - Distorting and Restoring Images: 1000', ...
    'units','normalized', 'outerposition', [0 0.50 1 0.5])
subplot(1,3,1)
imshow(echart)
title('Original Image')

subplot(1,3,2)
imshow(ech92_1000)
title('ech92\_1000')

subplot(1,3,3)
imshow(reconstructed_1000)
title('Reconstructed echart\_1000')

```

```
%{
As M increased, the errors approach zero. The higher the M value, the
better the
reconstructed image will be.
%}
```



worst case error (wce)

```
wce_10 = max(max(echart - reconstructed_10));
wce_15 = max(max(echart - reconstructed_15));
wce_30 = max(max(echart - reconstructed_30));
wce_1000 = max(max(echart - reconstructed_1000));

fprintf('Worse case error of M = 10: %s\n', num2str(wce_10))
fprintf('Worse case error of M = 15: %s\n', num2str(wce_15))
fprintf('Worse case error of M = 30: %s\n', num2str(wce_30))
fprintf('Worse case error of M = 1000: %s\n', num2str(wce_1000))
```

Worse case error of $M = 10$: 203.8151
Worse case error of $M = 15$: 134.3307
Worse case error of $M = 30$: 38.4585
Worse case error of $M = 1000$: $3.1264e-13$

Published with MATLAB® R2018b