

Platform-based Programming

#3 Classes

- 1) Class definition
- 2) constructor
- 3) Method definition
- 4) toString(), equals(), hashCode()

2019년 2학기

Program Output

- ❖ Make a Java program that can manage students for a school

```
Enter Command String! add
```

```
James 1
```

```
Enter Command String! list
```

```
School Name: PNU Student Count: 1
```

```
[James, 1학년]
```

```
Enter Command String! add
```

```
Brown 2
```

```
Enter Command String! list
```

```
School Name: PNU Student Count: 2
```

```
[James, 1학년]
```

```
[Brown, 2학년]
```

Enter Command String! find

Brown 2

[Brown, 2학년]

Enter Command String! find

Brown 1

Student Not Found with name Brown and year 1

Enter Command String! add

Kim 4

Enter Command String! list

School Name: PNU Student Count: 3

[James, 1학년]

[Brown, 2학년]

[Kim, 4학년]

Enter Command String! clear


Enter Command String! list

School Name: PNU Student Count: 0

```
Enter Command String! find
Brown 2
Student Not Found with name Brown and year 2
Enter Command String! add
Brown 2
Enter Command String! find
Brown 2
[Brown, 2학년]
Enter Command String! list
School Name: PNU Student Count: 1
[Brown, 2학년]

Enter Command String! find
brown 2
Student Not Found with name brown and year 2
Enter Command String! quit
Bye
```

Problem Description



Program Skeleton

- ❖ Write a program by extending the following code!
 - Just add you code! Do not modify/remove the given code

```
// SchoolTest.java
enum OperationKind {
    ...
}
public class SchoolTest {
    private static Scanner scanner = new Scanner(System.in);

    public static void main(String[] args) {
        School pnu = new School("PNU", 100) ;
        while ( true ) {
            final OperationKind op = getOperation() ;
            if ( op == OperationKind.QUIT ) {
                System.out.println("Bye") ;
                break;
            }
            if ( op == OperationKind.INVALID ) {
                System.out.println("Invalid Operation!") ;
                continue ;
            }
        }
    }
}
```

```
public class SchoolTest {  
    private static Scanner scanner = new Scanner(System.in);  
  
    public static void main(String[] args) {  
        School pnu = new School("PNU", 100) ;  
        while ( true ) {  
            // same code in the previous slide  
  
            switch ( op ) {  
                case ADD : {  
                    Student newStudent = createStudent() ;  
                    pnu.addStudent(newStudent) ;  
                    break ;  
                }  
                case FIND: findStudent(pnu) ; break ;  
                case CLEAR: pnu.removeAllStudent() ; break ;  
                case LIST: System.out.println(pnu) ; break ;  
            }  
        }  
    }  
}
```

```

private static void findStudent(final School school) {
    final String studentName = scanner.next() ;
    final int schoolYear = scanner.nextInt() ;
    final Student foundStudent =
        school.findStudent(studentName, schoolYear) ;
    if ( foundStudent != null )
        System.out.println(foundStudent) ;
    else
        System.out.println("Student Not Found with name " + studentName +
            " and year " + schoolYear) ;
}

private static Student createStudent() {
    final String studentName = scanner.next() ;
    final int schoolYear = scanner.nextInt() ;
    return new Student(studentName, schoolYear) ;
}
}

```

Enter Command String! find
Brown 2
[Brown, 2학년]

// School.java

```
public class School {  
    private String name ;  
    private int limit ;  
  
    private Student[] students ;  
    private int studentCount ;
```

```
    public String toString() {  
        String msg = "School Name: " + name + " Student Count: "  
            + studentCount + "\n" ;  
  
        for ( int i = 0 ; i < studentCount ; i ++ ) {  
            msg += "\t" + students[i] + "\n" ;  
        }  
        return msg ;  
    }  
}
```

```
// other methods including constructor, equals(), hashCode()
```

```
School Name: PNU Student Count: 3  
[James, 1학년]  
[Brown, 2학년]  
[Kim, 4학년]
```

// Student.java

```
public class Student {  
    private String name ;  
    private int year ;
```

```
    // other methods including constructor,  
    // toString(), equals(), hashCode()
```

```
}
```