

CPSVerification

By Jonathan

May 8, 2018

Contents

1	VC_diffKAD	3
1.1	Stack Theories Preliminaries: VC_KAD and ODEs	3
1.2	VC_diffKAD Preliminaries	5
1.2.1	(primed) dSolve preliminaries	6
1.2.2	dInv preliminaries	11
1.3	Phase Space Relational Semantics	14
1.4	Derivation of Differential Dynamic Logic Rules	16
1.4.1	"Differential Weakening"	16
1.4.2	"Differential Cut"	16
1.4.3	"Solve Differential Equation"	17
1.4.4	"Differential Invariant."	24
1.5	Rules Testing	32

1 VC_diffKAD

```
theory VC-diffKAD-auxiliarities
imports
  Main
  afpModified/VC-KAD
  Ordinary-Differential-Equations.IVP/Initial-Value-Problem
```

```
begin
```

1.1 Stack Theories Preliminaries: VC_KAD and ODEs

To make our notation less code-like and more mathematical we declare:

```
no-notation Archimedean-Field.ceiling ( $\lceil \cdot \rceil$ )
and Archimedean-Field.floor ( $\lfloor \cdot \rfloor$ )
and Set.image (  $'$  )
and Range-Semiring.antirange-semiring-class.ars-r ( $r$ )
```

```
notation p2r ( $\lceil \cdot \rceil$ )
and r2p ( $\lfloor \cdot \rfloor$ )
```

and *Set.image* ($\lambda \cdot \cdot$)
and *Product-Type.prod.fst* (π_1)
and *Product-Type.prod.snd* (π_2)
and *List.zip* (**infixl** \otimes 63)
and *rel-ad* (Δ^c_1)

This and more notation is explained by the following lemma.

lemma shows $\lceil P \rceil = \{(s, s) \mid s. P\ s\}$
and $\lfloor R \rfloor = (\lambda x. x \in r2s\ R)$
and $r2s\ R = \{x \mid x. \exists y. (x, y) \in R\}$
and $\pi_1\ (x, y) = x \wedge \pi_2\ (x, y) = y$
and $\Delta^c_1\ R = \{(x, x) \mid x. \nexists y. (x, y) \in R\}$
and $wp\ R\ Q = \Delta^c_1\ (R ; \Delta^c_1\ Q)$
and $[x1, x2, x3, x4] \otimes [y1, y2] = [(x1, y1), (x2, y2)]$
and $\{a..b\} = \{x. a \leq x \wedge x \leq b\}$
and $\{a <..< b\} = \{x. a < x \wedge x < b\}$
and $(x\ solves\ ode\ f)\ \{0..t\}\ R = ((x\ has\ vderiv\ on\ (\lambda t. f\ t\ (x\ t)))\ \{0..t\} \wedge x \in \{0..t\} \rightarrow R)$
and $f \in A \rightarrow B = (f \in \{f. \forall x. x \in A \longrightarrow (f\ x) \in B\})$
and $(x\ has\ vderiv\ on\ x')\ \{0..t\} =$
 $(\forall r \in \{0..t\}. (x\ has\ vector\ derivative\ x'\ r)\ (at\ r\ within\ \{0..t\}))$
and $(x\ has\ vector\ derivative\ x'\ r)\ (at\ r\ within\ \{0..t\}) =$
 $(x\ has\ derivative\ (\lambda x. x *_{\mathbb{R}} x'\ r))\ (at\ r\ within\ \{0..t\})$
apply(*simp-all add: p2r-def r2p-def rel-ad-def rel-antidomain-kleene-algebra.fbox-def*
solves-ode-def has-vderiv-on-def)
apply(*blast, fastforce, fastforce*)
using *has-vector-derivative-def by auto*

Observe also, the following consequences and facts:

proposition $\pi_1\ \lfloor R \rfloor = r2s\ R$
by (*simp add: fst-eq-Domain*)

proposition $\Delta^c_1\ R = Id - \{(s, s) \mid s. s \in (\pi_1\ \lfloor R \rfloor)\}$
by(*simp add: image-def rel-ad-def, fastforce*)

proposition $P \subseteq Q \implies wp\ R\ P \subseteq wp\ R\ Q$
by(*simp add: rel-antidomain-kleene-algebra.dka.dom-iso rel-antidomain-kleene-algebra.fbox-iso*)

proposition *boxProgrPred-IsProp*: $wp\ R\ \lceil P \rceil \subseteq Id$
by(*simp add: rel-antidomain-kleene-algebra.a-subid' rel-antidomain-kleene-algebra.addual.bbox-def*)

proposition *rdom-p2r-contents*: $(a, b) \in rdom\ \lceil P \rceil = ((a = b) \wedge P\ a)$

proof–

have $(a, b) \in rdom\ \lceil P \rceil = ((a = b) \wedge (a, a) \in rdom\ \lceil P \rceil)$ **using** *p2r-subid by fastforce*

also have $\dots = ((a = b) \wedge (a, a) \in \lceil P \rceil)$ **by** *simp*

also have $\dots = ((a = b) \wedge P\ a)$ **by** (*simp add: p2r-def*)

ultimately show *?thesis* **by** *simp*

qed

proposition *rel-ad-rule1*: $(x, x) \notin \Delta^c_1 \lceil P \rceil \implies P\ x$
by(*auto simp: rel-ad-def p2r-subid p2r-def*)

proposition *rel-ad-rule2*: $(x, x) \in \Delta^c_1 \lceil P \rceil \implies \neg P\ x$
by(*metis ComplD VC-KAD.p2r-neg-hom rel-ad-rule1 empty-iff mem-Collect-eq p2s-neg-hom*

rel-antidomain-kleene-algebra.a-one rel-antidomain-kleene-algebra.am1 relcomp.relcompI)

proposition *rel-ad-rule3*: $R \subseteq Id \implies (x, x) \notin R \implies (x, x) \in \Delta^c_1 R$
by(*metis IdI Un-iff d-p2r rel-antidomain-kleene-algebra.addual.ars3*
rel-antidomain-kleene-algebra.addual.ars-r-def rpr)

proposition *rel-ad-rule4*: $(x, x) \in R \implies (x, x) \notin \Delta^c_1 R$
by(*metis empty-iff rel-antidomain-kleene-algebra.addual.ars1 relcomp.relcompI*)

proposition *boxProgrPred-chrctrztn*: $(x, x) \in wp\ R \lceil P \rceil = (\forall\ y. (x, y) \in R \longrightarrow P\ y)$
by(*metis boxProgrPred-IsProp rel-ad-rule1 rel-ad-rule2 rel-ad-rule3*
rel-ad-rule4 d-p2r wp-simp wp-trafo)

proposition *cons-eq-zipE*:
 $(x, y) \# tail = xList \otimes yList \implies \exists xTail\ yTail. x \# xTail = xList \wedge y \# yTail = yList$
by(*induction xList, simp-all, induction yList, simp-all*)

proposition *set-zip-left-rightD*:
 $(x, y) \in set\ (xList \otimes yList) \implies x \in set\ xList \wedge y \in set\ yList$
apply(*rule conjI*)
apply(*rule-tac y=y and ys=yList in set-zip-leftD, simp*)
apply(*rule-tac x=x and xs=xList in set-zip-rightD, simp*)
done

declare *zip-map-fst-snd* [*simp*]

1.2 VC_diffKAD Preliminaries

In dL, the set of possible program variables is split in two, the set of variables V and their primed counterparts V' . To implement this, we use Isabelle's string-type and define a function that primes a given string. We then define the set of primed-strings based on it.

definition *vdiff* :: *string* \Rightarrow *string* (∂ - [55] 70) **where**
 $(\partial\ x) = "d["@x@"$

definition *varDiffs* :: *string set* **where**
 $varDiffs = \{y. \exists\ x. y = \partial\ x\}$

proposition *vdiff-inj*: $(\partial x) = (\partial y) \implies x = y$
by (*simp add: vdiff-def*)

proposition *vdiff-noFixPoints*: $x \neq (\partial x)$
by (*simp add: vdiff-def*)

lemma *varDiffsI*: $x = (\partial z) \implies x \in \text{varDiffs}$
by (*simp add: varDiffs-def vdiff-def*)

lemma *varDiffsE*:
assumes $x \in \text{varDiffs}$
obtains y **where** $x = \text{"d["} @ y @ \text{"}"}$
using *assms unfolding varDiffs-def vdiff-def* **by** *auto*

proposition *vdiff-invarDiffs*: $(\partial x) \in \text{varDiffs}$
by (*simp add: varDiffsI*)

1.2.1 (primed) dSolve preliminaries

This subsection is to define a function that takes a system of ODEs (expressed as a list *xfList*), a presumed solution $uInput = [u_1, \dots, u_n]$, a state s and a time t , and outputs the induced flow $sol\ s[xfList \leftarrow uInput]\ t$.

abbreviation *varDiffs-to-zero* :: $\text{real store} \Rightarrow \text{real store} (sol)$ **where**
 $sol\ a \equiv (\text{override-on } a\ (\lambda x. 0))\ \text{varDiffs}$

proposition *varDiffs-to-zero-vdiff*[*simp*]: $(sol\ s)\ (\partial x) = 0$
apply (*simp add: override-on-def varDiffs-def*)
by *auto*

proposition *varDiffs-to-zero-beginning*[*simp*]: $\text{take } 2\ x \neq \text{"d["} \implies (sol\ s)\ x = s\ x$
apply (*simp add: varDiffs-def override-on-def vdiff-def*)
by *fastforce*

— Next, for each entry of the input-list, we update the state using said entry.

definition *vderiv-of* $f\ S = (SOME\ f'. (f\ \text{has-vderiv-on } f')\ S)$

primrec *state-list-upd* :: $((\text{real} \Rightarrow \text{real store} \Rightarrow \text{real}) \times \text{string} \times (\text{real store} \Rightarrow \text{real}))\ \text{list} \Rightarrow$
 $\text{real} \Rightarrow \text{real store} \Rightarrow \text{real store}$ **where**
 $\text{state-list-upd } []\ t\ s = s$
 $\text{state-list-upd } (uxf \# \text{tail})\ t\ s = (\text{state-list-upd } \text{tail}\ t\ s)$
 $(\quad (\pi_1\ (\pi_2\ uxf)) := (\pi_1\ uxf)\ t\ s,$
 $\quad \partial\ (\pi_1\ (\pi_2\ uxf)) := (\text{if } t = 0 \text{ then } (\pi_2\ (\pi_2\ uxf))\ s$
 $\text{else } vderiv-of\ (\lambda r. (\pi_1\ uxf)\ r\ s)\ \{0 <..< (2 *_{\mathbb{R}} t)\}\ t))$

abbreviation *state-list-cross-upd* :: *real store* \Rightarrow (*string* \times (*real store* \Rightarrow *real*)) *list*
 \Rightarrow
(*real* \Rightarrow *real store* \Rightarrow *real*) *list* \Rightarrow *real* \Rightarrow (*char list* \Rightarrow *real*) ($[-\leftarrow-]$ - [64,64,64]
63) **where**
 $s[xfList \leftarrow uInput] \ t \equiv state_list_upd \ (uInput \otimes xfList) \ t \ s$

proposition *state-list-cross-upd-empty*[*simp*]: ($s[\square \leftarrow list] \ t$) = *s*
by(*induction list*, *simp-all*)

lemma *inductive-state-list-cross-upd-its-vars*:
assumes *distHyp*:*distinct* ($\text{map } \pi_1 \ ((y, g) \# xftail)$)
and *varHyp*: $\forall xf \in \text{set}((y, g) \# xftail). \pi_1 \ xf \notin \text{varDiffs}$
and *indHyp*: $(u, x, f) \in \text{set} \ (utail \otimes xftail) \implies (s[xftail \leftarrow utail] \ t) \ x = u \ t \ s$
and *disjHyp*: $(u, x, f) = (v, y, g) \vee (u, x, f) \in \text{set} \ (utail \otimes xftail)$
shows ($s[(y, g) \# xftail \leftarrow v \# utail] \ t$) $x = u \ t \ s$
using *disjHyp* **proof**
 assume $(u, x, f) = (v, y, g)$
 hence ($s[(y, g) \# xftail \leftarrow v \# utail] \ t$) $x = ((s[xftail \leftarrow utail] \ t)(x := u \ t \ s,$
 $\partial \ x := \text{if } t = 0 \text{ then } f \ s \text{ else } v \text{deriv-of } (\lambda \ r. \ u \ r \ s) \ \{0 <..< (2 *_{\mathcal{R}} t)\} \ t)) \ x \text{ by}$
simp
 also have $\dots = u \ t \ s$ **by** (*simp add: vdiff-def*)
 ultimately show *?thesis* **by** *simp*
next
 assume *yTailHyp*: $(u, x, f) \in \text{set} \ (utail \otimes xftail)$
 from this and indHyp have $\exists:(s[xftail \leftarrow utail] \ t) \ x = u \ t \ s$ **by** *fastforce*
 from yTailHyp and distHyp have $2:y \neq x$ **using** *set- zip-left-rightD* **by** *force*
 from yTailHyp and varHyp have $1:x \neq \partial \ y$
 using *set- zip-left-rightD* *vdiff-invarDiffs* **by** *fastforce*
 from 1 and 2 have ($s[(y, g) \# xftail \leftarrow v \# utail] \ t$) $x = (s[xftail \leftarrow utail] \ t) \ x$
by *simp*
 thus *?thesis* **using** 3 **by** *simp*
qed

theorem *state-list-cross-upd-its-vars*:
assumes *distinctHyp*:*distinct* ($\text{map } \pi_1 \ xfList$)
and *lengthHyp*: $\text{length } xfList = \text{length } uInput$
and *varsHyp*: $\forall \ xf \in \text{set } xfList. \pi_1 \ xf \notin \text{varDiffs}$
and *its-var*: $(u, x, f) \in \text{set} \ (uInput \otimes xfList)$
shows ($s[xfList \leftarrow uInput] \ t$) $x = u \ t \ s$
using *assms* **apply**(*induct xfList uInput arbitrary: x rule: list-induct2', simp,*
simp, simp)
by(*clarify, rule inductive-state-list-cross-upd-its-vars, simp-all*)

lemma *override-on-upd*: $x \in X \implies (\text{override-on } f \ g \ X)(x := z) = (\text{override-on } f$
 $(g(x := z)) \ X)$
by (*rule ext, simp add: override-on-def*)

lemma *inductive-state-list-cross-upd-its-dvars*:
assumes $\exists g. (s[xfTail \leftarrow uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$

and $\forall xf \in \text{set } (xf \# xfTail). \pi_1 xf \notin \text{varDiffs}$
and $\forall uxf \in \text{set } (u \# uTail \otimes xf \# xfTail). \pi_1 uxf \ 0 \ s = s \ (\pi_1 \ (\pi_2 \ uxf))$
shows $\exists g. (s[xf \# xfTail \leftarrow u \# uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$
proof –
let $?gLHS = (s[(xf \# xfTail) \leftarrow (u \# uTail)] \ 0)$
have $\text{observ} : \partial (\pi_1 xf) \in \text{varDiffs}$ **by** $(\text{auto simp: varDiffs-def})$
from $\text{assms}(1)$ **obtain** g **where** $(s[xfTail \leftarrow uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$
by force
then have $?gLHS = (\text{override-on } s \ g \ \text{varDiffs})(\pi_1 xf := u \ 0 \ s, \partial (\pi_1 xf) := \pi_2 \ xf \ s)$ **by** simp
also have $\dots = (\text{override-on } s \ g \ \text{varDiffs})(\partial (\pi_1 xf) := \pi_2 \ xf \ s)$
using $\text{override-on-def varDiffs-def assms}$ **by** auto
also have $\dots = (\text{override-on } s \ (g(\partial (\pi_1 xf) := \pi_2 \ xf \ s)) \ \text{varDiffs})$
using observ **and** override-on-upd **by** force
ultimately show $?thesis$ **by** auto
qed

theorem *state-list-cross-upd-its-dvars*:
assumes $\text{lengthHyp} : \text{length } xfList = \text{length } uInput$
and $\text{varsHyp} : \forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$
and $\text{solHyp1} : \forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 uxf) \ 0 \ s = s \ (\pi_1 \ (\pi_2 \ uxf))$
shows $\exists g. (s[xfList \leftarrow uInput] \ 0) = (\text{override-on } s \ g \ \text{varDiffs})$
using assms **proof** $(\text{induct } xfList \ uInput \ \text{rule: list-induct2'})$
case 1
have $(s[\square \leftarrow \square] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding override-on-def **by** simp
thus $?case$ **by** metis
next
case $(2 \ xf \ xfTail)$
have $(s[(xf \# xfTail) \leftarrow \square] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding override-on-def **by** simp
thus $?case$ **by** metis
next
case $(3 \ u \ utail)$
have $(s[\square \leftarrow utail] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding override-on-def **by** simp
thus $?case$ **by** force
next
case $(4 \ xf \ xfTail \ u \ uTail)$
then have $\exists g. (s[xfTail \leftarrow uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$ **by** simp
thus $?case$ **using** $\text{inductive-state-list-cross-upd-its-dvars } 4.\text{prems}$ **by** blast
qed

lemma *vderiv-unique-within-open-interval*:
assumes $(f \text{ has-vderiv-on } f') \ \{0 <..< t\}$ **and** $t > 0$
and $(f \text{ has-vderiv-on } f'') \ \{0 <..< t\}$ **and** $\text{tauHyp} : \tau \in \{0 <..< t\}$
shows $f' \ \tau = f'' \ \tau$
using assms **apply** $(\text{simp add: has-vderiv-on-def has-vector-derivative-def})$
using $\text{frechet-derivative-unique-within-open-interval}$ **by** $(\text{metis box-real}(1) \ \text{scaleR-one})$

tauHyp)

lemma *has-vderiv-on-cong-open-interval*:

assumes *gHyp*: $\forall \tau > 0. f \tau = g \tau$ **and** *tHyp*: $t > 0$

and *fHyp*: $(f \text{ has-vderiv-on } f') \{0 < \cdot < t\}$

shows $(g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$

proof–

from *gHyp* **have** $\bigwedge \tau. \tau \in \{0 < \cdot < t\} \implies f \tau = g \tau$ **using** *tHyp* **by** *force*

hence $\text{eqDs}:(f \text{ has-vderiv-on } f') \{0 < \cdot < t\} = (g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$

apply(*rule-tac has-vderiv-on-cong*) **by** *auto*

thus $(g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$ **using** *eqDs fHyp* **by** *simp*

qed

lemma *closed-vderiv-on-cong-to-open-vderiv*:

assumes *gHyp*: $\forall \tau > 0. f \tau = g \tau$

and *fHyp*: $\forall t \geq 0. (f \text{ has-vderiv-on } f') \{0 \leq \cdot \leq t\}$

and *tHyp*: $t > 0$ **and** *cHyp*: $c > 1$

shows $\text{vderiv-of } g \{0 < \cdot < (c *_R t)\} t = f' t$

proof–

have *ctHyp*: $c \cdot t > 0$ **using** *tHyp* **and** *cHyp* **by** *auto*

from *fHyp* **have** $(f \text{ has-vderiv-on } f') \{0 < \cdot < c \cdot t\}$ **using** *has-vderiv-on-subset*

by (*metis greaterThanLessThan-subseteq-atLeastAtMost-iff less-eq-real-def*)

then have *derivHyp*: $(g \text{ has-vderiv-on } f') \{0 < \cdot < c \cdot t\}$

using *gHyp ctHyp* **and** *has-vderiv-on-cong-open-interval* **by** *blast*

hence *f'Hyp*: $\forall f''. (g \text{ has-vderiv-on } f'') \{0 < \cdot < c \cdot t\} \longrightarrow (\forall \tau \in \{0 < \cdot < c \cdot t\}. f' \tau = f'' \tau)$

f' \tau = f'' \tau)

using *vderiv-unique-within-open-interval ctHyp* **by** *blast*

also have $(g \text{ has-vderiv-on } (\text{vderiv-of } g \{0 < \cdot < (c *_R t)\})) \{0 < \cdot < c \cdot t\}$

by(*simp add: vderiv-of-def, metis derivHyp someI-ex*)

ultimately show $\text{vderiv-of } g \{0 < \cdot < c *_R t\} t = f' t$ **using** *tHyp cHyp* **by** *force*

qed

lemma *vderiv-of-to-sol-its-vars*:

assumes *distinctHyp*:*distinct* (*map* π_1 *xfList*)

and *lengthHyp*:*length* *xfList* = *length* *uInput*

and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$

and *solHyp2*: $\forall t \geq 0. ((\lambda \tau. (\text{sol } s[xfList \leftarrow uInput] \tau) x)$

has-vderiv-on $(\lambda \tau. f (\text{sol } s[xfList \leftarrow uInput] \tau))) \{0 \leq \cdot \leq t\}$

and *tHyp*: $t > 0$ **and** *uxfHyp*: $(u, x, f) \in \text{set } (uInput \otimes xfList)$

shows $\text{vderiv-of } (\lambda \tau. u \tau (\text{sol } s)) \{0 < \cdot < (2 *_R t)\} t = f (\text{sol } s[xfList \leftarrow uInput] t)$

apply(*rule-tac f*=($\lambda \tau. (\text{sol } s[xfList \leftarrow uInput] \tau) x$) **in** *closed-vderiv-on-cong-to-open-vderiv*)

subgoal using *assms* **and** *state-list-cross-upd-its-vars* **by** *metis*

by(*simp-all add: solHyp2 tHyp*)

lemma *inductive-to-sol-zero-its-dvars*:

assumes *eqFuncs*: $\forall s. \forall g. \forall xf \in \text{set } ((x, f) \# xfs). \pi_2 xf (\text{override-on } s g \text{ varDiffs})$

= $\pi_2 xf s$

and *eqLengths*:*length* $((x, f) \# xfs) = \text{length } (u \# us)$

and *distinct*:*distinct* (*map* π_1 ($(x, f) \# xfs$))
and *vars*: $\forall xf \in set \ ((x, f) \# xfs). \pi_1 \ xf \notin varDiffs$
and *solHyp1*: $\forall uxf \in set \ ((u \# us) \otimes ((x, f) \# xfs)). \pi_1 \ uxf \ 0 \ (sol \ s) = sol \ s \ (\pi_1 \ (\pi_2 \ uxf))$
and *disjHyp*: $(y, g) = (x, f) \vee (y, g) \in set \ xfs$
and *indHyp*: $(y, g) \in set \ xfs \implies (sol \ s[xfs \leftarrow us] \ 0) \ (\partial \ y) = g \ (sol \ s[xfs \leftarrow us] \ 0)$
shows $(sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0) \ (\partial \ y) = g \ (sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0)$
proof–
from *assms* **obtain** *h1* **where** *h1Def*: $(sol \ s[((x, f) \# xfs) \leftarrow (u \# us)] \ 0) =$
 $(override-on \ (sol \ s) \ h1 \ varDiffs)$ **using** *state-list-cross-upd-its-dvars* **by** *blast*
from *disjHyp* **show** $(sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0) \ (\partial \ y) = g \ (sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0)$
proof
assume *eqHeads*: $(y, g) = (x, f)$
then have $g \ (sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0) = f \ (sol \ s)$ **using** *h1Def* *eqFuncs*
by *simp*
also have $\dots = (sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0) \ (\partial \ y)$ **using** *eqHeads* **by** *auto*
ultimately show *?thesis* **by** *linarith*
next
assume *tailHyp*: $(y, g) \in set \ xfs$
then have $y \neq x$ **using** *distinct* *set-zip-left-rightD* **by** *force*
hence $\partial \ x \neq \partial \ y$ **by** (*simp* *add: vdiff-def*)
have $x \neq \partial \ y$ **using** *vars* *vdiff-invarDiffs* **by** *auto*
obtain *h2* **where** *h2Def*: $(sol \ s[xfs \leftarrow us] \ 0) = override-on \ (sol \ s) \ h2 \ varDiffs$
using *state-list-cross-upd-its-dvars* *eqLengths* *distinct vars* **and** *solHyp1* **by** *force*
have $(sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0) \ (\partial \ y) = g \ (sol \ s[xfs \leftarrow us] \ 0)$
using *tailHyp* *indHyp* $\langle x \neq \partial \ y \rangle$ **and** $\langle \partial \ x \neq \partial \ y \rangle$ **by** *simp*
also have $\dots = g \ (override-on \ (sol \ s) \ h2 \ varDiffs)$ **using** *h2Def* **by** *simp*
also have $\dots = g \ (sol \ s)$ **using** *eqFuncs* **and** *tailHyp* **by** *force*
also have $\dots = g \ (sol \ s[(x, f) \# xfs \leftarrow u \# us] \ 0)$
using *eqFuncs* *h1Def* *tailHyp* **and** *eq-snd-iff* **by** *fastforce*
ultimately show *?thesis* **by** *simp*
qed
qed

lemma *to-sol-zero-its-dvars*:
assumes *funcsHyp*: $\forall \ s. \forall \ g. \forall \ xf \in set \ xfList. \pi_2 \ xf \ (override-on \ s \ g \ varDiffs)$
 $= \pi_2 \ xf \ s$
and *distinctHyp*:*distinct* (*map* $\pi_1 \ xfList$)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in set \ xfList. \pi_1 \ xf \notin varDiffs$
and *solHyp1*: $\forall \ uxf \in set \ (uInput \otimes xfList). (\pi_1 \ uxf) \ 0 \ (sol \ s) = (sol \ s) \ (\pi_1 \ (\pi_2 \ uxf))$
and *ygHyp*: $(y, g) \in set \ xfList$
shows $(sol \ s[xfList \leftarrow uInput] \ 0) \ (\partial \ y) = g \ (sol \ s[xfList \leftarrow uInput] \ 0)$
using *assms* **apply** (*induct* *xfList* *uInput* *rule: list-induct2'*, *simp*, *simp*, *simp*, *clarify*)
by (*rule inductive-to-sol-zero-its-dvars*, *simp-all*)

lemma *inductive-to-sol-greater-than-zero-its-dvars*:
assumes *lengthHyp*: $\text{length } ((y, g) \# xfs) = \text{length } (v \# vs)$
and *distHyp*: $\text{distinct } (\text{map } \pi_1 ((y, g) \# xfs))$
and *varHyp*: $\forall xf \in \text{set } ((y, g) \# xfs). \pi_1 xf \notin \text{varDiffs}$
and *indHyp*: $(u, x, f) \in \text{set } (vs \otimes xfs) \implies (s[xfs \leftarrow vs] t)(\partial x) = \text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < 2 *_{\mathbb{R}} t\} \ t$
and *disjHyp*: $(v, y, g) = (u, x, f) \vee (u, x, f) \in \text{set } (vs \otimes xfs)$ **and** *tHyp*: $t > 0$
shows $(s[(y, g) \# xfs \leftarrow v \# vs] t) (\partial x) = \text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < 2 *_{\mathbb{R}} t\} \ t$
proof–
let *?lhs* = $((s[xfs \leftarrow vs] t)(y := v \ t \ s, \partial y := \text{vderiv-of } (\lambda r. v \ r \ s) \{0 < .. < (2 \cdot t)\} t)) (\partial x)$
let *?rhs* = $\text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < (2 \cdot t)\} \ t$
have $(s[(y, g) \# xfs \leftarrow v \# vs] t) (\partial x) = ?lhs$ **using** *tHyp* **by** *simp*
also have $\text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < 2 *_{\mathbb{R}} t\} \ t = ?rhs$ **by** *simp*
ultimately have *obs*:*?thesis* = $(?lhs = ?rhs)$ **by** *simp*
from *disjHyp* **have** *?lhs* = *?rhs*
proof
assume *uxfEq*: $(v, y, g) = (u, x, f)$
then have *?lhs* = $\text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < (2 \cdot t)\} \ t$ **by** *simp*
also have $\text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < (2 \cdot t)\} \ t = ?rhs$ **using** *uxfEq* **by** *simp*
ultimately show *?lhs* = *?rhs* **by** *simp*
next
assume *sygTail*: $(u, x, f) \in \text{set } (vs \otimes xfs)$
from this have $y \neq x$ **using** *distHyp* *set-zip-left-rightD* **by** *force*
hence $\partial x \neq \partial y$ **by** (*simp add: vdiff-def*)
have $y \neq \partial x$ **using** *varHyp* **using** *vdiff-invarDiffs* **by** *auto*
then have *?lhs* = $(s[xfs \leftarrow vs] t) (\partial x)$ **using** $\langle y \neq \partial x \rangle$ **and** $\langle \partial x \neq \partial y \rangle$ **by** *simp*
also have $(s[xfs \leftarrow vs] t) (\partial x) = ?rhs$ **using** *indHyp* *sygTail* **by** *simp*
ultimately show *?lhs* = *?rhs* **by** *simp*
qed
from this and obs show *?thesis* **by** *simp*
qed

lemma *to-sol-greater-than-zero-its-dvars*:
assumes *distinctHyp*: $\text{distinct } (\text{map } \pi_1 \text{xfList})$
and *lengthHyp*: $\text{length } \text{xfList} = \text{length } u\text{Input}$
and *varsHyp*: $\forall xf \in \text{set } \text{xfList}. \pi_1 xf \notin \text{varDiffs}$
and *uxfHyp*: $(u, x, f) \in \text{set } (u\text{Input} \otimes \text{xfList})$ **and** *tHyp*: $t > 0$
shows $(s[\text{xfList} \leftarrow u\text{Input}] t) (\partial x) = \text{vderiv-of } (\lambda r. u \ r \ s) \{0 < .. < (2 *_{\mathbb{R}} t)\} \ t$
using *assms* **apply** (*induct xfList uInput rule: list-induct2', simp, simp, simp, clarify*)
by (*rule-tac f=f in inductive-to-sol-greater-than-zero-its-dvars, auto*)

1.2.2 dInv preliminaries

Here, we introduce syntactic notation to talk about differential invariants.

no-notation *Antidomain-Semiring*.*antidomain-left-monoid-class.am-add-op* (**infixl** \oplus 65)

no-notation *Dioid.times-class.opp-mult* (**infixl** \odot 70)

no-notation *Lattices.inf-class.inf* (**infixl** \sqcap 70)
no-notation *Lattices.sup-class.sup* (**infixl** \sqcup 65)

datatype *trms* = *Const real* (t_C - [54] 70) | *Var string* (t_V - [54] 70) |
Mns trms (\ominus - [54] 65) | *Sum trms trms* (**infixl** \oplus 65) |
Mult trms trms (**infixl** \odot 68)

primrec *tval* :: *trms* \Rightarrow (*real store* \Rightarrow *real*) ($\llbracket - \rrbracket_t$ [55] 60) **where**

$\llbracket t_C r \rrbracket_t = (\lambda s. r)|$
 $\llbracket t_V x \rrbracket_t = (\lambda s. s x)|$
 $\llbracket \ominus \vartheta \rrbracket_t = (\lambda s. - (\llbracket \vartheta \rrbracket_t) s)|$
 $\llbracket \vartheta \oplus \eta \rrbracket_t = (\lambda s. (\llbracket \vartheta \rrbracket_t) s + (\llbracket \eta \rrbracket_t) s)|$
 $\llbracket \vartheta \odot \eta \rrbracket_t = (\lambda s. (\llbracket \vartheta \rrbracket_t) s \cdot (\llbracket \eta \rrbracket_t) s)|$

datatype *props* = *Eq trms trms* (**infixr** \doteq 60) | *Less trms trms* (**infixr** \prec 62) |
Leq trms trms (**infixr** \preceq 61) | *And props props* (**infixl** \sqcap 63) |
Or props props (**infixl** \sqcup 64)

primrec *pval* :: *props* \Rightarrow (*real store* \Rightarrow *bool*) ($\llbracket - \rrbracket_P$ [55] 60) **where**

$\llbracket \vartheta \doteq \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t) s = (\llbracket \eta \rrbracket_t) s)|$
 $\llbracket \vartheta \prec \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t) s < (\llbracket \eta \rrbracket_t) s)|$
 $\llbracket \vartheta \preceq \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t) s \leq (\llbracket \eta \rrbracket_t) s)|$
 $\llbracket \varphi \sqcap \psi \rrbracket_P = (\lambda s. (\llbracket \varphi \rrbracket_P) s \wedge (\llbracket \psi \rrbracket_P) s)|$
 $\llbracket \varphi \sqcup \psi \rrbracket_P = (\lambda s. (\llbracket \varphi \rrbracket_P) s \vee (\llbracket \psi \rrbracket_P) s)|$

primrec *tdiff* :: *trms* \Rightarrow *trms* (∂_t - [54] 70) **where**

$(\partial_t t_C r) = t_C 0|$
 $(\partial_t t_V x) = t_V (\partial x)|$
 $(\partial_t \ominus \vartheta) = \ominus (\partial_t \vartheta)|$
 $(\partial_t (\vartheta \oplus \eta)) = (\partial_t \vartheta) \oplus (\partial_t \eta)|$
 $(\partial_t (\vartheta \odot \eta)) = ((\partial_t \vartheta) \odot \eta) \oplus (\vartheta \odot (\partial_t \eta))$

primrec *pdiff* :: *props* \Rightarrow *props* (∂_P - [54] 70) **where**

$(\partial_P (\vartheta \doteq \eta)) = ((\partial_t \vartheta) \doteq (\partial_t \eta))|$
 $(\partial_P (\vartheta \prec \eta)) = ((\partial_t \vartheta) \prec (\partial_t \eta))|$
 $(\partial_P (\vartheta \preceq \eta)) = ((\partial_t \vartheta) \preceq (\partial_t \eta))|$
 $(\partial_P (\varphi \sqcap \psi)) = (\partial_P \varphi) \sqcap (\partial_P \psi)|$
 $(\partial_P (\varphi \sqcup \psi)) = (\partial_P \varphi) \sqcap (\partial_P \psi)$

primrec *trmVars* :: *trms* \Rightarrow *string set* **where**

trmVars ($t_C r$) = $\{ \}$ |
trmVars ($t_V x$) = $\{ x \}$ |
trmVars ($\ominus \vartheta$) = *trmVars* ϑ |
trmVars ($\vartheta \oplus \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η |
trmVars ($\vartheta \odot \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η

fun *substList* :: (*string* \times *trms*) *list* \Rightarrow *trms* \Rightarrow *trms* ($\langle - \rangle$ [54] 80) **where**

$xtList \langle t_C r \rangle = t_C r|$
 $\llbracket \langle t_V x \rangle = t_V x|$

$((y, \xi) \# xtTail) \langle Var\ x \rangle = (if\ x = y\ then\ \xi\ else\ xtTail \langle Var\ x \rangle) |$
 $xtList \langle \ominus\ \vartheta \rangle = \ominus\ (xtList \langle \vartheta \rangle) |$
 $xtList \langle \vartheta \oplus \eta \rangle = (xtList \langle \vartheta \rangle) \oplus (xtList \langle \eta \rangle) |$
 $xtList \langle \vartheta \odot \eta \rangle = (xtList \langle \vartheta \rangle) \odot (xtList \langle \eta \rangle) |$

proposition *substList-on-compl-of-varDiffs*:
assumes $trmVars\ \eta \subseteq (UNIV - varDiffs)$
assumes $set\ (map\ \pi_1\ xtList) \subseteq varDiffs$
shows $xtList \langle \eta \rangle = \eta$
using *assms apply*(*induction* η , *simp-all* *add*: *varDiffs-def*)
by(*induction* *xtList*, *auto*)

lemma *substList-help1*: $set\ (map\ \pi_1\ ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes\ uInput)) \subseteq varDiffs$
apply(*induct* *xfList* *uInput* *rule*: *list-induct2'*, *simp-all* *add*: *varDiffs-def*)
by *auto*

lemma *substList-help2*:
assumes $trmVars\ \eta \subseteq (UNIV - varDiffs)$
shows $((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes\ uInput) \langle \eta \rangle = \eta$
using *assms substList-help1 substList-on-compl-of-varDiffs* **by** *blast*

lemma *substList-cross-vdiff-on-non-occurring-var*:
assumes $x \notin set\ list1$
shows $((map\ vdiff\ list1) \otimes\ list2) \langle t_V\ (\partial\ x) \rangle = t_V\ (\partial\ x)$
using *assms apply*(*induct* *list1* *list2* *rule*: *list-induct2'*, *simp*, *simp*, *clarsimp*)
by(*simp* *add*: *vdiff-def*)

primrec *propVars* :: *props* \Rightarrow *string set* **where**
 $propVars\ (\vartheta \doteq \eta) = trmVars\ \vartheta \cup trmVars\ \eta |$
 $propVars\ (\vartheta \prec \eta) = trmVars\ \vartheta \cup trmVars\ \eta |$
 $propVars\ (\vartheta \preceq \eta) = trmVars\ \vartheta \cup trmVars\ \eta |$
 $propVars\ (\varphi \sqcap \psi) = propVars\ \varphi \cup propVars\ \psi |$
 $propVars\ (\varphi \sqcup \psi) = propVars\ \varphi \cup propVars\ \psi$

primrec *subspList* :: (*string* \times *trms*) *list* \Rightarrow *props* \Rightarrow *props* ($- \vdash -$ [54] 80) **where**
 $xtList \vdash \vartheta \doteq \eta \vdash = ((xtList \langle \vartheta \rangle) \doteq (xtList \langle \eta \rangle)) |$
 $xtList \vdash \vartheta \prec \eta \vdash = ((xtList \langle \vartheta \rangle) \prec (xtList \langle \eta \rangle)) |$
 $xtList \vdash \vartheta \preceq \eta \vdash = ((xtList \langle \vartheta \rangle) \preceq (xtList \langle \eta \rangle)) |$
 $xtList \vdash \varphi \sqcap \psi \vdash = ((xtList \vdash \varphi \vdash) \sqcap (xtList \vdash \psi \vdash)) |$
 $xtList \vdash \varphi \sqcup \psi \vdash = ((xtList \vdash \varphi \vdash) \sqcup (xtList \vdash \psi \vdash))$

end
theory *VC-diffKAD*
imports *VC-diffKAD-auxiliarities*

begin

1.3 Phase Space Relational Semantics

definition *solvesStoreIVP* :: (*real* \Rightarrow *real store*) \Rightarrow (*string* \times (*real store* \Rightarrow *real*))
list \Rightarrow
real store \Rightarrow (*real store pred*) \Rightarrow *bool*
 ((- *solvesTheStoreIVP* - *withInitState* - *andGuard* -) [70, 70, 70, 70] 68) **where**
solvesStoreIVP φ_S *xfList* *s* *G* \equiv
 (* *F* preserves the guard statement and *F* sends *vdiffs*-in-list to *derivs*. *)
 ($\forall t \geq 0. G (\varphi_S t) \wedge (\forall xf \in \text{set } xfList. \varphi_S t (\partial (\pi_1 xf)) = \pi_2 xf (\varphi_S t)) \wedge$
 (* *F* preserves the rest of the variables and *F* sends *derivs* of constants to 0. *)
 ($\forall y. (y \notin (\pi_1 \downarrow \text{set } xfList)) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y) \wedge$
 ($y \notin (\pi_1 \downarrow \text{set } xfList) \longrightarrow \varphi_S t (\partial y) = 0)) \wedge$
 (* *F* solves the induced IVP. *)
 ($\forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\}$
UNIV \wedge
 $\varphi_S 0 (\pi_1 xf) = s(\pi_1 xf)))$

lemma *solves-store-ivpI*:

assumes $\forall t \geq 0. G (\varphi_S t)$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. (\varphi_S t (\partial (\pi_1 xf))) = (\pi_2 xf) (\varphi_S t)$
and $\forall t \geq 0. \forall y. y \notin (\pi_1 \downarrow \text{set } xfList) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y$
and $\forall t \geq 0. \forall y. y \notin (\pi_1 \downarrow \text{set } xfList) \longrightarrow \varphi_S t (\partial y) = 0$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\} \text{ UNIV}$
and $\forall xf \in \text{set } xfList. \varphi_S 0 (\pi_1 xf) = s(\pi_1 xf)$
shows $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s \text{ andGuard } G$
apply(*simp add: solvesStoreIVP-def, safe*)
using *assms apply simp-all*
by(*force, force, force*)

named-theorems *solves-store-ivpE* elimination rules for *solvesStoreIVP*

lemma [*solves-store-ivpE*]:

assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s \text{ andGuard } G$
shows $\forall t \geq 0. G (\varphi_S t)$
and $\forall t \geq 0. \forall y. y \notin (\pi_1 \downarrow \text{set } xfList) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y$
and $\forall t \geq 0. \forall y. y \notin (\pi_1 \downarrow \text{set } xfList) \longrightarrow \varphi_S t (\partial y) = 0$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. (\varphi_S t (\partial (\pi_1 xf))) = (\pi_2 xf) (\varphi_S t)$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\} \text{ UNIV}$
and $\forall xf \in \text{set } xfList. \varphi_S 0 (\pi_1 xf) = s(\pi_1 xf)$
using *assms solvesStoreIVP-def by auto*

lemma [*solves-store-ivpE*]:

assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s \text{ andGuard } G$
shows $\forall y. y \notin \text{varDiffs} \longrightarrow \varphi_S 0 y = s y$
proof(*clarify, rename-tac x*)
fix *x* **assume** $x \notin \text{varDiffs}$
from *assms* **and** *solves-store-ivpE*(6) **have** $x \in (\pi_1 \downarrow \text{set } xfList) \Longrightarrow \varphi_S 0 x = s$
x **by** *fastforce*

also have $x \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs} \implies \varphi_S \ 0 \ x = s \ x$
 using *assms* and *solves-store-ivpE(2)* by *simp*
 ultimately show $\varphi_S \ 0 \ x = s \ x$ using $\langle x \notin \text{varDiffs} \rangle$ by *auto*
 qed

named-theorems *solves-store-ivpD* computation rules for *solvesStoreIVP*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $t \geq 0$
 shows $G \ (\varphi_S \ t)$
 using *assms* *solves-store-ivpE(1)* by *blast*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $t \geq 0$
 and $y \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$
 shows $\varphi_S \ t \ y = s \ y$
 using *assms* *solves-store-ivpE(2)* by *simp*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $t \geq 0$
 and $y \notin (\pi_1(\text{set } xfList))$
 shows $\varphi_S \ t \ (\partial \ y) = 0$
 using *assms* *solves-store-ivpE(3)* by *simp*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $t \geq 0$
 and $xf \in \text{set } xfList$
 shows $(\varphi_S \ t \ (\partial \ (\pi_1 \ xf))) = (\pi_2 \ xf) \ (\varphi_S \ t)$
 using *assms* *solves-store-ivpE(4)* by *simp*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $t \geq 0$
 and $xf \in \text{set } xfList$
 shows $((\lambda \ t. \ \varphi_S \ t \ (\pi_1 \ xf)) \text{ solves-ode } (\lambda \ t. \lambda \ r. (\pi_2 \ xf) \ (\varphi_S \ t))) \ \{0..t\} \text{ UNIV}$
 using *assms* *solves-store-ivpE(5)* by *simp*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*
 and $(x, f) \in \text{set } xfList$
 shows $\varphi_S \ 0 \ x = s \ x$
 using *assms* *solves-store-ivpE(6)* by *fastforce*

lemma [*solves-store-ivpD*]:
 assumes φ_S *solvesTheStoreIVP* *xfList* withInitState *s* andGuard *G*

and $y \notin \text{varDiffs}$
shows $\varphi_S \ 0 \ y = s \ y$
using *assms solves-store-ivpE*(γ) **by** *simp*

definition *guarDiffEqtn* :: (string \times (real store \Rightarrow real)) list \Rightarrow (real store pred)
 \Rightarrow
 real store rel (ODEsystem - with - [70, 70] 61) **where**
 ODEsystem *xfList* with $G = \{(s, \varphi_S \ t) \mid s \ t \ \varphi_S. \ t \geq 0 \wedge \text{solvesStoreIVP} \ \varphi_S \ \text{xfList} \ s \ G\}$

1.4 Derivation of Differential Dynamic Logic Rules

1.4.1 "Differential Weakening"

lemma *wlp-evol-guard*: $\text{Id} \subseteq \text{wp} \ (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G) \ [\![G]\!]$
apply(*simp add: rel-antidomain-kleene-algebra.fbox-def rel-ad-def guarDiffEqtn-def p2r-def*)
using *solves-store-ivpD*(1) **by** *force*

theorem *dWeakening*:
assumes *guardImpliesPost*: $[\![G]\!] \subseteq [\![Q]\!]$
shows $\text{PRE} \ P \ (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G) \ \text{POST} \ Q$
using *assms and wlp-evol-guard by (metis (no-types, hide-lams) d-p2r order-trans p2r-subid rel-antidomain-kleene-algebra.fbox-iso)*

1.4.2 "Differential Cut"

lemma *condAfterEvol-remainsAlongEvol*:
assumes *boxDiffC*: $(s, s) \in \text{wp} \ (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G) \ [\![C]\!]$
and *FisSol*: *solvesStoreIVP* $\varphi_S \ \text{xfList} \ s \ G$
and *tHyp*: $0 \leq t$
shows $G \ (\varphi_S \ t) \wedge C \ (\varphi_S \ t)$
proof–
from *boxDiffC* **have** $\forall \ c. (s, c) \in (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G) \longrightarrow C \ c$
by (*simp add: boxProgrPred-chrctrzn*)
also from *tHyp* **have** $(s, \varphi_S \ t) \in (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G)$
using *FisSol guarDiffEqtn-def* **by** *auto*
ultimately show $G \ (\varphi_S \ t) \wedge C \ (\varphi_S \ t)$
using *solves-store-ivpD*(1) *tHyp FisSol* **by** *blast*
qed

lemma *condAfterEvol-isGuard*:
assumes *boxDiffC*: $(s, s) \in \text{wp} \ (\text{ODEsystem} \ \text{xfList} \ \text{with} \ G) \ [\![C]\!]$
assumes *FisSol*: *solvesStoreIVP* $\varphi_S \ \text{xfList} \ s \ G$
shows *solvesStoreIVP* $\varphi_S \ \text{xfList} \ s \ (\lambda s. G \ s \wedge C \ s)$
apply(*rule solves-store-ivpI*)
using *assms condAfterEvol-remainsAlongEvol* **apply**(*fastforce*)
using *FisSol solvesStoreIVP-def* **by** *auto*

theorem *dCut*:

assumes $pBoxDiffCut:(PRE\ P\ (ODEsystem\ xfList\ with\ G)\ POST\ C)$
assumes $pBoxCutQ:(PRE\ P\ (ODEsystem\ xfList\ with\ (\lambda\ s.\ G\ s\ \wedge\ C\ s))\ POST\ Q)$
shows $PRE\ P\ (ODEsystem\ xfList\ with\ G)\ POST\ Q$
proof(clarify)
fix $a\ b::real\ store$ **assume** $abHyp:(a,b) \in rdom\ [P]$ **{hence** $a = b$ **by** (metis
 $rdom-p2r-contents$)**}**
then have $(a,a) \in wp\ (ODEsystem\ xfList\ with\ G)\ [C]$ **using** $abHyp$ **and** $pBoxD-$
 $iffCut$ **by** blast
moreover have $\forall\ c.\ (a,c) \in (ODEsystem\ xfList\ with\ (\lambda s.\ G\ s\ \wedge\ C\ s)) \longrightarrow Q\ c$
using $pBoxCutQ$ **by** (metis (no-types, lifting) $\langle a = b \rangle\ abHyp\ boxProgrPred-chrctrztn$
 $subsetCE$)
ultimately have $\forall\ c.\ (a,c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow Q\ c$
using $guarDiffEqtn-def\ condAfterEvol-isGuard$ **by** fastforce
thus $(a,b) \in wp\ (ODEsystem\ xfList\ with\ G)\ [Q]$
using $\langle a = b \rangle$ **by** (simp add: $boxProgrPred-chrctrztn$)
qed

1.4.3 "Solve Differential Equation"

lemma *prelim-dSolve*:
assumes $solHyp:(\lambda t.\ sol\ s[xfList \leftarrow uInput]\ t)\ solvesTheStoreIVP\ xfList\ withInit-$
 $State\ s\ andGuard\ G$
and $uniqHyp:\forall\ X.\ solvesStoreIVP\ X\ xfList\ s\ G \longrightarrow (\forall\ t \geq 0.\ (sol\ s[xfList \leftarrow uInput]\ t) = X\ t)$
and $diffAssgn:\forall\ t \geq 0.\ G\ (sol\ s[xfList \leftarrow uInput]\ t) \longrightarrow Q\ (sol\ s[xfList \leftarrow uInput]\ t)$
shows $\forall\ c.\ (s,c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow Q\ c$
proof(clarify)
fix c **assume** $(s,c) \in (ODEsystem\ xfList\ with\ G)$
from this **obtain** $t::real$ **and** $\varphi_S::real \Rightarrow real\ store$
where $FHyp:t \geq 0 \wedge \varphi_S\ t = c$ **solvesStoreIVP** $\varphi_S\ xfList\ s\ G$ **using** $guarDiffEqtn-def$
by auto
from this **and** $uniqHyp$ **have** $(sol\ s[xfList \leftarrow uInput]\ t) = \varphi_S\ t$ **by** blast
then have $cHyp:c = (sol\ s[xfList \leftarrow uInput]\ t)$ **using** $FHyp$ **by** simp
from $solHyp$ **have** $G\ (sol\ s[xfList \leftarrow uInput]\ t)$ **by** (simp add: $solvesStoreIVP-def$
 $FHyp$)
then show $Q\ c$ **using** $diffAssgn\ FHyp\ cHyp$ **by** auto
qed

theorem *wlp-guard-inv*:
assumes $solHyp:solvesStoreIVP\ (\lambda t.\ sol\ s[xfList \leftarrow uInput]\ t)\ xfList\ s\ G$
and $uniqHyp:\forall\ X.\ solvesStoreIVP\ X\ xfList\ s\ G \longrightarrow (\forall\ t \geq 0.\ (sol\ s[xfList \leftarrow uInput]\ t) = X\ t)$
and $diffAssgn:\forall\ t \geq 0.\ G\ (sol\ s[xfList \leftarrow uInput]\ t) \longrightarrow Q\ (sol\ s[xfList \leftarrow uInput]\ t)$
shows $\lfloor wp\ (ODEsystem\ xfList\ with\ G)\ [Q] \rfloor\ s$
apply(simp add: $r2p-def\ Domain-iff$)
apply(rule exI , $subst\ boxProgrPred-chrctrztn$)
apply(rule-tac $uInput=uInput$ **in** *prelim-dSolve*)
by (simp-all add: $r2p-def\ Domain-unfold\ assms$)

theorem *dSolve*:
assumes *solHyp*: $\forall s. \text{ solvesStoreIVP } (\lambda t. \text{ sol } s[xfList \leftarrow uInput] \ t) \ xfList \ s \ G$
and *uniqHyp*: $\forall s. \forall X. \text{ solvesStoreIVP } X \ xfList \ s \ G \longrightarrow (\forall t \geq 0. (\text{ sol } s[xfList \leftarrow uInput] \ t) = X \ t)$
and *diffAssgn*: $\forall s. P \ s \longrightarrow (\forall t \geq 0. G \ (\text{ sol } s[xfList \leftarrow uInput] \ t) \longrightarrow Q \ (\text{ sol } s[xfList \leftarrow uInput] \ t))$
shows *PRE* *P* (*ODEsystem* *xfList* with *G*) *POST* *Q*
apply(*clarsimp*, *subgoal-tac* *a=b*)
apply(*clarify*, *subst* *boxProgrPred-chrcrtrzn*)
apply(*simp-all* *add*: *p2r-def*)
apply(*rule-tac* *uInput=uInput* **in** *prelim-dSolve*)
apply(*simp* *add*: *solHyp*, *simp* *add*: *uniqHyp*)
by (*metis* (*no-types*, *lifting*) *diffAssgn*)

lemma *conds4vdiffs-prelim*:
assumes *funcsHyp*: $\forall s \ g. \forall xf \in \text{set } xfList. \pi_2 \ xf \ (\text{override-on } s \ g \ \text{varDiffs}) = \pi_2 \ xf \ s$
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \ xf \notin \text{varDiffs}$
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 \ uxf) \ 0 \ (\text{sol } s) = (\text{sol } s) \ (\pi_1 \ (\pi_2 \ uxf))$
and *solHyp2*: $\forall t \geq 0. ((\lambda \tau. (\text{sol } s[xfList \leftarrow uInput] \ \tau) \ x) \text{ has-vderiv-on } (\lambda \tau. f \ (\text{sol } s[xfList \leftarrow uInput] \ \tau))) \ \{0..t\}$
and *xfHyp*: $(x, f) \in \text{set } xfList$ **and** *tHyp*: $t \geq 0$
shows $(\text{sol } s[xfList \leftarrow uInput] \ t) \ (\partial \ x) = f \ (\text{sol } s[xfList \leftarrow uInput] \ t)$
proof–
from *xfHyp* **obtain** *u* **where** *xfuHyp*: $(u, x, f) \in \text{set } (uInput \otimes xfList)$
by (*metis* *in-set-impl-in-set-zip2* *lengthHyp*)
show $(\text{sol } s[xfList \leftarrow uInput] \ t) \ (\partial \ x) = f \ (\text{sol } s[xfList \leftarrow uInput] \ t)$
proof(*cases* *t=0*)
case *True*
have $(\text{sol } s[xfList \leftarrow uInput] \ 0) \ (\partial \ x) = f \ (\text{sol } s[xfList \leftarrow uInput] \ 0)$
using *assms* **and** *to-sol-zero-its-dvars* **by** *blast*
then show *?thesis* **using** *True* **by** *blast*
next
case *False*
from this **have** $t > 0$ **using** *tHyp* **by** *simp*
hence $(\text{sol } s[xfList \leftarrow uInput] \ t) \ (\partial \ x) = \text{vderiv-of } (\lambda r. u \ r \ (\text{sol } s)) \ \{0 <.. < (2 *_{\mathbb{R}} t)\} \ t$
using *xfuHyp* *assms* *to-sol-greater-than-zero-its-dvars* **by** *blast*
also have $\text{vderiv-of } (\lambda r. u \ r \ (\text{sol } s)) \ \{0 <.. < (2 *_{\mathbb{R}} t)\} \ t = f \ (\text{sol } s[xfList \leftarrow uInput] \ t)$
using *assms* *xfuHyp* $\langle t > 0 \rangle$ **and** *vderiv-of-to-sol-its-vars* **by** *blast*
ultimately show *?thesis* **by** *simp*
qed
qed

lemma *conds4vdiffs*:
assumes *funcsHyp*: $\forall s g. \forall xf \in \text{set } xfList. \pi_2 \text{ } xf \text{ (override-on } s \text{ } g \text{ } varDiffs) = \pi_2 \text{ } xf$
 s
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 \text{ } uxf) \text{ } 0 \text{ (sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ } uxf))$
and *solHyp2*: $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda \tau. (\text{sol } s [xfList \leftarrow uInput] \text{ } \tau) (\pi_1 \text{ } xf))$
has-vderiv-on ($\lambda \tau. (\pi_2 \text{ } xf) (\text{sol } s [xfList \leftarrow uInput] \text{ } \tau))) \{0..t\}$
shows $\forall t \geq 0. \forall xf \in \text{set } xfList. (\text{sol } s [xfList \leftarrow uInput] \text{ } t) (\partial (\pi_1 \text{ } xf)) = (\pi_2 \text{ } xf)$
 $(\text{sol } s [xfList \leftarrow uInput] \text{ } t)$
apply(*rule allI*, *rule impI*, *rule ballI*, *rule conds4vdiffs-prelim*)
using *assms* **by** *simp-all*

lemma *conds4Consts*:
assumes *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
shows $\forall x. x \notin (\pi_1 (\text{set } xfList)) \longrightarrow (\text{sol } s [xfList \leftarrow uInput] \text{ } t) (\partial x) = 0$
using *varsHyp* **apply**(*induct* *xfList* *uInput* *rule: list-induct2'*)
apply(*simp-all add: override-on-def varDiffs-def vdiff-def*)
by *clarsimp*

lemma *conds4InitState*:
assumes *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 \text{ } uxf) \text{ } 0 \text{ (sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ } uxf))$
and *xfHyp*: $(x, f) \in \text{set } xfList$
shows $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = s x$
proof–
from *xfHyp* **obtain** *u* **where** *uxfHyp*: $(u, x, f) \in \text{set } (uInput \otimes xfList)$
by (*metis in-set-impl-in-set-zip2 lengthHyp*)
from *varsHyp* **have** *toZeroHyp*: $(\text{sol } s) x = s x$ **using** *override-on-def xfHyp* **by** *auto*
from *uxfHyp* **and** *solHyp1* **have** $u \text{ } 0 \text{ (sol } s) = (\text{sol } s) x$ **by** *fastforce*
also **have** $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = u \text{ } 0 \text{ (sol } s)$
using *state-list-cross-upd-its-vars uxfHyp* **and** *assms* **by** *blast*
ultimately show $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = s x$ **using** *toZeroHyp* **by** *simp*
qed

lemma *conds4RestOfStrings*:
assumes $x \notin (\pi_1 (\text{set } xfList)) \cup varDiffs$
shows $(\text{sol } s [xfList \leftarrow uInput] \text{ } t) x = s x$
using *assms* **apply**(*induct* *xfList* *uInput* *rule: list-induct2'*)
by(*auto simp: varDiffs-def*)

lemma *conds4storeIVP-on-toSol*:
assumes *funcsHyp*: $\forall s g. \forall xf \in \text{set } xfList. \pi_2 \text{ } xf \text{ (override-on } s \text{ } g \text{ } varDiffs) = \pi_2 \text{ } xf$

s
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall \text{ xf} \in \text{set } \text{xfList}. \pi_1 \text{ xf} \notin \text{varDiffs}$
and *guardHyp*: $\forall t \geq 0. G (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t)$
and *solHyp1*: $\forall \text{ uxf} \in \text{set } (\text{uInput} \otimes \text{xfList}). (\pi_1 \text{ uxf}) 0 (\text{sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ uxf}))$
and *solHyp2*: $\forall t \geq 0. \forall \text{ xf} \in \text{set } \text{xfList}.$
 $((\lambda t. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t) (\pi_1 \text{ xf})) \text{ has-vderiv-on } (\lambda t. \pi_2 \text{ xf } (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t))) \{0..t\}$
shows *solvesStoreIVP* ($\lambda t. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t)$) *xfList* *s* *G*
apply(*rule solves-store-ivpI*)
subgoal using *guardHyp* **by** *simp*
subgoal using *conds4vdiffs* *assms* **by** *blast*
subgoal using *conds4RestOfStrings* **by** *blast*
subgoal using *conds4Consts varsHyp* **by** *blast*
subgoal apply(*rule allI*, *rule impI*, *rule ballI*, *rule solves-odeI*)
using *solHyp2* **by** *simp-all*
subgoal using *conds4InitState* **and** *assms* **by** *force*
done

theorem *dSolve-toSolve*:
assumes *funcsHyp*: $\forall s g. \forall \text{ xf} \in \text{set } \text{xfList}. \pi_2 \text{ xf } (\text{override-on } s g \text{ varDiffs}) = \pi_2 \text{ xf } s$
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall \text{ xf} \in \text{set } \text{xfList}. \pi_1 \text{ xf} \notin \text{varDiffs}$
and *guardHyp*: $\forall s. \forall t \geq 0. G (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t)$
and *solHyp1*: $\forall s. \forall \text{ uxf} \in \text{set } (\text{uInput} \otimes \text{xfList}). (\pi_1 \text{ uxf}) 0 (\text{sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ uxf}))$
and *solHyp2*: $\forall s. \forall t \geq 0. \forall \text{ xf} \in \text{set } \text{xfList}.$
 $((\lambda t. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t) (\pi_1 \text{ xf})) \text{ has-vderiv-on } (\lambda t. \pi_2 \text{ xf } (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t))) \{0..t\}$
and *uniqHyp*: $\forall s. \forall X. \text{solvesStoreIVP } X \text{ xfList } s G \longrightarrow (\forall t \geq 0. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t) = X t)$
and *postCondHyp*: $\forall s. P s \longrightarrow (\forall t \geq 0. Q (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] t))$
shows *PRE* *P* (*ODEsystem* *xfList* *with* *G*) *POST* *Q*
apply(*rule-tac* *uInput=uInput* **in** *dSolve*)
subgoal using *assms* **and** *conds4storeIVP-on-toSol* **by** *simp*
subgoal by (*simp add: uniqHyp*)
using *postCondHyp* *guardHyp* *postCondHyp* **by** *simp*

lemma *conds4UniqSol*:
fixes *f*:*real store* \Rightarrow *real*
assumes *tHyp*: $t \geq 0$
and *contHyp*:*continuous-on* ($\{0..t\} \times \text{UNIV}$) ($\lambda(t, (r::\text{real})). f (\varphi_s t)$)
shows *unique-on-bounded-closed* $0 \{0..t\} \tau (\lambda t r. f (\varphi_s t)) \text{ UNIV}$ (*if* $t = 0$ *then*

```

1 else 1/(t+1))
apply(simp add: unique-on-bounded-closed-def unique-on-bounded-closed-axioms-def

unique-on-closed-def compact-interval-def compact-interval-axioms-def nonempty-set-def

interval-def self-mapping-def self-mapping-axioms-def closed-domain-def global-lipschitz-def

lipschitz-def, rule conjI)
subgoal using contHyp continuous-rhs-def by fastforce
subgoal using assms continuous-rhs-def by fastforce
done

lemma solves-store-ivp-at-beginning-overrides:
assumes solvesStoreIVP  $\varphi_s$  xfList a G
shows  $\varphi_s$  0 = override-on a ( $\varphi_s$  0) varDiffs
apply(rule ext, subgoal-tac  $x \notin \text{varDiffs} \longrightarrow \varphi_s$  0  $x = a$  x)
subgoal by (simp add: override-on-def)
using assms and solves-store-ivpD( $\gamma$ ) by simp

lemma ubcStoreUniqueSol:
assumes tHyp:  $t \geq 0$ 
assumes contHyp:  $\forall x f \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$ 
 $(\lambda(t, (r::\text{real})). (\pi_2 x f) (sol\ s[xfList \leftarrow uInput]\ t))$ 
and eqDerivs:  $\forall x f \in \text{set } xfList. \forall \tau \in \{0..t\}. (\pi_2 x f) (\varphi_s \tau) = (\pi_2 x f) (sol\ s[xfList \leftarrow uInput]\ \tau)$ 
and Fsolves: solvesStoreIVP  $\varphi_s$  xfList s G
and solHyp: solvesStoreIVP  $(\lambda \tau. (sol\ s[xfList \leftarrow uInput]\ \tau))$  xfList s G
shows  $(sol\ s[xfList \leftarrow uInput]\ t) = \varphi_s t$ 
proof
  fix x::string show  $(sol\ s[xfList \leftarrow uInput]\ t) x = \varphi_s t x$ 
  proof(cases  $x \in (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$ )
  case False
    then have notInVars:  $x \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$  by simp
    from solHyp have  $(sol\ s[xfList \leftarrow uInput]\ t) x = s x$ 
    using tHyp notInVars solves-store-ivpD(2) by blast
    also from Fsolves have  $\varphi_s t x = s x$  using tHyp notInVars solves-store-ivpD(2)
  by blast
  ultimately show  $(sol\ s[xfList \leftarrow uInput]\ t) x = \varphi_s t x$  by simp
next case True
  then have  $x \in (\pi_1(\text{set } xfList)) \vee x \in \text{varDiffs}$  by simp
  from this show ?thesis
proof
  assume  $x \in (\pi_1(\text{set } xfList))$ 
  from this obtain f where xfHyp:  $(x, f) \in \text{set } xfList$  by fastforce

  then have expand1:  $\forall x f \in \text{set } xfList. ((\lambda \tau. \varphi_s \tau (\pi_1 x f)) \text{ solves-ode } (\lambda \tau r. (\pi_2 x f) (\varphi_s \tau))) \{0..t\} UNIV \wedge \varphi_s 0 (\pi_1 x f) = s (\pi_1 x f)$ 
  using Fsolves tHyp by (simp add: solvesStoreIVP-def)
  hence expand2:  $\forall x f \in \text{set } xfList. \forall \tau \in \{0..t\}. ((\lambda r. \varphi_s r (\pi_1 x f))$ 

```

$has_vector_derivative$ $(\lambda r. (\pi_2 \ xf) \ (sol \ s[xfList \leftarrow uInput] \ \tau)) \ \tau$ $(at \ \tau \ within \ \{0..t\})$
using $eqDerivs$ **by** $(simp \ add: \ solves_ode_def \ has_vderiv_on_def)$

then have $\forall \ xf \in set \ xfList. ((\lambda \tau. \ \varphi_s \ \tau \ (\pi_1 \ xf)) \ solves_ode \ (\lambda \tau \ r. \ (\pi_2 \ xf) \ (sol \ s[xfList \leftarrow uInput] \ \tau))) \{0..t\} \ UNIV \wedge \varphi_s \ 0 \ (\pi_1 \ xf) = s \ (\pi_1 \ xf)$
by $(simp \ add: \ has_vderiv_on_def \ solves_ode_def \ expand1 \ expand2)$
then have $1:((\lambda \tau. \ \varphi_s \ \tau \ x) \ solves_ode \ (\lambda \tau \ r. \ f \ (sol \ s[xfList \leftarrow uInput] \ \tau))) \{0..t\} \ UNIV \wedge \varphi_s \ 0 \ x = s \ x$ **using** $xfHyp$ **by** $fastforce$

from $solHyp$ **and** $xfHyp$ **have** $2:((\lambda \tau. \ (sol \ s[xfList \leftarrow uInput] \ \tau) \ x) \ solves_ode \ (\lambda \tau \ r. \ f \ (sol \ s[xfList \leftarrow uInput] \ \tau))) \{0..t\} \ UNIV \wedge (sol \ s[xfList \leftarrow uInput] \ 0) \ x = s \ x$
using $solvesStoreIVP_def \ tHyp$ **by** $fastforce$

from $tHyp$ **and** $contHyp$ **have** $\forall \ xf \in set \ xfList. \ unique_on_bounded_closed \ 0 \ \{0..t\} \ (s \ (\pi_1 \ xf)) \ (\lambda \tau \ r. \ (\pi_2 \ xf) \ (sol \ s[xfList \leftarrow uInput] \ \tau)) \ UNIV \ (if \ t = 0 \ then \ 1 \ else \ 1/(t+1))$

apply $(clarify)$ **apply** $(rule \ conds4UniqSol)$ **by** $(auto)$
from $this$ **have** $3:unique_on_bounded_closed \ 0 \ \{0..t\} \ (s \ x) \ (\lambda \tau \ r. \ f \ (sol \ s[xfList \leftarrow uInput] \ \tau)) \ UNIV \ (if \ t = 0 \ then \ 1 \ else \ 1/(t+1))$ **using** $xfHyp$ **by** $fastforce$
from $1 \ 2$ **and** 3 **show** $(sol \ s[xfList \leftarrow uInput] \ t) \ x = \varphi_s \ t \ x$
using $unique_on_bounded_closed.unique_solution$ **using** $real-Icc-closed-segment \ tHyp$ **by** $blast$
next
assume $x \in varDiffs$
then obtain y **where** $xDef: x = \partial \ y$ **by** $(auto \ simp: \ varDiffs_def)$
show $(sol \ s[xfList \leftarrow uInput] \ t) \ x = \varphi_s \ t \ x$
proof $(cases \ y \in set \ (map \ \pi_1 \ xfList))$
case $True$
then obtain f **where** $xfHyp:(y, f) \in set \ xfList$ **by** $fastforce$
from $tHyp$ **and** $Fsolves$ **have** $\varphi_s \ t \ x = f \ (\varphi_s \ t)$
using $solves_store_ivpD(4) \ xfHyp \ xDef$ **by** $force$
also have $(sol \ s[xfList \leftarrow uInput] \ t) \ x = f \ (sol \ s[xfList \leftarrow uInput] \ t)$
using $solves_store_ivpD(4) \ xfHyp \ xDef \ solHyp \ tHyp$ **by** $force$
ultimately show $?thesis$ **using** $eqDerivs \ xfHyp \ tHyp$ **by** $auto$
next case $False$
then have $\varphi_s \ t \ x = 0$
using $xDef \ solves_store_ivpD(3) \ Fsolves \ tHyp$ **by** $simp$
also have $(sol \ s[xfList \leftarrow uInput] \ t) \ x = 0$
using $False \ solHyp \ tHyp \ solves_store_ivpD(3) \ xDef$ **by** $fastforce$
ultimately show $?thesis$ **by** $simp$
qed
qed

qed
qed

theorem *dSolveUBC*:

assumes *contHyp*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$

$(\lambda(t, (r::\text{real})). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$
and *solHyp*: $\forall s. \text{solvesStoreIVP } (\lambda t. (sol\ s[xfList \leftarrow uInput]\ t))\ xfList\ s\ G$
and *uniqHyp*: $\forall s. \forall \varphi_s. \varphi_s \text{ solvesTheStoreIVP } xfList \text{ withInitState } s \text{ andGuard } G$
 \longrightarrow
 $(\forall t \geq 0. \forall xf \in \text{set } xfList. \forall r \in \{0..t\}. (\pi_2 xf) (\varphi_s\ r) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ r))$
and *diffAssgn*: $\forall s. P\ s \longrightarrow (\forall t \geq 0. G\ (sol\ s[xfList \leftarrow uInput]\ t) \longrightarrow Q\ (sol\ s[xfList \leftarrow uInput]\ t))$
shows *PRE* *P* (*ODEsystem* *xfList* with *G*) *POST* *Q*
apply(*rule-tac* *uInput*=*uInput* **in** *dSolve*)
prefer 2 **subgoal proof**(*clarify*)
fix *s*::*real* **store** **and** $\varphi_s::\text{real} \Rightarrow \text{real store}$ **and** *t*::*real*
assume *isSol*:*solvesStoreIVP* $\varphi_s\ xfList\ s\ G$ **and** *sHyp*: $0 \leq t$
from this and *uniqHyp* **have** $\forall xf \in \text{set } xfList. \forall t \in \{0..t\}. (\pi_2 xf) (\varphi_s\ t) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t)$ **by** *auto*
also have $\forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$
 $(\lambda(t, (r::\text{real})). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$ **using** *contHyp* *sHyp* **by** *blast*
ultimately show $(sol\ s[xfList \leftarrow uInput]\ t) = \varphi_s\ t$
using *sHyp* *isSol* *ubcStoreUniqueSol* *solHyp* **by** *simp*
qed **using** *assms* **by** *simp-all*

theorem *dSolve-toSolveUBC*:

assumes *funcsHyp*: $\forall s\ g. \forall xf \in \text{set } xfList. \pi_2\ xf\ (\text{override-on } s\ g\ \text{varDiffs}) = \pi_2\ xf\ s$
and *distinctHyp*:*distinct* (*map* $\pi_1\ xfList$)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1\ xf \notin \text{varDiffs}$
and *guardHyp*: $\forall s. \forall t \geq 0. G\ (sol\ s[xfList \leftarrow uInput]\ t)$
and *solHyp1*: $\forall s. \forall uxf \in \text{set } (uInput \otimes xfList). \pi_1\ uxf\ 0\ (sol\ s) = sol\ s\ (\pi_1\ (\pi_2\ uxf))$
and *solHyp2*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. (sol\ s[xfList \leftarrow uInput]\ t) (\pi_1\ xf)))$
has-vderiv-on
 $(\lambda t. \pi_2\ xf\ (sol\ s[xfList \leftarrow uInput]\ t))\ \{0..t\}$
and *contHyp*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$
 $(\lambda(t, (r::\text{real})). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$
and *uniqHyp*: $\forall s. \forall \varphi_s. \varphi_s \text{ solvesTheStoreIVP } xfList \text{ withInitState } s \text{ andGuard } G$
 \longrightarrow
 $(\forall t \geq 0. \forall xf \in \text{set } xfList. \forall r \in \{0..t\}. (\pi_2 xf) (\varphi_s\ r) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ r))$
and *postCondHyp*: $\forall s. P\ s \longrightarrow (\forall t \geq 0. Q\ (sol\ s[xfList \leftarrow uInput]\ t))$
shows *PRE* *P* (*ODEsystem* *xfList* with *G*) *POST* *Q*
apply(*rule-tac* *uInput*=*uInput* **in** *dSolveUBC*)
using *contHyp* **apply** *simp*

apply(rule *allI*, rule-tac *uInput=uInput* in *conds4storeIVP-on-toSol*)
using *assms* **by** *auto*

1.4.4 "Differential Invariant."

lemma *solvesStoreIVP-couldBeModified*:
fixes *F::real* \Rightarrow *real store*
assumes *vars*: $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ solves-ode } (\lambda t r. \pi_2 xf (F t))) \{0..t\}$ *UNIV*
and *dvars*: $\forall t \geq 0. \forall xf \in \text{set } xfList. (F t (\partial (\pi_1 xf))) = (\pi_2 xf) (F t)$
shows $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ has-vector-derivative } F r (\partial (\pi_1 xf))) (at r \text{ within } \{0..t\})$
proof(*clarify*, *rename-tac t r x f*)
fix *x f* **and** *t r::real*
assume *tHyp*: $0 \leq t$ **and** *xfHyp*: $(x, f) \in \text{set } xfList$ **and** *rHyp*: $r \in \{0..t\}$
from *this* **and** *vars* **have** $((\lambda t. F t x) \text{ solves-ode } (\lambda t r. f (F t))) \{0..t\}$ *UNIV*
using *tHyp* **by** *fastforce*
hence $\forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } (\lambda t. f (F t)) r) (at r \text{ within } \{0..t\})$
by (*simp add: solves-ode-def has-vderiv-on-def tHyp*)
have $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. (F r (\partial (\pi_1 xf))) = (\pi_2 xf) (F r)$
using *assms* **by** *auto*
from *this* *rHyp* **and** *xfHyp* **have** $(F r (\partial x)) = f (F r)$ **by** *force*
then **show** $((\lambda t. F t (\pi_1 (x, f))) \text{ has-vector-derivative } F r (\partial (\pi_1 (x, f)))) (at r \text{ within } \{0..t\})$
using $*$ *rHyp* **by** *auto*
qed

lemma *derivationLemma-baseCase*:
fixes *F::real* \Rightarrow *real store*
assumes *solves*:*solvesStoreIVP F xfList a G*
shows $\forall x \in (UNIV - \text{varDiffs}). \forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } F r (\partial x)) (at r \text{ within } \{0..t\})$
proof
fix *x*
assume $x \in UNIV - \text{varDiffs}$
then **have** *notVarDiff*: $\forall z. x \neq \partial z$ **using** *varDiffs-def* **by** *fastforce*
show $\forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } F r (\partial x)) (at r \text{ within } \{0..t\})$
proof(*cases x* \in *set (map* π_1 *xfList)*)
case *True*
from *this* **and** *solves* **have** $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ has-vector-derivative } F r (\partial (\pi_1 xf))) (at r \text{ within } \{0..t\})$
apply(rule-tac *solvesStoreIVP-couldBeModified*) **using** *solves solves-store-ivpD*
by *auto*
from *this* **show** *?thesis* **using** *True* **by** *auto*
next
case *False*
from *this* *notVarDiff* **and** *solves* **have** *const*: $\forall t \geq 0. F t x = a x$

```

using solves-store-ivpD(2) by (simp add: varDiffs-def)
have constD:  $\forall t \geq 0. \forall r \in \{0..t\}. ((\lambda r. a\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$ 
by (auto intro: derivative-eq-intros)
{fix t r::real
  assume  $t \geq 0$  and  $r \in \{0..t\}$ 
  hence  $((\lambda s. a\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$  by (simp add:
constD)
  moreover have  $\bigwedge s. s \in \{0..t\} \implies (\lambda r. F\ r\ x)\ s = (\lambda r. a\ x)\ s$ 
  using const by (simp add:  $0 \leq t$ )
  ultimately have  $((\lambda s. F\ s\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$ 
  using has-vector-derivative-imp by (metis  $\langle r \in \{0..t\} \rangle$ )
  hence  $\text{isZero} : \forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F\ t\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$  by blast
  from False solves and notVarDiff have  $\forall t \geq 0. F\ t\ (\partial\ x) = 0$ 
  using solves-store-ivpD(3) by simp
  then show ?thesis using isZero by simp
qed
qed

```

```

lemma derivationLemma:
assumes solvesStoreIVP F xfList a G
and tHyp:  $t \geq 0$ 
and termVarsHyp:  $\forall x \in \text{trmVars } \eta. x \in (\text{UNIV} - \text{varDiffs})$ 
shows  $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F\ s)) \text{ has-vector-derivative } (\llbracket \partial_t \eta \rrbracket_t) (F\ r)) \text{ (at } r \text{ within } \{0..t\})$ 
using termVarsHyp proof (induction  $\eta$ )
  case (Const r)
    then show ?case by simp
  next
    case (Var y)
      then have yHyp:  $y \in \text{UNIV} - \text{varDiffs}$  by auto
      from this tHyp and assms(1) show ?case
      using derivationLemma-baseCase by auto
  next
    case (Mns  $\eta$ )
      then show ?case
      apply (clarsimp)
      by (rule derivative-intros, simp)
  next
    case (Sum  $\eta1\ \eta2$ )
      then show ?case
      apply (clarsimp)
      by (rule derivative-intros, simp-all)
  next
    case (Mult  $\eta1\ \eta2$ )
      then show ?case
      apply (clarsimp)
      apply (subgoal-tac  $((\lambda s. (\llbracket \eta1 \rrbracket_t) (F\ s)) *_R (\llbracket \eta2 \rrbracket_t) (F\ s)) \text{ has-vector-derivative}$ 

```

$(\llbracket \partial_t \eta 1 \rrbracket_t) (F r) \cdot (\llbracket \eta 2 \rrbracket_t) (F r) + (\llbracket \eta 1 \rrbracket_t) (F r) \cdot (\llbracket \partial_t \eta 2 \rrbracket_t) (F r)$ (at r within $\{0..t\}$), *simp*)
apply(*rule-tac* $f'1 = (\llbracket \partial_t \eta 1 \rrbracket_t) (F r)$ **and** $g'1 = (\llbracket \partial_t \eta 2 \rrbracket_t) (F r)$ **in** *derivative-eq-intros*(25))
by (*simp-all add: has-field-derivative-iff-has-vector-derivative*)
qed

lemma *diff-subst-prprty-4terms*:

assumes *solves*: $\forall x f \in \text{set } x f \text{List}. F t (\partial (\pi_1 x f)) = \pi_2 x f (F t)$
and *tHyp*: $(t :: \text{real}) \geq 0$
and *listsHyp*: $\text{map } \pi_2 x f \text{List} = \text{map } \text{tval } u \text{Input}$
and *termVarsHyp*: $\text{trmVars } \eta \subseteq (\text{UNIV} - \text{varDiffs})$
shows $(\llbracket \partial_t \eta \rrbracket_t) (F t) = (\llbracket (\text{map } (vdiff \circ \pi_1) x f \text{List}) \otimes u \text{Input} \rrbracket_t (\partial_t \eta)) (F t)$
using *termVarsHyp* **apply**(*induction* η) **apply**(*simp-all add: substList-help2*)
using *listsHyp* **and** *solves* **apply**(*induct* $x f \text{List}$ $u \text{Input}$ *rule: list-induct2'*, *simp*, *simp*, *simp*)
proof(*clarify*, *rename-tac* $y g x f \text{Tail } \vartheta \text{ trmTail } x$)
fix $x y :: \text{string}$ **and** $\vartheta :: \text{trms}$ **and** g **and** $x f \text{Tail} :: ((\text{string} \times (\text{real store} \Rightarrow \text{real})) \text{ list})$
and trmTail
assume $IH: \bigwedge x. x \notin \text{varDiffs} \Rightarrow \text{map } \pi_2 x f \text{Tail} = \text{map } \text{tval } \text{trmTail} \Rightarrow$
 $\forall x f \in \text{set } x f \text{Tail}. F t (\partial (\pi_1 x f)) = \pi_2 x f (F t) \Rightarrow$
 $F t (\partial x) = (\llbracket (\text{map } (vdiff \circ \pi_1) x f \text{Tail} \otimes \text{trmTail}) \langle t_V (\partial x) \rangle \rrbracket_t) (F t)$
and $1: x \notin \text{varDiffs}$ **and** $2: \text{map } \pi_2 ((y, g) \# x f \text{Tail}) = \text{map } \text{tval } (\vartheta \# \text{trmTail})$
and $3: \forall x f \in \text{set } ((y, g) \# x f \text{Tail}). F t (\partial (\pi_1 x f)) = \pi_2 x f (F t)$
hence $*$: $(\llbracket (\text{map } (vdiff \circ \pi_1) x f \text{Tail} \otimes \text{trmTail}) \langle \text{Var } (\partial x) \rangle \rrbracket_t) (F t) = F t (\partial x)$
using *tHyp* **by** *auto*
show $F t (\partial x) = (\llbracket (\text{map } (vdiff \circ \pi_1) ((y, g) \# x f \text{Tail})) \otimes (\vartheta \# \text{trmTail}) \rangle \langle t_V (\partial x) \rangle \rrbracket_t) (F t)$
proof(*cases* $x \in \text{set } (\text{map } \pi_1 ((y, g) \# x f \text{Tail}))$)
case *True*
then **have** $x = y \vee (x \neq y \wedge x \in \text{set } (\text{map } \pi_1 x f \text{Tail}))$ **by** *auto*
moreover
{ **assume** $x = y$
from *this* **have** $((\text{map } (vdiff \circ \pi_1) ((y, g) \# x f \text{Tail})) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial x) \rangle = \vartheta$ **by** *simp*
also **from** 3 *tHyp* **have** $F t (\partial y) = g (F t)$ **by** *simp*
moreover **from** 2 **have** $(\llbracket \vartheta \rrbracket_t) (F t) = g (F t)$ **by** *simp*
ultimately **have** *?thesis* **by** (*simp add: (x = y)*)
moreover
{ **assume** $x \neq y \wedge x \in \text{set } (\text{map } \pi_1 x f \text{Tail})$
then **have** $\partial x \neq \partial y$ **using** *vdiff-inj* **by** *auto*
from *this* **have** $((\text{map } (vdiff \circ \pi_1) ((y, g) \# x f \text{Tail})) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial x) \rangle =$
 $((\text{map } (vdiff \circ \pi_1) x f \text{Tail}) \otimes \text{trmTail}) \langle t_V (\partial x) \rangle$ **by** *simp*
hence *?thesis* **using** $*$ **by** *simp*
ultimately **show** *?thesis* **by** *blast*
next
case *False*
then **have** $((\text{map } (vdiff \circ \pi_1) ((y, g) \# x f \text{Tail})) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial x) \rangle$
 $= t_V (\partial x)$

using *substList-cross-vdiff-on-non-occurring-var* **by** (*metis*(*no-types*, *lifting*) *List.map.compositionality*)
thus *?thesis* **by** *simp*
qed
qed

lemma *eqInVars-impl-eqInTrms*:
assumes *termVarsHyp*:*trmVars* $\eta \subseteq (UNIV - \text{varDiffs})$
and *initHyp*: $\forall x. x \notin \text{varDiffs} \longrightarrow b\ x = a\ x$
shows $(\llbracket \eta \rrbracket_t)\ a = (\llbracket \eta \rrbracket_t)\ b$
using *assms* **by**(*induction* η , *simp-all*)

lemma *non-empty-funList-implies-non-empty-trmList*:
shows $\forall \text{list}. (x, f) \in \text{set list} \wedge \text{map } \pi_2 \text{ list} = \text{map tval tList} \longrightarrow (\exists \vartheta. (\llbracket \vartheta \rrbracket_t) = f$
 $\wedge \vartheta \in \text{set tList})$
by(*induction* *tList*, *auto*)

lemma *dInvForTrms-prelim*:
assumes *substHyp*:
 $\forall st. G\ st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket \text{set } xfList \rrbracket)) \longrightarrow st\ (\partial\ str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ (\partial_t \eta) \rrbracket_t)\ st = 0$
and *termVarsHyp*:*trmVars* $\eta \subseteq (UNIV - \text{varDiffs})$
and *listsHyp*: $\text{map } \pi_2\ xfList = \text{map tval } uInput$
shows $(\llbracket \eta \rrbracket_t)\ a = 0 \longrightarrow (\forall c. (a, c) \in (\text{ODEsystem } xfList\ \text{with } G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c = 0)$
proof(*clarify*)
fix *c* **assume** *aHyp*: $(\llbracket \eta \rrbracket_t)\ a = 0$ **and** *cHyp*: $(a, c) \in \text{ODEsystem } xfList\ \text{with } G$
from this **obtain** *t*:*real* **and** *F*::*real* \Rightarrow *real store*
where *tcHyp*: $t \geq 0 \wedge F\ t = c \wedge \text{solvesStoreIVP } F\ xfList\ a\ G$ **using** *guarDiffEqtn-def*
by *auto*
then have $\forall x. x \notin \text{varDiffs} \longrightarrow F\ 0\ x = a\ x$ **using** *solves-store-ivpD*(7) **by** *blast*
from this **have** $(\llbracket \eta \rrbracket_t)\ a = (\llbracket \eta \rrbracket_t)\ (F\ 0)$ **using** *termVarsHyp* *eqInVars-impl-eqInTrms*
by *blast*
hence *obs1*: $(\llbracket \eta \rrbracket_t)\ (F\ 0) = 0$ **using** *aHyp* *tcHyp* **by** *simp*
from *tcHyp* **have** *obs2*: $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t)\ (F\ s))\ \text{has-vector-derivative}$
 $(\llbracket \partial_t \eta \rrbracket_t)\ (F\ r))\ (\text{at } r\ \text{within } \{0..t\})$ **using** *derivationLemma* *termVarsHyp* **by** *blast*
have $\forall r \in \{0..t\}. \forall xf \in \text{set } xfList. F\ r\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ r)$
using *tcHyp* *solves-store-ivpD*(4) **by** *fastforce*
hence $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t)\ (F\ r) = (\llbracket ((\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ (\partial_t$
 $\eta) \rrbracket_t)\ (F\ r)$
using *tcHyp* *diff-subst-prprty-4terms* *termVarsHyp* *listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket ((\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ (\partial_t$
 $\eta) \rrbracket_t)\ (F\ r) = 0$
using *solves-store-ivpD*(1) *solves-store-ivpD*(3) *tcHyp* **by** *fastforce*
ultimately have $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t)\ (F\ s))\ \text{has-vector-derivative } 0)\ (\text{at } r$
 $\text{within } \{0..t\})$
using *obs2* **by** *auto*
from this and *tcHyp* **have** $\forall s \in \{0..t\}. ((\lambda x. (\llbracket \eta \rrbracket_t)\ (F\ x))\ \text{has-derivative } (\lambda x. x$
 $*_R\ 0))$
 $(\text{at } s\ \text{within } \{0..t\})$ **by** (*metis* *has-vector-derivative-def*)

hence $(\llbracket \eta \rrbracket_t) (F\ t) - (\llbracket \eta \rrbracket_t) (F\ 0) = (\lambda x. x *_R\ 0) (t - 0)$
 using *mvt-very-simple* and *tcHyp* by *fastforce*
 then show $(\llbracket \eta \rrbracket_t) c = 0$ using *obs1 tcHyp* by *auto*
 qed

theorem *dInvForTrms*:

assumes $\forall\ st. G\ st \longrightarrow (\forall\ str. str \notin (\pi_1(\downarrow set\ xfList))) \longrightarrow st\ (\partial\ str) = 0 \longrightarrow$
 $(\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t\ \eta \rangle \rrbracket_t) st = 0$
 and *termVarsHyp*: $trmVars\ \eta \subseteq (UNIV - varDiffs)$
 and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
 and *eta-f*: $f = (\llbracket \eta \rrbracket_t)$
 shows $PRE\ (\lambda\ s. f\ s = 0)\ (ODEsystem\ xfList\ with\ G)\ POST\ (\lambda\ s. f\ s = 0)$
 using *eta-f* **proof**(*clarsimp*)
 fix *a b*
 assume $(a, b) \in \lceil \lambda s. (\llbracket \eta \rrbracket_t) s = 0 \rceil$ and $f = (\llbracket \eta \rrbracket_t)$
 from *this* have *aHyp*: $a = b \wedge (\llbracket \eta \rrbracket_t) a = 0$ by (*metis* (*full-types*) *d-p2r rdom-p2r-contents*)
 have $(\llbracket \eta \rrbracket_t) a = 0 \longrightarrow (\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t) c = 0)$
 using *assms dInvForTrms-prelim* by *metis*
 from *this* and *aHyp* have $\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t) c = 0$ by *blast*
 thus $(a, b) \in wp\ (ODEsystem\ xfList\ with\ G)\ \lceil \lambda s. (\llbracket \eta \rrbracket_t) s = 0 \rceil$
 using *aHyp* by (*simp add: boxProgrPred-chrctrzn*)
 qed

lemma *diff-subst-prprty-4props*:

assumes *solves*: $\forall\ xf \in set\ xfList. F\ t\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ t)$
 and *tHyp*: $t \geq 0$
 and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
 and *propVarsHyp*: $propVars\ \varphi \subseteq (UNIV - varDiffs)$
 shows $(\llbracket \partial_P\ \varphi \rrbracket_P) (F\ t) = (\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput) \upharpoonright \partial_P\ \varphi \rrbracket_P) (F\ t)$
 using *propVarsHyp* **apply**(*induction* φ , *simp-all*)
 using *assms diff-subst-prprty-4terms* **apply** *fastforce*
 using *assms diff-subst-prprty-4terms* **apply** *fastforce*
 using *assms diff-subst-prprty-4terms* by *fastforce*

lemma *dInvForProps-prelim*:

assumes *substHyp*:
 $\forall\ st. G\ st \longrightarrow (\forall\ str. str \notin (\pi_1(\downarrow set\ xfList))) \longrightarrow st\ (\partial\ str) = 0 \longrightarrow$
 $(\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t\ \eta \rangle \rrbracket_t) st \geq 0$
 and *termVarsHyp*: $trmVars\ \eta \subseteq (UNIV - varDiffs)$
 and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
 shows $(\llbracket \eta \rrbracket_t) a > 0 \longrightarrow (\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t) c > 0)$
 and $(\llbracket \eta \rrbracket_t) a \geq 0 \longrightarrow (\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t) c \geq 0)$
proof(*clarify*)
 fix *c* assume *aHyp*: $(\llbracket \eta \rrbracket_t) a > 0$ and *cHyp*: $(a, c) \in ODEsystem\ xfList\ with\ G$
 from *this* obtain *t::real* and *F::real* \Rightarrow *real store*
 where *tcHyp*: $t \geq 0 \wedge F\ t = c \wedge solvesStoreIVP\ F\ xfList\ a\ G$ using *guarDiffEqtn-def*

by *auto*
then have $\forall x. x \notin \text{varDiffs} \longrightarrow F\ 0\ x = a\ x$ **using** *solves-store-ivpD(7)* **by** *blast*
from this have $(\llbracket \eta \rrbracket_t) a = (\llbracket \eta \rrbracket_t) (F\ 0)$ **using** *termVarsHyp eqInVars-impl-eqInTrms*
by *blast*
hence $\text{obs1}:(\llbracket \eta \rrbracket_t) (F\ 0) > 0$ **using** *aHyp tcHyp* **by** *simp*
from *tcHyp* **have** $\text{obs2}:\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F\ s)) \text{ has-vector-derivative } (\partial_t \eta)_t) (F\ r))$ **at** r **within** $\{0..t\}$ **using** *derivationLemma termVarsHyp* **by** *blast*
have $(\forall t \geq 0. \forall xf \in \text{set } xfList. F\ t\ (\partial (\pi_1\ xf)) = \pi_2\ xf\ (F\ t))$
using *tcHyp solves-store-ivpD(4)* **by** *blast*
hence $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F\ r) = (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput \rrbracket_t) (\partial_t \eta)_t) (F\ r)$
using *diff-subst-prprty-4terms termVarsHyp tcHyp listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput \rrbracket_t) (\partial_t \eta)_t) (F\ r) \geq 0$
using *solves-store-ivpD(1) solves-store-ivpD(3) tcHyp* **by** *(metis atLeastAtMost-iff)*
ultimately have $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F\ r) \geq 0$ **by** *(simp)*
from *obs2* **and** *tcHyp* **have** $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F\ s)) \text{ has-derivative } (\lambda x. x *_{\mathbb{R}} ((\llbracket \partial_t \eta \rrbracket_t) (F\ r))))$ **at** r **within** $\{0..t\}$ **by** *(simp add: has-vector-derivative-def)*

hence $\exists r \in \{0..t\}. (\llbracket \eta \rrbracket_t) (F\ t) - (\llbracket \eta \rrbracket_t) (F\ 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F\ r))$
using *mvt-very-simple* **and** *tcHyp* **by** *fastforce*
then obtain r **where** $(\llbracket \partial_t \eta \rrbracket_t) (F\ r) \geq 0 \wedge 0 \leq r \wedge r \leq t \wedge ((\llbracket \partial_t \eta \rrbracket_t) (F\ t) \geq 0 \wedge (\llbracket \eta \rrbracket_t) (F\ t) - (\llbracket \eta \rrbracket_t) (F\ 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F\ r)))$ **using** $*$ *tcHyp* **by** *fastforce*
thus $(\llbracket \eta \rrbracket_t) c > 0$
using *obs1 tcHyp* **by** *(metis cancel-comm-monoid-add-class.diff-cancel diff-ge-0-iff-ge)*

diff-strict-mono linorder-neqE-linordered-idom linordered-field-class.sign-simps(45)
not-le)

next
show $0 \leq (\llbracket \eta \rrbracket_t) a \longrightarrow (\forall c. (a, c) \in \text{ODEsystem } xfList \text{ with } G \longrightarrow 0 \leq (\llbracket \eta \rrbracket_t) c)$
proof(*clarify*)
fix c **assume** *aHyp*: $(\llbracket \eta \rrbracket_t) a \geq 0$ **and** *cHyp*: $(a, c) \in \text{ODEsystem } xfList \text{ with } G$
from this obtain $t::\text{real}$ **and** $F::\text{real} \Rightarrow \text{real store}$
where *tcHyp*: $t \geq 0 \wedge F\ t = c \wedge \text{solvesStoreIVP } F\ xfList\ a\ G$ **using** *guarDiffEqtn-def*
by *auto*
then have $\forall x. x \notin \text{varDiffs} \longrightarrow F\ 0\ x = a\ x$ **using** *solves-store-ivpD(7)* **by** *blast*
from this have $(\llbracket \eta \rrbracket_t) a = (\llbracket \eta \rrbracket_t) (F\ 0)$ **using** *termVarsHyp eqInVars-impl-eqInTrms*
by *blast*
hence $\text{obs1}:(\llbracket \eta \rrbracket_t) (F\ 0) \geq 0$ **using** *aHyp tcHyp* **by** *simp*
from *tcHyp* **have** $\text{obs2}:\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F\ s)) \text{ has-vector-derivative } (\partial_t \eta)_t) (F\ r))$ **at** r **within** $\{0..t\}$ **using** *derivationLemma termVarsHyp* **by** *blast*
have $(\forall t \geq 0. \forall xf \in \text{set } xfList. F\ t\ (\partial (\pi_1\ xf)) = \pi_2\ xf\ (F\ t))$
using *tcHyp solves-store-ivpD(4)* **by** *blast*
from this and *tcHyp* **have** $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F\ r) = (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput \rrbracket_t) (\partial_t \eta)_t) (F\ r)$
using *diff-subst-prprty-4terms termVarsHyp listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput \rrbracket_t) (\partial_t \eta)_t) (F\ r) \geq 0$
using *solves-store-ivpD(1) solves-store-ivpD(3) tcHyp* **by** *(metis atLeastAtMost-iff)*

ultimately have $\ast: \forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0$ **by** (*simp*)
from *obs2* **and** *tcHyp* **have** $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F s)) \text{ has-derivative } (\lambda x. x \ast_R ((\llbracket \partial_t \eta \rrbracket_t) (F r))))$ (*at r within* $\{0..t\}$) **by** (*simp add: has-vector-derivative-def*)

hence $\exists r \in \{0..t\}. (\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r))$
using *mvt-very-simple* **and** *tcHyp* **by** *fastforce*
then obtain *r* **where** $(\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0 \wedge 0 \leq r \wedge r \leq t \wedge (\llbracket \partial_t \eta \rrbracket_t) (F t) \geq 0$
 $\wedge (\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r))$ **using** \ast *tcHyp* **by** *fastforce*
thus $(\llbracket \eta \rrbracket_t) c \geq 0$
using *obs1 tcHyp* **by** (*metis cancel-comm-monoid-add-class.diff-cancel diff-ge-0-iff-ge*

diff-strict-mono linorder-neqE-linordered-idom linordered-field-class.sign-simps(45)
not-le)
qed
qed

lemma *less-pval-to-tval*:

assumes $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \prec \eta) \upharpoonright_P \rrbracket_P) st$
shows $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \upharpoonright_t \rrbracket_t) st \geq 0$
using *assms* **by** (*auto*)

lemma *leq-pval-to-tval*:

assumes $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \preceq \eta) \upharpoonright_P \rrbracket_P) st$
shows $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \upharpoonright_t \rrbracket_t) st \geq 0$
using *assms* **by** (*auto*)

lemma *dInv-prelim*:

assumes *substHyp*: $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} \varphi \upharpoonright_P \rrbracket_P) st$
and *propVarsHyp*: $\text{propVars } \varphi \subseteq (UNIV - \text{varDiffs})$
and *listsHyp*: $\text{map } \pi_2 \text{ xfList} = \text{map tval } uInput$
shows $(\llbracket \varphi \rrbracket_P) a \longrightarrow (\forall c. (a, c) \in (\text{ODEsystem xfList with } G) \longrightarrow (\llbracket \varphi \rrbracket_P) c)$
proof (*clarify*)
fix *c* **assume** *aHyp*: $(\llbracket \varphi \rrbracket_P) a$ **and** *cHyp*: $(a, c) \in \text{ODEsystem xfList with } G$
from this obtain *t*:*real* **and** *F*:*real* \Rightarrow *real store*
where *tcHyp*: $t \geq 0 \wedge F t = c \wedge \text{solvesStoreIVP } F \text{ xfList } a \text{ } G$ **using** *guarDiffEqtn-def*
by *auto*
from *aHyp propVarsHyp* **and** *substHyp* **show** $(\llbracket \varphi \rrbracket_P) c$
proof (*induction* φ)
case (*Eq* $\vartheta \eta$)
hence *hyp*: $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \doteq \eta) \upharpoonright_P \rrbracket_P) st$ **by** *blast*
then have $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \langle \partial_t (\vartheta \oplus (\ominus \eta)) \rangle \upharpoonright_t \rrbracket_t) st = 0$ **by** *simp*
also have $\text{trmVars } (\vartheta \oplus (\ominus \eta)) \subseteq UNIV - \text{varDiffs}$ **using** *Eq.prem(2)* **by** *simp*
moreover have $(\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) a = 0$ **using** *Eq.prem(1)* **by** *simp*
ultimately have $(\forall c. (a, c) \in \text{ODEsystem xfList with } G \longrightarrow (\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) c = 0)$

using *dInvForTrms-prelim listsHyp* by *blast*
 hence $(\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) (F t) = 0$ using *tcHyp cHyp* by *simp*
 from this have $(\llbracket \vartheta \rrbracket_t) (F t) = (\llbracket \eta \rrbracket_t) (F t)$ by *simp*
 also have $(\llbracket \vartheta \doteq \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) = (\llbracket \eta \rrbracket_t) (F t))$ using *tcHyp* by *simp*
 ultimately show *?case* by *simp*
 next
 case (*Less* $\vartheta \eta$)
 hence $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set \ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $0 \leq ((\llbracket (map (vdiff \circ \pi_1) \ xfList \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \rrbracket_t) st$
 using *less-pval-to-tval* by *metis*
 also from *Less.premis(2)* have *trmVars* $(\eta \oplus (\ominus \vartheta)) \subseteq UNIV - varDiffs$ by *simp*
 moreover have $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) a > 0$ using *Less.premis(1)* by *simp*
 ultimately have $(\forall c. (a, c) \in ODEsystem \ xfList \text{ with } G \longrightarrow (\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) c > 0)$
 using *dInvForProps-prelim(1) listsHyp* by *blast*
 hence $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) (F t) > 0$ using *tcHyp cHyp* by *simp*
 from this have $(\llbracket \eta \rrbracket_t) (F t) > (\llbracket \vartheta \rrbracket_t) (F t)$ by *simp*
 also have $(\llbracket \vartheta \prec \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) < (\llbracket \eta \rrbracket_t) (F t))$ using *tcHyp* by *simp*
 ultimately show *?case* by *simp*
 next
 case (*Leq* $\vartheta \eta$)
 hence $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set \ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $0 \leq ((\llbracket (map (vdiff \circ \pi_1) \ xfList \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \rrbracket_t) st$ using *leq-pval-to-tval*
 by *metis*
 also from *Leq.premis(2)* have *trmVars* $(\eta \oplus (\ominus \vartheta)) \subseteq UNIV - varDiffs$ by *simp*
 moreover have $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) a \geq 0$ using *Leq.premis(1)* by *simp*
 ultimately have $(\forall c. (a, c) \in ODEsystem \ xfList \text{ with } G \longrightarrow (\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) c \geq 0)$
 using *dInvForProps-prelim(2) listsHyp* by *blast*
 hence $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) (F t) \geq 0$ using *tcHyp cHyp* by *simp*
 from this have $(\llbracket \eta \rrbracket_t) (F t) \geq (\llbracket \vartheta \rrbracket_t) (F t)$ by *simp*
 also have $(\llbracket \vartheta \preceq \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) \leq (\llbracket \eta \rrbracket_t) (F t))$ using *tcHyp* by *simp*
 ultimately show *?case* by *simp*
 next
 case (*And* $\varphi 1 \ \varphi 2$)
 then show *?case* by (*simp*)
 next
 case (*Or* $\varphi 1 \ \varphi 2$)
 from this show *?case* by *auto*
 qed
 qed

theorem *dInv*:

assumes $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set \ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((map (vdiff \circ \pi_1) \ xfList) \otimes uInput) \restriction \partial_P \varphi \rrbracket_P) st$
 and *termVarsHyp*: *propVars* $\varphi \subseteq (UNIV - varDiffs)$
 and *listsHyp*: $map \ \pi_2 \ xfList = map \ tval \ uInput$
 and *phi-p*: $P = (\llbracket \varphi \rrbracket_P)$
 shows *PRE* $P \ (ODEsystem \ xfList \text{ with } G) \ POST \ P$

```

proof(clarsimp)
fix a b
assume  $(a, b) \in \lceil P \rceil$ 
from this have  $aHyp: a = b \wedge P \text{ a by } (metis \text{ (full-types) d-p2r rdom-p2r-contents})$ 
have  $P \text{ a} \longrightarrow (\forall c. (a, c) \in (ODEsystem \text{ xfList with } G) \longrightarrow P \text{ c})$ 
using assms dInv-prelim by metis
from this and aHyp have  $\forall c. (a, c) \in (ODEsystem \text{ xfList with } G) \longrightarrow P \text{ c by}$ 
blast
thus  $(a, b) \in wp \text{ (ODEsystem xfList with } G \text{ ) } \lceil P \rceil$ 
using aHyp by (simp add: boxProgrPred-chrctrzn)
qed

theorem dInvFinal:
assumes  $\forall st. G \text{ st} \longrightarrow (\forall str. str \notin (\pi_1(\lceil set \text{ xfList} \rceil)) \longrightarrow st \text{ (} \partial \text{ str)} = 0) \longrightarrow$ 
 $(\lceil ((map \text{ (vdiff} \circ \pi_1) \text{ xfList)} \otimes uInput) \lceil \partial_P \varphi \rceil_P) \text{ st}$ 
and termVarsHyp: propVars  $\varphi \subseteq (UNIV - varDiffs)$ 
and listsHyp: map  $\pi_2 \text{ xfList} = map \text{ tval } uInput$ 
and impls:  $\lceil P \rceil \subseteq \lceil F \rceil \wedge \lceil F \rceil \subseteq \lceil Q \rceil$ 
and phi-f:  $F = (\lceil \varphi \rceil_P)$ 
shows  $PRE \text{ P (ODEsystem xfList with } G) \text{ POST } Q$ 
apply(rule-tac  $C = (\lceil \varphi \rceil_P)$  in dCut)
apply(subgoal-tac  $\lceil F \rceil \subseteq wp \text{ (ODEsystem xfList with } G) \lceil F \rceil$ , simp)
using impls and phi-f apply blast
apply(subgoal-tac  $PRE \text{ F (ODEsystem xfList with } G) \text{ POST } F$ , simp)
apply(rule-tac  $\varphi = \varphi$  and  $uInput = uInput$  in dInv)
prefer 5 apply(subgoal-tac  $PRE \text{ P (ODEsystem xfList with } (\lambda s. G \text{ s} \wedge F \text{ s}))$ 
 $POST \text{ Q, simp add: phi-f}$ )
apply(rule dWeakening)
using impls apply simp
using assms by simp-all

end
theory VC-diffKAD-examples
imports VC-diffKAD

begin

```

1.5 Rules Testing

In this section we test the recently developed rules with simple dynamical systems.

— Example of hybrid program verified with the rule *dSolve*.

lemma *motion-with-constant-velocity*:

```

   $PRE \text{ (} \lambda s. s \text{ ''y''} < s \text{ ''x''} \wedge s \text{ ''v''} > 0 \text{)}$ 
   $(ODEsystem \text{ [(''x'', (} \lambda s. s \text{ ''v''}))]} \text{ with } (\lambda s. True))$ 
   $POST \text{ (} \lambda s. (s \text{ ''y''} < s \text{ ''x''}))$ 

```

apply(*rule-tac* $uInput = [\lambda t s. s \text{ ''v''} \cdot t + s \text{ ''x''}]$ **in** *dSolve-toSolveUBC*)

prefer 10 **subgoal** **by**(*simp add: wp-trafo vdiff-def add-strict-increasing2*)

apply(*simp-all add: vdiff-def varDiffs-def*)

```

prefer 2 apply(clarify, rule continuous-intros)
prefer 2 apply(simp add: solvesStoreIVP-def vdiff-def varDiffs-def)
apply(clarify, rule-tac f'1= $\lambda x. s \text{ ''}v\text{''}$  and g'1= $\lambda x. 0$  in derivative-intros(173))
apply(rule-tac f'1= $\lambda x. 0$  and g'1= $\lambda x. 1$  in derivative-intros(176))
by(auto intro: derivative-intros)

```

— Example of hybrid program verified with differential weakening.

lemma *system-where-the-guard-implies-the-postcondition*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}x\text{''} + 1)$ )] with ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ )
using dWeakening by blast

```

lemma *system-where-the-guard-implies-the-postcondition2*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}x\text{''} + 1)$ )] with ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ )
apply(clarify, simp add: p2r-def)
apply(simp add: rel-ad-def rel-antidomain-kleene-algebra.addual.ars-r-def)
apply(simp add: rel-antidomain-kleene-algebra.fbox-def)
apply(simp add: relcomp-def rel-ad-def guarDiffEqtn-def solvesStoreIVP-def)
by auto

```

— Example of system proved with a differential invariant.

lemma *circular-motion*:

```

  PRE ( $\lambda s. (s \text{ ''}x\text{''}) \cdot (s \text{ ''}x\text{''}) + (s \text{ ''}y\text{''}) \cdot (s \text{ ''}y\text{''}) - (s \text{ ''}r\text{''}) \cdot (s \text{ ''}r\text{''}) = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}y\text{''})$ ), ( $\text{''}y\text{''}, (\lambda s. -s \text{ ''}x\text{''})$ )] with G)
  POST ( $\lambda s. (s \text{ ''}x\text{''}) \cdot (s \text{ ''}x\text{''}) + (s \text{ ''}y\text{''}) \cdot (s \text{ ''}y\text{''}) - (s \text{ ''}r\text{''}) \cdot (s \text{ ''}r\text{''}) = 0$ )
apply(rule-tac  $\eta = (t_V \text{ ''}x\text{''}) \odot (t_V \text{ ''}x\text{''}) \oplus (t_V \text{ ''}y\text{''}) \odot (t_V \text{ ''}y\text{''}) \oplus (\ominus(t_V \text{ ''}r\text{''}) \odot (t_V \text{ ''}r\text{''}))$ )
  and uInput= $[t_V \text{ ''}y\text{''}, \ominus(t_V \text{ ''}x\text{''})]$  in dInvForTrms)
apply(simp-all add: vdiff-def varDiffs-def)
apply(clarsimp, erule-tac  $x = \text{''}r\text{''}$  in allE)
by simp

```

— Example of systems proved with differential invariants, cuts and weakenings.

declare d-p2r [simp del]

lemma *motion-with-constant-velocity-and-invariants*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''} \wedge s \text{ ''}v\text{''} > 0$ )
  (ODEsystem [( $\text{''}x\text{''}, \lambda s. s \text{ ''}v\text{''}$ )] with ( $\lambda s. \text{True}$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$ )
apply(rule-tac  $C = \lambda s. s \text{ ''}v\text{''} > 0$  in dCut)
apply(rule-tac  $\varphi = (t_C 0) \prec (t_V \text{ ''}v\text{''})$  and uInput= $[t_V \text{ ''}v\text{''}]$  in dInvFinal)
apply(simp-all add: vdiff-def varDiffs-def, clarify, erule-tac  $x = \text{''}v\text{''}$  in allE, simp)
apply(rule-tac  $C = \lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$  in dCut)
apply(rule-tac  $\varphi = (t_V \text{ ''}y\text{''}) \prec (t_V \text{ ''}x\text{''})$  and uInput= $[t_V \text{ ''}v\text{''}]$  and
  F= $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$  in dInvFinal)
apply(simp-all add: vdiff-def varDiffs-def, clarify, erule-tac  $x = \text{''}y\text{''}$  in allE, simp)
using dWeakening by simp

```

```

lemma motion-with-constant-acceleration-and-invariants:
  PRE ( $\lambda s. s''y'' < s''x'' \wedge s''v'' \geq 0 \wedge s''a'' > 0$ )
  (ODEsystem [(" $x''$ "),( $\lambda s. s''v''$ )], (" $v''$ "),( $\lambda s. s''a''$ )] with ( $\lambda s. \text{True}$ ))
  POST ( $\lambda s. (s''y'' < s''x'')$ )
  apply(rule-tac C =  $\lambda s. s''a'' > 0$  in dCut)
  apply(rule-tac  $\varphi = (t_C 0) \prec (t_V ''a'')$  and uInput=[ $t_V ''v'', t_V ''a''$ ] in dInvFinal)
  apply(simp-all add: vdiff-def varDiffs-def, clarify, erule-tac  $x = ''a''$  in allE, simp)
  apply(rule-tac C =  $\lambda s. s''v'' \geq 0$  in dCut)
  apply(rule-tac  $\varphi = (t_C 0) \preceq (t_V ''v'')$  and uInput=[ $t_V ''v'', t_V ''a''$ ] in dInvFinal)
  apply(simp-all add: vdiff-def varDiffs-def)
  apply(rule-tac C =  $\lambda s. s''x'' > s''y''$  in dCut)
  apply(rule-tac  $\varphi = (t_V ''y'') \prec (t_V ''x'')$  and uInput=[ $t_V ''v'', t_V ''a''$ ] in dInvFinal)
  apply(simp-all add: varDiffs-def vdiff-def, clarify, erule-tac  $x = ''y''$  in allE, simp)
  using dWeakening by simp
  declare d-p2r [simp]

end

```