

CPSVerification

By Jonathan

July 17, 2018

Contents

1	VC_diffKAD	3
1.1	Stack Theories Preliminaries: VC_KAD and ODEs	3
1.2	VC_diffKAD Preliminaries	6
1.2.1	(primed) dSolve preliminaries	6
1.2.2	dInv preliminaries	12
1.3	Phase Space Relational Semantics	14
1.4	Derivation of Differential Dynamic Logic Rules	16
1.4.1	"Differential Weakening"	16
1.4.2	"Differential Cut"	16
1.4.3	"Solve Differential Equation"	18
1.4.4	"Differential Invariant."	25
1.5	Rules Testing	33

1 VC_diffKAD

```
theory VC-diffKAD-auxiliarities
imports
  Main
  afpModified/VC-KAD
  Ordinary-Differential-Equations.ODE-Analysis
```

```
begin
```

1.1 Stack Theories Preliminaries: VC_KAD and ODEs

To make our notation less code-like and more mathematical we declare:

```
no-notation Archimedean-Field.ceiling ( $\lceil \cdot \rceil$ )
and Archimedean-Field.floor ( $\lfloor \cdot \rfloor$ )
and Set.image (  $'$  )
and Range-Semiring.antirange-semiring-class.ars-r ( $r$ )
```

```
notation p2r ( $\lceil \cdot \rceil$ )
and r2p ( $\lfloor \cdot \rfloor$ )
```

and *Set.image* $(-\llbracket - \rrbracket)$
and *Product-Type.prod.fst* (π_1)
and *Product-Type.prod.snd* (π_2)
and *List.zip* $(\mathbf{infixl} \otimes 63)$
and *rel-ad* (Δ^c_1)

This and more notation is explained by the following lemma.

lemma shows $\lceil P \rceil = \{(s, s) \mid s. P\ s\}$
and $\lfloor R \rfloor = (\lambda x. x \in r2s\ R)$
and $r2s\ R = \{x \mid x. \exists y. (x, y) \in R\}$
and $\pi_1\ (x, y) = x \wedge \pi_2\ (x, y) = y$
and $\Delta^c_1\ R = \{(x, x) \mid x. \nexists y. (x, y) \in R\}$
and $wp\ R\ Q = \Delta^c_1\ (R ; \Delta^c_1\ Q)$
and $[x1, x2, x3, x4] \otimes [y1, y2] = [(x1, y1), (x2, y2)]$
and $\{a..b\} = \{x. a \leq x \wedge x \leq b\}$
and $\{a <..< b\} = \{x. a < x \wedge x < b\}$
and $(x\ solves\ ode\ f)\ \{0..t\}\ R = ((x\ has\ vderiv\ on\ (\lambda t. f\ t\ (x\ t)))\ \{0..t\} \wedge x \in \{0..t\} \rightarrow R)$
and $f \in A \rightarrow B = (f \in \{f. \forall x. x \in A \longrightarrow (f\ x) \in B\})$
and $(x\ has\ vderiv\ on\ x')\ \{0..t\} =$
 $(\forall r \in \{0..t\}. (x\ has\ vector\ derivative\ x'\ r)\ (at\ r\ within\ \{0..t\}))$
and $(x\ has\ vector\ derivative\ x'\ r)\ (at\ r\ within\ \{0..t\}) =$
 $(x\ has\ derivative\ (\lambda x. x *_{\mathbb{R}} x'\ r))\ (at\ r\ within\ \{0..t\})$
apply $(simp\ add: p2r\ def\ r2p\ def\ rel\ ad\ def\ rel\ antidomain\ kleene\ algebra.\ fbox\ def$
 $\ solves\ ode\ def\ has\ vderiv\ on\ def)$
apply $(blast, fastforce, fastforce)$
using *has-vector-derivative-def* **by** *auto*

Observe also, the following consequences and facts:

proposition $\pi_1\ \lfloor R \rfloor = r2s\ R$
by $(simp\ add: fst\ eq\ Domain)$

proposition $\Delta^c_1\ R = Id - \{(s, s) \mid s. s \in (\pi_1\ \lfloor R \rfloor)\}$
by $(simp\ add: image\ def\ rel\ ad\ def, fastforce)$

proposition $P \subseteq Q \implies wp\ R\ P \subseteq wp\ R\ Q$
by $(simp\ add: rel\ antidomain\ kleene\ algebra.\ dka.\ dom\ iso\ rel\ antidomain\ kleene\ algebra.\ fbox\ iso)$

proposition *boxProgrPred-IsProp*: $wp\ R\ \lceil P \rceil \subseteq Id$
by $(simp\ add: rel\ antidomain\ kleene\ algebra.\ a\ subid'\ rel\ antidomain\ kleene\ algebra.\ addual.\ bbox\ def)$

proposition *rdom-p2r-contents*: $(a, b) \in rdom\ \lceil P \rceil = ((a = b) \wedge P\ a)$

proof–

have $(a, b) \in rdom\ \lceil P \rceil = ((a = b) \wedge (a, a) \in rdom\ \lceil P \rceil)$ **using** *p2r-subid* **by**
fastforce

also have $\dots = ((a = b) \wedge (a, a) \in \lceil P \rceil)$ **by** *simp*

also have $\dots = ((a = b) \wedge P\ a)$ **by** $(simp\ add: p2r\ def)$

ultimately show *?thesis* **by** *simp*

qed

proposition *rel-ad-rule1*: $(x, x) \notin \Delta^c_1 \upharpoonright P \implies P\ x$
by(*auto simp: rel-ad-def p2r-subid p2r-def*)

proposition *rel-ad-rule2*: $(x, x) \in \Delta^c_1 \upharpoonright P \implies \neg P\ x$
by(*metis ComplD VC-KAD.p2r-neg-hom rel-ad-rule1 empty-iff mem-Collect-eq p2s-neg-hom*

rel-antidomain-kleene-algebra.a-one rel-antidomain-kleene-algebra.am1 relcomp.relcompI)

proposition *rel-ad-rule3*: $R \subseteq Id \implies (x, x) \notin R \implies (x, x) \in \Delta^c_1 R$
by(*metis IdI Un-iff d-p2r rel-antidomain-kleene-algebra.addual.ars3*
rel-antidomain-kleene-algebra.addual.ars-r-def rpr)

proposition *rel-ad-rule4*: $(x, x) \in R \implies (x, x) \notin \Delta^c_1 R$
by(*metis empty-iff rel-antidomain-kleene-algebra.addual.ars1 relcomp.relcompI*)

proposition *boxProgrPred-chrctrzn*: $(x, x) \in wp\ R \upharpoonright P = (\forall\ y. (x, y) \in R \longrightarrow P\ y)$
by(*metis boxProgrPred-IsProp rel-ad-rule1 rel-ad-rule2 rel-ad-rule3*
rel-ad-rule4 d-p2r wp-simp wp-trafo)

lemma (*in antidomain-kleene-algebra*) *fbox-starI*:
assumes $d\ p \leq d\ i$ **and** $d\ i \leq |x|\ i$ **and** $d\ i \leq d\ q$
shows $d\ p \leq |x^*|\ q$
proof–
from $\langle d\ i \leq |x|\ i \rangle$ **have** $d\ i \leq |x|\ (d\ i)$
using *local.fbox-simp* **by** *auto*
hence $|1|\ p \leq |x^*|\ i$ **using** $\langle d\ p \leq d\ i \rangle$ **by** (*metis (no-types)*
local.dual-order.trans local.fbox-one local.fbox-simp local.fbox-star-induct-var)
thus *?thesis* **using** $\langle d\ i \leq d\ q \rangle$ **by** (*metis (full-types)*
local.fbox-mult local.fbox-one local.fbox-seq-var local.fbox-simp)
qed

proposition *cons-eq-zipE*:
 $(x, y) \# tail = xList \otimes yList \implies \exists xTail\ yTail. x \# xTail = xList \wedge y \# yTail = yList$
by(*induction xList, simp-all, induction yList, simp-all*)

proposition *set-zip-left-rightD*:
 $(x, y) \in set\ (xList \otimes yList) \implies x \in set\ xList \wedge y \in set\ yList$
apply(*rule conjI*)
apply(*rule-tac y=y and ys=yList in set-zip-leftD, simp*)
apply(*rule-tac x=x and xs=xList in set-zip-rightD, simp*)
done

declare *zip-map-fst-snd* [*simp*]

1.2 VC_diffKAD Preliminaries

In dL, the set of possible program variables is split in two, the set of variables V and their primed counterparts V' . To implement this, we use Isabelle's string-type and define a function that primes a given string. We then define the set of primed-strings based on it.

definition $vdiff :: string \Rightarrow string$ (∂ - [55] 70) **where**
 $(\partial x) = "d[" @ x @ "]"$

definition $varDiffs :: string \text{ set}$ **where**
 $varDiffs = \{y. \exists x. y = \partial x\}$

proposition $vdiff\text{-}inj: (\partial x) = (\partial y) \implies x = y$
by ($simp$ $add: vdiff\text{-}def$)

proposition $vdiff\text{-}noFixPoints: x \neq (\partial x)$
by ($simp$ $add: vdiff\text{-}def$)

lemma $varDiffsI: x = (\partial z) \implies x \in varDiffs$
by ($simp$ $add: varDiffs\text{-}def$ $vdiff\text{-}def$)

lemma $varDiffsE$:
assumes $x \in varDiffs$
obtains y **where** $x = "d[" @ y @ "]"$
using $assms$ **unfolding** $varDiffs\text{-}def$ $vdiff\text{-}def$ **by** $auto$

proposition $vdiff\text{-}invarDiffs: (\partial x) \in varDiffs$
by ($simp$ $add: varDiffsI$)

1.2.1 (primed) dSolve preliminaries

This subsection is to define a function that takes a system of ODEs (expressed as a list $xfList$), a presumed solution $uInput = [u_1, \dots, u_n]$, a state s and a time t , and outputs the induced flow $sol\ s[xfList \leftarrow uInput]\ t$.

abbreviation $varDiffs\text{-}to\text{-}zero :: real\ store \Rightarrow real\ store$ (sol) **where**
 $sol\ a \equiv (override\text{-}on\ a\ (\lambda x. 0)\ varDiffs)$

proposition $varDiffs\text{-}to\text{-}zero\text{-}vdiff[simp]: (sol\ s)\ (\partial x) = 0$
apply ($simp$ $add: override\text{-}on\text{-}def$ $varDiffs\text{-}def$)
by $auto$

proposition $varDiffs\text{-}to\text{-}zero\text{-}beginning[simp]: take\ 2\ x \neq "d[" \implies (sol\ s)\ x = s$
 x
apply ($simp$ $add: varDiffs\text{-}def$ $override\text{-}on\text{-}def$ $vdiff\text{-}def$)
by $fastforce$

— Next, for each entry of the input-list, we update the state using said entry.

definition $vderiv\text{-}of\ f\ S = (SOME\ f'.\ (f\ \text{has-}vderiv\text{-}on\ f')\ S)$

primrec $state\text{-}list\text{-}upd :: ((real \Rightarrow real\ store \Rightarrow real) \times string \times (real\ store \Rightarrow real))\ list \Rightarrow real \Rightarrow real\ store \Rightarrow real\ store$ **where**
 $state\text{-}list\text{-}upd\ []\ t\ s = s$
 $state\text{-}list\text{-}upd\ (uxf\ \# tail)\ t\ s = (state\text{-}list\text{-}upd\ tail\ t\ s)$
 $(\pi_1\ (\pi_2\ uxf)) := (\pi_1\ uxf)\ t\ s,$
 $\partial\ (\pi_1\ (\pi_2\ uxf)) := (if\ t = 0\ then\ (\pi_2\ (\pi_2\ uxf))\ s$
 $else\ vderiv\text{-}of\ (\lambda\ r.\ (\pi_1\ uxf)\ r\ s)\ \{0 <..< (2 *_{\mathbb{R}} t)\}\ t))$

abbreviation $state\text{-}list\text{-}cross\text{-}upd :: real\ store \Rightarrow (string \times (real\ store \Rightarrow real))\ list \Rightarrow (real \Rightarrow real\ store \Rightarrow real)\ list \Rightarrow real \Rightarrow (char\ list \Rightarrow real)\ (-[\leftarrow] - [64,64,64] 63)$ **where**
 $s[xfList \leftarrow uInput]\ t \equiv state\text{-}list\text{-}upd\ (uInput \otimes xfList)\ t\ s$

proposition $state\text{-}list\text{-}cross\text{-}upd\text{-}empty[simp]: (s[\leftarrow list]\ t) = s$
by(*induction list, simp-all*)

lemma *inductive-state-list-cross-upd-its-vars:*

assumes $distHyp: distinct\ (map\ \pi_1\ ((y, g) \# xftail))$
and $varHyp: \forall xf \in set((y, g) \# xftail). \pi_1\ xf \notin varDiffs$
and $indHyp: (u, x, f) \in set\ (utail \otimes xftail) \implies (s[xftail \leftarrow utail]\ t)\ x = u\ t\ s$
and $disjHyp: (u, x, f) = (v, y, g) \vee (u, x, f) \in set\ (utail \otimes xftail)$
shows $(s[(y, g) \# xftail \leftarrow v \# utail]\ t)\ x = u\ t\ s$
using $disjHyp$ **proof**
 $assume\ (u, x, f) = (v, y, g)$
 $hence\ (s[(y, g) \# xftail \leftarrow v \# utail]\ t)\ x = ((s[xftail \leftarrow utail]\ t)(x := u\ t\ s,$
 $\partial\ x := if\ t = 0\ then\ f\ s\ else\ vderiv\text{-}of\ (\lambda\ r.\ u\ r\ s)\ \{0 <..< (2 *_{\mathbb{R}} t)\}\ t))\ x$ **by**
 $simp$
 $also\ have\ \dots = u\ t\ s$ **by** ($simp\ add: vdiff\text{-}def$)
 $ultimately\ show\ ?thesis$ **by** $simp$
next
 $assume\ yTailHyp: (u, x, f) \in set\ (utail \otimes xftail)$
from $this$ **and** $indHyp$ **have** $3: (s[xftail \leftarrow utail]\ t)\ x = u\ t\ s$ **by** $fastforce$
from $yTailHyp$ **and** $distHyp$ **have** $2: y \neq x$ **using** $set\text{-}zip\text{-}left\text{-}rightD$ **by** $force$
from $yTailHyp$ **and** $varHyp$ **have** $1: x \neq \partial\ y$
using $set\text{-}zip\text{-}left\text{-}rightD\ vdiff\text{-}invarDiffs$ **by** $fastforce$
from 1 **and** 2 **have** $(s[(y, g) \# xftail \leftarrow v \# utail]\ t)\ x = (s[xftail \leftarrow utail]\ t)\ x$
by $simp$
 $thus\ ?thesis$ **using** 3 **by** $simp$
qed

theorem *state-list-cross-upd-its-vars:*

assumes $distinctHyp: distinct\ (map\ \pi_1\ xfList)$
and $lengthHyp: length\ xfList = length\ uInput$
and $varsHyp: \forall xf \in set\ xfList. \pi_1\ xf \notin varDiffs$
and $its\text{-}var: (u, x, f) \in set\ (uInput \otimes xfList)$

shows $(s[xfList \leftarrow uInput] \ t) \ x = u \ t \ s$
using *assms* **apply**(*induct* *xfList* *uInput* *arbitrary: x rule: list-induct2'*, *simp*,
simp, *simp*)
by(*clarify*, *rule inductive-state-list-cross-upd-its-vars*, *simp-all*)

lemma *override-on-upd*: $x \in X \implies (\text{override-on } f \ g \ X)(x := z) = (\text{override-on } f \ (g(x := z)) \ X)$
by (*rule ext*, *simp add: override-on-def*)

lemma *inductive-state-list-cross-upd-its-dvars*:
assumes $\exists g. (s[xfTail \leftarrow uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$
and $\forall xf \in \text{set} \ (xf \ \# \ xfTail). \ \pi_1 \ xf \notin \text{varDiffs}$
and $\forall uxf \in \text{set} \ (u \ \# \ uTail \otimes xf \ \# \ xfTail). \ \pi_1 \ uxf \ 0 \ s = s \ (\pi_1 \ (\pi_2 \ uxf))$
shows $\exists g. (s[xf \ \# \ xfTail \leftarrow u \ \# \ uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$
proof –
let $?gLHS = (s[(xf \ \# \ xfTail) \leftarrow (u \ \# \ uTail)] \ 0)$
have *observ*: $\partial (\pi_1 \ xf) \in \text{varDiffs}$ **by** (*auto simp: varDiffs-def*)
from *assms*(1) **obtain** *g* **where** $(s[xfTail \leftarrow uTail] \ 0) = \text{override-on } s \ g \ \text{varDiffs}$
by *force*
then have $?gLHS = (\text{override-on } s \ g \ \text{varDiffs})(\pi_1 \ xf := u \ 0 \ s, \ \partial (\pi_1 \ xf) := \pi_2 \ xf \ s)$ **by** *simp*
also have $\dots = (\text{override-on } s \ g \ \text{varDiffs})(\partial (\pi_1 \ xf) := \pi_2 \ xf \ s)$
using *override-on-def* *varDiffs-def* *assms* **by** *auto*
also have $\dots = (\text{override-on } s \ (g(\partial (\pi_1 \ xf) := \pi_2 \ xf \ s)) \ \text{varDiffs})$
using *observ* **and** *override-on-upd* **by** *force*
ultimately show *?thesis* **by** *auto*
qed

theorem *state-list-cross-upd-its-dvars*:
assumes *lengthHyp*: $\text{length } xfList = \text{length } uInput$
and *varsHyp*: $\forall \ xf \in \text{set } xfList. \ \pi_1 \ xf \notin \text{varDiffs}$
and *solHyp1*: $\forall uxf \in \text{set} \ (uInput \otimes xfList). \ (\pi_1 \ uxf) \ 0 \ s = s \ (\pi_1 \ (\pi_2 \ uxf))$
shows $\exists g. (s[xfList \leftarrow uInput] \ 0) = (\text{override-on } s \ g \ \text{varDiffs})$
using *assms* **proof**(*induct* *xfList* *uInput* *rule: list-induct2'*)
case 1
have $(s[\] \leftarrow \] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding *override-on-def* **by** *simp*
thus *?case* **by** *metis*
next
case (2 *xf xfTail*)
have $(s[(xf \ \# \ xfTail) \leftarrow \] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding *override-on-def* **by** *simp*
thus *?case* **by** *metis*
next
case (3 *u utail*)
have $(s[\] \leftarrow utail] \ 0) = \text{override-on } s \ s \ \text{varDiffs}$
unfolding *override-on-def* **by** *simp*
thus *?case* **by** *force*
next

case ($\not\vdash$ $xf\ xfTail\ u\ uTail$)
 then have $\exists g. (s[xfTail \leftarrow uTail]\ 0) = \text{override-on } s\ g\ \text{varDiffs}$ by simp
 thus ?case using inductive-state-list-cross-upd-its-dvars $\not\vdash$.prems by blast
 qed

lemma *vderiv-unique-within-open-interval*:
 assumes (f has-vderiv-on f') $\{0 < \cdot < t\}$ and $t > 0$
 and (f has-vderiv-on f'') $\{0 < \cdot < t\}$ and $\text{tauHyp}:\tau \in \{0 < \cdot < t\}$
 shows $f' \tau = f'' \tau$
 using assms apply (simp add: has-vderiv-on-def has-vector-derivative-def)
 using frechet-derivative-unique-within-open-interval by (metis box-real(1) scaleR-one tauHyp)

lemma *has-vderiv-on-cong-open-interval*:
 assumes $gHyp:\forall \tau > 0. f \tau = g \tau$ and $tHyp: t > 0$
 and $fHyp:(f \text{ has-vderiv-on } f') \{0 < \cdot < t\}$
 shows $(g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$
proof–
 from $gHyp$ have $\bigwedge \tau. \tau \in \{0 < \cdot < t\} \implies f \tau = g \tau$ using $tHyp$ by force
 hence $\text{eqDs}:(f \text{ has-vderiv-on } f') \{0 < \cdot < t\} = (g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$
 apply (rule-tac has-vderiv-on-cong) by auto
 thus $(g \text{ has-vderiv-on } f') \{0 < \cdot < t\}$ using $\text{eqDs } fHyp$ by simp
 qed

lemma *closed-vderiv-on-cong-to-open-vderiv*:
 assumes $gHyp:\forall \tau > 0. f \tau = g \tau$
 and $fHyp:\forall t \geq 0. (f \text{ has-vderiv-on } f') \{0..t\}$
 and $tHyp: t > 0$ and $cHyp: c > 1$
 shows $\text{vderiv-of } g \{0 < \cdot < (c *_R t)\} t = f' t$
proof–
 have $ctHyp:c \cdot t > 0$ using $tHyp$ and $cHyp$ by auto
 from $fHyp$ have $(f \text{ has-vderiv-on } f') \{0 < \cdot < c \cdot t\}$ using has-vderiv-on-subset
 by (metis greaterThanLessThan-subseteq-atLeastAtMost-iff less-eq-real-def)
 then have $\text{derivHyp}:(g \text{ has-vderiv-on } f') \{0 < \cdot < c \cdot t\}$
 using $gHyp\ ctHyp$ and has-vderiv-on-cong-open-interval by blast
 hence $f'Hyp:\forall f''. (g \text{ has-vderiv-on } f'') \{0 < \cdot < c \cdot t\} \longrightarrow (\forall \tau \in \{0 < \cdot < c \cdot t\}. f' \tau = f'' \tau)$
 using vderiv-unique-within-open-interval $ctHyp$ by blast
 also have $(g \text{ has-vderiv-on } (\text{vderiv-of } g \{0 < \cdot < (c *_R t)\})) \{0 < \cdot < c \cdot t\}$
 by (simp add: vderiv-of-def, metis derivHyp someI-ex)
 ultimately show $\text{vderiv-of } g \{0 < \cdot < c *_R t\} t = f' t$ using $tHyp\ cHyp$ by force
 qed

lemma *vderiv-of-to-sol-its-vars*:
 assumes $\text{distinctHyp}:\text{distinct } (\text{map } \pi_1\ xfList)$
 and $\text{lengthHyp}:\text{length } xfList = \text{length } uInput$
 and $\text{varsHyp}:\forall xf \in \text{set } xfList. \pi_1\ xf \notin \text{varDiffs}$
 and $\text{solHyp2}:\forall t \geq 0. ((\lambda \tau. (\text{sol } s[xfList \leftarrow uInput]\ \tau)\ x)$
 $\text{has-vderiv-on } (\lambda \tau. f (\text{sol } s[xfList \leftarrow uInput]\ \tau))) \{0..t\}$

and $tHyp: t > 0$ **and** $uxfHyp: (u, x, f) \in \text{set } (uInput \otimes xfList)$
shows $vderiv\text{-}of\ (\lambda\tau. u\ \tau\ (sol\ s))\ \{0 < .. < (2 *_{\mathcal{R}} t)\}\ t = f\ (sol\ s[xfList \leftarrow uInput])$
 $t)$
apply($rule\text{-}tac\ f = (\lambda\tau. (sol\ s[xfList \leftarrow uInput])\ \tau)\ x$) **in** $closed\text{-}vderiv\text{-}on\text{-}cong\text{-}to\text{-}open\text{-}vderiv)$
subgoal using $assms$ **and** $state\text{-}list\text{-}cross\text{-}upd\text{-}its\text{-}vars$ **by** $metis$
by($simp\text{-}all\ add: solHyp2\ tHyp$)

lemma $inductive\text{-}to\text{-}sol\text{-}zero\text{-}its\text{-}dvars:$

assumes $eqFuncs: \forall\ s. \forall\ g. \forall\ xf \in \text{set } ((x, f) \# xfs). \pi_2\ xf\ (override\text{-}on\ s\ g\ varDiffs)$
 $= \pi_2\ xf\ s$

and $eqLengths: length\ ((x, f) \# xfs) = length\ (u \# us)$

and $distinct: distinct\ (map\ \pi_1\ ((x, f) \# xfs))$

and $vars: \forall\ xf \in \text{set } ((x, f) \# xfs). \pi_1\ xf \notin varDiffs$

and $solHyp1: \forall\ uxf \in \text{set } ((u \# us) \otimes ((x, f) \# xfs)). \pi_1\ uxf\ 0\ (sol\ s) = sol\ s\ (\pi_1\ (\pi_2\ uxf))$

and $disjHyp: (y, g) = (x, f) \vee (y, g) \in \text{set } xfs$

and $indHyp: (y, g) \in \text{set } xfs \implies (sol\ s[xfs \leftarrow us]\ 0)\ (\partial\ y) = g\ (sol\ s[xfs \leftarrow us]\ 0)$

shows $(sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)\ (\partial\ y) = g\ (sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)$

proof –

from $assms$ **obtain** $h1$ **where** $h1Def: (sol\ s[((x, f) \# xfs) \leftarrow (u \# us)]\ 0) =$

$(override\text{-}on\ (sol\ s)\ h1\ varDiffs)$ **using** $state\text{-}list\text{-}cross\text{-}upd\text{-}its\text{-}dvars$ **by** $blast$

from $disjHyp$ **show** $(sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)\ (\partial\ y) = g\ (sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)$

proof

assume $eqHeads: (y, g) = (x, f)$

then have $g\ (sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0) = f\ (sol\ s)$ **using** $h1Def\ eqFuncs$

by $simp$

also have $... = (sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)\ (\partial\ y)$ **using** $eqHeads$ **by** $auto$

ultimately show $?thesis$ **by** $linarith$

next

assume $tailHyp: (y, g) \in \text{set } xfs$

then have $y \neq x$ **using** $distinct\ set\text{-}zip\text{-}left\text{-}rightD$ **by** $force$

hence $\partial\ x \neq \partial\ y$ **by**($simp\ add: vdiff\text{-}def$)

have $x \neq \partial\ y$ **using** $vars\ vdiff\text{-}invarDiffs$ **by** $auto$

obtain $h2$ **where** $h2Def: (sol\ s[xfs \leftarrow us]\ 0) = override\text{-}on\ (sol\ s)\ h2\ varDiffs$

using $state\text{-}list\text{-}cross\text{-}upd\text{-}its\text{-}dvars\ eqLengths\ distinct\ vars$ **and** $solHyp1$ **by** $force$

have $(sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)\ (\partial\ y) = g\ (sol\ s[xfs \leftarrow us]\ 0)$

using $tailHyp\ indHyp\ (x \neq \partial\ y)$ **and** $(\partial\ x \neq \partial\ y)$ **by** $simp$

also have $... = g\ (override\text{-}on\ (sol\ s)\ h2\ varDiffs)$ **using** $h2Def$ **by** $simp$

also have $... = g\ (sol\ s)$ **using** $eqFuncs$ **and** $tailHyp$ **by** $force$

also have $... = g\ (sol\ s[(x, f) \# xfs \leftarrow u \# us]\ 0)$

using $eqFuncs\ h1Def\ tailHyp$ **and** $eq\text{-}snd\text{-}iff$ **by** $fastforce$

ultimately show $?thesis$ **by** $simp$

qed

qed

lemma $to\text{-}sol\text{-}zero\text{-}its\text{-}dvars:$

assumes $funcsHyp: \forall\ s. \forall\ g. \forall\ xf \in \text{set } xfList. \pi_2\ xf\ (override\text{-}on\ s\ g\ varDiffs)$
 $= \pi_2\ xf\ s$

and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 uxf) \ 0 \ (sol \ s) = (sol \ s) \ (\pi_1 \ (\pi_2 \ uxf))$
and *ygHyp*: $(y, g) \in \text{set } xfList$
shows $(sol \ s[xfList \leftarrow uInput] \ 0)(\partial \ y) = g \ (sol \ s[xfList \leftarrow uInput] \ 0)$
using *assms* **apply**(*induct* *xfList* *uInput* *rule*: *list-induct2'*, *simp*, *simp*, *simp*, *clarify*)
by(*rule inductive-to-sol-zero-its-dvars*, *simp-all*)

lemma *inductive-to-sol-greater-than-zero-its-dvars*:
assumes *lengthHyp*:*length* $((y, g) \# xfs) = \text{length } (v \# vs)$
and *distHyp*:*distinct* (*map* π_1 $((y, g) \# xfs)$)
and *varHyp*: $\forall xf \in \text{set } ((y, g) \# xfs). \pi_1 xf \notin \text{varDiffs}$
and *indHyp*: $(u, x, f) \in \text{set } (vs \otimes xfs) \implies (s[xfs \leftarrow vs]t)(\partial \ x) = vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < 2 * _R t\} \ t$
and *disjHyp*: $(v, y, g) = (u, x, f) \vee (u, x, f) \in \text{set } (vs \otimes xfs)$ **and** *tHyp*: $t > 0$
shows $(s[(y, g) \# xfs \leftarrow v \# vs] \ t) \ (\partial \ x) = vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < 2 * _R t\} \ t$
proof–
let *?lhs* = $((s[xfs \leftarrow vs] \ t)(y := v \ t \ s, \partial \ y := vderiv-of \ (\lambda r. v \ r \ s) \ \{0 < .. < (2 \cdot t)\} \ t)) \ (\partial \ x)$
let *?rhs* = $vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < (2 \cdot t)\} \ t$
have $(s[(y, g) \# xfs \leftarrow v \# vs] \ t) \ (\partial \ x) = ?lhs$ **using** *tHyp* **by** *simp*
also have $vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < 2 * _R t\} \ t = ?rhs$ **by** *simp*
ultimately have *obs*:*?thesis* = $(?lhs = ?rhs)$ **by** *simp*
from *disjHyp* **have** *?lhs* = *?rhs*
proof
assume *uxfEq*: $(v, y, g) = (u, x, f)$
then have *?lhs* = $vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < (2 \cdot t)\} \ t$ **by** *simp*
also have $vderiv-of \ (\lambda r. u \ r \ s) \ \{0 < .. < (2 \cdot t)\} \ t = ?rhs$ **using** *uxfEq* **by** *simp*
ultimately show *?lhs* = *?rhs* **by** *simp*
next
assume *sygTail*: $(u, x, f) \in \text{set } (vs \otimes xfs)$
from *this* **have** $y \neq x$ **using** *distHyp* *set-zip-left-rightD* **by** *force*
hence $\partial \ x \neq \partial \ y$ **by**(*simp* *add*: *vdiff-def*)
have $y \neq \partial \ x$ **using** *varHyp* **using** *vdiff-invarDiffs* **by** *auto*
then have *?lhs* = $(s[xfs \leftarrow vs] \ t) \ (\partial \ x)$ **using** $\langle y \neq \partial \ x \rangle$ **and** $\langle \partial \ x \neq \partial \ y \rangle$ **by** *simp*
also have $(s[xfs \leftarrow vs] \ t) \ (\partial \ x) = ?rhs$ **using** *indHyp* *sygTail* **by** *simp*
ultimately show *?lhs* = *?rhs* **by** *simp*
qed
from *this* **and** *obs* **show** *?thesis* **by** *simp*
qed

lemma *to-sol-greater-than-zero-its-dvars*:
assumes *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$
and *uxfHyp*: $(u, x, f) \in \text{set } (uInput \otimes xfList)$ **and** *tHyp*: $t > 0$

shows ($s[xfList \leftarrow uInput]$ t) (∂x) = $vderiv\text{-}of$ ($\lambda r. u\ r\ s$) $\{0 < .. < (2 *R\ t)\}$ t
using *assms* **apply**(*induct xfList uInput rule: list-induct2', simp, simp, simp, clarify*)
by(*rule-tac f=f in inductive-to-sol-greater-than-zero-its-dvars, auto*)

1.2.2 dInv preliminaries

Here, we introduce syntactic notation to talk about differential invariants.

no-notation *Antidomain-Semiring.antidomain-left-monoid-class.am-add-op* (**infixl** \oplus 65)

no-notation *Dioid.times-class.opp-mult* (**infixl** \odot 70)

no-notation *Lattices.inf-class.inf* (**infixl** \sqcap 70)

no-notation *Lattices.sup-class.sup* (**infixl** \sqcup 65)

datatype *trms* = *Const real* (t_C - [54] 70) | *Var string* (t_V - [54] 70) |
Mns trms (\ominus - [54] 65) | *Sum trms trms* (**infixl** \oplus 65) |
Mult trms trms (**infixl** \odot 68)

primrec *tval* :: *trms* \Rightarrow (*real store* \Rightarrow *real*) ($\llbracket - \rrbracket_t$ [55] 60) **where**

$\llbracket t_C\ r \rrbracket_t = (\lambda s. r)$
 $\llbracket t_V\ x \rrbracket_t = (\lambda s. s\ x)$
 $\llbracket \ominus\ \vartheta \rrbracket_t = (\lambda s. - (\llbracket \vartheta \rrbracket_t)\ s)$
 $\llbracket \vartheta \oplus \eta \rrbracket_t = (\lambda s. (\llbracket \vartheta \rrbracket_t)\ s + (\llbracket \eta \rrbracket_t)\ s)$
 $\llbracket \vartheta \odot \eta \rrbracket_t = (\lambda s. (\llbracket \vartheta \rrbracket_t)\ s \cdot (\llbracket \eta \rrbracket_t)\ s)$

datatype *props* = *Eq trms trms* (**infixr** \doteq 60) | *Less trms trms* (**infixr** \prec 62) |
Leq trms trms (**infixr** \preceq 61) | *And props props* (**infixl** \sqcap 63) |
Or props props (**infixl** \sqcup 64)

primrec *pval* :: *props* \Rightarrow (*real store* \Rightarrow *bool*) ($\llbracket - \rrbracket_P$ [55] 60) **where**

$\llbracket \vartheta \doteq \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t)\ s = (\llbracket \eta \rrbracket_t)\ s)$
 $\llbracket \vartheta \prec \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t)\ s < (\llbracket \eta \rrbracket_t)\ s)$
 $\llbracket \vartheta \preceq \eta \rrbracket_P = (\lambda s. (\llbracket \vartheta \rrbracket_t)\ s \leq (\llbracket \eta \rrbracket_t)\ s)$
 $\llbracket \varphi \sqcap \psi \rrbracket_P = (\lambda s. (\llbracket \varphi \rrbracket_P)\ s \wedge (\llbracket \psi \rrbracket_P)\ s)$
 $\llbracket \varphi \sqcup \psi \rrbracket_P = (\lambda s. (\llbracket \varphi \rrbracket_P)\ s \vee (\llbracket \psi \rrbracket_P)\ s)$

primrec *tdiff* :: *trms* \Rightarrow *trms* (∂_t - [54] 70) **where**

$(\partial_t\ t_C\ r) = t_C\ 0$
 $(\partial_t\ t_V\ x) = t_V\ (\partial\ x)$
 $(\partial_t\ \ominus\ \vartheta) = \ominus\ (\partial_t\ \vartheta)$
 $(\partial_t\ (\vartheta \oplus \eta)) = (\partial_t\ \vartheta) \oplus (\partial_t\ \eta)$
 $(\partial_t\ (\vartheta \odot \eta)) = ((\partial_t\ \vartheta) \odot \eta) \oplus (\vartheta \odot (\partial_t\ \eta))$

primrec *pdiff* :: *props* \Rightarrow *props* (∂_P - [54] 70) **where**

$(\partial_P\ (\vartheta \doteq \eta)) = ((\partial_t\ \vartheta) \doteq (\partial_t\ \eta))$
 $(\partial_P\ (\vartheta \prec \eta)) = ((\partial_t\ \vartheta) \prec (\partial_t\ \eta))$
 $(\partial_P\ (\vartheta \preceq \eta)) = ((\partial_t\ \vartheta) \preceq (\partial_t\ \eta))$
 $(\partial_P\ (\varphi \sqcap \psi)) = (\partial_P\ \varphi) \sqcap (\partial_P\ \psi)$
 $(\partial_P\ (\varphi \sqcup \psi)) = (\partial_P\ \varphi) \sqcup (\partial_P\ \psi)$

primrec *trmVars* :: *trms* \Rightarrow *string set* **where**

trmVars (t_C *r*) = $\{\}$ |
trmVars (t_V *x*) = $\{x\}$ |
trmVars (\ominus ϑ) = *trmVars* ϑ |
trmVars ($\vartheta \oplus \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η |
trmVars ($\vartheta \odot \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η

fun *substList* :: (*string* \times *trms*) *list* \Rightarrow *trms* \Rightarrow *trms* ($[-]$ [54] 80) **where**

xtList (t_C *r*) = t_C *r*|
 $\llbracket t_V$ *x* $\rrbracket = t_V$ *x*|
 $((y, \xi) \# xtTail)(Var\ x) = (if\ x = y\ then\ \xi\ else\ xtTail(Var\ x))$ |
xtList (\ominus ϑ) = \ominus (*xtList* $\langle \vartheta \rangle$)|
xtList ($\vartheta \oplus \eta$) = (*xtList* $\langle \vartheta \rangle$) \oplus (*xtList* $\langle \eta \rangle$)|
xtList ($\vartheta \odot \eta$) = (*xtList* $\langle \vartheta \rangle$) \odot (*xtList* $\langle \eta \rangle$)

proposition *substList-on-compl-of-varDiffs*:

assumes *trmVars* $\eta \subseteq (UNIV - varDiffs)$
assumes *set* (*map* π_1 *xtList*) $\subseteq varDiffs$
shows *xtList* $\langle \eta \rangle = \eta$
using *assms* **apply** (*induction* η , *simp-all* *add*: *varDiffs-def*)
by (*induction* *xtList*, *auto*)

lemma *substList-help1*: *set* (*map* π_1 ((*map* (*vdiff* \circ π_1) *xfList*) \otimes *uInput*)) \subseteq *varDiffs*

apply (*induct* *xfList* *uInput* *rule*: *list-induct2'*, *simp-all* *add*: *varDiffs-def*)
by *auto*

lemma *substList-help2*:

assumes *trmVars* $\eta \subseteq (UNIV - varDiffs)$
shows ((*map* (*vdiff* \circ π_1) *xfList*) \otimes *uInput*) $\langle \eta \rangle = \eta$
using *assms* *substList-help1* *substList-on-compl-of-varDiffs* **by** *blast*

lemma *substList-cross-vdiff-on-non-occurring-var*:

assumes $x \notin \text{set } list1$
shows ((*map* *vdiff* *list1*) \otimes *list2*) $\langle t_V (\partial\ x) \rangle = t_V (\partial\ x)$
using *assms* **apply** (*induct* *list1* *list2* *rule*: *list-induct2'*, *simp*, *simp*, *clarsimp*)
by (*simp* *add*: *vdiff-def*)

primrec *propVars* :: *props* \Rightarrow *string set* **where**

propVars ($\vartheta \doteq \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η |
propVars ($\vartheta \prec \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η |
propVars ($\vartheta \preceq \eta$) = *trmVars* $\vartheta \cup$ *trmVars* η |
propVars ($\varphi \sqcap \psi$) = *propVars* $\varphi \cup$ *propVars* ψ |
propVars ($\varphi \sqcup \psi$) = *propVars* $\varphi \cup$ *propVars* ψ

primrec *subspList* :: (*string* \times *trms*) *list* \Rightarrow *props* \Rightarrow *props* ($[-]$ [54] 80) **where**

xtList $\upharpoonright \vartheta \doteq \eta \upharpoonright = ((xtList \langle \vartheta \rangle) \doteq (xtList \langle \eta \rangle))$ |
xtList $\upharpoonright \vartheta \prec \eta \upharpoonright = ((xtList \langle \vartheta \rangle) \prec (xtList \langle \eta \rangle))$ |

$$\begin{aligned}
xtList \upharpoonright \vartheta \preceq \eta \upharpoonright &= ((xtList \langle \vartheta \rangle) \preceq (xtList \langle \eta \rangle)) \\
xtList \upharpoonright \varphi \sqcap \psi \upharpoonright &= ((xtList \upharpoonright \varphi) \sqcap (xtList \upharpoonright \psi)) \\
xtList \upharpoonright \varphi \sqcup \psi \upharpoonright &= ((xtList \upharpoonright \varphi) \sqcup (xtList \upharpoonright \psi))
\end{aligned}$$

end
theory *VC-diffKAD*
imports *VC-diffKAD-auxiliarities*

begin

1.3 Phase Space Relational Semantics

definition *solvesStoreIVP* :: (*real* \Rightarrow *real store*) \Rightarrow (*string* \times (*real store* \Rightarrow *real*))
list \Rightarrow
real store \Rightarrow *bool*
 ((- *solvesTheStoreIVP* - *withInitState* -) [70, 70, 70] 68) **where**
solvesStoreIVP φ_S *xfList* *s* \equiv
 (* *F* sends *vdiffs-in-list* to *derivs*. *)
 ($\forall t \geq 0. (\forall xf \in \text{set } xfList. \varphi_S t (\partial (\pi_1 xf)) = \pi_2 xf (\varphi_S t)) \wedge$
 (* *F* preserves the rest of the variables and *F* sends *derivs* of constants to 0. *)
 ($\forall y. (y \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y) \wedge$
 ($y \notin (\pi_1(\text{set } xfList)) \longrightarrow \varphi_S t (\partial y) = 0)) \wedge$
 (* *F* solves the induced IVP. *)
 ($\forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\}$
UNIV \wedge
 $\varphi_S 0 (\pi_1 xf) = s(\pi_1 xf))$

lemma *solves-store-ivpI*:

assumes $\forall t \geq 0. \forall xf \in \text{set } xfList. (\varphi_S t (\partial (\pi_1 xf))) = (\pi_2 xf) (\varphi_S t)$
and $\forall t \geq 0. \forall y. y \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y$
and $\forall t \geq 0. \forall y. y \notin (\pi_1(\text{set } xfList)) \longrightarrow \varphi_S t (\partial y) = 0$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\}$ *UNIV*
and $\forall xf \in \text{set } xfList. \varphi_S 0 (\pi_1 xf) = s(\pi_1 xf)$
shows $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
apply(*simp add: solvesStoreIVP-def, safe*)
using *assms* **apply** *simp-all*
by(*force,force,force*)

named-theorems *solves-store-ivpE* *elimination rules for solvesStoreIVP*

lemma [*solves-store-ivpE*]:

assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
shows $\forall t \geq 0. \forall y. y \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs} \longrightarrow \varphi_S t y = s y$
and $\forall t \geq 0. \forall y. y \notin (\pi_1(\text{set } xfList)) \longrightarrow \varphi_S t (\partial y) = 0$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. (\varphi_S t (\partial (\pi_1 xf))) = (\pi_2 xf) (\varphi_S t)$
and $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\}$ *UNIV*

$(\varphi_S t))) \{0..t\} \text{ UNIV}$
and $\forall xf \in \text{set } xfList. \varphi_S 0 (\pi_1 xf) = s(\pi_1 xf)$
using *assms solvesStoreIVP-def* **by** *auto*

lemma [*solves-store-ivpE*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
shows $\forall y. y \notin \text{varDiffs} \longrightarrow \varphi_S 0 y = s y$
proof(*clarify, rename-tac x*)
fix x **assume** $x \notin \text{varDiffs}$
from *assms* **and** *solves-store-ivpE(5)* **have** $x \in (\pi_1(\text{set } xfList)) \implies \varphi_S 0 x = s x$
by *fastforce*
also **have** $x \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs} \implies \varphi_S 0 x = s x$
using *assms* **and** *solves-store-ivpE(1)* **by** *simp*
ultimately show $\varphi_S 0 x = s x$ **using** $\langle x \notin \text{varDiffs} \rangle$ **by** *auto*
qed

named-theorems *solves-store-ivpD computation rules for solvesStoreIVP*

lemma [*solves-store-ivpD*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
and $t \geq 0$
and $y \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$
shows $\varphi_S t y = s y$
using *assms solves-store-ivpE(1)* **by** *simp*

lemma [*solves-store-ivpD*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
and $t \geq 0$
and $y \notin (\pi_1(\text{set } xfList))$
shows $\varphi_S t (\partial y) = 0$
using *assms solves-store-ivpE(2)* **by** *simp*

lemma [*solves-store-ivpD*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
and $t \geq 0$
and $xf \in \text{set } xfList$
shows $(\varphi_S t (\partial (\pi_1 xf))) = (\pi_2 xf) (\varphi_S t)$
using *assms solves-store-ivpE(3)* **by** *simp*

lemma [*solves-store-ivpD*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
and $t \geq 0$
and $xf \in \text{set } xfList$
shows $((\lambda t. \varphi_S t (\pi_1 xf)) \text{ solves-ode } (\lambda t. \lambda r. (\pi_2 xf) (\varphi_S t))) \{0..t\} \text{ UNIV}$
using *assms solves-store-ivpE(4)* **by** *simp*

lemma [*solves-store-ivpD*]:
assumes $\varphi_S \text{ solvesTheStoreIVP } xfList \text{ withInitState } s$
and $(x, f) \in \text{set } xfList$

shows $\varphi_S \ 0 \ x = s \ x$
using *assms solves-store-ivpE(5)* **by** *fastforce*

lemma [*solves-store-ivpD*]:
assumes φ_S *solvesTheStoreIVP xflist withInitState s*
and $y \notin \text{varDiffs}$
shows $\varphi_S \ 0 \ y = s \ y$
using *assms solves-store-ivpE(6)* **by** *simp*

definition *guarDiffEqtn* :: $(\text{string} \times (\text{real store} \Rightarrow \text{real})) \text{ list} \Rightarrow (\text{real store} \text{ pred})$
 \Rightarrow
 $\text{real store rel } (\text{ODEsystem} - \text{with} - [\gamma 0, \gamma 0] \ 61)$ **where**
 $\text{ODEsystem } xflist \text{ with } G = \{(s, \varphi_S \ t) \mid s \ t \ \varphi_S. \ t \geq 0 \wedge (\forall \ r \in \{0..t\}. \ G \ (\varphi_S \ r))$
 $\wedge \text{ solvesStoreIVP } \varphi_S \ xflist \ s\}$

1.4 Derivation of Differential Dynamic Logic Rules

1.4.1 "Differential Weakening"

lemma *wlp-evol-guard*: $\text{Id} \subseteq \text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil G \rceil$
by (*simp add: rel-antidomain-kleene-algebra.fbox-def rel-ad-def guarDiffEqtn-def p2r-def*,
force)

theorem *dWeakening*:
assumes *guardImpliesPost*: $\lceil G \rceil \subseteq \lceil Q \rceil$
shows $\text{PRE } P \ (\text{ODEsystem } xflist \text{ with } G) \ \text{POST } Q$
using *assms and wlp-evol-guard by (metis (no-types, hide-lams) d-p2r*
order-trans p2r-subid rel-antidomain-kleene-algebra.fbox-iso)

lemma *dW1*: $\text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil Q \rceil \subseteq \text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil \lambda s. \ G \ s \longrightarrow Q \ s \rceil$
unfolding *rel-antidomain-kleene-algebra.fbox-def rel-ad-def guarDiffEqtn-def*
by (*simp add: p2r-def relcomp.simps, blast*)

lemma *dW2*: $\text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil \lambda s. \ G \ s \longrightarrow Q \ s \rceil \subseteq \text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil Q \rceil$
unfolding *rel-antidomain-kleene-algebra.fbox-def rel-ad-def guarDiffEqtn-def*
by (*simp add: relcomp.simps p2r-def, fastforce*)

theorem *dW*: $\text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil Q \rceil = \text{wp } (\text{ODEsystem } xflist \text{ with } G) \ \lceil \lambda s. \ G \ s \longrightarrow Q \ s \rceil$
using *dW1 and dW2 by blast*

1.4.2 "Differential Cut"

lemma *all-interval-guarDiffEqtn*:
assumes *solvesStoreIVP* $\varphi_S \ xflist \ s \wedge (\forall \ r \in \{0..t\}. \ G \ (\varphi_S \ r)) \wedge 0 \leq t$
shows $\forall \ r \in \{0..t\}. \ (s, \varphi_S \ r) \in (\text{ODEsystem } xflist \text{ with } G)$
unfolding *guarDiffEqtn-def* **using** *atLeastAtMost-iff* **apply** *clarsimp*
apply (*rule-tac x=r in exI, rule-tac x= φ_S in exI*) **using** *assms by simp*

lemma *condAfterEvol-remainsAlongEvol*:
assumes *boxDiffC*: $(s, s) \in wp \ (ODEsystem \ xfList \ with \ G) \ [C]$
and *FisSol*:*solvesStoreIVP* $\varphi_S \ xfList \ s \wedge (\forall \ r \in \{0..t\}. G \ (\varphi_S \ r)) \wedge 0 \leq t$
shows $\forall \ r \in \{0..t\}. G \ (\varphi_S \ r) \wedge C \ (\varphi_S \ r)$
proof–
from *boxDiffC* **have** $\forall \ c. (s, c) \in (ODEsystem \ xfList \ with \ G) \longrightarrow C \ c$
by (*simp add: boxProgrPred-chrcrzn*)
also from *FisSol* **have** $\forall \ r \in \{0..t\}. (s, \varphi_S \ r) \in (ODEsystem \ xfList \ with \ G)$
using *all-interval-guarDiffEqtn* **by** *blast*
ultimately show *?thesis*
using *FisSol atLeastAtMost-iff guarDiffEqtn-def* **by** *fastforce*
qed

theorem *dCut*:
assumes *pBoxDiffCut*: $(PRE \ P \ (ODEsystem \ xfList \ with \ G) \ POST \ C)$
assumes *pBoxCutQ*: $(PRE \ P \ (ODEsystem \ xfList \ with \ (\lambda \ s. G \ s \wedge C \ s)) \ POST \ Q)$
shows $PRE \ P \ (ODEsystem \ xfList \ with \ G) \ POST \ Q$
apply(*clarify, subgoal-tac a = b*) **defer**
proof(*metis d-p2r rdom-p2r-contents, simp, subst boxProgrPred-chrcrzn, clarify*)
fix *b y* **assume** $(b, b) \in [P]$ **and** $(b, y) \in ODEsystem \ xfList \ with \ G$
then obtain $\varphi_S \ t$ **where** **:solvesStoreIVP* $\varphi_S \ xfList \ b \wedge (\forall \ r \in \{0..t\}. G \ (\varphi_S \ r)) \wedge 0 \leq t \wedge \varphi_S \ t = y$
using *guarDiffEqtn-def* **by** *auto*
hence $\forall \ r \in \{0..t\}. (b, \varphi_S \ r) \in (ODEsystem \ xfList \ with \ G)$
using *all-interval-guarDiffEqtn* **by** *blast*
from this and *pBoxDiffCut* **have** $\forall \ r \in \{0..t\}. C \ (\varphi_S \ r)$
using *boxProgrPred-chrcrzn* $\langle (b, b) \in [P] \rangle$ **by** (*metis (no-types, lifting) d-p2r subsetCE*)
then have $\forall \ r \in \{0..t\}. (b, \varphi_S \ r) \in (ODEsystem \ xfList \ with \ (\lambda \ s. G \ s \wedge C \ s))$
using ** all-interval-guarDiffEqtn* **by** (*metis (mono-tags, lifting)*)
from this and *pBoxCutQ* **have** $\forall \ r \in \{0..t\}. Q \ (\varphi_S \ r)$
using *boxProgrPred-chrcrzn* $\langle (b, b) \in [P] \rangle$ **by** (*metis (no-types, lifting) d-p2r subsetCE*)
thus $Q \ y$ **using** *** **by** *auto*
qed

theorem *dC*:
assumes $Id \subseteq wp \ (ODEsystem \ xfList \ with \ G) \ [C]$
shows $wp \ (ODEsystem \ xfList \ with \ G) \ [Q] = wp \ (ODEsystem \ xfList \ with \ (\lambda \ s. G \ s \wedge C \ s)) \ [Q]$
proof(*rule-tac f = $\lambda \ x. wp \ x \ [Q]$ in HOL.arg-cong, safe*)
fix *a b* **assume** $(a, b) \in ODEsystem \ xfList \ with \ G$
then obtain $\varphi_S \ t$ **where** **:solvesStoreIVP* $\varphi_S \ xfList \ a \wedge (\forall \ r \in \{0..t\}. G \ (\varphi_S \ r)) \wedge 0 \leq t \wedge \varphi_S \ t = b$
using *guarDiffEqtn-def* **by** *auto*
hence $1: \forall \ r \in \{0..t\}. (a, \varphi_S \ r) \in ODEsystem \ xfList \ with \ G$
by (*meson all-interval-guarDiffEqtn*)
from this have $\forall \ r \in \{0..t\}. C \ (\varphi_S \ r)$ **using** *assms boxProgrPred-chrcrzn*

```

    by (metis IdI boxProgrPred-IsProp subset-antisym)
  thus (a, b) ∈ ODEsystem xfList with (λs. G s ∧ C s)
    using * guarDiffEqtn-def by blast
next
  fix a b assume (a, b) ∈ ODEsystem xfList with (λs. G s ∧ C s)
  then show (a, b) ∈ ODEsystem xfList with G
    unfolding guarDiffEqtn-def by (clarsimp, rule-tac x=t in exI, rule-tac x=φS in
exI, simp)
qed

```

1.4.3 "Solve Differential Equation"

lemma *prelim-dSolve*:

```

assumes solHyp:(λt. sol s[xfList←uInput] t) solvesTheStoreIVP xfList withInit-
State s
and uniqHyp:∀ X. solvesStoreIVP X xfList s ⟶ (∀ t ≥ 0. (sol s[xfList←uInput]
t) = X t)
and diffAssgn: ∀ t ≥ 0. G (sol s[xfList←uInput] t) ⟶ Q (sol s[xfList←uInput] t)
shows ∀ c. (s, c) ∈ (ODEsystem xfList with G) ⟶ Q c
proof(clarify)
fix c assume (s, c) ∈ (ODEsystem xfList with G)
from this obtain t::real and φS::real ⇒ real store
where FHyp:t ≥ 0 ∧ φS t = c ∧ solvesStoreIVP φS xfList s ∧ (∀ r ∈ {0..t}. G
(φS r))
using guarDiffEqtn-def by auto
from this and uniqHyp have (sol s[xfList←uInput] t) = φS t by blast
then have cHyp:c = (sol s[xfList←uInput] t) using FHyp by simp
from this have G (sol s[xfList←uInput] t) using FHyp by force
then show Q c using diffAssgn FHyp cHyp by auto
qed

```

theorem *dS*:

```

assumes solHyp:∀ s. solvesStoreIVP (λt. sol s[xfList←uInput] t) xfList s
and uniqHyp:∀ s X. solvesStoreIVP X xfList s ⟶ (∀ t ≥ 0. (sol s[xfList←uInput]
t) = X t)
shows wp (ODEsystem xfList with G) [Q] =
  [λ s. ∀ t ≥ 0. (∀ r ∈ {0..t}. G (sol s[xfList←uInput] r)) ⟶ Q (sol s[xfList←uInput]
t)]
apply(simp add: p2r-def, rule subset-antisym)
unfolding guarDiffEqtn-def rel-antidomain-kleene-algebra.fbox-def rel-ad-def
using solHyp apply(simp add: relcomp.simps) apply clarify
apply(rule-tac x=x in exI, clarsimp)
apply(erule-tac x=sol x[xfList←uInput] t in allE, erule disjE)
apply(erule-tac x=x in allE, erule-tac x=t in allE)
apply(erule impE, simp, erule-tac x=λt. sol x[xfList←uInput] t in allE)
apply(simp-all, clarify, rule-tac x=s in exI, simp add: relcomp.simps)
using uniqHyp by fastforce

```

theorem *dSolve*:

assumes $\text{solHyp}:\forall s. \text{solvesStoreIVP } (\lambda t. \text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) \ \text{xfList } s$
and $\text{uniqHyp}:\forall s. \forall X. \text{solvesStoreIVP } X \ \text{xfList } s \longrightarrow (\forall t \geq 0. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) = X \ t)$
and $\text{diffAssgn}:\forall s. P \ s \longrightarrow (\forall t \geq 0. G \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) \longrightarrow Q \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t))$
shows $\text{PRE } P \ (\text{ODEsystem } \text{xfList} \text{ with } G) \ \text{POST } Q$
apply(clarsimp , $\text{subgoal-tac } a=b$)
apply(clarify , $\text{subst } \text{boxProgrPred-chrcrtrzn}$)
apply($\text{simp-all add: p2r-def}$)
apply($\text{rule-tac } \text{uInput}=\text{uInput}$ **in** prelim-dSolve)
apply(simp add: solHyp , simp add: uniqHyp)
by ($\text{metis (no-types, lifting) diffAssgn}$)

— We proceed to refine the previous rule by finding the necessary restrictions on varFunList and uInput so that the solution to the store-IVP is guaranteed.

lemma $\text{conds4vdiffs-prelim}$:

assumes $\text{funcsHyp}:\forall s \ g. \forall \text{xf} \in \text{set } \text{xfList}. \pi_2 \ \text{xf} \ (\text{override-on } s \ g \ \text{varDiffs}) = \pi_2 \ \text{xf}$
 s
and $\text{distinctHyp}:\text{distinct } (\text{map } \pi_1 \ \text{xfList})$
and $\text{varsHyp}:\forall \text{xf} \in \text{set } \text{xfList}. \pi_1 \ \text{xf} \notin \text{varDiffs}$
and $\text{lengthHyp}:\text{length } \text{xfList} = \text{length } \text{uInput}$
and $\text{solHyp1}:\forall \text{uxf} \in \text{set } (\text{uInput} \otimes \text{xfList}). (\pi_1 \ \text{uxf}) \ 0 \ (\text{sol } s) = (\text{sol } s) \ (\pi_1 \ (\pi_2 \ \text{uxf}))$
and $\text{solHyp2}:\forall t \geq 0. ((\lambda \tau. (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ \tau) \ x) \text{ has-vderiv-on } (\lambda \tau. f \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ \tau))) \ \{0..t\}$
and $\text{xfHyp}:(x, f) \in \text{set } \text{xfList}$ **and** $t\text{Hyp}:t \geq 0$
shows $(\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) \ (\partial \ x) = f \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t)$
proof—
from xfHyp **obtain** u **where** $\text{xfuHyp}:(u, x, f) \in \text{set } (\text{uInput} \otimes \text{xfList})$
by ($\text{metis in-set-impl-in-set-zip2 lengthHyp}$)
show $(\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) \ (\partial \ x) = f \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t)$
proof($\text{cases } t=0$)
case True
have $(\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ 0) \ (\partial \ x) = f \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ 0)$
using assms **and** $\text{to-sol-zero-its-dvars}$ **by** blast
then show $?thesis$ **using** True **by** blast
next
case False
from this have $t > 0$ **using** $t\text{Hyp}$ **by** simp
hence $(\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t) \ (\partial \ x) = \text{vderiv-of } (\lambda r. u \ r \ (\text{sol } s)) \ \{0 < .. < (2 *_{\text{R}} t)\} \ t$
using $\text{xfuHyp assms to-sol-greater-than-zero-its-dvars}$ **by** blast
also have $\text{vderiv-of } (\lambda r. u \ r \ (\text{sol } s)) \ \{0 < .. < (2 *_{\text{R}} t)\} \ t = f \ (\text{sol } s[\text{xfList} \leftarrow \text{uInput}] \ t)$
using $\text{assms xfuHyp } \langle t > 0 \rangle$ **and** $\text{vderiv-of-to-sol-its-vars}$ **by** blast
ultimately show $?thesis$ **by** simp
qed
qed

lemma *conds4vdiffs*:
assumes *funcsHyp*: $\forall s g. \forall xf \in \text{set } xfList. \pi_2 \text{ } xf \text{ (override-on } s \text{ } g \text{ } varDiffs) = \pi_2 \text{ } xf$
 s
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 \text{ } uxf) \text{ } 0 \text{ (sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ } uxf))$
and *solHyp2*: $\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda \tau. (\text{sol } s [xfList \leftarrow uInput] \text{ } \tau) (\pi_1 \text{ } xf))$
has-vderiv-on ($\lambda \tau. (\pi_2 \text{ } xf) (\text{sol } s [xfList \leftarrow uInput] \text{ } \tau))) \{0..t\}$
shows $\forall t \geq 0. \forall xf \in \text{set } xfList. (\text{sol } s [xfList \leftarrow uInput] \text{ } t) (\partial (\pi_1 \text{ } xf)) = (\pi_2 \text{ } xf)$
 $(\text{sol } s [xfList \leftarrow uInput] \text{ } t)$
apply(*rule allI*, *rule impI*, *rule ballI*, *rule conds4vdiffs-prelim*)
using *assms* **by** *simp-all*

lemma *conds4Consts*:
assumes *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
shows $\forall x. x \notin (\pi_1 (\text{set } xfList)) \longrightarrow (\text{sol } s [xfList \leftarrow uInput] \text{ } t) (\partial x) = 0$
using *varsHyp* **apply**(*induct* *xfList* *uInput* *rule: list-induct2'*)
apply(*simp-all add: override-on-def varDiffs-def vdiff-def*)
by *clarsimp*

lemma *conds4InitState*:
assumes *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 \text{ } xf \notin varDiffs$
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 \text{ } uxf) \text{ } 0 \text{ (sol } s) = (\text{sol } s) (\pi_1 (\pi_2 \text{ } uxf))$
and *xfHyp*: $(x, f) \in \text{set } xfList$
shows $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = s x$
proof–
from *xfHyp* **obtain** *u* **where** *uxfHyp*: $(u, x, f) \in \text{set } (uInput \otimes xfList)$
by (*metis in-set-impl-in-set-zip2 lengthHyp*)
from *varsHyp* **have** *toZeroHyp*: $(\text{sol } s) x = s x$ **using** *override-on-def xfHyp* **by** *auto*
from *uxfHyp* **and** *solHyp1* **have** $u \text{ } 0 \text{ (sol } s) = (\text{sol } s) x$ **by** *fastforce*
also **have** $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = u \text{ } 0 \text{ (sol } s)$
using *state-list-cross-upd-its-vars uxfHyp* **and** *assms* **by** *blast*
ultimately show $(\text{sol } s [xfList \leftarrow uInput] \text{ } 0) x = s x$ **using** *toZeroHyp* **by** *simp*
qed

lemma *conds4RestOfStrings*:
assumes $x \notin (\pi_1 (\text{set } xfList)) \cup varDiffs$
shows $(\text{sol } s [xfList \leftarrow uInput] \text{ } t) x = s x$
using *assms* **apply**(*induct* *xfList* *uInput* *rule: list-induct2'*)
by(*auto simp: varDiffs-def*)

lemma *conds4storeIVP-on-toSol*:
assumes *funcsHyp*: $\forall s g. \forall xf \in \text{set } xfList. \pi_2 \text{ } xf \text{ (override-on } s \text{ } g \text{ } varDiffs) = \pi_2 \text{ } xf$

s
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$
and *solHyp1*: $\forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 uxf) \ 0 \ (sol \ s) = (sol \ s) \ (\pi_1 \ (\pi_2 \ uxf))$
and *solHyp2*: $\forall t \geq 0. \forall xf \in \text{set } xfList.$
 $((\lambda t. (sol \ s[xfList \leftarrow uInput] \ t) \ (\pi_1 \ xf)) \text{ has-vderiv-on } (\lambda t. \pi_2 \ xf \ (sol \ s[xfList \leftarrow uInput] \ t))) \ \{0..t\}$
shows *solvesStoreIVP* ($\lambda t. (sol \ s[xfList \leftarrow uInput] \ t)$) *xfList* *s*
apply(*rule solves-store-ivpI*)
subgoal using *conds4vdiffs* *assms* **by** *blast*
subgoal using *conds4RestOfStrings* **by** *blast*
subgoal using *conds4Consts varsHyp* **by** *blast*
subgoal apply(*rule allI*, *rule impI*, *rule ballI*, *rule solves-odeI*)
using *solHyp2* **by** *simp-all*
subgoal using *conds4InitState* **and** *assms* **by** *force*
done

theorem *dSolve-toSolve*:
assumes *funcsHyp*: $\forall s \ g. \forall xf \in \text{set } xfList. \pi_2 \ xf \ (\text{override-on } s \ g \ \text{varDiffs}) = \pi_2 \ xf$
 s
and *distinctHyp*:*distinct* (*map* π_1 *xfList*)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1 xf \notin \text{varDiffs}$
and *solHyp1*: $\forall s. \forall uxf \in \text{set } (uInput \otimes xfList). (\pi_1 uxf) \ 0 \ (sol \ s) = (sol \ s) \ (\pi_1 \ (\pi_2 \ uxf))$
and *solHyp2*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList.$
 $((\lambda t. (sol \ s[xfList \leftarrow uInput] \ t) \ (\pi_1 \ xf)) \text{ has-vderiv-on } (\lambda t. \pi_2 \ xf \ (sol \ s[xfList \leftarrow uInput] \ t))) \ \{0..t\}$
and *uniqHyp*: $\forall s. \forall X. \text{solvesStoreIVP } X \ xfList \ s \longrightarrow (\forall t \geq 0. (sol \ s[xfList \leftarrow uInput] \ t) = X \ t)$
and *postCondHyp*: $\forall s. P \ s \longrightarrow (\forall t \geq 0. Q \ (sol \ s[xfList \leftarrow uInput] \ t))$
shows *PRE* *P* (*ODEsystem* *xfList* *with* *G*) *POST* *Q*
apply(*rule-tac* *uInput=uInput* **in** *dSolve*)
subgoal using *assms* **and** *conds4storeIVP-on-toSol* **by** *simp*
subgoal by (*simp* *add*: *uniqHyp*)
using *postCondHyp* *postCondHyp* **by** *simp*

— As before, we keep refining the rule *dSolve*. This time we find the necessary restrictions to attain uniqueness.

lemma *conds4UniqSol*:
fixes *f*:*real store* \Rightarrow *real*
assumes *tHyp*: $t \geq 0$
and *contHyp*:*continuous-on* ($\{0..t\} \times UNIV$) ($\lambda(t, (r::real)). f \ (\varphi_s \ t)$)
shows *unique-on-bounded-closed* $0 \ \{0..t\} \ \tau \ (\lambda t \ r. f \ (\varphi_s \ t)) \ UNIV$ (*if* $t = 0$ *then* 1 *else* $1/(t+1)$)
apply(*simp* *add*: *unique-on-bounded-closed-def* *unique-on-bounded-closed-axioms-def*)

unique-on-closed-def compact-interval-def compact-interval-axioms-def nonempty-set-def
interval-def self-mapping-def self-mapping-axioms-def closed-domain-def global-lipschitz-def
lipschitz-def, rule conjI)
subgoal using *contHyp continuous-rhs-def* **by** *fastforce*
subgoal using *assms continuous-rhs-def* **by** *fastforce*
done

lemma *solves-store-ivp-at-beginning-overrides:*
assumes *solvesStoreIVP* φ_s *xfList* *a*
shows $\varphi_s \ 0 = \text{override-on } a \ (\varphi_s \ 0) \ \text{varDiffs}$
apply(*rule ext, subgoal-tac* $x \notin \text{varDiffs} \longrightarrow \varphi_s \ 0 \ x = a \ x$)
subgoal by (*simp add: override-on-def*)
using *assms and solves-store-ivpD(6)* **by** *simp*

lemma *ubcStoreUniqueSol:*
assumes *tHyp*: $t \geq 0$
assumes *contHyp*: $\forall \ xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$
 $(\lambda(t, (r::\text{real})). (\pi_2 \ xf) \ (\text{sol } s[xfList \leftarrow uInput] \ t))$
and *eqDerivs*: $\forall \ xf \in \text{set } xfList. \forall \ \tau \in \{0..t\}. (\pi_2 \ xf) \ (\varphi_s \ \tau) = (\pi_2 \ xf) \ (\text{sol } s[xfList \leftarrow uInput] \ \tau)$
and *Fsolves*:*solvesStoreIVP* φ_s *xfList* *s*
and *solHyp*:*solvesStoreIVP* $(\lambda \ \tau. (\text{sol } s[xfList \leftarrow uInput] \ \tau))$ *xfList* *s*
shows $(\text{sol } s[xfList \leftarrow uInput] \ t) = \varphi_s \ t$
proof
fix *x::string* **show** $(\text{sol } s[xfList \leftarrow uInput] \ t) \ x = \varphi_s \ t \ x$
proof(*cases* $x \in (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$)
case *False*
then have *notInVars*: $x \notin (\pi_1(\text{set } xfList)) \cup \text{varDiffs}$ **by** *simp*
from *solHyp* **have** $(\text{sol } s[xfList \leftarrow uInput] \ t) \ x = s \ x$
using *tHyp notInVars solves-store-ivpD(1)* **by** *blast*
also from *Fsolves* **have** $\varphi_s \ t \ x = s \ x$ **using** *tHyp notInVars solves-store-ivpD(1)*
by *blast*
ultimately show $(\text{sol } s[xfList \leftarrow uInput] \ t) \ x = \varphi_s \ t \ x$ **by** *simp*
next case *True*
then have $x \in (\pi_1(\text{set } xfList)) \vee x \in \text{varDiffs}$ **by** *simp*
from this show *?thesis*
proof
assume $x \in (\pi_1(\text{set } xfList))$
from this obtain *f* **where** *xfHyp*: $(x, f) \in \text{set } xfList$ **by** *fastforce*

then have *expand1*: $\forall \ xf \in \text{set } xfList. ((\lambda \tau. \varphi_s \ \tau \ (\pi_1 \ xf)) \text{ solves-ode } (\lambda \tau \ r. (\pi_2 \ xf) \ (\varphi_s \ \tau))) \{0..t\} \ UNIV \wedge \varphi_s \ 0 \ (\pi_1 \ xf) = s \ (\pi_1 \ xf)$
using *Fsolves tHyp* **by** (*simp add:solvesStoreIVP-def*)
hence *expand2*: $\forall \ xf \in \text{set } xfList. \forall \ \tau \in \{0..t\}. ((\lambda r. \varphi_s \ r \ (\pi_1 \ xf)) \text{ has-vector-derivative } (\lambda r. (\pi_2 \ xf) \ (\text{sol } s[xfList \leftarrow uInput] \ \tau)) \ \tau) \ (\text{at } \tau \ \text{within } \{0..t\})$

```

using eqDerivs by (simp add: solves-ode-def has-vderiv-on-def)

then have  $\forall xf \in \text{set } xfList. ((\lambda \tau. \varphi_s \tau (\pi_1 xf)) \text{ solves-ode}$ 
   $(\lambda \tau r. (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ \tau))) \{0..t\} \text{ UNIV} \wedge \varphi_s\ 0\ (\pi_1 xf) = s$ 
   $(\pi_1 xf)$ 
  by (simp add: has-vderiv-on-def solves-ode-def expand1 expand2)
then have  $1:((\lambda \tau. \varphi_s \tau x) \text{ solves-ode } (\lambda \tau r. f (sol\ s[xfList \leftarrow uInput]\ \tau))) \{0..t\}$ 
   $\text{UNIV} \wedge$ 
   $\varphi_s\ 0\ x = s\ x$  using xfHyp by fastforce

from solHyp and xfHyp have  $2:((\lambda \tau. (sol\ s[xfList \leftarrow uInput]\ \tau)\ x) \text{ solves-ode}$ 
   $(\lambda \tau r. f (sol\ s[xfList \leftarrow uInput]\ \tau))) \{0..t\} \text{ UNIV} \wedge (sol\ s[xfList \leftarrow uInput]\ 0)$ 
   $x = s\ x$ 
  using solvesStoreIVP-def tHyp by fastforce

from tHyp and contHyp have  $\forall xf \in \text{set } xfList. \text{unique-on-bounded-closed } 0$ 
   $\{0..t\} (s (\pi_1 xf))$ 
   $(\lambda \tau r. (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ \tau)) \text{ UNIV (if } t = 0 \text{ then } 1 \text{ else } 1/(t+1))$ 

apply(clarify) apply(rule conds4UniqSol) by(auto)
from this have  $3:\text{unique-on-bounded-closed } 0\ \{0..t\} (s\ x) (\lambda \tau r. f (sol$ 
   $s[xfList \leftarrow uInput]\ \tau))$ 
   $\text{UNIV (if } t = 0 \text{ then } 1 \text{ else } 1/(t+1))$  using xfHyp by fastforce
from  $1\ 2$  and  $3$  show  $(sol\ s[xfList \leftarrow uInput]\ t)\ x = \varphi_s\ t\ x$ 
using unique-on-bounded-closed.unique-solution using real-Icc-closed-segment
tHyp by blast
next
assume  $x \in \text{varDiffs}$ 
then obtain  $y$  where  $xDef:x = \partial\ y$  by (auto simp: varDiffs-def)
show  $(sol\ s[xfList \leftarrow uInput]\ t)\ x = \varphi_s\ t\ x$ 
proof(cases  $y \in \text{set } (\text{map } \pi_1\ xfList)$ )
case True
then obtain  $f$  where  $xfHyp:(y, f) \in \text{set } xfList$  by fastforce
from tHyp and Fsolves have  $\varphi_s\ t\ x = f\ (\varphi_s\ t)$ 
using solves-store-ivpD(3) xfHyp xDef by force
also have  $(sol\ s[xfList \leftarrow uInput]\ t)\ x = f\ (sol\ s[xfList \leftarrow uInput]\ t)$ 
using solves-store-ivpD(3) xfHyp xDef solHyp tHyp by force
ultimately show ?thesis using eqDerivs xfHyp tHyp by auto
next case False
then have  $\varphi_s\ t\ x = 0$ 
using xDef solves-store-ivpD(2) Fsolves tHyp by simp
also have  $(sol\ s[xfList \leftarrow uInput]\ t)\ x = 0$ 
using False solHyp tHyp solves-store-ivpD(2) xDef by fastforce
ultimately show ?thesis by simp
qed
qed
qed
qed

```

theorem *dSolveUBC*:

assumes *contHyp*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$

$(\lambda(t, (r::real)). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$
and *solHyp*: $\forall s. \text{solvesStoreIVP } (\lambda t. (sol\ s[xfList \leftarrow uInput]\ t))\ xfList\ s$
and *uniqHyp*: $\forall s. \forall \varphi_s. \varphi_s \text{ solvesTheStoreIVP } xfList\ \text{withInitState } s \longrightarrow$
 $(\forall t \geq 0. \forall xf \in \text{set } xfList. \forall r \in \{0..t\}. (\pi_2 xf) (\varphi_s\ r) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ r))$
and *diffAssgn*: $\forall s. P\ s \longrightarrow (\forall t \geq 0. G\ (sol\ s[xfList \leftarrow uInput]\ t) \longrightarrow Q\ (sol\ s[xfList \leftarrow uInput]\ t))$
shows *PRE* *P* (*ODEsystem* *xfList* with *G*) *POST* *Q*
apply(*rule-tac* *uInput*=*uInput* **in** *dSolve*)
prefer 2 **subgoal proof**(*clarify*)
fix *s*::*real* **store** **and** $\varphi_s::real \Rightarrow real\ \text{store}$ **and** *t*::*real*
assume *isSol*:*solvesStoreIVP* $\varphi_s\ xfList\ s$ **and** *sHyp*: $0 \leq t$
from *this* **and** *uniqHyp* **have** $\forall xf \in \text{set } xfList. \forall t \in \{0..t\}.$
 $(\pi_2 xf) (\varphi_s\ t) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t)$ **by** *auto*
also **have** $\forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$
 $(\lambda(t, (r::real)). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$ **using** *contHyp* *sHyp* **by** *blast*
ultimately show $(sol\ s[xfList \leftarrow uInput]\ t) = \varphi_s\ t$
using *sHyp* *isSol* *ubcStoreUniqueSol* *solHyp* **by** *simp*
qed **using** *assms* **by** *simp-all*

theorem *dSolve-toSolveUBC*:

assumes *funcsHyp*: $\forall s\ g. \forall xf \in \text{set } xfList. \pi_2\ xf\ (\text{override-on } s\ g\ \text{varDiffs}) = \pi_2\ xf\ s$
and *distinctHyp*:*distinct* (*map* $\pi_1\ xfList$)
and *lengthHyp*:*length* *xfList* = *length* *uInput*
and *varsHyp*: $\forall xf \in \text{set } xfList. \pi_1\ xf \notin \text{varDiffs}$
and *solHyp1*: $\forall s. \forall uxf \in \text{set } (uInput \otimes xfList). \pi_1\ uxf\ 0\ (sol\ s) = sol\ s\ (\pi_1\ (\pi_2\ uxf))$
and *solHyp2*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. (sol\ s[xfList \leftarrow uInput]\ t) (\pi_1\ xf)))$
has-vderiv-on
 $(\lambda t. \pi_2\ xf\ (sol\ s[xfList \leftarrow uInput]\ t)))\ \{0..t\}$
and *contHyp*: $\forall s. \forall t \geq 0. \forall xf \in \text{set } xfList. \text{continuous-on } (\{0..t\} \times UNIV)$
 $(\lambda(t, (r::real)). (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ t))$
and *uniqHyp*: $\forall s. \forall \varphi_s. \varphi_s \text{ solvesTheStoreIVP } xfList\ \text{withInitState } s \longrightarrow$
 $(\forall t \geq 0. \forall xf \in \text{set } xfList. \forall r \in \{0..t\}. (\pi_2 xf) (\varphi_s\ r) = (\pi_2 xf) (sol\ s[xfList \leftarrow uInput]\ r))$
and *postCondHyp*: $\forall s. P\ s \longrightarrow (\forall t \geq 0. Q\ (sol\ s[xfList \leftarrow uInput]\ t))$
shows *PRE* *P* (*ODEsystem* *xfList* with *G*) *POST* *Q*
apply(*rule-tac* *uInput*=*uInput* **in** *dSolveUBC*)
using *contHyp* **apply** *simp*
apply(*rule* *allI*, *rule-tac* *uInput*=*uInput* **in** *conds4storeIVP-on-toSol*)
using *assms* **by** *auto*

1.4.4 "Differential Invariant."

lemma *solvesStoreIVP-couldBeModified*:
fixes $F::\text{real} \Rightarrow \text{real store}$
assumes $\text{vars}:\forall t \geq 0. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ solves-ode } (\lambda t r. \pi_2 xf (F t))) \{0..t\} \text{ UNIV}$
and $\text{dvars}:\forall t \geq 0. \forall xf \in \text{set } xfList. (F t (\partial (\pi_1 xf))) = (\pi_2 xf) (F t)$
shows $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ has-vector-derivative } F r (\partial (\pi_1 xf))) (at r \text{ within } \{0..t\})$
proof(*clarify, rename-tac t r x f*)
fix $x f$ **and** $t r::\text{real}$
assume $tHyp:0 \leq t$ **and** $xfHyp:(x, f) \in \text{set } xfList$ **and** $rHyp:r \in \{0..t\}$
from *this* **and** *vars* **have** $((\lambda t. F t x) \text{ solves-ode } (\lambda t r. f (F t))) \{0..t\} \text{ UNIV}$
using $tHyp$ **by** *fastforce*
hence $*\forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } (\lambda t. f (F t)) r) (at r \text{ within } \{0..t\})$
by (*simp add: solves-ode-def has-vderiv-on-def tHyp*)
have $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. (F r (\partial (\pi_1 xf))) = (\pi_2 xf) (F r)$
using *assms* **by** *auto*
from *this* $rHyp$ **and** $xfHyp$ **have** $(F r (\partial x)) = f (F r)$ **by** *force*
then show $((\lambda t. F t (\pi_1 (x, f))) \text{ has-vector-derivative } F r (\partial (\pi_1 (x, f)))) (at r \text{ within } \{0..t\})$
using $* rHyp$ **by** *auto*
qed

lemma *derivationLemma-baseCase*:
fixes $F::\text{real} \Rightarrow \text{real store}$
assumes $\text{solves}:\text{solvesStoreIVP } F \text{ } xfList \text{ } a$
shows $\forall x \in (\text{UNIV} - \text{varDiffs}). \forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } F r (\partial x)) (at r \text{ within } \{0..t\})$
proof
fix x
assume $x \in \text{UNIV} - \text{varDiffs}$
then have $\text{notVarDiff}:\forall z. x \neq \partial z$ **using** *varDiffs-def* **by** *fastforce*
show $\forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F t x) \text{ has-vector-derivative } F r (\partial x)) (at r \text{ within } \{0..t\})$
proof(*cases* $x \in \text{set } (\text{map } \pi_1 \text{ } xfList)$)
case *True*
from *this* **and** *solves* **have** $\forall t \geq 0. \forall r \in \{0..t\}. \forall xf \in \text{set } xfList. ((\lambda t. F t (\pi_1 xf)) \text{ has-vector-derivative } F r (\partial (\pi_1 xf))) (at r \text{ within } \{0..t\})$
apply(*rule-tac solvesStoreIVP-couldBeModified*) **using** *solves solves-store-ivpD*
by *auto*
from *this* **show** *?thesis* **using** *True* **by** *auto*
next
case *False*
from *this* notVarDiff **and** *solves* **have** $\text{const}:\forall t \geq 0. F t x = a \text{ } x$
using *solves-store-ivpD(1)* **by** (*simp add: varDiffs-def*)
have $\text{constD}:\forall t \geq 0. \forall r \in \{0..t\}. ((\lambda r. a \text{ } x) \text{ has-vector-derivative } 0) (at r \text{ within } \{0..t\})$
by (*auto intro: derivative-eq-intros*)

```

{fix t r::real
  assume  $t \geq 0$  and  $r \in \{0..t\}$ 
  hence  $((\lambda s. a\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$  by (simp add:
constD)
  moreover have  $\bigwedge s. s \in \{0..t\} \implies (\lambda r. F\ r\ x)\ s = (\lambda r. a\ x)\ s$ 
  using const by (simp add:  $\langle 0 \leq t \rangle$ )
  ultimately have  $((\lambda s. F\ s\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$ 
  using has-vector-derivative-imp by (metis  $\langle r \in \{0..t\} \rangle$ )
  hence  $\text{isZero}:\forall t \geq 0. \forall r \in \{0..t\}. ((\lambda t. F\ t\ x) \text{ has-vector-derivative } 0) \text{ (at } r \text{ within } \{0..t\})$  by blast
  from False solves and notVarDiff have  $\forall t \geq 0. F\ t\ (\partial\ x) = 0$ 
  using solves-store-ivpD(2) by simp
  then show ?thesis using isZero by simp
qed
qed

```

```

lemma derivationLemma:
assumes solvesStoreIVP  $F\ xfList\ a$ 
and  $tHyp:t \geq 0$ 
and termVarsHyp: $\forall x \in trmVars\ \eta. x \in (UNIV - varDiffs)$ 
shows  $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F\ s)) \text{ has-vector-derivative } (\llbracket \partial_t\ \eta \rrbracket_t) (F\ r)) \text{ (at } r \text{ within } \{0..t\})$ 
using termVarsHyp proof(induction  $\eta$ )
  case (Const r)
  then show ?case by simp
next
  case (Var y)
  then have  $yHyp:y \in UNIV - varDiffs$  by auto
  from this tHyp and assms(1) show ?case
  using derivationLemma-baseCase by auto
next
  case (Mns  $\eta$ )
  then show ?case
  apply(clarsimp)
  by(rule derivative-intros, simp)
next
  case (Sum  $\eta1\ \eta2$ )
  then show ?case
  apply(clarsimp)
  by(rule derivative-intros, simp-all)
next
  case (Mult  $\eta1\ \eta2$ )
  then show ?case
  apply(clarsimp)
  apply(subgoal-tac  $((\lambda s. (\llbracket \eta1 \rrbracket_t) (F\ s) *_{\mathbb{R}} (\llbracket \eta2 \rrbracket_t) (F\ s)) \text{ has-vector-derivative } (\llbracket \partial_t\ \eta1 \rrbracket_t) (F\ r) \cdot (\llbracket \eta2 \rrbracket_t) (F\ r) + (\llbracket \eta1 \rrbracket_t) (F\ r) \cdot (\llbracket \partial_t\ \eta2 \rrbracket_t) (F\ r)) \text{ (at } r \text{ within } \{0..t\}), \text{simp}$ )
  apply(rule-tac  $f'1 = (\llbracket \partial_t\ \eta1 \rrbracket_t) (F\ r)$  and  $g'1 = (\llbracket \partial_t\ \eta2 \rrbracket_t) (F\ r)$  in derivative-eq-intros(25))
  by (simp-all add: has-field-derivative-iff-has-vector-derivative)

```


qed

lemma *diff-subst-prprty-4terms*:

assumes *solves*: $\forall xf \in \text{set } xfList. F\ t\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ t)$

and *tHyp*: $(t::\text{real}) \geq 0$

and *listsHyp*: $\text{map } \pi_2\ xfList = \text{map } tval\ uInput$

and *termVarsHyp*: $\text{trmVars } \eta \subseteq (\text{UNIV} - \text{varDiffs})$

shows $(\llbracket \partial_t \eta \rrbracket_t) (F\ t) = (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfList) \otimes uInput \rrbracket_t) (F\ t)$

using *termVarsHyp* **apply**(*induction* η) **apply**(*simp-all* *add: substList-help2*)

using *listsHyp* **and** *solves* **apply**(*induct* *xfList* *uInput* *rule: list-induct2'*, *simp*, *simp*, *simp*)

proof(*clarify*, *rename-tac* $y\ g\ xfTail\ \vartheta\ \text{trmTail}\ x$)

fix $x\ y::\text{string}$ **and** $\vartheta::\text{trms}$ **and** g **and** $xfTail::(\text{string} \times (\text{real store} \Rightarrow \text{real}))\ \text{list}$ **and** trmTail

assume *IH*: $\bigwedge x. x \notin \text{varDiffs} \Rightarrow \text{map } \pi_2\ xfTail = \text{map } tval\ \text{trmTail} \Rightarrow$

$\forall xf \in \text{set } xfTail. F\ t\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ t) \Rightarrow$

$F\ t\ (\partial\ x) = (\llbracket (\text{map } (vdiff \circ \pi_1)\ xfTail \otimes \text{trmTail}) \rrbracket_t) (F\ t)$

and $1:x \notin \text{varDiffs}$ **and** $2:\text{map } \pi_2\ ((y, g) \# xfTail) = \text{map } tval\ (\vartheta \# \text{trmTail})$

and $3:\forall xf \in \text{set } ((y, g) \# xfTail). F\ t\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ t)$

hence $*:(\llbracket (\text{map } (vdiff \circ \pi_1)\ xfTail \otimes \text{trmTail}) \rrbracket_t) (F\ t) = F\ t\ (\partial\ x)$

using *tHyp* **by** *auto*

show $F\ t\ (\partial\ x) = (\llbracket (\text{map } (vdiff \circ \pi_1)\ ((y, g) \# xfTail)) \otimes (\vartheta \# \text{trmTail}) \rrbracket_t) (F\ t)$

proof(*cases* $x \in \text{set } (\text{map } \pi_1\ ((y, g) \# xfTail))$)

case *True*

then have $x = y \vee (x \neq y \wedge x \in \text{set } (\text{map } \pi_1\ xfTail))$ **by** *auto*

moreover

{**assume** $x = y$

from this have $((\text{map } (vdiff \circ \pi_1)\ ((y, g) \# xfTail)) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial\ x) \rangle = \vartheta$ **by** *simp*

also from $3\ tHyp$ **have** $F\ t\ (\partial\ y) = g\ (F\ t)$ **by** *simp*

moreover from 2 **have** $(\llbracket \vartheta \rrbracket_t) (F\ t) = g\ (F\ t)$ **by** *simp*

ultimately have *?thesis* **by** (*simp* *add: (x = y)*)}

moreover

{**assume** $x \neq y \wedge x \in \text{set } (\text{map } \pi_1\ xfTail)$

then have $\partial\ x \neq \partial\ y$ **using** *vdiff-inj* **by** *auto*

from this have $((\text{map } (vdiff \circ \pi_1)\ ((y, g) \# xfTail)) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial\ x) \rangle =$

$((\text{map } (vdiff \circ \pi_1)\ xfTail) \otimes \text{trmTail}) \langle t_V (\partial\ x) \rangle$ **by** *simp*

hence *?thesis* **using** $*$ **by** *simp*}

ultimately show *?thesis* **by** *blast*

next

case *False*

then have $((\text{map } (vdiff \circ \pi_1)\ ((y, g) \# xfTail)) \otimes (\vartheta \# \text{trmTail})) \langle t_V (\partial\ x) \rangle =$

$t_V (\partial\ x)$

using *substList-cross-vdiff-on-non-occurring-var* **by**(*metis*(*no-types*, *lifting*) *List.map.compositionality*)

thus *?thesis* **by** *simp*

qed

qed

lemma *eqInVars-impl-eqInTrms*:
assumes *termVarsHyp*:*trmVars* $\eta \subseteq (UNIV - varDiffs)$
and *initHyp*: $\forall x. x \notin varDiffs \longrightarrow b\ x = a\ x$
shows $(\llbracket \eta \rrbracket_t)\ a = (\llbracket \eta \rrbracket_t)\ b$
using *assms* **by**(*induction* η , *simp-all*)

lemma *non-empty-funList-implies-non-empty-trmList*:
shows $\forall\ list.(x,f) \in set\ list \wedge map\ \pi_2\ list = map\ tval\ tList \longrightarrow (\exists\ \vartheta. (\llbracket \vartheta \rrbracket_t) = f$
 $\wedge\ \vartheta \in set\ tList)$
by(*induction* *tList*, *auto*)

lemma *dInvForTrms-prelim*:
assumes *substHyp*:
 $\forall\ st. G\ st \longrightarrow (\forall\ str. str \notin (\pi_1(\llbracket set\ xfList \rrbracket)) \longrightarrow st\ (\partial\ str) = 0) \longrightarrow$
 $(\llbracket ((map\ (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t\ \eta \rangle_t) st = 0$
and *termVarsHyp*:*trmVars* $\eta \subseteq (UNIV - varDiffs)$
and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
shows $(\llbracket \eta \rrbracket_t)\ a = 0 \longrightarrow (\forall\ c. (a,c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c =$
 $0)$
proof(*clarify*)
fix *c* **assume** *aHyp*: $(\llbracket \eta \rrbracket_t)\ a = 0$ **and** *cHyp*: $(a, c) \in ODEsystem\ xfList\ with\ G$
from this obtain *t::real* **and** *F::real* \Rightarrow *real store*
where *tcHyp*: $t \geq 0 \wedge F\ t = c \wedge solvesStoreIVP\ F\ xfList\ a \wedge (\forall\ r \in \{0..t\}. G\ (F\ r))$

using *guarDiffEqtn-def* **by** *auto*
then have $\forall x. x \notin varDiffs \longrightarrow F\ 0\ x = a\ x$ **using** *solves-store-ivpD(6)* **by** *blast*
from this have $(\llbracket \eta \rrbracket_t)\ a = (\llbracket \eta \rrbracket_t)\ (F\ 0)$ **using** *termVarsHyp* *eqInVars-impl-eqInTrms*
by *blast*
hence *obs1*: $(\llbracket \eta \rrbracket_t)\ (F\ 0) = 0$ **using** *aHyp* *tcHyp* **by** *simp*
from *tcHyp* **have** *obs2*: $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t)\ (F\ s))\ has_vector_derivative$
 $(\llbracket \partial_t\ \eta \rrbracket_t)\ (F\ r))\ (at\ r\ within\ \{0..t\})$ **using** *derivationLemma* *termVarsHyp* **by** *blast*
have $\forall r \in \{0..t\}. \forall\ xf \in set\ xfList. F\ r\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ r)$
using *tcHyp* *solves-store-ivpD(3)* **by** *fastforce*
hence $\forall r \in \{0..t\}. (\llbracket \partial_t\ \eta \rrbracket_t)\ (F\ r) = (\llbracket ((map\ (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t$
 $\eta \rangle_t) (F\ r)$
using *tcHyp* *diff-subst-prprty-4terms* *termVarsHyp* *listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket ((map\ (vdiff \circ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t$
 $\eta \rangle_t) (F\ r) = 0$
using *solves-store-ivpD(2)* *tcHyp* **by** *fastforce*
ultimately have $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t)\ (F\ s))\ has_vector_derivative\ 0)\ (at\ r$
 $within\ \{0..t\})$
using *obs2* **by** *auto*
from this and *tcHyp* **have** $\forall s \in \{0..t\}. ((\lambda x. (\llbracket \eta \rrbracket_t)\ (F\ x))\ has_derivative\ (\lambda x. x$
 $*_R\ 0))$
 $(at\ s\ within\ \{0..t\})$ **by** (*metis* *has-vector-derivative-def*)
hence $(\llbracket \eta \rrbracket_t)\ (F\ t) - (\llbracket \eta \rrbracket_t)\ (F\ 0) = (\lambda x. x *_R\ 0)\ (t - 0)$
using *mut-very-simple* **and** *tcHyp* **by** *fastforce*
then show $(\llbracket \eta \rrbracket_t)\ c = 0$ **using** *obs1* *tcHyp* **by** *auto*

qed

theorem *dInvForTrms*:

assumes $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\downarrow set\ xfList)) \longrightarrow st\ (\partial\ str) = 0) \longrightarrow$
 $(\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t\ \eta \rangle \rrbracket_t)\ st = 0$
and *termVarsHyp*: $trmVars\ \eta \subseteq (UNIV - varDiffs)$
and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
and *eta-f*: $f = (\llbracket \eta \rrbracket_t)$
shows *PRE* $(\lambda s. f\ s = 0)$ (*ODEsystem* *xfList* with *G*) *POST* $(\lambda s. f\ s = 0)$
using *eta-f* **proof**(*clarsimp*)
fix *a b*
assume $(a, b) \in \lceil \lambda s. (\llbracket \eta \rrbracket_t)\ s = 0 \rceil$ **and** $f = (\llbracket \eta \rrbracket_t)$
from *this* **have** *aHyp*: $a = b \wedge (\llbracket \eta \rrbracket_t)\ a = 0$ **by** (*metis* (*full-types*) *d-p2r rdom-p2r-contents*)
have $(\llbracket \eta \rrbracket_t)\ a = 0 \longrightarrow (\forall c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c = 0)$
using *assms* *dInvForTrms-prelim* **by** *metis*
from *this* **and** *aHyp* **have** $\forall c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c = 0$ **by** *blast*
thus $(a, b) \in wp\ (ODEsystem\ xfList\ with\ G)\ \lceil \lambda s. (\llbracket \eta \rrbracket_t)\ s = 0 \rceil$
using *aHyp* **by** (*simp* *add*: *boxProgrPred-chrctrzn*)
qed

lemma *diff-subst-prprty-4props*:

assumes *solves*: $\forall xf \in set\ xfList. F\ t\ (\partial\ (\pi_1\ xf)) = \pi_2\ xf\ (F\ t)$
and *tHyp*: $t \geq 0$
and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
and *propVarsHyp*: $propVars\ \varphi \subseteq (UNIV - varDiffs)$
shows $(\llbracket \partial_P\ \varphi \rrbracket_P)\ (F\ t) = (\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput)\ \downarrow \partial_P\ \varphi \rrbracket_P)\ (F\ t)$
using *propVarsHyp* **apply**(*induction* φ , *simp-all*)
using *assms* *diff-subst-prprty-4terms* **apply** *fastforce*
using *assms* *diff-subst-prprty-4terms* **apply** *fastforce*
using *assms* *diff-subst-prprty-4terms* **by** *fastforce*

lemma *dInvForProps-prelim*:

assumes *substHyp*:
 $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\downarrow set\ xfList)) \longrightarrow st\ (\partial\ str) = 0) \longrightarrow$
 $(\llbracket ((map\ (vdiff\ \circ\ \pi_1)\ xfList) \otimes uInput)\ \langle \partial_t\ \eta \rangle \rrbracket_t)\ st \geq 0$
and *termVarsHyp*: $trmVars\ \eta \subseteq (UNIV - varDiffs)$
and *listsHyp*: $map\ \pi_2\ xfList = map\ tval\ uInput$
shows $(\llbracket \eta \rrbracket_t)\ a > 0 \longrightarrow (\forall c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c > 0)$
and $(\llbracket \eta \rrbracket_t)\ a \geq 0 \longrightarrow (\forall c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow (\llbracket \eta \rrbracket_t)\ c \geq 0)$
proof(*clarify*)
fix *c* **assume** *aHyp*: $(\llbracket \eta \rrbracket_t)\ a > 0$ **and** *cHyp*: $(a, c) \in ODEsystem\ xfList\ with\ G$
from *this* **obtain** *t*:*real* **and** *F*:*real* \Rightarrow *real store*
where *tcHyp*: $t \geq 0 \wedge F\ t = c \wedge solvesStoreIVP\ F\ xfList\ a \wedge (\forall r \in \{0..t\}. G\ (F\ r))$

using *guarDiffEqtn-def* **by** *auto*

then **have** $\forall x. x \notin varDiffs \longrightarrow F\ 0\ x = a\ x$ **using** *solves-store-ivpD(6)* **by** *blast*

from this have $(\llbracket \eta \rrbracket_t) a = (\llbracket \eta \rrbracket_t) (F 0)$ **using** *termVarsHyp eqInVars-impl-eqInTrms*
by *blast*
hence $obs1: (\llbracket \eta \rrbracket_t) (F 0) > 0$ **using** *aHyp tcHyp* **by** *simp*
from *tcHyp* **have** $obs2: \forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F s)) \text{ has-vector-derivative } (\llbracket \partial_t \eta \rrbracket_t) (F r))$ **at** r **within** $\{0..t\}$ **using** *derivationLemma termVarsHyp* **by** *blast*
have $(\forall t \geq 0. \forall xf \in \text{set } xfList. F t (\partial (\pi_1 xf)) = \pi_2 xf (F t))$
using *tcHyp solves-store-ivpD(3)* **by** *blast*
hence $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F r) = (\llbracket ((\text{map } (vdiff \circ \pi_1) xfList) \otimes uInput) \langle \partial_t \eta \rangle_t) (F r)$
using *diff-subst-prprty-4terms termVarsHyp tcHyp listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket ((\text{map } (vdiff \circ \pi_1) xfList) \otimes uInput) \langle \partial_t \eta \rangle_t) (F r) \geq 0$
using *solves-store-ivpD(2) tcHyp* **by** *(metis atLeastAtMost-iff)*
ultimately have $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0$ **by** *(simp)*
from *obs2* **and** *tcHyp* **have** $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F s)) \text{ has-derivative } (\lambda x. x *_R ((\llbracket \partial_t \eta \rrbracket_t) (F r))))$ **at** r **within** $\{0..t\}$ **by** *(simp add: has-vector-derivative-def)*

hence $\exists r \in \{0..t\}. (\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r))$
using *mvt-very-simple* **and** *tcHyp* **by** *fastforce*
then obtain r **where** $(\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0 \wedge 0 \leq r \wedge r \leq t \wedge ((\llbracket \partial_t \eta \rrbracket_t) (F t) \geq 0 \wedge ((\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r)))$
using $*$ *tcHyp* **by** *(meson atLeastAtMost-iff order-refl)*
thus $(\llbracket \eta \rrbracket_t) c > 0$
using *obs1 tcHyp* **by** *(metis cancel-comm-monoid-add-class.diff-cancel diff-ge-0-iff-ge)*

diff-strict-mono linorder-neqE-linordered-idom linordered-field-class.sign-simps(45)
not-le)

next

show $0 \leq (\llbracket \eta \rrbracket_t) a \longrightarrow (\forall c. (a, c) \in \text{ODEsystem } xfList \text{ with } G \longrightarrow 0 \leq (\llbracket \eta \rrbracket_t) c)$
proof *(clarify)*
fix c **assume** *aHyp*: $(\llbracket \eta \rrbracket_t) a \geq 0$ **and** *cHyp*: $(a, c) \in \text{ODEsystem } xfList \text{ with } G$
from this obtain $t::\text{real}$ **and** $F::\text{real} \Rightarrow \text{real store}$
where *tcHyp*: $t \geq 0 \wedge F t = c \wedge \text{solvesStoreIVP } F \text{ } xfList \text{ } a \wedge (\forall r \in \{0..t\}. G (F r))$

using *guarDiffEqtn-def* **by** *auto*

then have $\forall x. x \notin \text{varDiffs} \longrightarrow F 0 x = a x$ **using** *solves-store-ivpD(6)* **by** *blast*
from this have $(\llbracket \eta \rrbracket_t) a = (\llbracket \eta \rrbracket_t) (F 0)$ **using** *termVarsHyp eqInVars-impl-eqInTrms*
by *blast*

hence $obs1: (\llbracket \eta \rrbracket_t) (F 0) \geq 0$ **using** *aHyp tcHyp* **by** *simp*
from *tcHyp* **have** $obs2: \forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F s)) \text{ has-vector-derivative } (\llbracket \partial_t \eta \rrbracket_t) (F r))$ **at** r **within** $\{0..t\}$ **using** *derivationLemma termVarsHyp* **by** *blast*
have $(\forall t \geq 0. \forall xf \in \text{set } xfList. F t (\partial (\pi_1 xf)) = \pi_2 xf (F t))$
using *tcHyp solves-store-ivpD(3)* **by** *blast*
from this and *tcHyp* **have** $\forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F r) = (\llbracket ((\text{map } (vdiff \circ \pi_1) xfList) \otimes uInput) \langle \partial_t \eta \rangle_t) (F r)$
using *diff-subst-prprty-4terms termVarsHyp listsHyp* **by** *fastforce*
also from *substHyp* **have** $\forall r \in \{0..t\}. (\llbracket ((\text{map } (vdiff \circ \pi_1) xfList) \otimes uInput) \langle \partial_t \eta \rangle_t) (F r) \geq 0$
using *solves-store-ivpD(2) tcHyp* **by** *(metis atLeastAtMost-iff)*

ultimately have $\ast: \forall r \in \{0..t\}. (\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0$ by (simp)
 from obs2 and tcHyp have $\forall r \in \{0..t\}. ((\lambda s. (\llbracket \eta \rrbracket_t) (F s)) \text{ has-derivative } (\lambda x. x \ast_R ((\llbracket \partial_t \eta \rrbracket_t) (F r))))$ (at r within $\{0..t\}$) by (simp add: has-vector-derivative-def)

hence $\exists r \in \{0..t\}. (\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r))$
 using mvt-very-simple and tcHyp by fastforce
 then obtain r where $(\llbracket \partial_t \eta \rrbracket_t) (F r) \geq 0 \wedge 0 \leq r \wedge r \leq t \wedge (\llbracket \partial_t \eta \rrbracket_t) (F t) \geq 0$
 $\wedge (\llbracket \eta \rrbracket_t) (F t) - (\llbracket \eta \rrbracket_t) (F 0) = t \cdot ((\llbracket \partial_t \eta \rrbracket_t) (F r))$
 using \ast tcHyp by (meson atLeastAtMost-iff order-refl)
 thus $(\llbracket \eta \rrbracket_t) c \geq 0$
 using obs1 tcHyp by (metis cancel-comm-monoid-add-class.diff-cancel diff-ge-0-iff-ge

diff-strict-mono linorder-neqE-linordered-idom linordered-field-class.sign-simps(45)
 not-le)
 qed
 qed

lemma less-pval-to-tval:

assumes $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \prec \eta) \upharpoonright_P \rrbracket_P) st$
 shows $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_t} (\eta \oplus (\ominus \vartheta)) \upharpoonright_t \rrbracket_t) st \geq 0$
 using assms by(auto)

lemma leq-pval-to-tval:

assumes $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \preceq \eta) \upharpoonright_P \rrbracket_P) st$
 shows $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_t} (\eta \oplus (\ominus \vartheta)) \upharpoonright_t \rrbracket_t) st \geq 0$
 using assms by(auto)

lemma dInv-prelim:

assumes substHyp: $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} \varphi \upharpoonright_P \rrbracket_P) st$
 and propVarsHyp: $\text{propVars } \varphi \subseteq (UNIV - \text{varDiffs})$
 and listsHyp: $\text{map } \pi_2 \text{ xfList} = \text{map tval uInput}$
 shows $(\llbracket \varphi \rrbracket_P) a \longrightarrow (\forall c. (a, c) \in (\text{ODEsystem xfList with } G) \longrightarrow (\llbracket \varphi \rrbracket_P) c)$
 proof(clarify)
 fix c assume aHyp: $(\llbracket \varphi \rrbracket_P) a$ and cHyp: $(a, c) \in \text{ODEsystem xfList with } G$
 from this obtain t::real and F::real \Rightarrow real store
 where tcHyp: $t \geq 0 \wedge F t = c \wedge \text{solvesStoreIVP } F \text{ xfList } a$ using guarDiffEqtn-def
 by auto
 from aHyp propVarsHyp and substHyp show $(\llbracket \varphi \rrbracket_P) c$
 proof(induction φ)
 case (Eq $\vartheta \eta$)
 hence hyp: $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_P} (\vartheta \doteq \eta) \upharpoonright_P \rrbracket_P) st$ by blast
 then have $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1 \llbracket \text{set xfList} \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((\text{map } (vdiff \circ \pi_1) \text{ xfList}) \otimes uInput) \upharpoonright_{\partial_t} (\vartheta \oplus (\ominus \eta)) \upharpoonright_t \rrbracket_t) st = 0$ by simp
 also have $\text{trmVars } (\vartheta \oplus (\ominus \eta)) \subseteq UNIV - \text{varDiffs}$ using Eq.prem(2) by simp
 moreover have $(\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) a = 0$ using Eq.prem(1) by simp
 ultimately have $(\forall c. (a, c) \in \text{ODEsystem xfList with } G \longrightarrow (\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) c$

$= 0)$
using *dInvForTrms-prelim listsHyp* **by** *blast*
hence $(\llbracket \vartheta \oplus (\ominus \eta) \rrbracket_t) (F t) = 0$ **using** *tcHyp cHyp* **by** *simp*
from this have $(\llbracket \vartheta \rrbracket_t) (F t) = (\llbracket \eta \rrbracket_t) (F t)$ **by** *simp*
also have $(\llbracket \vartheta \doteq \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) = (\llbracket \eta \rrbracket_t) (F t))$ **using** *tcHyp* **by** *simp*
ultimately show *?case* **by** *simp*
next
case (*Less* $\vartheta \eta$)
hence $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set\ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $0 \leq ((\llbracket (map (vdiff \circ \pi_1) xfList \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \rrbracket_t) st$
using *less-pval-to-tval* **by** *metis*
also from *Less.premis(2)* **have** $trmVars (\eta \oplus (\ominus \vartheta)) \subseteq UNIV - varDiffs$ **by** *simp*
moreover have $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) a > 0$ **using** *Less.premis(1)* **by** *simp*
ultimately have $(\forall c. (a, c) \in ODEsystem\ xfList\ with\ G \longrightarrow (\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) c > 0)$
using *dInvForProps-prelim(1) listsHyp* **by** *blast*
hence $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) (F t) > 0$ **using** *tcHyp cHyp* **by** *simp*
from this have $(\llbracket \eta \rrbracket_t) (F t) > (\llbracket \vartheta \rrbracket_t) (F t)$ **by** *simp*
also have $(\llbracket \vartheta \prec \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) < (\llbracket \eta \rrbracket_t) (F t))$ **using** *tcHyp* **by** *simp*
ultimately show *?case* **by** *simp*
next
case (*Leq* $\vartheta \eta$)
hence $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set\ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $0 \leq ((\llbracket (map (vdiff \circ \pi_1) xfList \otimes uInput) \langle \partial_t (\eta \oplus (\ominus \vartheta)) \rangle \rrbracket_t) st$ **using** *leq-pval-to-tval*
by *metis*
also from *Leq.premis(2)* **have** $trmVars (\eta \oplus (\ominus \vartheta)) \subseteq UNIV - varDiffs$ **by** *simp*
moreover have $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) a \geq 0$ **using** *Leq.premis(1)* **by** *simp*
ultimately have $(\forall c. (a, c) \in ODEsystem\ xfList\ with\ G \longrightarrow (\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) c \geq 0)$
using *dInvForProps-prelim(2) listsHyp* **by** *blast*
hence $(\llbracket \eta \oplus (\ominus \vartheta) \rrbracket_t) (F t) \geq 0$ **using** *tcHyp cHyp* **by** *simp*
from this have $((\llbracket \eta \rrbracket_t) (F t) \geq (\llbracket \vartheta \rrbracket_t) (F t))$ **by** *simp*
also have $(\llbracket \vartheta \preceq \eta \rrbracket_P) c = ((\llbracket \vartheta \rrbracket_t) (F t) \leq (\llbracket \eta \rrbracket_t) (F t))$ **using** *tcHyp* **by** *simp*
ultimately show *?case* **by** *simp*
next
case (*And* $\varphi 1 \varphi 2$)
then show *?case* **by** (*simp*)
next
case (*Or* $\varphi 1 \varphi 2$)
from this show *?case* **by** *auto*
qed
qed

theorem *dInv*:
assumes $\forall st. G st \longrightarrow (\forall str. str \notin (\pi_1(\llbracket set\ xfList \rrbracket)) \longrightarrow st (\partial str) = 0) \longrightarrow$
 $(\llbracket ((map (vdiff \circ \pi_1) xfList) \otimes uInput) \upharpoonright \partial_P \varphi \rrbracket_P) st$
and *termVarsHyp:propVars* $\varphi \subseteq (UNIV - varDiffs)$
and *listsHyp:map* $\pi_2\ xfList = map\ tval\ uInput$
and *phi-p:P* $= (\llbracket \varphi \rrbracket_P)$

```

shows  $PRE\ P\ (ODEsystem\ xfList\ with\ G)\ POST\ P$ 
proof(clarsimp)
fix  $a\ b$ 
assume  $(a, b) \in \lceil P \rceil$ 
from this have  $aHyp: a = b \wedge P\ a$  by (metis (full-types) d-p2r rdom-p2r-contents)
have  $P\ a \longrightarrow (\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow P\ c)$ 
using assms dInv-prelim by metis
from this and  $aHyp$  have  $\forall\ c. (a, c) \in (ODEsystem\ xfList\ with\ G) \longrightarrow P\ c$  by
blast
thus  $(a, b) \in wp\ (ODEsystem\ xfList\ with\ G)\ \lceil P \rceil$ 
using  $aHyp$  by (simp add: boxProgrPred-chrctrztn)
qed

```

```

theorem dInvFinal:
assumes  $\forall\ st. G\ st \longrightarrow (\forall\ str. str \notin (\pi_1(\lceil set\ xfList \rceil)) \longrightarrow st\ (\partial\ str) = 0) \longrightarrow$ 
 $(\lceil ((map\ (vdiff \circ \pi_1)\ xfList) \otimes uInput) \upharpoonright \partial_P\ \varphi \rceil_P)\ st$ 
and termVarsHyp: propVars  $\varphi \subseteq (UNIV - varDiffs)$ 
and listsHyp: map  $\pi_2\ xfList = map\ tval\ uInput$ 
and impls:  $\lceil P \rceil \subseteq \lceil F \rceil \wedge \lceil F \rceil \subseteq \lceil Q \rceil$ 
and phi-f:  $F = (\lceil \varphi \rceil_P)$ 
shows  $PRE\ P\ (ODEsystem\ xfList\ with\ G)\ POST\ Q$ 
apply(rule-tac  $C = (\lceil \varphi \rceil_P)$  in dCut)
apply(subgoal-tac  $\lceil F \rceil \subseteq wp\ (ODEsystem\ xfList\ with\ G)\ \lceil F \rceil$ , simp)
using impls and phi-f apply blast
apply(subgoal-tac  $PRE\ F\ (ODEsystem\ xfList\ with\ G)\ POST\ F$ , simp)
apply(rule-tac  $\varphi = \varphi$  and  $uInput = uInput$  in dInv)
prefer 5 apply(subgoal-tac  $PRE\ P\ (ODEsystem\ xfList\ with\ (\lambda s. G\ s \wedge F\ s))$ 
 $POST\ Q$ , simp add: phi-f)
apply(rule dWeakening)
using impls apply simp
using assms by simp-all

end
theory VC-diffKAD-examples
imports VC-diffKAD

```

begin

1.5 Rules Testing

In this section we test the recently developed rules with simple dynamical systems.

— Example of hybrid program verified with the rule *dSolve*.

lemma *motion-with-constant-velocity*:

```

 $PRE\ (\lambda\ s. s\ ''y'' < s\ ''x'' \wedge s\ ''v'' > 0)$ 
 $(ODEsystem\ [(''x'', (\lambda\ s. s\ ''v''))]\ with\ (\lambda\ s. True))$ 
 $POST\ (\lambda\ s. (s\ ''y'' < s\ ''x''))$ 

```

```

apply(rule-tac  $uInput = [\lambda\ t\ s. s\ ''v'' \cdot t + s\ ''x'']$  in dSolve-toSolveUBC)
prefer 9 subgoal by(simp add: wp-trafo vdiff-def add-strict-increasing2)

```

```

apply(simp-all add: vdiff-def varDiffs-def)
prefer 2 apply(clarify, rule continuous-intros)
prefer 2 apply(simp add: solvesStoreIVP-def vdiff-def varDiffs-def)
apply(clarify, rule-tac f'1= $\lambda x. s \text{ ''}v\text{''}$  and g'1= $\lambda x. 0$  in derivative-intros(173))
apply(rule-tac f'1= $\lambda x. 0$  and g'1= $\lambda x. 1$  in derivative-intros(176))
by(auto intro: derivative-intros)

```

— Example of hybrid program verified with differential weakening.

lemma *system-where-the-guard-implies-the-postcondition*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}x\text{''} + 1)$ )] with ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ )
using dWeakening by blast

```

lemma *system-where-the-guard-implies-the-postcondition2*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}x\text{''} + 1)$ )] with ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} \geq 0$ )
apply(clarify, simp add: p2r-def)
apply(simp add: rel-ad-def rel-antidomain-kleene-algebra.addual.ars-r-def)
apply(simp add: rel-antidomain-kleene-algebra.fbox-def)
apply(simp add: relcomp-def rel-ad-def guarDiffEqtn-def solvesStoreIVP-def)
by auto

```

— Example of system proved with a differential invariant.

lemma *circular-motion*:

```

  PRE ( $\lambda s. (s \text{ ''}x\text{''}) \cdot (s \text{ ''}x\text{''}) + (s \text{ ''}y\text{''}) \cdot (s \text{ ''}y\text{''}) - (s \text{ ''}r\text{''}) \cdot (s \text{ ''}r\text{''}) = 0$ )
  (ODEsystem [( $\text{''}x\text{''}, (\lambda s. s \text{ ''}y\text{''})$ ), ( $\text{''}y\text{''}, (\lambda s. -s \text{ ''}x\text{''})$ )] with G)
  POST ( $\lambda s. (s \text{ ''}x\text{''}) \cdot (s \text{ ''}x\text{''}) + (s \text{ ''}y\text{''}) \cdot (s \text{ ''}y\text{''}) - (s \text{ ''}r\text{''}) \cdot (s \text{ ''}r\text{''}) = 0$ )
apply(rule-tac  $\eta = (t_V \text{ ''}x\text{''}) \odot (t_V \text{ ''}x\text{''}) \oplus (t_V \text{ ''}y\text{''}) \odot (t_V \text{ ''}y\text{''}) \oplus (\ominus(t_V \text{ ''}r\text{''}) \odot (t_V \text{ ''}r\text{''}))$ )
  and uInput= $[t_V \text{ ''}y\text{''}, \ominus(t_V \text{ ''}x\text{''})]$  in dInvForTrms)
apply(simp-all add: vdiff-def varDiffs-def)
apply(clarsimp, erule-tac  $x = \text{''}r\text{''}$  in allE)
by simp

```

— Example of systems proved with differential invariants, cuts and weakenings.

declare d-p2r [simp del]

lemma *motion-with-constant-velocity-and-invariants*:

```

  PRE ( $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''} \wedge s \text{ ''}v\text{''} > 0$ )
  (ODEsystem [( $\text{''}x\text{''}, \lambda s. s \text{ ''}v\text{''}$ )] with ( $\lambda s. \text{True}$ ))
  POST ( $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$ )
apply(rule-tac  $C = \lambda s. s \text{ ''}v\text{''} > 0$  in dCut)
apply(rule-tac  $\varphi = (t_C 0) \prec (t_V \text{ ''}v\text{''})$  and uInput= $[t_V \text{ ''}v\text{''}]$  in dInvFinal)
apply(simp-all add: vdiff-def varDiffs-def, clarify, erule-tac  $x = \text{''}v\text{''}$  in allE, simp)
apply(rule-tac  $C = \lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$  in dCut)
apply(rule-tac  $\varphi = (t_V \text{ ''}y\text{''}) \prec (t_V \text{ ''}x\text{''})$  and uInput= $[t_V \text{ ''}v\text{''}]$  and
  F= $\lambda s. s \text{ ''}x\text{''} > s \text{ ''}y\text{''}$  in dInvFinal)
apply(simp-all add: vdiff-def varDiffs-def, clarify, erule-tac  $x = \text{''}y\text{''}$  in allE, simp)

```


using *dWeakening* **by** *simp*

lemma *motion-with-constant-acceleration-and-invariants:*

PRE $(\lambda s. s \text{ ''}y'' < s \text{ ''}x'' \wedge s \text{ ''}v'' \geq 0 \wedge s \text{ ''}a'' > 0)$
(ODEsystem $[(\text{''}x'', (\lambda s. s \text{ ''}v'')), (\text{''}v'', (\lambda s. s \text{ ''}a''))]$ *with* $(\lambda s. \text{True})$)
POST $(\lambda s. (s \text{ ''}y'' < s \text{ ''}x'))$

apply(*rule-tac* $C = \lambda s. s \text{ ''}a'' > 0$ **in** *dCut*)

apply(*rule-tac* $\varphi = (t_C \ 0) \prec (t_V \ \text{''}a'')$ **and** $uInput = [t_V \ \text{''}v'', t_V \ \text{''}a'']$ **in** *dInvFinal*)

apply(*simp-all add: vdiff-def varDiffs-def, clarify, erule-tac* $x = \text{''}a''$ **in** *allE, simp*)

apply(*rule-tac* $C = \lambda s. s \text{ ''}v'' \geq 0$ **in** *dCut*)

apply(*rule-tac* $\varphi = (t_C \ 0) \preceq (t_V \ \text{''}v'')$ **and** $uInput = [t_V \ \text{''}v'', t_V \ \text{''}a'']$ **in** *dInvFinal*)

apply(*simp-all add: vdiff-def varDiffs-def*)

apply(*rule-tac* $C = \lambda s. s \text{ ''}x'' > s \text{ ''}y''$ **in** *dCut*)

apply(*rule-tac* $\varphi = (t_V \ \text{''}y'') \prec (t_V \ \text{''}x'')$ **and** $uInput = [t_V \ \text{''}v'', t_V \ \text{''}a'']$ **in** *dInvFinal*)

apply(*simp-all add: varDiffs-def vdiff-def, clarify, erule-tac* $x = \text{''}y''$ **in** *allE, simp*)

using *dWeakening* **by** *simp*

declare *d-p2r* [*simp*]

end