

Dataset

Pipeline

Operator

Execution

Manual

...

Save & Run

🗑️

🔒

task1b_qa_e...

Dataset

qa_chunks_sample

Input field name

chunk

0_L1_generation

Dataset Preview

```
{
  "chunk": "For a fair and effective evaluation of RAG systems, it is essential to consider metrics that assess ..."
}
```

Switch Dataset

Start

Node

Text2MultiHopQAG...

text2MultiHopQAGenerator

Init. Parameters

model_name

gpt-4o-mini

num_questions

5

persona

Please act as a

...

Run Parameters

max_skip

0

qa_num

5

context

{{_INPUT_}}

system_config_file

qa_system

Next

Node

PandasOperator

Init. Parameters

code

import pandas as pd

def explode_qa_pairs(df):

return df.explode('qa_pairs')

param_schema

custom_kernel

Run Parameters

input_df

{{_INPUT_}}

Next

Node

Text2QASampleEval...

Init. Parameters

model_name

gpt-4o-2024-08-06

main_evaluation_dimensions

question_quality, answer_align...

add_evaluation_dimensions

verifiability, downstream_value

run_mode

evaluation

Run Parameters

eval_mode

question_with_reference

question

{{QUESTION}}

answer

{{ANSWER}}

reference

{{CHUNK}}

...

Next

Node

PandasOperator

Init. Parameters

code

def score(df):

df['quality_score'] = df[['ques...

param_schema

custom_kernel

Run Parameters

input_df

{{_INPUT_}}

Next

Node

GeneralFilter

Init. Parameters

condition

{{ quality_score }} >= 3

Run Parameters

input_df

{{_INPUT_}}

End



DataFlow Assistant

Claude Code



I have a JSONL dataset where each line contains a 'chunk' field with factual text. Please help me construct a pipeline to first generate multi-hop QA pairs for each chunk, then score the quality of the generated QAs, and finally filter out low-quality records (score < 3).



On it — task (QA generation + quality scoring + filtering). Let me pull the operator details for Text2QASampleEvaluator and GeneralFilter via MCP to get exact field bindings before designing the chain.

- ✓ Got operator detail: Text2QASampleEvaluator
- ✓ Got operator detail: GeneralFilter
- ✓ Got operator detail: PandasOperator

These operator contracts reveal the core challenge: Text2QASampleEvaluator needs scalar input_question_key / input_answer_key columns — it cannot consume the nested qa_pairs list directly. So I must explode qa_pairs into per-QA rows

Type your message...



Enter to send, Shift+Enter for new line