СМС шлюз от Eskiz.uz — API

🔐 **Credentials**

- Email: yoqub.xamidoff19@gmail.com
- Secret key: nJ45jlD82I5BcSMCFloA0p0GRqzWUA548irsiPGh

Base URL
1) Auth
    POST Login (get token)
    PATCH Refresh token
2) Templates
    POST Create / list templates
3) SMS Sending
    Message status (overall)
    Message part status (per part)
4) Send SMS
    POST Send single SMS
5) Send batch
    POST Send batch SMS
6) Message listing / details
    POST Get user messages (filter by status)
7) Get messages by dispatch
    POST Get messages by dispatch id
    GET Dispatch status
8) SMS check (parts, blacklist, prices)
    GET Check message
9) Balance
    GET Get limit / balance
10) Logs
    GET System SMS logs
11) Status by ID
    GET Status by ID
12) Prices

GET Prices

Base URL

- `https://notify.eskiz.uz`

---

1) Auth

POST Login (get token)

- **Endpoint:** `POST /api/auth/login`
- **Description:** Returns an access token.

```
curl --location 'https://notify.eskiz.uz/api/auth/login' \
--form 'email="vash@email.uz"' \
--form 'password="vash_sekretniy_kod_s_kabineta"'
```

Response (example)

```
{
  "message": "token_generated",
  "data": {
    "token": "Ваш токен"
  },
  "token_type": "bearer"
}
```

- **Token TTL:** 30 days

PATCH Refresh token

- **Endpoint:** `PATCH /api/auth/refresh`

---

2) Templates

POST Create / list templates

- **Endpoint:** `POST /api/user/template`
- **Auth:** `Authorization: Bearer {token}`

```
curl --location --request POST 'https://notify.eskiz.uz/api/user/template' \
--header 'Authorization: Bearer {vash_token_zdes}'
```

Response (example)

```
{
  "success": true,
  "result": [
    {
      "id": 1,
      "template": "",
      "original_text": "Eskiz API test 2",
      "status": "moderation"
    }
  ]
}
```

Template status values

- `moderation` → На модерации
- `inproccess` → В процессе
- `service` → Сервисный
- `reklama` → Рекламный
- `rejected` → Отказано

---

3) SMS Sending

Message status (overall)

- `NEW` — СМС в ожидании отправления оператору

- `STORED` — Отправляется только через `CALLBACK_URL` и означает, что SMS уже записано в базу данных
- `ACCEPTED` — Минимум одна часть SMS передана оператору, но финальный статус не получен
- `PARTDELIVERED` — Минимум одна часть SMS доставлена
- `DELIVERED` — Доставлено
- `REJECTED` — Одна из частых причин: номер в черном списке

Message part status (per part)

- `NEW` — В ожидании
- `ACCEPTED` — Передан оператору, но DLR не получен
- `DELIVRD` — Доставлено
- `UNDELIV` / `UNDELIVERABLE` — Недоставлено (часто блокировка/недостаточно средств/долг)
- `EXPIRED` — Истек срок жизни SMS
- `REJECTD` — Часто: номер в черном списке
- `DELETED` — Ошибка запроса (например неверный sender)
- `UNKNOWN` — Неопределенный статус
- `ENROUTE` — В процессе доставки (неопределенный статус)

---

4) Send SMS

POST Send single SMS

- **Endpoint:** `POST /api/message/sms/send`
- **Notes:** To use your nickname, set `from` to your own sender.

Optional callback

- `callback_url` (optional) — URL that will receive POST status updates.

- Payload format:

```
{
  "request_id": "UUID",
  "message_id": "4385062",
  "user_sms_id": "vash_ID_zdes",
  "country": "UZ",
  "phone_number": "998991234567",
  "sms_count": "1",
  "status": "DELIVRD",
  "status_date": "2021-04-02 00:39:36"
}
```

- `request_id` — Returned as `id` from `send`, `send-batch`, `send-global` and also equals `request_id` in other APIs.

```
curl --location 'https://notify.eskiz.uz/api/message/sms/sen
d' \
--form 'mobile_phone="99899012345678"' \
--form 'message="Eskiz Test"' \
--form 'from="4546"' \
--form 'callback_url="http://0000.uz/test.php"'
```

Response (example)

```
{
  "id": "59bf10a2-aba8-4694-8fd5-0be20102a580",
  "message": "Waiting for SMS provider",
  "status": "waiting"
}
```

---

5) Send batch

POST Send batch SMS

- **Endpoint:** `POST /api/message/sms/send-batch`
- **Auth:** `Authorization: Bearer {token}`

```
curl --location 'https://notify.eskiz.uz/api/message/sms/send
-batch' \
--header 'Authorization: Bearer {vash_token_zdes}' \
--data '{
  "messages": [
    {"user_sms_id":"sms1","to": 998990000000, "text": "eto te
st"},
    {"user_sms_id":"sms2","to": 998980000000, "text": "eto te
st 2"}
  ],
  "from": "4546",
  "dispatch_id": 123
}'
```

Response (example)

```
{
  "id": "03759b6d-c4db-449f-81c1-f625ab1bc1b4",
  "message": "Waiting for SMS provider",
  "status": ["waiting", "waiting"]
}
```

---

6) Message listing / details

POST Get user messages (filter by status)

- **Endpoint:** `POST /api/message/sms/get-user-messages?status`

Common fields (meaning)

- `id` — Идентификатор пользователя
- `country_id` — Идентификатор страны (null = Узбекистан)

- `smsc_id` — Идентификатор компании
- `dispatch_id` — Идентификатор рассылки
- `user_sms_id` — Идентификатор SMS от пользователя
- `request_id` — Идентификатор запроса
- `price` — Цена за часть SMS
- `is_ad` — Рекламное SMS
- `nick` — Никнейм
- `to` — Номер получателя
- `message` — Текст
- `encoding` — 0 (GSM 0338), 1 (ASCII), 8 (UCS2)
- `parts_count` — Кол-во частей
- `parts` — Детализация по частям (`part_index`, `accepted`, `dlr_state`, `dlr_time`, ...)
- `status` — Общий статус
- `sent_at`, `submit_sm_resp_at`, `delivery_sm_at` — Таймстемпы
- `created_at`, `updated_at` — Даты записи

---

7) Get messages by dispatch

POST Get messages by dispatch id

- **Endpoint:** `POST /api/message/sms/get-user-messages-by-dispatch?status`

```
curl --location 'https://notify.eskiz.uz/api/message/sms/get-
user-messages-by-dispatch' \
--header 'Authorization: Bearer {vash_token_zdes}' \
--form 'dispatch_id="123"' \
--form 'count="0"'
```

Response (example)

```
{
  "result": "Одинокий с детализацией"
}
```

GET Dispatch status

- **Endpoint:** `GET /api/message/sms/get-dispatch-status`
- **Body:** `user_id`, `dispatch_id`

Response (example)

```
{
  "status": "success",
  "data": [
    {
      "status": "DELIVERED",
      "total": 18
    }
  ],
  "id": null
}
```

---

8) SMS check (parts, blacklist, prices)

GET Check message

- **Endpoint:** `GET /api/message/sms/check`

```
curl --location --request GET 'https://notify.eskiz.uz/api/me
ssage/sms/check' \
--data '{
  "message": "Тест Тест Тест Тест Тест Тест Тест Тест Тест Те
ст Тест Тест Тест Тест Тест Тест Тест Тест Тест Тест Тест Тес
```

```
T"
}'
```

---

9) Balance

GET Get limit / balance

- **Endpoint:** `GET /api/user/get-limit`

Response (example)

```
{
  "data": {
    "balance": 0
  },
  "status": "success"
}
```

---

10) Logs

GET System SMS logs

- **Endpoint:** `GET /api/logs/sms/:id`

Response (example)

```
{
  "messages": [
    {
      "ip": "127.0.0.1",
      "from": "4546",
      "to": "99899*******",
      "dispatch_id": "<nil>",
      "user_sms_id": "test-sms-1",
      "timestamp": "2024-02-27T11:30:28.066Z",
```

```
        "message": "CallbackURL bo'sh",
        "full_message": "",
        "level_name": "WARN"
      }
    ]
  }
```

---

11) Status by ID

GET Status by ID

- **Endpoint:** `GET /api/message/sms/status_by_id/:id`

Notes

- If `:id` is **INT**, it is the SMS id on Eskiz platform.
- If `:id` is a **UUID** (from `send`, `send-batch`, `send-global`, or `request_id`), returns status for SMS sent in the last 30 days.
- If older than 30 days, use Eskiz platform INT id.

```
curl --location 'https://notify.eskiz.uz/api/message/sms/status_by_id/61359094'
```

---

12) Prices

GET Prices

- **Endpoint:** `GET /api/user/prices`
- **Docs:** https://documenter.getpostman.com/view/663428/RzfmES4z?version=latest#427e14c5-3f8d-449f-9533-374a923b7f78