

ELLWOOD SYSTEMS -- OPERATIONAL CONTROLLED DOCUMENT

CNC TABLE NESTING LAYOUT - BED 1 & 2

JOB: 25036 | RELEASE: 1 | REV: A | DATE: 2026-08-29 | Routing Bed 5ft x 12ft Vacuum Table

1. Nesting Summary & Sheet Allocation

Table Bed: CNC-01 (Thermwood Model 70 5x12 Bed)
Raw Sheet: 4mm Mitsubishi ACM Charcoal Grey (48" x 96")
Yield Efficiency: 94.2% | Tool: 1/4" Spiral 0-Flute + 90 deg V-Groove

Nesting Position	Mark	Dimensions	Flanges (L/R/T/B)	Toolpath File
Pos 1 (X:0, Y:0)	P-101	48.00" x 48.00"	1.0" / 1.0" / 1.0" / 1.0"	25036_1_P101.tap
Pos 2 (X:0, Y:48)	P-102	48.00" x 48.00"	1.0" / 1.0" / 1.0" / 1.0"	25036_1_P102.tap
Pos 3 (X:48, Y:0)	C-201	24.00" x 96.00"	1.0" / 1.0" / 1.0" / 1.0"	25036_1_C201.tap

2. Operator Instructions

- * Verify protective masking film orientation and grain direction arrow prior to vacuum pull-down.
- * Set Z-Zero to spoilboard face. V-groove skin retention target: 0.030" +/- 0.005".
- * Verify perimeter tabs (4 per panel) prior to final perimeter cut-out cycle.