

ELLWOOD SYSTEMS -- OPERATIONAL CONTROLLED DOCUMENT

CNC ROUTING & CUT PROFILE DRAWINGS

JOB: 25036 | RELEASE: 1 | REV: A | DATE: 2026-08-31 | Sheet Profiles, Kerf Allowances & V-Groove Details

1. Panel Mark Geometry & Flange Profiles

Mark P-101 (Qty 4): Finished Face 46.00" x 94.00" (Stretch-Out 48.00" x 96.00")

- Flange North: 1.000" return w/ #12 screw pilot holes @ 12.0" O.C.
- Flange South: 1.000" return w/ slot-drain weeping weep notch @ quarter-points
- Flange East / West: 1.000" perimeter return for ALU-EXT-4001 insertion
- V-Groove: 90-degree 0.090" depth leaving 0.030" aluminum skin

Mark C-201 (Qty 4 Outside Corner): Finished Face (12.00"+12.00") x 96.00"

- Center bend groove: Single continuous V-groove at X=24.000"
- Flange returns: 1.000" left/right return for structural clip attachment

2. Machine Parameters

- * Spindle Speed: 18,000 RPM | Feed Rate: 250 IPM | Ramp Entry: 45 deg smooth spiral
- * Coolant / Air Blast: Continuous vortex cold air gun on cutter flute.