
Pocket SDR Signal IDs

Pocket SDR Signal IDs (1/3)

System	Carrier Freq. (MHz)	Signal	I/Q	Min Rec. Power (dBW)	Modulation	Primary Code			Overlay Code		Navigation Data				Notes	Pocket SDR Signal ID
						Length (chip)	Rate (Mcps)	Cycle (ms)	Length (chip)	Cycle (ms)	Data	Symbol Rate (sps)	Rate (bps)	FEC		
GPS [1][2][3]	1575.42	L1C/A	Q	-158.5	BPSK(1)	1023	1.023	1	-	1	LNAV	50	50	-		L1CA
		L1P(Y)*1	I	-161.5	BPSK(10)	1week	10.23	1week	-	1week	LNAV	50	50	-		-
		L1M*3	I	?	BOC(10,5)	?	5.115	?	?	?	?	?	?	?	Block IIR-M~	-
		L1C-D	I	-163.0	BOC(1,1)	10230	1.023	10	-	10	CNAV-2	100	50	BCH, LDPC	GPS III~	L1CD
		L1C-P	I	-158.25	TMBOC(6,1,4/33)	10230	1.023	10	1800	18000	-	-	-	-		L1CP
	1227.6	L2C/A	Q	-164.5	BPSK(1)	1023	1.023	1	-	1	LNAV	50	50	-	Block IIR-M~	-
		L2P(Y)*1	I	-164.5/-161.5	BPSK(10)	1week	10.23	1week	-	1week	LNAV	50	50	-		-
		L2M*3	I	?	BOC(10,5)	?	5.115	?	?	?	?	?	?	?	Block IIR-M~	-
		L2C-M	Q/I	-160.0/-158.5	BPSK(1), TDM	10230	0.5115	20	-	20	LNAV	50	50	-		-
		L2C-L				767250	0.5115	1500	-	1500	CNAV	50	25	1/2	Block IIR-M~	L2CM
	1176.45	L5-I	I	-157.9/-157.0	BPSK(10)	10230	10.23	1	10 (NH)	10	CNAV	100	50	1/2	Block IIF~	L5I
		L5-Q	Q	-157.9/-157.0	BPSK(10)	10230	10.23	1	20 (NH)	20	-	-	-	-		L5Q
GLONASS [4][5][6][7]	1602.0 + 0.5625K*2	L1C/A	I	-161.0	BPSK(0.5)	511	0.511	1	-	1	GLO-STR	100	50	-		G1CA
		L1P	Q	?	BPSK(5)	5110000	5.11	1000	-	1000	?	?	?	-		-
	1600.995	L1OCd	Q	?	BPSK(1), TDM	1023	0.5115	2	2	4	GLO-STR	250	125	1/2	GLO-K2~	-
		L1OCp				4092	2.046	2	4 (MS)	8	-	-	-	-		-
		L1SC*4	I	?	?	?	?	?	?	?	?	?	?	?		-
	1246.0 + 0.4375K*2	L2C/A	I	-167.0	BPSK(0.5)	511	0.511	1	-	1	GLO-STR	100	50	-		G2CA
		L2P	Q	?	BPSK(5)	5110000	5.11	1000	-	1000	?	?	?	-		-
	1248.06	L2CSI	Q	?	BPSK(1), TDM	?	0.5115	?	?	?	?	?	?	?	GLO-K2~	-
		L2OCp				10230	0.5115	20	50	1000	-	-	-	-		-
		L2SC*4	I	?	?	?	?	?	?	?	?	?	?	?		-
	1202.025	L3OCd	I	?	BPSK(10)	10230	10.23	1	5 (BC)	5	GLO-STR	200	100	1/2	GLO-K1~	G3OCD
		L3OCp	Q	?	BPSK(10)	10230	10.23	1	10 (NH)	10	-	-	-	-		G3OCP
Galileo ^[8]	1575.42	E1-A	Q	-157.0	BOC(15,2.5)	?	2.5575	?	?	?	G/NAV	?	?	?	PRS	-
		E1-B	I		CBOC(6,1,1/11)	4092	1.023	4	-	4	I/NAV	250	125	1/2	OS, SoL, CS	E1B
		E1-C	Q		CBOC(6,1,1/11)	4092	1.023	4	25	100	-	-	-	-		E1C
	1176.45	E5a-I	I	-155.0	BPSK(10)	10230	10.23	1	20	20	F/NAV	50	25	1/2	OS, CS	E5AI
		E5a-Q	Q		BPSK(10)	10230	10.23	1	100	100	-	-	-	-		E5AQ
	1207.14	E5b-I	I	-155.0	BPSK(10)	10230	10.23	1	4	4	I/NAV	250	125	1/2	OS, SoL, CS	E5BI
		E5b-Q	Q		BPSK(10)	10230	10.23	1	100	100	-	-	-	-		E5BQ

*1 AS ON, *2 K = {-7 ... +6}, *3 Military Signal, *4 Secured Service Signal

Pocket SDR Signal IDs (2/3)

System	Carrier Freq. (MHz)	Signal	I/Q	Min Rec. Power (dBW)	Modulation	Primary Code			Overlay Code		Navigation Data				Notes	Pocket SDR Signal ID	
						Length (chip)	Rate (Mcps)	Cycle (ms)	Length (chip)	Cycle (ms)	Data	Symbol Rate (sps)	Rate (bps)	FEC			
Galileo (Cont.)	1191.795	E5a+b*5	-	(-152.0)	8-PSK(10)	10230	10.23	1	100	100	-	-	-	-	-	-	
		E6-A	Q	?	BOC(10,5)	?	5.115	?	?	?	G/NAV	?	?	?	PRS	-	
	1278.75	E6-B	I	-155.0	BPSK(5)	5115	5.115	1	-	1	C/NAV	1000	500	1/2	CAS, HAS	E6B	
		E6-C	Q		BPSK(5)	5115	5.115	1	100	100	-	-	-	-		E6C	
QZSS [9][10][11][12]	1575.42	L1C/A	I/Q	-158.5*6	BPSK(1)	1023	1.023	1	-	1	LNAV	50	50	-		L1CA	
		L1C/B	I	-158.5	BOC(1,1)	1023	1.023	1	-	1	LNAV	50	50	-		L1CB	
		L1C-D	I	-163.0*7	BOC(1,1)	10230	1.023	10	-	10	CNAV2	100	50	BCH,LDPC		L1CD	
		L1C-P	Q	-158.25	BOC(1,1)	10230	1.023	10	1800	18000	-	-	-	-	Block I	L1CP	
			I	-158.25*8	TMBOC(6,1,4/33)	10230	1.023	10	1800	18000	-	-	-	-	Block II	L1CP	
		L1S	I	-161.0/-158.5	BPSK(1)	1023	1.023	1	-	1	L1S	500	250	1/2	SLAS	L1S	
	1227.6	L2C-M	I	-160.0/-158.5	BPSK(1), TDM	10230	0.5115	20	-	20	CNAV	50	25	1/2		L2CM	
		L2C-L				767250	0.5115	1500	-	-	-	-		-			
	1176.45	L5-I	I	-157.9/-157.0	BPSK(10)	10230	10.23	1	10 (NH)	10	CNAV	100	50	1/2		L5I	
		L5-Q	Q	-157.9/-157.0	BPSK(10)	10230	10.23	1	20 (NH)	20	-	-	-	-		L5Q	
		L5S-I	I	-157.0*9	BPSK(10)	10230	10.23	1	-	1	L5S	500	250	1/2	Normal mode	L5SI	
									2 (MC)	2	L5S	500	250	1/2	Verif. mode	L5SIV	
		L5S-Q	Q		BPSK(10)	10230	10.23	1	20 (NH)	20	-	-	-	-	Normal mode	L5SQ	
									2 (MC)	2	-	-	-	-	Verif. mode	L5SQV	
	1278.75	L6D	I		-155.7	BPSK(5), TDM	10230	2.5575	4	-	4	L6D	2000	2000	RS	CLAS	L6D
		L6L					1048575	2.5575	410	2	820	-	-	-	-	Block I	-
		L6E		10230			2.5575	4	-	4	L6E	2000	2000	RS	MADOCA-PPP	L6E	
BeiDou [13][14][15][16][17]	1561.098	B1I	I	-163.0	BPSK(2)	2046	2.046	1	20 (NH)	20	D1	50	50	BCH		B1I	
			1	-	1	D2	500	500	BCH	GEO	B1I						
		B1Q*10	Q	?	BPSK(2)	?	2.046	?	?	?	?	?	?	?		-	
	1575.42	B1C-D	I	-159.0/	BOC(1,1)	10230	1.023	10	-	10	B-CNAV1	100	50	NB-LDPC		B1CD	
		B1C-P	Q	-161.0	QMBOC(6,1,4/33)	10230	1.023	10	1800	18000	-	-	-	-	BDS-3	B1CP	
		B1A-D*10	I	?	BOC(14,2)	?	?	?	?	?	?	?	?	-			
			B1A-P*10			Q	?	?	?	?	?	-	-	-		-	
	1176.45	B2a-D	I	-156.0/	BPSK(10)	10230	10.23	1	5	5	B-CNAV2	50	25	NB-LDPC	BDS-3	B2AD	
		B2a-P	Q	-158.0	BPSK(10)	10230	10.23	1	100	100	-	-	-	-		B2AP	
1207.14	B2I	I	?	BPSK(2)	2046	2.046	1	20 (NH)	20	D1	50	50	BCH		B2I		
							1	-	1	D2	500	500	BCH	GEO	-		

*5 AltBOC *6 -164.0 dBW (SVID=7), *7 -167.2 dBW (SVID=7), *8 -162.4 dBW (SVID=7), *9 -162.6 dBW (SVID=3), *10 Authorized signal

Pocket SDR Signal IDs (3/3)

System	Carrier Freq. (MHz)	Signal	I/Q	Min Rec. Power (dBW)	Modulation	Primary Code			Overlay Code		Navigation Data				Notes	Pocket SDR Signal ID
						Length (chip)	Rate (Mcps)	Cycle (ms)	Length (chip)	Cycle (ms)	Data	Symbol Rate (sps)	Rate (bps)	FEC		
BeiDou (Cont.)	1207.14	B2Q ^{*10}	Q	?	BPSK(10)	10230	10.23	1	?	?	?	?	?	?		-
		B2b-I	I	-160.0/-162.0	BPSK(10)	10230	10.23	1	-	1	B-CNAV3	1000	500	NB-LDPC	BDS-3	B2BI
		B2b-Q ^{*10}	Q	?	BPSK(10)	10230	10.23	1	?	?	B2b-PPP	1000	500	NB-LDPC	BDS-3, GEO	B2BI
	1191.795	B2a+b ^{*11}	-	?	8-PSK(10)	10230	10.23	1	?	?	-	-	-	-		-
		B3I	I	-163.0	BPSK(10)	10230	10.23	1	20 (NH)	20	D1	50	50	BCH		B3I
	1268.52	B3Q ^{*10}	Q	?	BPSK(10)	?	10.23	?	?	?	?	?	?	?		-
		B3A-D ^{*10}	I	?	BPSK(10)	?	10.23	?	?	?	?	?	?	?	BDS-3	-
		B3A-P ^{*10}	Q	?	BPSK(10)	?	10.23	?	?	?	-	-	-	-		-
NavIC [18][19]	1575.42	L1-SPS-D	Q	-159.6	BOC(1,1)	10230	1.023	10	-	10	IRN-NAV	100	50	BCH, LDPC	NVS-01~	-
		L1-SPS-P	I	-158.2	MBOC(6,1,4/33)	10230	1.023	10	1800	18000	-	-	-	-		-
	1176.45	L5-SPS	*12	-159.0	BPSK(1)	1023	1.023	1	-	1	IRN-NAV	50	25	1/2		ISS
		L5-RS-D	*12	?	BOC(5,2)	?	2.046	?	?	?	?	50	25	1/2	*10	-
		L5-RS-P	*12	?	BOC(5,2)	?	2.046	?	?	?	-	-	-	-	*10	-
	2492.028	S-SPS	*12	-162.3	BPSK(1)	1023	1.023	1	-	1	IRN-NAV	50	25	1/2		ISS
		S-RS-D	*12	?	BOC(5,2)	?	2.046	?	?	?	?	50	25	1/2	*10	-
		S-RS-P	*12	?	BOC(5,2)	?	2.046	?	?	?	-	-	-	-	*10	-
SBAS	1575.42	L1C/A	I	-	BPSK(1)	1023	1.023	1	-	1	SBAS	500	250	1/2	PRN120-158	L1CA
	1176.45	L5-I	I	-	BPSK(10)	10230	10.23	1	2 (MC)	2	L5 SBAS	500	250	1/2	PRN120-158	L5I
		L5-Q	Q	-	BPSK(10)	10230	10.23	1	2 (MC)	2	-	-	-	-		L5Q

*10 Authorized signal, *11 ACE-BOC, *12 Interplex Modulation

[1] IS-GPS-200K, Navstar GPS space segment/navigation user interfaces - interface specification, 2019, [2] IS-GPS-800F, Navstar GPS space segment/user segment L1C interface - interface specification, 2019, [3] IS-GPS-705A, Navstar GPS space segment/user segment L5 interface - interface specification, 2010, [4] GLONASS interface control document - navigation radiosignal in bands L1, L2, version 5.1, 2008, [5] GLONASS interface control document - code division multiple access open service navigation signal in L1 frequency band, edition 1.0, 2016, [6] GLONASS interface control document - code division multiple access open service navigation signal in L2 frequency band, edition 1.0, 2016, [7] GLONASS interface control document - code division multiple access open service navigation signal in L3 frequency band, edition 1.0, 2016, [8] European GNSS (Galileo) open service signal-in-space interface control document (OS SIS ICD), Issue 1, Revision 3, 2016, [9] Quasi-Zenith satellite system interface specification - satellite positioning, navigation and timing service (IS-QZSS-PNT-003), 2018, [10] Quasi-zenith satellite system interface specification - sub-meter level augmentation service (IS-QZSS-L1S-003), 2018, [11] Quasi-zenith satellite system interface specification - centimeter level augmentation service (IS-QZSS-L6-003), 2018, [12] Quasi-zenith satellite system interface specification - positioning technology verification service (IS-QZSS-TV-004), 2023, [13] BeiDou navigation satellite system signal in space interface control document - open service signal B1I, version 3, 2019, [14] BeiDou navigation satellite system signal in space interface control document - open service signal B1C, version 1.0, 2017, [15] BeiDou navigation satellite system signal in space interface control document - open service signal B2a, version 1.0, 2017, [16] BeiDou navigation satellite system signal in space interface control document - open service signal B3I, version 1.0, 2018, [17] BeiDou navigation satellite system signal in space interface control document - Precise Point Positioning service signal PPP-B2b, version 1.0, 2020, [18] Indian Regional Navigation Satellite System, Signal in space ICD for standard positioning service version 1.1, 2017, [19] NAVIC signal in space ICD for standard positioning service in L1 frequency version 1.0, 2023