

1、复制接口示例

```
curl -X POST 'http://192.168.52.141/v1/chat-messages' \
--header 'Authorization: Bearer {api_key}' \
--header 'Content-Type: application/json' \
--data-raw '{
  "inputs": {},
  "query": "what are the specs of the iPhone 13 Pro Max?",
  "response_mode": "streaming",
  "conversation_id": "",
  "user": "abc-123",
  "files": [
    {
      "type": "image",
      "transfer_method": "remote_url",
      "url": "https://cloud.dify.ai/logo/logo-site.png"
    }
  ]
}'
```

2、apipost测试接口

POST

http://192.168.52.141/v1/chat-messages

Header (2)

Query

Path

Body (1)

认证

Cookie

预执行操作

后执行操作

公共参数 (Header)

☒ 参数名	参数值	描述
☒ Authorization	string	* Bearer app-asY5jmKSIBrjR1k2In1IdaRt
☒ Content-Type	string	* application/json
☒	string	*

3、请求体

```
{
  "inputs": {},
  "query": "感冒的分类",
  "conversation_id": "",
  "response_mode": "blocking",
  "user": "abc-123"
}
```

POST <http://192.168.52.141/v1/chat-messages>

Header (2)	Query	Path	Body (1)	认证	Cookie	预执行操作	后执行操作
------------	-------	------	----------	----	--------	-------	-------

☐ none ☐ form-data ☐ urlencoded ☐ binary ☐ msgpack ☒ raw

④ 基于数据结构生成

```
1 {
2   "inputs": {},
3   "query": "感冒的分类",
4   "conversation_id": "",
5   "response_mode": "blocking",
6   "user": "abc-123"
7 }
```

4、

4、输出结果

[illegible]