

JUAS22: Accelerator Design Workshop - Lattice Design

Group 10


Marvin Noll Javier Olivares Adrien Plaçais

February 1, 2022

Design of Arc Cell (1): Cell type and phase advance

- Cell type: **FODO**
- Phase advance: $\mu = 90^\circ$

Design of Arc Cell (1): Cell layout



Design of Arc Cell (1): θ and k_1

- Bending angle θ :

$$\epsilon_x = \frac{C_q}{J_x} \gamma^2 \theta^3 F, \quad \text{with: } F = F_{\text{FODO}} = \frac{1}{2 \sin \mu} \frac{5 + 3 \cos \mu}{1 - \cos \mu} \frac{L_{\text{cell}}}{L_B}$$
$$\Leftrightarrow \theta = 1.323 \text{ mrad}$$

- Quadrupole strength k_1 :

$$\sin \frac{\mu}{2} = \frac{L_Q}{4f}, \quad \text{and } \frac{1}{f} = k_1 L_Q$$
$$\Leftrightarrow k_1 = 0.05714 \text{ m}^{-2}$$

Design of Arc Cell (1): Tune Matching

```
match, sequence = JC_fodo_arc;  
  GLOBAL, Q1=0.25+0.00001;  
  GLOBAL, Q2=0.25+0.00001;  
  VARY, NAME= K1QF, STEP=0.000001;  
  VARY, NAME= K1QD, STEP=0.000001;  
  LMDIF, CALLS=50, TOLERANCE=1e-8;//method adopted  
endmatch;
```

	Target Value	Final Value
q1	2.5001×10^{-1}	2.5001003×10^{-1}
q2	2.5001×10^{-1}	2.5001003×10^{-1}
	Before matching	After matching
k1qf	5.714×10^{-2}	4.767×10^{-2}
k1qd	-5.714×10^{-2}	-4.767×10^{-2}

Design of Arc Cell (1): Chromaticity Matching

```
match , sequence = JC_fodo_arc ;  
  GLOBAL, dq1=0;  
  GLOBAL, dq2=0;  
  VARY, NAME= K2SF, STEP=0.0000001;  
  VARY, NAME= K2SD, STEP=0.0000001;  
  LMDIF, CALLS=200, TOLERANCE=1e-6;  
endmatch ;
```

	Target Value	Final Value
dq1	0	7.035×10^{-14}
dq2	0	2.599×10^{-13}

	Before matching	After matching
k2sf	0	2.61×10^{-1}
k2sd	0	-5.003×10^{-1}

Design of Arc Cell (1): Closing the Ring

- Close the ring with a loop:

```
i = 0;  
JC_ring : SEQUENCE, refer=centre , L=L_JC_ring;  
    while (i < numberOfCells) {  
        JC_fodo_arc , at=(i + 0.5) * Lcell;  
        i = i + 1;  
    }  
ENDSEQUENCE;
```

- Check if ring is closed with survey:

$$\frac{\int \rho d\theta - 2\pi}{2\pi} = \frac{6.2854196 - 2\pi}{2\pi} = 0.035\%$$

Design of Arc Cell (1): Synchrotron Radiation and Emittance

- Energy loss:

$$U_0 = \frac{C_q E^4 I_2}{2 \pi} = 3.96 \times 10^{-8} \text{ J} \quad (1)$$

- Emittance:

$$\epsilon_x = \frac{C_q \gamma_L^2 I_5}{J_x I_2} = 2.58 \text{ nm rad} \quad (2)$$