

# 取消文化之現象分析

高嘉好、柯堯城、吳承恩、趙友誠

2024-11-14

## Table of contents

report 的重要頁碼	1
處理後資料簡介	1
人口結構變數處理	2
其他變數的更動	2
對抵制行為相關問題變數之處理	4
資料視覺化	8
describe	8
對各變數依 q28_YN 二元變數畫比例圖	8
Logistic and Decision tree and PCA and XGboost	9
Canonical analysis and PCA	31

## report 的重要頁碼

52: 網路癮誘與脫序行為之子題說明  
92: 資料人口結構與母群人口結構比較表  
281: 各題目之測量概念

## 處理後資料簡介

原始資料維度: rows×columns = 1004 × 207

原始的資料有 207 個變數，代表問卷中所有的問題選項 (包含複選題以及注意力偵測題等等)。

我們首先移除與分析無關的變數:

8 題: 大部分的人都有透過網路接觸名人的資訊或討論 (只有四個人沒有)，所以決定移除。

9 題: 即時通訊軟體多為聯繫熟人或工作上使用，較難顯現是否有突破同溫層的現象，所以決定移除。

疫情相關題目 (12~15): 關心的題目 (28,29) 時間範圍較廣，並不只局限於疫情期間，所以決定移除。

```
library(haven)           #read sav file
library(labelled)        #remove attribute of sav data
library(Hmisc)           #describe
library(showtext)        #show zw-tw in ggplot2
library(dplyr);library(ggplot2);library(MASS)
library(rlang)           #for building function
```

```

#DB.sav <-read_sav("DisruptiveBehavior.sav")
#write.csv(DB.sav,file="DisruptiveBehavior.csv", row.names= FALSE)
DB.csv <-read.csv("DisruptiveBehavior.csv")[,-c(1:4)]
showtext_auto() #render 的 ggplot 可以顯示中文

# 移除注意力偵測題
DB.csv[,match("q21a_1", colnames(DB.csv)):match("q21a_6_text", colnames(DB.csv))] <- NULL
DB.csv$q37a <- NULL
DB.csv$rrq21a <- NULL
DB.csv$rrq37a <- NULL
DB.csv$r <- NULL # 基本資料與第一波網調是否相符

# 移除 q8,q9
DB.csv[, match("q8_1", colnames(DB.csv)):match("q8_90", colnames(DB.csv))] <- NULL
DB.csv[, match("q9_1", colnames(DB.csv)):match("q9_90", colnames(DB.csv))] <- NULL

# 移除疫情相關的問題 (12 題到 15 題)
DB.csv[,match("q12_1", colnames(DB.csv)):match("q15_03_1", colnames(DB.csv))] <- NULL

```

接著在對一些題目進行細部的選項討論：

## 人口結構變數處理

年齡：移除出生年的資訊，將 rrq2 的年齡分層變數重新命名”q2\_rr”。

出生地：其他類別歸在一類 (24)。但是類別有點多，考慮對人口結構表格中的分類方式 (北北基宜、桃竹苗等區分)，還沒做。

教育程度：重新劃分為四個等級 (1: 高中及以下, 2: 專科, 3: 大學, 4: 研究所)，劃分參考人口結構表格的分類方式。

```

# 第二題 (出生年) 改成年齡的區段
DB.csv$q2 <- DB.csv$qrq2
DB.csv$qrq2 <- NULL
DB.csv$q2_rr <- DB.csv$rrq2
DB.csv$rrq2 <- NULL

# 把第三題 (出生地) 的其他類別歸為一類
DB.csv$q3_other <- NULL

# 第四題沒有人選其他
DB.csv$q4_88_text <- NULL

# 教育程度重新劃分為四個等級
DB.csv$q4[DB.csv$q4<=8] <- 1
DB.csv$q4[DB.csv$q4!=1 & DB.csv$q4<=15] <- 2
DB.csv$q4[DB.csv$q4>2 & DB.csv$q4<=19] <- 3
DB.csv$q4[DB.csv$q4>3] <- 4

```

## 其他變數的更動

6、7 題：時間統一單位 (分)

10 題：改成”使用幾個與 yt 名人討論相關的社群媒體”，因為有些社群媒體不會造成抵制名人行為，例如：Pinterest,Linkedin,+ 其他類 Pixiv,Mobile01,Komica,MeWe 跟名人相關的討論比較少，所以決定簡化選項；巴哈姆特, 巴哈姆特場外休憩區兩個則要計算。

```
# 時間統一單位 (分)
DB.csv$q6 <- DB.csv$q6_h*60+DB.csv$q6_m
DB.csv$q7 <- DB.csv$q7_h*60+DB.csv$q7_m
DB.csv$q6_h <- NULL; DB.csv$q6_m <- NULL
DB.csv$q7_h <- NULL; DB.csv$q7_m <- NULL

# 整理第十題
DB.csv$q10_4 <- NULL
DB.csv$q10_10 <- NULL
DB.csv$q10_90 <- NULL
DB.csv$q10_88[DB.csv$q10_88_text!=" 巴哈姆特場外休憩區"&DB.csv$q10_88_text!=" 巴哈姆特"] <- 1
DB.csv$q10_88_text <- NULL
DB.csv$q10 <- apply(DB.csv[,c("q10_1", "q10_2", "q10_3", "q10_5", "q10_6", "q10_7", "q10_8", "q10_9", "q10_10", "q10_90", "q10_88")],
                    1, function(row){sum(!is.na(row))})
DB.csv[,c("q10_1", "q10_2", "q10_3", "q10_5", "q10_6", "q10_7", "q10_8", "q10_9", "q10_88")] <- DB.csv$q10

# 整理第十一題
DB.csv$q11_2 <- NULL
DB.csv$q11_3 <- NULL
DB.csv$q11_4 <- NULL
DB.csv$q11_5 <- NULL
DB.csv$q11_6 <- NULL
DB.csv$q11_8 <- NULL
DB.csv$q11_90 <- NULL
DB.csv$q11_88[DB.csv$q11_88_text!="bilibili"] <- NA
DB.csv$q11_88_text <- NULL
DB.csv$q11 <- apply(DB.csv[,c("q11_1", "q11_7")],
                    1, function(row){sum(!is.na(row))})
DB.csv[,c("q11_1", "q11_7", "q11_88")] <- NULL
```

```
DB.csv$q16 <- NULL
DB.csv$q18 <- NULL
DB.csv$q17_01[is.na(DB.csv$q17_01)|DB.csv$q17_01==2] <- 0
DB.csv$q17_02[is.na(DB.csv$q17_02)|DB.csv$q17_02==2] <- 0

DB.csv$q19_01[is.na(DB.csv$q19_01)|DB.csv$q19_01==2] <- 0
DB.csv$q19_02[is.na(DB.csv$q19_02)|DB.csv$q19_02==2] <- 0

DB.csv$q1719_label <- apply(
  DB.csv[,match("q17_01",colnames(DB.csv)):match("q19_02",colnames(DB.csv))],
  MARGIN = 1,
  function(row){
    return(paste0(row,collapse = ""))
  })
unique(DB.csv$q1719_label)

[1] "0000" "1101" "1100" "1000" "0100" "1110" "1111" "0101" "0001"

DB.csv$q1719_label <- ifelse(DB.csv$q1719_label=="0000", 0, 1)
```

3

(<https://www.airtilibrary.com/Article/Detail/U0004-G0107932056>) 之做法，將相同大主題的 ordinal 主觀評分加總作為該主題程度的分數。

這裡的分數要不要用加總的？跟哪些分數要加在一起要討論一下，我覺得 25 的幾題跟 20 題那邊的蠻像的。

22 題 (看見他人網路攻擊行為 (網路使用環境)): 分數越高越常看到環境中其他人的攻擊。

23 題 (自己的網路攻擊行為): 分數越高代表自己的攻擊性越高

24 題 (回聲室效應): 分數越高則較常突破同溫層或是媒體識讀素養較高

25 題 (網路攻擊接受性): 分數越高越覺得網路上的攻擊行為 OK。但是 25 題的第三題

26 題 (推測對他人之攻擊意圖): 受訪者對網路攻擊行為的看法，分數越高代表受訪者越覺得網路攻擊行為容易引起他人的攻擊性。

```
DB.csv$q22 <- rowSums(DB.csv[,c("q22_01_1", "q22_02_1", "q22_03_1", "q22_04_1", "q22_05_1")])
DB.csv$q23 <- rowSums(DB.csv[,c("q23_01_1", "q23_02_1", "q23_03_1", "q23_04_1", "q23_05_1")])
DB.csv$q24 <- rowSums(DB.csv[,c("q24_01_1", "q24_02_1", "q24_03_1", "q24_04_1", "q24_05_1")])
DB.csv$q25 <- rowSums(DB.csv[,c("q25_01_1", "q25_02_1", "q25_03_1", "q25_04_1")])
DB.csv$q26 <- rowSums(DB.csv[,c("q26_01_1", "q26_02_1", "q26_03_1")])
DB.csv[,match("q22_01_1", colnames(DB.csv)):match("q26_03_1", colnames(DB.csv))] <- NULL
```

38 題 ~42 題 (最後一題)

38 題: 心理幸福感 (表現自尊) 的評分，將 (生活滿意度、社會滿意度) 加總

40 題: 國民黨偏好 0 ~ 100 → 1 ~ 5

41 題: 民進黨偏好 0 ~ 100 → 1 ~ 5

42 題: 反台獨程度 1 ~ 10

```
DB.csv$q38 <- rowSums(DB.csv[,c("q38_01_1", "q38_02_1")])
DB.csv$q38_01_1 <- NULL
DB.csv$q38_02_1 <- NULL

DB.csv$q40 <- cut(DB.csv$q40_1,
                  breaks = c(0, 20, 40, 60, 80, 100),
                  labels = c(1, 2, 3, 4, 5),
                  right = TRUE)
DB.csv$q40[is.na(DB.csv$q40)] <- 1

DB.csv$q41 <- cut(DB.csv$q41_1,
                  breaks = c(0, 20, 40, 60, 80, 100),
                  labels = c(1, 2, 3, 4, 5),
                  right = TRUE)
DB.csv$q41[is.na(DB.csv$q41)] <- 1

DB.csv$q41_1 <- NULL
DB.csv$q40_1 <- NULL
```

### 對抵制行為相關問題變數之處理

針對 28,29 進行細部討論後，針對選項進行合理的歸類。

首先對其他類進行歸類：

28 題 (做過的抵制行為): 其他類 (16 個人有填) 分到前三類或是設 0: 沒有抵制行為。

29 題(抵制原因): 原先將其他類裡面有出現的不當發言歸為第五類, 後續覺得”不當發言”可以與”不道德、不正當或不合法行為”合併, “有不同的政治意識型態或價值觀”可以與”不表態支持重要的社會議題”合併, 最後 29 題剩下三個類別 + 沒有抵制行為的 000

```
# 處理 28 的選項
DB.csv$q28_5 <- NULL
q28.manipulation <- function(row){
  # 亂回答的要把其他抵制行為的問題回答 (28-36) 也移除
  delete.term <- c(" 會破壞我對他(她)的形象",
    " 從來都不關注",
    " 若名人不自我反省就會抵制, 但是通常名人都會願意出來面對錯誤",
    " 未來此人所說的話均會產生疑問",
    " 用選票來抵制",
    " 很多時候都是立場不同、換位思考一下後, 就可以消弭一些爭議。",
    " 看看就好",
    " 沒意見",
    " 看看就好, 自己會有自己的判斷")
  # 要移除 q28_4 標籤的
  amend.term <- c(" 指正他的錯誤",
    " 拒買相關商品",
    " 與親朋好友說明事實真相",
    " 要看是什麼原因決定一時間這麼做還是永久")
  if(row[5] %in% delete.term){row <- c(rep(NA,4), "", rep(NA,5), "", rep(NA,7))}
  else if(row[5] %in% amend.term){row[4:5] <- c(NA, "")}
  return(row)
}

DB.csv[,match("q28_1",colnames(DB.csv)):match("q36_1",colnames(DB.csv))] <- as.data.frame(
  t(apply(DB.csv[,match("q28_1",colnames(DB.csv)):match("q36_1",colnames(DB.csv))],
    1,
    q28.manipulation))
)

# 要歸類的要一個一個看歸在哪類
DB.csv[DB.csv$q28_4_text==" 每個人有合法的言論自由, 我只會拒絕觀看有問題違法的影片, 不會一竿子打翻一條船。",
  c('q28_2','q28_4','q28_4_text')] <- c(1,NA,"")

DB.csv[DB.csv$q28_4_text==" 減少看他們的發文或影片", c('q28_2','q28_4','q28_4_text')] <- c(1,NA,"")

DB.csv[DB.csv$q28_4_text==" 轉發相關的指正或譴責文章",c('q28_3','q28_4','q28_4_text')] <- c(1,NA,"")

DB.csv$q28_4 <- NULL
DB.csv$q28_4_text <- NULL

# 處理 29 的選項
#29 的第五選項改定義為 錯誤資訊、不當言論
q29.manipulation <- function(row){
  # 亂回答的要把其他抵制行為的問題回答 (28-36) 也移除
  delete.term <- c(" 道不同不相為謀不理他們",
    " 沒有此情況",
    " 不會抵制",
    " 我沒有特別抵制過呢",
    " 從來沒有",
    " 不明白指的是什麼",
    " 已讀",
    " 不理他們",
```

```

      " 不予置評",
      " 無",
      " 不會做無聊的事情",
      " 目前沒有",
      " 不曾",
      " 沒遇過要抵制的事",
      " 沒有",
      " 沒有抵制過")
# 要被歸類到第五類（不當發言、錯誤資訊）的
class5 <- c(" 錯誤資訊",
            " 發表錯誤資訊且不更改",
            " 指鹿為馬，不實言論，刻意誤導輿論方向。",
            " 不當發言",
            " 謾罵",
            " 誤導",
            " 散播不正確消息且不認錯",
            " 對動物議題留下錯誤言論，對疫情走向發出錯誤言論（去年康健發文說嬰幼兒不會染疫，被我指正，卻不改",
            " 假名人之姿發表利己損害公眾利益的言論，企圖影響他人判斷的言論者。",
            "")
if(row[9] %in% delete.term){row <- c(rep(NA,8),"",rep(NA,7))}
else if(row[9] %in% class5){row[9] <- ""}
return(row)
}

DB.csv[,match("q28_1",colnames(DB.csv)):match("q36_1",colnames(DB.csv))] <- as.data.frame(
  t(apply(DB.csv[,match("q28_1",colnames(DB.csv)):match("q36_1",colnames(DB.csv))],
        1,
        q29.manipulation))
)
# 要歸類的要一個一個看歸在哪類
DB.csv[DB.csv$q29_5_text==" 過於私人或主觀意識的回答會讓我反感進而抵制收看",
       c('q29_2','q29_5','q29_5_text')] <- c(1,NA,"")

DB.csv[DB.csv$q29_5_text==" 味全黑心油事件",
       c('q29_5','q29_5_text')] <- c(NA,"")

DB.csv[DB.csv$q29_5_text==" 說謊話（至少是我覺得他在說謊），做錯事不負責還甩鍋給別人。",
       c('q29_5','q29_5_text')] <- c(NA,"")

DB.csv[DB.csv$q29_5_text==" 有些事情的看法 做法不同",
       c('q29_2','q29_5','q29_5_text')] <- c(1,NA,"")

DB.csv[DB.csv$q29_5_text==" 違反當初自己宣揚的理念",
       c('q29_4','q29_5','q29_5_text')] <- c(1,NA,"")

DB.csv[
  DB.csv$q29_5_text==" 泛指公眾人物沒有責任表態但有義務不支持通稱反人類行為，私領域不要太誇張都沒差",
  c('q29_4','q29_5','q29_5_text')] <- c(1,NA,"")

DB.csv$q29_5_text <- NULL

```

NA 補 0 是在這個階段處理完其他類（文字）之後才做。

因為想要做的方向有兩個：“甚麼原因會造成有抵制行為?”，“甚麼原因會影響抵制行為的程度”，所以在最後建

立 q28\_YN 的二元變數。

```
# 處理完其他類之後先把 NA 補 0
DB.csv <- as.data.frame(
  apply(DB.csv,2,function(col){
    col <- as.numeric(col)
    col[is.na(col)] <- 0
    return(col)
  })

DB.csv$q29_2 <- ifelse(DB.csv$q29_2 | DB.csv$q29_3, 1,0)
DB.csv$q29_3 <- ifelse(DB.csv$q29_4 | DB.csv$q29_5, 1,0)
DB.csv$q29_4 <- NULL
DB.csv$q29_5 <- NULL

# 有無抵制行為 (1: 有,0: 沒有)
DB.csv$q28_YN[DB.csv$q28_1 | DB.csv$q28_2 | DB.csv$q28_3] <- 1
DB.csv$q28_YN[!(DB.csv$q28_1 | DB.csv$q28_2 | DB.csv$q28_3)] <- 0

# 重新調整欄位 index
#colnames(DB.csv)
#colnames(DB.csv)[c(1:2,29,3:5,30:33,6:9,34,10:11,35:39,12,43,13:25,40,26,41:42,27,28)]
DB.csv <- DB.csv[,c(1:2,29,3:5,30:33,6:9,34,10:11,35:39,12,43,13:25,40,26,41:42,27,28)]
for(i in c(1:5,7:42)){
  DB.csv[,i] <- as.integer(DB.csv[,i])
}
```

Table 1: 變數解釋

Variables	Explanation	remark
q1	性別	1: 男性, 2: 女性
q2	年齡	
q2_rr	年齡分層	1:18~29, 2:30~39, 3:40~49, 4:50~59, 5:60~69, 6:70+
q3	出生縣市	1~19: 台灣的縣市 (資料沒有連江、澎湖、金門), 24: 其他
q4	教育程度	1: 高中及以下, 2: 專科, 3: 大學, 4: 研究所
q5_1	週平均上網天數	
q6	上網分鐘 (工作、學習)	
q7	上網分鐘 (娛樂、休閒)	
q10	使用幾個與名人討論相關的社群媒體	
q11	是否使用 YT,Twitch 或 bilibili	
q17_01	是否參與過: 不傷害、騙人	1: 是,0: 否
q17_02	是否參與過: 不傷害、不騙人	1: 是,0: 否
q19_01	是否參與過: 傷害、騙人	1: 是,0: 否
q19_02	是否參與過: 傷害、不騙人	1: 是,0: 否
q1719_label	是否至少有參與過一種網路惡搞	1: 是,0: 否
q20_01_1	主動激化傾向	
q20_02_1	主動激化傾向	
q22	他人攻擊傾向	
q23	自己攻擊傾向	
q24	回聲室效應	
q25	被攻擊的接受度	

Variables	Explanation	remark
q26	推測他人攻擊意圖	
q27_1	抵制意圖	
q28_YN	是否採取過抵制行為	
q28_1	採取過: 取消關注	
q28_2	採取過: 拒絕觀看	
q28_3	採取過: 在網路上留言或發文指責	
q29_1	抵制的原因: 歧視特定國家、種族或性別	
q29_2	抵制的原因: 有不同的政治意識型態或價值觀	
q29_3	抵制的原因: 做出不道德、不正當或不合法行為	
q30_1	抵制行為的有效程度	
q31_1	抵制前的同理心	
q32_1	抵制行為的對名人的傷害程度	
q33_1	抵制行為的對自己的重要程度	
q34_1	抵制成本	
q35_1	抵制規模感知	
q36_1	抵制的社會壓力	
q38	心理幸福感	不滿意 2~5 滿意
q39_1	生活品質	不快樂 1~5 快樂
q40	國民黨喜好程度	不喜歡 0~5 喜歡
q41	民進黨喜好程度	不喜歡 0~5 喜歡
q42_1	意識形態	0~10: 台獨 ~ 統一
weight	人口結構修正權重	

## 資料視覺化


### describe

```
latex(describe(DB.csv),title="",file="")
```

對各變數依 **q28\_YN** 二元變數畫比例圖

```
#test code chunk
Barplot.p(din = myCount_q28(DB.csv,colnames(DB.csv)[-match("q28_YN", colnames(DB.csv))][1:20]))
```





## Logistic and Decision tree and PCA and XGboost

```
glm_log <- glm(
  factor(q28_YN)~
  factor(q1)+
  factor(q2_rr)+
  factor(q3)+
  factor(q4)+
  q5_1+
  q6+
  q7+
  q10+
  factor(q11)+
  q1719_label+
  factor(q20_01_1)+
  factor(q20_02_1)+
  q22+ q23+ q24+ q25+ q26+
  factor(q27_1), family = binomial, data = DB.csv, weights = weight)
```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

```
summary(stepAIC(glm_log, direction = 'both'))
```

Start: AIC=852.73

```
factor(q28_YN) ~ factor(q1) + factor(q2_rr) + factor(q3) + factor(q4) +
  q5_1 + q6 + q7 + q10 + factor(q11) + q1719_label + factor(q20_01_1) +
  factor(q20_02_1) + q22 + q23 + q24 + q25 + q26 + factor(q27_1)
```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

	Df	Deviance	AIC
- factor(q2_rr)	5	883.44	847.01
- factor(q4)	3	879.94	847.51
- factor(q20_02_1)	4	882.40	847.97
- factor(q11)	2	880.25	849.82
- q26	1	879.16	850.73
- q5_1	1	879.16	850.73
- factor(q1)	1	879.16	850.74
- q25	1	879.21	850.78
- q24	1	879.36	850.93
- q1719_label	1	879.66	851.23
<none>		879.15	852.73
- q10	1	881.49	853.06
- q7	1	881.65	853.22
- q6	1	882.45	854.02
- q23	1	884.91	856.48
- factor(q20_01_1)	4	892.75	858.33
- q22	1	895.80	867.38
- factor(q3)	19	967.64	903.22
- factor(q27_1)	4	1031.09	996.66

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```



```

- q10          1    887.32 847.15
- q6           1    887.67 847.50
- q23          1    888.48 848.31
- factor(q20_01_1) 4    896.53 850.36
+ factor(q2_rr)   5    879.15 850.98
- q22          1    897.13 856.96
- factor(q3)     19    976.21 900.04
- factor(q27_1)  4   1039.90 993.73

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=840.44

```

factor(q28_YN) ~ factor(q1) + factor(q3) + q5_1 + q6 + q7 + q10 +
  factor(q11) + q1719_label + factor(q20_01_1) + factor(q20_02_1) +
  q22 + q23 + q24 + q25 + q26 + factor(q27_1)

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Df Deviance AIC

```

- factor(q20_02_1) 4 887.63 835.95
- factor(q11) 2 885.91 838.23
- q26 1 884.13 838.45
- q24 1 884.15 838.47
- q5_1 1 884.17 838.49
- factor(q1) 1 884.20 838.52
- q25 1 884.31 838.63
- q1719_label 1 884.40 838.72
<none> 884.12 840.44
- q7 1 886.22 840.54
- q10 1 888.21 842.53
- q6 1 888.73 843.05
- q23 1 889.01 843.33
- factor(q20_01_1) 4 897.30 845.62
+ factor(q4) 3 883.44 845.76
+ factor(q2_rr) 5 879.94 846.26
- q22 1 897.87 852.19
- factor(q3) 19 976.65 894.97
- factor(q27_1) 4 1040.26 988.58

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=836.26

```

factor(q28_YN) ~ factor(q1) + factor(q3) + q5_1 + q6 + q7 + q10 +
  factor(q11) + q1719_label + factor(q20_01_1) + q22 + q23 +
  q24 + q25 + q26 + factor(q27_1)

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

	Df	Deviance	AIC
- factor(q11)	2	889.39	834.02
- q5_1	1	887.64	834.26
- q24	1	887.69	834.32
- q26	1	887.74	834.37
- q25	1	887.78	834.41
- factor(q1)	1	887.79	834.42
- q1719_label	1	887.85	834.48
- q7	1	889.55	836.17
<none>		887.63	836.26
- q10	1	890.95	837.58
- q6	1	891.79	838.42
- q23	1	892.51	839.14
+ factor(q20_02_1)	4	884.12	840.75
+ factor(q4)	3	886.86	841.49
+ factor(q2_rr)	5	883.35	841.98
- factor(q20_01_1)	4	904.67	845.30
- q22	1	902.04	848.67
- factor(q3)	19	980.15	890.78
- factor(q27_1)	4	1043.66	984.29

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=832.54

```
factor(q28_YN) ~ factor(q1) + factor(q3) + q5_1 + q6 + q7 + q10 +
  q1719_label + factor(q20_01_1) + q22 + q23 + q24 + q25 +
  q26 + factor(q27_1)
```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

	Df	Deviance	AIC
- q5_1	1	889.42	830.57
- q24	1	889.45	830.60
- q1719_label	1	889.50	830.65
- q26	1	889.55	830.71
- factor(q1)	1	889.59	830.75
- q25	1	889.64	830.80
- q7	1	891.07	832.22
<none>		889.39	832.54
+ factor(q11)	2	887.63	834.79
- q10	1	893.72	834.87
- q6	1	893.74	834.90
- q23	1	893.89	835.04
+ factor(q20_02_1)	4	885.91	837.06
+ factor(q2_rr)	5	884.48	837.63
+ factor(q4)	3	888.58	837.73
- factor(q20_01_1)	4	907.89	843.04
- q22	1	904.31	845.46
- factor(q3)	19	985.46	890.61
- factor(q27_1)	4	1045.67	980.82

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=830.79

factor(q28\_YN) ~ factor(q1) + factor(q3) + q6 + q7 + q10 + q1719\_label +  
 factor(q20\_01\_1) + q22 + q23 + q24 + q25 + q26 + factor(q27\_1)

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

	Df	Deviance	AIC
- q24	1	889.49	828.85
- q1719_label	1	889.52	828.89
- q26	1	889.58	828.95
- factor(q1)	1	889.62	828.98
- q25	1	889.66	829.03
- q7	1	891.07	830.44
<none>		889.42	830.79
+ q5_1	1	889.39	832.76
+ factor(q11)	2	887.64	833.00
- q6	1	893.84	833.21
- q23	1	893.90	833.27
- q10	1	893.93	833.30
+ factor(q20_02_1)	4	886.03	835.40
+ factor(q2_rr)	5	884.53	835.90
+ factor(q4)	3	888.60	835.97
- factor(q20_01_1)	4	907.89	841.26
- q22	1	904.31	843.68
- factor(q3)	19	985.52	888.89
- factor(q27_1)	4	1046.62	979.99

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=829.28



[illegible]

```

+ factor(q4)          3   888.67 834.46
+ factor(q2_rr)       5   884.87 834.66
- factor(q20_01_1)    4   907.90 839.69
- q22                 1   904.35 842.14
- factor(q3)          19   989.20 890.99
- factor(q27_1)       4  1047.77 979.56

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=827.62

```

factor(q28_YN) ~ factor(q1) + factor(q3) + q6 + q7 + q10 + factor(q20_01_1) +
  q22 + q23 + q25 + q26 + factor(q27_1)

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

```

      Df Deviance    AIC
- factor(q1)      1   889.77 825.81
- q26             1   889.78 825.82
- q25             1   889.85 825.89

```

```

- q7                1    891.31 827.35
<none>              889.58 827.62
+ q1719_label       1    889.49 829.52
+ q24               1    889.52 829.56
+ q5_1              1    889.55 829.59
+ factor(q11)        2    887.91 829.95
- q10               1    894.08 830.12
- q6                1    894.31 830.35
- q23               1    894.84 830.88
+ factor(q20_02_1)   4    886.22 832.26
+ factor(q4)         3    888.80 832.84
+ factor(q2_rr)      5    885.07 833.11
- factor(q20_01_1)   4    907.91 837.95
- q22               1    904.58 840.62
- factor(q3)         19   990.11 890.14
- factor(q27_1)      4   1048.22 978.26

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=825.84

```

factor(q28_YN) ~ factor(q3) + q6 + q7 + q10 + factor(q20_01_1) +
  q22 + q23 + q25 + q26 + factor(q27_1)

```

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

	Df	Deviance	AIC
- q26	1	889.93	824.00
- q25	1	890.02	824.08
- q7	1	891.37	825.44
<none>		889.77	825.84
+ factor(q1)	1	889.58	827.65
+ q1719_label	1	889.66	827.73
+ q24	1	889.73	827.79
+ q5_1	1	889.74	827.81
+ factor(q11)	2	888.05	828.11
- q10	1	894.45	828.52
- q6	1	894.65	828.72
- q23	1	895.63	829.70
+ factor(q20_02_1)	4	886.34	830.41
+ factor(q4)	3	888.96	831.03
+ factor(q2_rr)	5	885.07	831.14
- factor(q20_01_1)	4	907.92	835.98
- q22	1	904.75	838.82
- factor(q3)	19	991.49	889.56
- factor(q27_1)	4	1049.93	978.00

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Step: AIC=823.88

factor(q28\_YN) ~ factor(q3) + q6 + q7 + q10 + factor(q20\_01\_1) +  
q22 + q23 + q25 + factor(q27\_1)

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

Warning in eval(family\$initialize): non-integer #successes in a binomial glm!

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

	Df	Deviance	AIC
- q25	1	890.17	822.13
- q7	1	891.48	823.44
<none>		889.93	823.88
+ q26	1	889.77	825.72
+ factor(q1)	1	889.78	825.73
+ q1719_label	1	889.82	825.77
+ q24	1	889.87	825.82
+ q5_1	1	889.90	825.85
+ factor(q11)	2	888.16	826.11
- q10	1	894.81	826.76
- q6	1	895.00	826.96
- q23	1	895.75	827.70
+ factor(q20_02_1)	4	886.37	828.32
+ factor(q4)	3	889.12	829.07
+ factor(q2_rr)	5	885.16	829.11
- factor(q20_01_1)	4	908.02	833.97
- q22	1	909.93	841.88
- factor(q3)	19	991.81	887.76
- factor(q27_1)	4	1051.75	977.71

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

Step: AIC=822.69

```
factor(q28_YN) ~ factor(q3) + q6 + q7 + q10 + factor(q20_01_1) +
  q22 + q23 + factor(q27_1)
```

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

	Df	Deviance	AIC
- q7	1	891.64	822.16
<none>		890.17	822.69
+ q25	1	889.93	824.44
+ q26	1	890.02	824.53
+ factor(q1)	1	890.04	824.55
+ q1719_label	1	890.05	824.56
+ q24	1	890.11	824.62
+ q5_1	1	890.15	824.67
+ factor(q11)	2	888.30	824.81
- q6	1	895.21	825.72
- q10	1	895.40	825.91
- q23	1	895.94	826.46
+ factor(q20_02_1)	4	886.70	827.21
+ factor(q2_rr)	5	885.22	827.74
+ factor(q4)	3	889.40	827.91
- factor(q20_01_1)	4	908.03	832.55
- q22	1	909.95	840.47
- factor(q3)	19	991.81	886.32
- factor(q27_1)	4	1052.64	977.15

```
Warning in eval(family$initialize): non-integer #successes in a binomial glm!
```

Step: AIC=823.17

```
factor(q28_YN) ~ factor(q3) + q6 + q10 + factor(q20_01_1) + q22 +
  q23 + factor(q27_1)
```

Call:

```
glm(formula = factor(q28_YN) ~ factor(q3) + q6 + q10 + factor(q20_01_1) +
    q22 + q23 + factor(q27_1), family = binomial, data = DB.csv,
    weights = weight)
```

Coefficients:

	Estimate	Std. Error	z value	Pr(> z )
(Intercept)	1.2550617	1.3646272	0.920	0.357724
factor(q3)2	-3.7016521	1.3915703	-2.660	0.007813 **
factor(q3)3	-4.0078695	1.3978406	-2.867	0.004141 **
factor(q3)4	-3.3160304	1.4209972	-2.334	0.019617 *
factor(q3)5	-2.6750755	1.7868612	-1.497	0.134372
factor(q3)6	-4.0853317	1.4637853	-2.791	0.005256 **
factor(q3)7	-2.5793886	1.4483397	-1.781	0.074924 .
factor(q3)8	-2.9539964	1.5137013	-1.952	0.050997 .
factor(q3)9	-2.3762308	1.4112700	-1.684	0.092229 .
factor(q3)10	-4.6413021	1.3959327	-3.325	0.000885 ***
factor(q3)11	-3.3791212	1.4064383	-2.403	0.016279 *
factor(q3)12	-3.5726507	1.4190294	-2.518	0.011813 *
factor(q3)13	-1.1007775	1.7007817	-0.647	0.517491
factor(q3)14	-2.5463636	1.4007548	-1.818	0.069087 .
factor(q3)15	-2.8243291	1.3964057	-2.023	0.043117 *
factor(q3)16	-3.7307116	1.3972777	-2.670	0.007585 **
factor(q3)17	-3.9543060	1.4349890	-2.756	0.005858 **
factor(q3)18	-5.5456206	1.4900729	-3.722	0.000198 ***
factor(q3)19	-4.7039317	1.7470998	-2.692	0.007093 **
factor(q3)24	-3.5900582	1.5169602	-2.367	0.017952 *
q6	-0.0009015	0.0004410	-2.044	0.040942 *
q10	-0.1549530	0.0713357	-2.172	0.029843 *
factor(q20_01_1)2	0.4819075	0.2364915	2.038	0.041576 *
factor(q20_01_1)3	0.6411000	0.2886885	2.221	0.026369 *
factor(q20_01_1)4	-1.3036924	0.4845737	-2.690	0.007137 **
factor(q20_01_1)5	-1.4066257	1.0237434	-1.374	0.169441
q22	0.1163618	0.0257926	4.511	6.44e-06 ***
q23	0.1100196	0.0450363	2.443	0.014569 *
factor(q27_1)2	0.0640050	0.3419154	0.187	0.851507
factor(q27_1)3	0.9976101	0.3357019	2.972	0.002961 **
factor(q27_1)4	2.6922838	0.4006163	6.720	1.81e-11 ***
factor(q27_1)5	4.4761444	0.9611724	4.657	3.21e-06 ***

---

Signif. codes: 0 '\*\*\*' 0.001 '\*\*' 0.01 '\*' 0.05 '.' 0.1 ' ' 1

(Dispersion parameter for binomial family taken to be 1)

Null deviance: 1261.72 on 1003 degrees of freedom  
 Residual deviance: 891.64 on 972 degrees of freedom  
 AIC: 823.17

Number of Fisher Scoring iterations: 6

`summary(glm_log)`

Call:

```
glm(formula = factor(q28_YN) ~ factor(q1) + factor(q2_rr) + factor(q3) +
    factor(q4) + q5_1 + q6 + q7 + q10 + factor(q11) + q1719_label +
```

```
factor(q20_01_1) + factor(q20_02_1) + q22 + q23 + q24 + q25 +
q26 + factor(q27_1), family = binomial, data = DB.csv, weights = weight)
```

Coefficients:

	Estimate	Std. Error	z value	Pr(> z )
(Intercept)	1.159e+00	1.560e+00	0.743	0.457640
factor(q1)2	2.124e-02	2.031e-01	0.105	0.916715
factor(q2_rr)2	-1.994e-01	3.169e-01	-0.629	0.529191
factor(q2_rr)3	1.484e-02	3.402e-01	0.044	0.965220
factor(q2_rr)4	3.438e-01	3.670e-01	0.937	0.348893
factor(q2_rr)5	3.879e-01	3.939e-01	0.985	0.324773
factor(q2_rr)6	4.254e-01	4.632e-01	0.918	0.358369
factor(q3)2	-3.787e+00	1.412e+00	-2.683	0.007300 **
factor(q3)3	-4.221e+00	1.424e+00	-2.964	0.003033 **
factor(q3)4	-3.451e+00	1.443e+00	-2.392	0.016764 *
factor(q3)5	-2.847e+00	1.838e+00	-1.549	0.121321
factor(q3)6	-4.094e+00	1.486e+00	-2.754	0.005883 **
factor(q3)7	-2.874e+00	1.478e+00	-1.944	0.051839 .
factor(q3)8	-3.083e+00	1.543e+00	-1.998	0.045718 *
factor(q3)9	-2.560e+00	1.433e+00	-1.786	0.074121 .
factor(q3)10	-4.708e+00	1.418e+00	-3.321	0.000898 ***
factor(q3)11	-3.535e+00	1.430e+00	-2.472	0.013447 *
factor(q3)12	-3.629e+00	1.450e+00	-2.504	0.012296 *
factor(q3)13	-1.234e+00	1.735e+00	-0.711	0.476914
factor(q3)14	-2.879e+00	1.427e+00	-2.017	0.043646 *
factor(q3)15	-3.043e+00	1.420e+00	-2.142	0.032159 *
factor(q3)16	-3.836e+00	1.418e+00	-2.705	0.006839 **
factor(q3)17	-3.999e+00	1.462e+00	-2.736	0.006217 **
factor(q3)18	-5.922e+00	1.521e+00	-3.893	9.90e-05 ***
factor(q3)19	-4.803e+00	1.779e+00	-2.700	0.006943 **
factor(q3)24	-3.630e+00	1.539e+00	-2.358	0.018375 *
factor(q4)2	2.531e-01	2.937e-01	0.862	0.388904
factor(q4)3	5.722e-02	2.377e-01	0.241	0.809787
factor(q4)4	-1.108e-03	3.662e-01	-0.003	0.997587
q5_1	4.566e-03	5.412e-02	0.084	0.932761
q6	-8.912e-04	4.891e-04	-1.822	0.068433 .
q7	9.483e-04	6.086e-04	1.558	0.119206
q10	-1.234e-01	8.101e-02	-1.523	0.127705
factor(q11)1	-3.173e-01	4.021e-01	-0.789	0.430041
factor(q11)2	-7.046e-01	6.963e-01	-1.012	0.311533
q1719_label	2.762e-01	3.919e-01	0.705	0.480986
factor(q20_01_1)2	5.214e-01	2.725e-01	1.913	0.055690 .
factor(q20_01_1)3	4.923e-01	3.977e-01	1.238	0.215777
factor(q20_01_1)4	-1.104e+00	5.346e-01	-2.064	0.038979 *
factor(q20_01_1)5	-1.457e+00	1.084e+00	-1.344	0.178961
factor(q20_02_1)2	1.784e-03	3.321e-01	0.005	0.995714
factor(q20_02_1)3	3.907e-01	5.117e-01	0.763	0.445223
factor(q20_02_1)4	-1.051e+00	7.558e-01	-1.391	0.164195
factor(q20_02_1)5	1.140e+01	6.001e+02	0.019	0.984837
q22	1.391e-01	3.466e-02	4.012	6.03e-05 ***
q23	1.190e-01	5.058e-02	2.353	0.018617 *
q24	-1.675e-02	3.689e-02	-0.454	0.649852
q25	-5.686e-03	2.508e-02	-0.227	0.820622
q26	-3.543e-03	4.226e-02	-0.084	0.933177



```

factor(q27_1)2    -2.557e-02  3.599e-01  -0.071  0.943367
factor(q27_1)3     9.567e-01  3.512e-01   2.724  0.006450 **
factor(q27_1)4     2.634e+00  4.171e-01   6.315  2.71e-10 ***
factor(q27_1)5     4.458e+00  9.767e-01   4.564  5.02e-06 ***
---
Signif. codes:  0 '***' 0.001 '**' 0.01 '*' 0.05 '.' 0.1 ' ' 1

```

(Dispersion parameter for binomial family taken to be 1)

```

Null deviance: 1261.72  on 1003  degrees of freedom
Residual deviance:  879.15  on  951  degrees of freedom
AIC: 852.73

```

Number of Fisher Scoring iterations: 13


```

#Decision tree
library(rpart)
library(rpart.plot)

tree_model <- rpart(
  factor(q28_YN)~
    factor(q1)+
    factor(q2_rr)+
    factor(q3)+
    factor(q4)+
    q5_1+
    q6+
    q7+
    q10+
    factor(q11)+
    q1719_label+
    factor(q20_01_1)+
    factor(q20_02_1)+
    q22+ q23+ q24+ q25+ q26+
    factor(q27_1),data = DB.csv, method = "class",weights = weight)

rpart.plot(tree_model,
  type = 3,
  extra = 106,
  under = TRUE,
  faclen = 0,
  fallen.leaves = TRUE,
  box.palette = "RdYlGn",
  shadow.col = "gray",
  cex = 0.75)

```



```
# glmnet and xgboost
library(glmnet)
```

Loading required package: Matrix

Loaded glmnet 4.1-8

```
x <- model.matrix(factor(q28_YN)~
  factor(q1)+
  factor(q2_rr)+
  factor(q3)+
  factor(q4)+
  q5_1+
  q6+
  q7+
  q10+
  factor(q11)+
  q1719_label+
  factor(q20_01_1)+
  factor(q20_02_1)+
  q22+ q23+ q24+ q25+ q26+
  factor(q27_1), data = DB.csv)[, -1]
y <- as.factor(DB.csv$q28_YN)
glmnet_model <- cv.glmnet(x, y, family = "binomial", alpha = 1)
glmnet_model
```

Call: `cv.glmnet(x = x, y = y, family = "binomial", alpha = 1)`

Measure: Binomial Deviance

	Lambda	Index	Measure	SE	Nonzero
min	0.00803	29	1.068	0.03174	31
1se	0.03906	12	1.096	0.02729	6

```
library(xgboost)
```

Attaching package: 'xgboost'

The following object is masked from 'package:dplyr':

slice

```
xgb_data <- xgb.DMatrix(data = x, label = as.numeric(y) - 1, weight = DB.csv$weight)
xgb_model <- xgboost(data = xgb_data, objective = "binary:logistic", nrounds = 100)
```

```
[1] train-logloss:0.574666
[2] train-logloss:0.493215
[3] train-logloss:0.429208
[4] train-logloss:0.389516
[5] train-logloss:0.358326
[6] train-logloss:0.330614
[7] train-logloss:0.314755
[8] train-logloss:0.299092
[9] train-logloss:0.284489
[10]   train-logloss:0.270964
[11]   train-logloss:0.261739
[12]   train-logloss:0.249105
[13]   train-logloss:0.241648
[14]   train-logloss:0.232529
[15]   train-logloss:0.225461
[16]   train-logloss:0.216504
[17]   train-logloss:0.213187
[18]   train-logloss:0.210046
[19]   train-logloss:0.205544
[20]   train-logloss:0.201221
[21]   train-logloss:0.195001
[22]   train-logloss:0.192773
[23]   train-logloss:0.188282
[24]   train-logloss:0.185185
[25]   train-logloss:0.180532
[26]   train-logloss:0.175191
[27]   train-logloss:0.169632
[28]   train-logloss:0.162943
[29]   train-logloss:0.160096
[30]   train-logloss:0.155941
[31]   train-logloss:0.152498
[32]   train-logloss:0.150827
[33]   train-logloss:0.148601
[34]   train-logloss:0.146105
[35]   train-logloss:0.142850
[36]   train-logloss:0.138865
[37]   train-logloss:0.137224
[38]   train-logloss:0.135617
[39]   train-logloss:0.134019
[40]   train-logloss:0.132901
[41]   train-logloss:0.128400
[42]   train-logloss:0.126397
[43]   train-logloss:0.123882
```


[44] train-logloss:0.119471  
[45] train-logloss:0.117321  
[46] train-logloss:0.115881  
[47] train-logloss:0.114528  
[48] train-logloss:0.112168  
[49] train-logloss:0.110848  
[50] train-logloss:0.110056  
[51] train-logloss:0.109196  
[52] train-logloss:0.107770  
[53] train-logloss:0.105331  
[54] train-logloss:0.104177  
[55] train-logloss:0.103222  
[56] train-logloss:0.102752  
[57] train-logloss:0.100455  
[58] train-logloss:0.099342  
[59] train-logloss:0.097922  
[60] train-logloss:0.096223  
[61] train-logloss:0.095029  
[62] train-logloss:0.093646  
[63] train-logloss:0.091576  
[64] train-logloss:0.088959  
[65] train-logloss:0.087818  
[66] train-logloss:0.087059  
[67] train-logloss:0.085210  
[68] train-logloss:0.083371  
[69] train-logloss:0.081275  
[70] train-logloss:0.079933  
[71] train-logloss:0.079209  
[72] train-logloss:0.078521  
[73] train-logloss:0.078028  
[74] train-logloss:0.076624  
[75] train-logloss:0.074534  
[76] train-logloss:0.072216  
[77] train-logloss:0.070940  
[78] train-logloss:0.070147  
[79] train-logloss:0.069122  
[80] train-logloss:0.068415  
[81] train-logloss:0.067022  
[82] train-logloss:0.065554  
[83] train-logloss:0.064586  
[84] train-logloss:0.063931  
[85] train-logloss:0.063062  
[86] train-logloss:0.061561  
[87] train-logloss:0.060931  
[88] train-logloss:0.060578  
[89] train-logloss:0.059746  
[90] train-logloss:0.058945  
[91] train-logloss:0.058250  
[92] train-logloss:0.057910  
[93] train-logloss:0.057316  
[94] train-logloss:0.056885  
[95] train-logloss:0.056308  
[96] train-logloss:0.055865  
[97] train-logloss:0.054884

```
[98]    train-logloss:0.053853
[99]    train-logloss:0.052588
[100]   train-logloss:0.052071
```

```
importance_matrix <- xgb.importance(model = xgb_model)
importance_matrix
```

	Feature	Gain	Cover	Frequency
1:	q7	0.1006014818	0.0869011388	0.1144475921
2:	q22	0.0997652266	0.0879794214	0.1014164306
3:	factor(q27_1)2	0.0960891679	0.0313989583	0.0147308782
4:	q24	0.0762530783	0.0696095066	0.0787535411
5:	q6	0.0751986631	0.1091082918	0.1184135977
6:	q25	0.0513265858	0.0610713404	0.0770538244
7:	q10	0.0498453929	0.0366651821	0.0611898017
8:	q23	0.0457890618	0.0616189312	0.0657223796
9:	q26	0.0445914564	0.0415649448	0.0634560907
10:	factor(q27_1)4	0.0360202125	0.0544773962	0.0209631728
11:	factor(q27_1)5	0.0301873688	0.0585528482	0.0158640227
12:	factor(q27_1)3	0.0278206632	0.0141968799	0.0215297450
13:	factor(q3)10	0.0261380393	0.0177619363	0.0073654391
14:	factor(q3)15	0.0245024601	0.0095432797	0.0084985836
15:	q5_1	0.0204062232	0.0202677462	0.0169971671
16:	factor(q4)3	0.0197054761	0.0106482746	0.0300283286
17:	factor(q2_rr)6	0.0165076672	0.0211964073	0.0079320113
18:	factor(q1)2	0.0162385112	0.0116488761	0.0266288952
19:	factor(q3)18	0.0146431542	0.0248320604	0.0062322946
20:	factor(q11)1	0.0146411486	0.0085891738	0.0050991501
21:	factor(q2_rr)4	0.0142578982	0.0049844483	0.0090651558
22:	factor(q3)2	0.0104549392	0.0119665244	0.0096317280
23:	factor(q2_rr)3	0.0103919175	0.0084545116	0.0164305949
24:	factor(q2_rr)2	0.0089299687	0.0079951363	0.0147308782
25:	factor(q4)2	0.0065179947	0.0058619459	0.0090651558
26:	factor(q2_rr)5	0.0064266914	0.0063681736	0.0073654391
27:	factor(q3)16	0.0063710811	0.0065533432	0.0033994334
28:	factor(q20_01_1)2	0.0057090976	0.0130485028	0.0084985836
29:	factor(q4)4	0.0055326696	0.0061001275	0.0107648725
30:	factor(q20_01_1)5	0.0051199941	0.0005388135	0.0005665722
31:	factor(q3)14	0.0046382541	0.0084937609	0.0033994334
32:	q1719_label1	0.0045868711	0.0088767414	0.0062322946
33:	factor(q3)9	0.0039125798	0.0185257093	0.0062322946
34:	factor(q20_01_1)3	0.0037028945	0.0114151481	0.0062322946
35:	factor(q20_01_1)4	0.0036669837	0.0021630422	0.0011331445
36:	factor(q20_02_1)3	0.0031811496	0.0064089829	0.0039660057
37:	factor(q20_02_1)2	0.0028894211	0.0019694675	0.0045325779
38:	factor(q3)3	0.0025281345	0.0045682236	0.0033994334
39:	factor(q11)2	0.0017416238	0.0094845525	0.0033994334
40:	factor(q3)4	0.0010497378	0.0028209978	0.0022662890
41:	factor(q3)13	0.0005684266	0.0059322212	0.0016997167
42:	factor(q3)11	0.0004391047	0.0016507497	0.0011331445
43:	factor(q3)7	0.0004077576	0.0027097133	0.0016997167
44:	factor(q3)17	0.0003570660	0.0023370553	0.0011331445
45:	factor(q3)12	0.0003467037	0.0031395131	0.0016997167

```
xgb.plot.importance(importance_matrix)
```



```
index.q28_1 <- match("q28_1", colnames(DB.csv))
index.q28_3 <- match("q28_3", colnames(DB.csv))
index.q29_1 <- match("q29_1", colnames(DB.csv))
index.q29_3 <- match("q29_3", colnames(DB.csv))
```

```
q28.label <- as.factor(apply(
  DB.csv[, index.q28_1:index.q28_3],
  MARGIN = 1,
  function(row){
    return(paste0(row, collapse = ""))
  })
unique(q28.label)
```

```
[1] 000 100 010 111 110 101 011 001
Levels: 000 001 010 011 100 101 110 111
```

```
q29.label <- as.factor(apply(
  DB.csv[, index.q29_1:index.q29_3],
  MARGIN = 1,
  function(row){
    return(paste0(row, collapse = ""))
  })
unique(q29.label)
```

```
[1] 000 111 011 101 010 100 001 110
Levels: 000 001 010 011 100 101 110 111
```

```
q2829.label <- as.factor(apply(
  DB.csv[, c(index.q28_1:index.q28_3, index.q29_1:index.q29_3)],
  MARGIN = 1,
  function(row){
    return(paste0(row, collapse = ""))
  })
```

```

}))
unique(q2829.label)

[1] 000000 100111 010011 111111 110101 110010 010100 110111 110001 010101
[11] 100001 100101 010111 110110 010001 100010 101001 100011 011001 110011
[21] 111110 010010 111100 111011 110100 011011 100100 111101 011010 100110
[31] 010110 001010 111001 011101 011100 001111 101011 111010 001011 001001
[41] 001101 101101 101010 011111
44 Levels: 000000 001001 001010 001011 001101 001111 010001 010010 ... 111111

table(q28.label)

```

```

q28.label
000 001 010 011 100 101 110 111
301 8 195 10 98 6 355 31

```

```
table(q29.label)
```

```

q29.label
000 001 010 011 100 101 110 111
301 189 63 70 24 197 18 142

```

```
table(q2829.label)
```

```

q2829.label
000000 001001 001010 001011 001101 001111 010001 010010 010011 010100 010101
    301      2      3      1      1      1      68      31      24      9      35
010110 010111 011001 011010 011011 011100 011101 011111 100001 100010 100011
    5     23     2     2     2     1     2     1     37     10     5
100100 100101 100110 100111 101001 101010 101011 101101 110001 110010 110011
    8     21     3     14     2     1     2     1     74     15     35
110100 110101 110110 110111 111001 111010 111011 111100 111101 111110 111111
    5    133     6    87     4     1     1     1     4     4     16

```

預期 28 題有選三 (發文等抵制行為) 的抵制程度較高

法一: 1,0 法二: 選項一二合併 vs. 有選三 (11,10,01,00)

第 29 題:

分成: 1 自己, 23 至少選一, 45 至少選一

抵制程度 ~ 其他因素關聯分析

## Canonical analysis and PCA

```

library(FactoMineR)
library(factoextra)
boycott <- subset(DB.csv, q28_YN == 1)
# 缺失值轉 0

boycott[,c('q30_1','q32_1','q35_1')] <- lapply(boycott[, c('q30_1','q32_1','q35_1')], as.numeric)
y <- boycott[,c('q30_1','q32_1','q35_1')]

boycott$q28_1_2 <- ifelse(boycott$q28_1==1 | boycott$q28_2==1,1,0)
boycott$q29_1_2_inter<-boycott$q29_1*boycott$q29_2

```

```
boycott[, c("q28_1_2", "q28_3", "q29_1", "q29_2", "q29_3")] <- lapply(boycott[, c("q28_1_2", "q28_3", "q29_1", "q29_2", "q29_3")],
y <- boycott[, c('q30_1', 'q32_1', 'q35_1')])
```

```
cca <-cancor(x,y)
# 典型相關係數
cca$cor
```

```
x_loadings <-cor(x,as.matrix(x)%%% cca$xcoef)
y_loadings <-cor(y,as.matrix(y)%%% cca$ycoef)
x_loadings[,c(1,2)]
```

```
y_loadings[,c(1,2)]
```

32



```
# 第一典型變數與 q22,q33_1 高度相關,q2(負),q4,q10,q23,q24,q26,q29_1,q29_3,q31_1,q36_1,q29_1_3_inter 中度相
# 第一典型變數與 q35_1 高度相關,q30_1 中度相關
# 越常看到別人在網路上的攻擊行為，抵制行為程度越高。如果認為抵制行為很重要，抵制程度也會比較高。抵制程度與抵制不
```

```
# 自我相關係數
```

```
round((colSums(x_loadings^2)[1:2]/4),4)
```

```
[1] 0.7328 0.3660
```

```
round((colSums(y_loadings^2)[1:2]/4),4)
```

```
[1] 0.3172 0.2360
```

```
# 典型相關係數平方
```

```
num<-round(cca$cor^2,4)[1:2]
```

```
round((colSums(x_loadings^2)[1:2]/4)*num,4)
```

```
[1] 0.2212 0.0337
```

```
round((colSums(y_loadings^2)[1:2]/4)*num,4)
```

```
[1] 0.0958 0.0217
```

```
# 第一典型變數能解釋約 9.67% 的預測變數變異、7.42% 的準則變數變異
```

```
library(Rtsne)
```

```
library(ggpubr)
```

```
set.seed(2024)
```

```
tsne_result <- Rtsne(DB.csv[, -c(45,64)], dims = 2)
```

```
tsne_df <- as.data.frame(tsne_result$Y)
```


```
tsne_df$cluster <- q29.label
```

```
centroids <- tsne_df %>%
```

```
  group_by(cluster) %>%
```

```
  summarize(V1 = mean(V1), V2 = mean(V2), .groups = 'drop')
```

```
ggscatter(data = tsne_df, x = "V1", y = "V2",
  size = 1, color = "cluster", # 使用 cluster 列进行颜色映射
  ellipse = TRUE,
  ellipse.type = "convex",
  repel = TRUE, # 防止标签重叠
  title = "t-SNE Visualization labelled by DBscan",
  xlab = "Dimension 1", ylab = "Dimension 2") +
  scale_color_discrete()+
  geom_text(data = centroids, aes(x = V1, y = V2, label = cluster),
    vjust = -1, size = 8, color = "black")+
  theme(legend.position = "right")
```



```
ggplot(data = tsne_df)+
  geom_point(aes(x=V1, y=V2, color = as.factor(cluster)))+
  labs(title = "t-SNE Visualization labelled by DBscan",
       x = "Dimension 1",
       y = "Dimension 2",
       color = "Number") +
  geom_text(data = centroids, aes(x = V1, y = V2, label = cluster),
           vjust = -1, size = 10, color = "black")+
  theme(legend.position = "right")
```

