

[toc]

# 课上测试

## 作业题目：Linux命令实践

### 学习Linux核心命令

- ls
- who
- pwd
- cd
- man
- whereis
- which
- find
- locate
- grep

### 作业要求（9'）

- 参考课件，针对上面核心命令重复老师的演示内容（3'）
- 选择自己习惯的 AI 工具，针对上面核心命令，让 AI 给自己生成至少例子，然后自己进行验证，总结（3'）
- 让 AI工具推荐一些重要命令，然后选择自己认为会高频应用的至少 3个命令（重点推荐 echo，od，sort，bc，ls）进行自主深入学习，每个命令不少于 5 个例子，提交验证，实践过程和总结（3'）

### 作业提交要求（1'）

0. 记录实践过程和 AI 问答过程，尽量不要截图，给出文本内容
1. [github链接](#)
2. (必做)提交作业 markdown文档，命名为“学号-姓名-作业题目.md”
3. (必做)提交作业 markdown文档转成的 PDF 文件，命名为“学号-姓名-作业题目.pdf”

### 针对上面核心命令重复老师的演示内容：

- **ls**实践内容

```
root@Youer:~# ls
Desktop      GmSSL      Templates  client     main       snap       testmainso
Downloads    Pictures    cheat      homework   server     socket
root@Youer:~# ls .
Desktop      GmSSL      Templates  client     main       snap       testmainso
Downloads    Pictures    cheat      homework   server     socket
root@Youer:~# ls -a
.              .bashrc    .dotnet    .motd_shown  .vscode-server
Pictures       homework   socket
```

```
..          .cache  .head.h.swo  .profile      Desktop
Templates  main      testmainso
.Xauthority .cgdb    .head.h.swp  .python_history Downloads      cheat
server
.bash_history .ddd      .lessht      .viminfo      GmSSL         client
snap
root@Youer:~# ls -l
total 92
lrwxrwxrwx 1 root root 13 Sep 2 2022 Desktop -> /root/Desktop
lrwxrwxrwx 1 root root 15 Sep 2 2022 Downloads -> /root/Downloads
drwxr-xr-x 10 root root 4096 Sep 8 14:45 GmSSL
lrwxrwxrwx 1 root root 14 Sep 2 2022 Pictures -> /root/Pictures
lrwxrwxrwx 1 root root 15 Sep 2 2022 Templates -> /root/Templates
drwxr-xr-x 3 root root 4096 Sep 29 2022 cheat
-rwxr-xr-x 1 root root 16472 Dec 14 2022 client
drwxr-xr-x 2 root root 4096 Sep 3 2022 homework
-rwxr-xr-x 1 root root 16048 Dec 4 2022 main
-rwxr-xr-x 1 root root 16464 Dec 14 2022 server
drwxr-xr-x 4 root root 4096 Sep 2 2022 snap
drwxr-xr-x 2 root root 4096 Sep 2 2022 socket
-rwxr-xr-x 1 root root 16160 Dec 4 2022 testmainso
```

- who 实践内容

```
root@Youer:~# who
root@Youer:~# whoami
root
root@Youer:~# who -a
```

- pwd 实践内容

```
root@Youer:~# pwd
/root
root@Youer:~# cd GmSSL
root@Youer:~/GmSSL# pwd
/root/GmSSL
```

- cd 实践内容

```
root@Youer:~/GmSSL# cd /root/GmSSL
root@Youer:~/GmSSL# cd .
root@Youer:~/GmSSL# cd ..
root@Youer:~# cd -
/root/GmSSL
root@Youer:~/GmSSL# cd ~
root@Youer:~# cd -
```

```
/root/GmSSL  
root@Youer:~/GmSSL# cd ..
```

- **man** 实践内容

```
root@Youer:~# man man  
root@Youer:~# man printf  
root@Youer:~# man 3 printf  
root@Youer:~# man -k sort  
alphasort (3)          - scan a directory for matching entries  
apt-sortpkgs (1)       - Utility to sort package index files  
bsearch (3)           - binary search of a sorted array  
bunzip2 (1)           - a block-sorting file compressor, v1.0.8  
bzip2 (1)             - a block-sorting file compressor, v1.0.8  
comm (1)              - compare two sorted files line by line  
qsort (3)             - sort an array  
qsort_r (3)           - sort an array  
sort (1)              - sort lines of text files  
Sort::Naturally (3pm) - - sort lexically, but sort numeral parts numerically  
tsort (1)             - perform topological sort  
versionsort (3)       - scan a directory for matching entries  
XConsortium (7)       - X Consortium information  
root@Youer:~# man -k sort |grep 3  
alphasort (3)          - scan a directory for matching entries  
bsearch (3)           - binary search of a sorted array  
qsort (3)             - sort an array  
qsort_r (3)           - sort an array  
Sort::Naturally (3pm) - - sort lexically, but sort numeral parts numerically  
versionsort (3)       - scan a directory for matching entries  
root@Youer:~# man -f qsort  
qsort (3)             - sort an array
```

- **whereis** 实践内容

```
root@Youer:~# whereis ls  
ls: /usr/bin/ls /usr/share/man/man1/ls.1.gz
```

- **which** 实践内容

```
root@Youer:~# which ls  
/usr/bin/ls
```

- **find** 实践内容

```
root@Youer:~# find main
main
```

- **locate** 实践内容

```
root@Youer:~# locate GmSSL
/mnt/c/Users/xlm20/Downloads/GmSSL-master.zip
/root/GmSSL
/root/GmSSL/.git
/root/GmSSL/.github
/root/GmSSL/.gitignore
.....
```

- **grep** 实践内容

```
root@Youer:~# grep -nr O_RDWR /usr/include
/usr/include/asm-generic/fcntl.h:22:#define O_RDWR          00000002
/usr/include/linux/dma-heap.h:18:/* Valid FD_FLAGS are O_CLOEXEC, O_RDONLY,
O_WRONLY, O_RDWR */
/usr/include/scsi/cxlflash_ioctl.h:65: * and O_RDWR flags defined in the
fcntl.h header file.
/usr/include/drm/drm.h:839:#define DRM_RDWR O_RDWR
/usr/include/x86_64-linux-gnu/bits/fcntl-linux.h:45:#define O_RDWR
02
```

使用Kimi针对上面核心命令，让AI生成至少例子，然后进行验证，总结：

- 与AI的对话：
  - [对话链接](#)
  - 对话内容如下: User:

学习Linux核心命令

- ls
- who
- pwd
- cd
- man
- whereis
- which
- find
- locate
- grep

针对以上命令，请为我生成一些例子

Kimi: 当然，以下是针对你列出的Linux核心命令的一些示例：

### 1. `ls`：列出目录内容

```
ls          # 列出当前目录下的文件和文件夹
ls -l       # 以长格式列出详细信息
ls -a       # 显示所有文件，包括隐藏文件
ls /path/to/dir # 列出指定目录下的文件和文件夹
```

### 2. `who`：显示当前登录用户的信息

```
who          # 显示当前登录的用户列表
who -a       # 显示所有登录用户的信息
who -m       # 显示最后登录的用户信息
```

### 3. `pwd`：显示当前工作目录的路径

```
pwd          # 显示当前目录的完整路径
```

### 4. `cd`：改变当前目录

```
cd           # 切换到用户的主目录
cd /path/to/dir # 切换到指定的目录
cd ..        # 切换到当前目录的父目录
```

### 5. `man`：查看命令的手册页

```
man ls       # 查看 `ls` 命令的手册页
man 5 passwd  # 查看与密码文件相关的手册页（第5节）
```

### 6. `whereis`：定位二进制、源和手册页文件的位置

```
whereis java # 查找 `java` 命令的位置
whereis ssh   # 查找 `ssh` 相关的文件
```

### 7. `which`：在系统路径中查找执行文件

```
which python # 查找 `python` 命令的路径
which vim     # 查找 `vim` 编辑器的路径
```

## 8. `find`: 在文件系统中搜索文件

```
find / -name "filename" # 在整个文件系统中搜索名为 "filename" 的文件
find /home -type d -name "*logs*" # 在 /home 目录下搜索所有名为
"*logs*" 的目录
```

## 9. `locate`: 使用数据库快速查找文件

```
locate filename # 查找名为 "filename" 的文件
locate "*.txt" # 查找所有扩展名为 ".txt" 的文件
```

## 10. `grep`: 搜索文件内容

```
```bash
grep "pattern" filename # 在 "filename" 文件中搜索 "pattern"
grep -r "pattern" /path/to/dir # 在指定目录及其子目录中递归搜索
"pattern"
```
```

请注意，这些命令可能需要根据你的具体需求进行调整。例如，你可能需要指定正确的文件名或路径。此外，一些命令（如 `man` 和 `grep`）有大量的选项，可以进一步定制它们的输出和行为。

- 我的验证:

### 1. `ls`:

```
root@Youer:~# ls
Desktop    GmSSL      Templates  client     main      snap      testmainso
Downloads  Pictures   cheat      homework   server    socket
root@Youer:~# ls -l
total 92
lrwxrwxrwx 1 root root    13 Sep  2  2022 Desktop -> /root/Desktop
lrwxrwxrwx 1 root root    15 Sep  2  2022 Downloads -> /root/Downloads
drwxr-xr-x 10 root root 4096 Sep  8 14:45 GmSSL
lrwxrwxrwx 1 root root    14 Sep  2  2022 Pictures -> /root/Pictures
lrwxrwxrwx 1 root root    15 Sep  2  2022 Templates -> /root/Templates
drwxr-xr-x 3 root root 4096 Sep 29  2022 cheat
-rwxr-xr-x 1 root root 16472 Dec 14  2022 client
drwxr-xr-x 2 root root 4096 Sep  3  2022 homework
-rwxr-xr-x 1 root root 16048 Dec  4  2022 main
-rwxr-xr-x 1 root root 16464 Dec 14  2022 server
drwxr-xr-x 4 root root 4096 Sep  2  2022 snap
drwxr-xr-x 2 root root 4096 Sep  2  2022 socket
-rwxr-xr-x 1 root root 16160 Dec  4  2022 testmainso
root@Youer:~# ls -a
```

```
.          .bashrc  .dotnet    .motd_shown  .vscode-server
Pictures  homework  socket
..         .cache  .head.h.swo .profile      Desktop
Templates main      testmainso
.Xauthority .cgdb    .head.h.swp .python_history Downloads
cheat      server
.bash_history .ddd     .lessht     .viminfo      GmSSL
client     snap
root@Youer:~# ls /path/to/dir
ls: cannot access '/path/to/dir': No such file or directory
```

## 2. who:

```
root@Youer:~# who
root@Youer:~# who -a
root@Youer:~# who -m
```

## 3. pwd:

```
root@Youer:~# cd GmSSL
root@Youer:~/GmSSL# cd build
root@Youer:~/GmSSL/build# pwd
/root/GmSSL/build
```

## 4. cd:

```
root@Youer:~/GmSSL/build# cd ..
root@Youer:~/GmSSL# cd
root@Youer:~# cd /root/GmSSL/build
root@Youer:~/GmSSL/build#
```

## 5. man:

### 1. man ls: (省略了部分内容)

```
LS(1)                                                    User Commands
LS(1)

NAME
    ls - list directory contents

SYNOPSIS
    ls [OPTION]... [FILE]...

DESCRIPTION
    List information about the FILES (the current directory
```

```
by default). Sort entries alphabeti-
cally if none of -cftuvSUX nor --sort is specified.

Mandatory arguments to long options are mandatory for short
options too.

-a, --all
    do not ignore entries starting with .

-A, --almost-all
    do not list implied . and ..

--author
    with -l, print the author of each file

-b, --escape
    print C-style escapes for nongraphic characters

--block-size=SIZE
Manual page ls(1) line 1 (press h for help or q to quit)
```

## 2. man 5 passwd: (省略了部分内容)

```
PASSWD(5)                                File Formats and Conversions
PASSWD(5)

NAME
    passwd - the password file

DESCRIPTION
    /etc/passwd contains one line for each user account, with
    seven fields delimited by colons
    (":"). These fields are:

    • login name

    • optional encrypted password

    • numerical user ID

    • numerical group ID

    • user name or comment field

    • user home directory

    • optional user command interpreter

    If the password field is a lower-case "x", then the
    encrypted password is actually stored in the
    shadow(5) file instead; there must be a corresponding line
    in the /etc/shadow file, or else the
```



```
user account is invalid.
```

```
Manual page passwd(5) line 1 (press h for help or q to quit)
```

## 6. whereis:

```
root@Youer:~# whereis java
java: /usr/share/java
root@Youer:~# whereis ssh
ssh: /usr/bin/ssh /etc/ssh /usr/share/man/man1/ssh.1.gz
```

## 7. which:

```
root@Youer:~# which python
root@Youer:~# which vim
/usr/bin/vim
root@Youer:~# which python3
/usr/bin/python3
```

## 8. find:

```
root@Youer:~# find / -name "testmainso"
/root/testmainso
find: File system loop detected; '/mnt/wslg/distro' is part of the same
file system loop as '/'.// 表示 /mnt/wslg/distro 指向了一个循环挂载点, 这
通常发生在挂载配置错误时。
find: '/mnt/d/$RECYCLE.BIN/S-1-5-18': Permission denied // 表明没有足够
的权限来访问某些目录
find: '/mnt/d/$RECYCLE.BIN/S-1-5-21-2139585154-949242277-2800085354-
500': Permission denied
root@Youer:~# find /home -type d -name "*logs*"
root@Youer:~#
```

## 9. locate:

```
root@Youer:~# locate testmainso
/root/testmainso
root@Youer:~# locate ".c"
/etc/adduser.conf
/etc/apg.conf
/etc/appstream.conf
/etc/brltty.conf
/etc/ca-certificates.conf
/etc/ca-certificates.conf.dpkg-old
```

```
/etc/debconf.conf
/etc/deluser.conf
```

## 10. grep:

```
...
root@Youer:~# grep "argc" /root/GmSSL/tools/sm4_ctr_sm3_hmac.c
int sm4_ctr_sm3_hmac_main(int argc, char **argv)
    argc--;
    if (argc < 1) {
    while (argc > 0) {
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
        if (--argc < 1) goto bad;
    }
    argc--;
root@Youer:~# grep -r "argc" /root/GmSSL/tools
/root/GmSSL/tools/reqparse.c:int reqparse_main(int argc, char **argv)
/root/GmSSL/tools/reqparse.c:    argc--;
/root/GmSSL/tools/reqparse.c:    while (argc > 0) {
/root/GmSSL/tools/reqparse.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/reqparse.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/reqparse.c:        argc--;
/root/GmSSL/tools/sm4_cbc.c:int sm4_cbc_main(int argc, char **argv)
/root/GmSSL/tools/sm4_cbc.c:    argc--;
/root/GmSSL/tools/sm4_cbc.c:    if (argc < 1) {
/root/GmSSL/tools/sm4_cbc.c:    while (argc > 0) {
/root/GmSSL/tools/sm4_cbc.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm4_cbc.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm4_cbc.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm4_cbc.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm4_cbc.c:        argc--;
/root/GmSSL/tools/sm2decrypt.c:int sm2decrypt_main(int argc, char **argv)
/root/GmSSL/tools/sm2decrypt.c:    argc--;
/root/GmSSL/tools/sm2decrypt.c:    if (argc < 1) {
/root/GmSSL/tools/sm2decrypt.c:    while (argc > 0) {
/root/GmSSL/tools/sm2decrypt.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm2decrypt.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm2decrypt.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm2decrypt.c:        if (--argc < 1) goto bad;
/root/GmSSL/tools/sm2decrypt.c:        argc--;
...

```

- 总结: man命令是自学命令的神器, 可以查看命令的文档。who命令显示当前登录用户信息。ls、pwd、cd命令都与目录有关, ls用于列出目录内容, pwd用于打印当前工作目录路径, cd则用于改变当前目录。whereis、which、find、locate 和 grep 都是 Linux 系统中用于查找的工具, 其中whereis用于搜索二进

制、源和手册页文件的位置，比如whereis java；which用于搜索可执行文件的路径，比如which python；find在文件系统中递归搜索文件和目录，而locate使用数据库快速搜索文件路径，而grep用于搜索文件中的文本内容。

让Kimi推荐一些重要命令，然后选择会高频应用的3个命令echo、sort、sed进行自主深入学习，每个命令不少于5个例子，提交验证，实践过程和总结

- AI的推荐

- [对话链接](#)

- 对话内容 User: 请为我推荐Linux的高频应用的一些重要命令并给出至少五个示例

Kimi: Linux 系统以其强大的命令行界面而闻名，许多高频应用都可以通过命令行高效地完成。以下是一些重要的命令及其示例：

1. **grep**：搜索文件内容

- 查找包含特定文本的行：

```
grep "text" filename
```

- 在所有 .txt 文件中递归搜索包含 "text" 的行：

```
grep -r "text" /path/to/directory/*.txt
```

2. **cp**：复制文件或目录

- 复制单个文件：

```
cp source.txt destination.txt
```

- 复制整个目录（递归复制）：

```
cp -r source_directory destination_directory
```

3. **mv**：移动或重命名文件/目录

- 重命名文件：

```
mv oldname.txt newname.txt
```

- 移动文件到另一个目录：

```
mv filename.txt /path/to/directory/
```

#### 4. **chmod**: 更改文件或目录的权限

- 给文件所有者添加写权限:

```
chmod u+w filename
```

- 将目录设置为只有所有者可读写执行:

```
chmod 700 directoryname
```

#### 5. **tar**: 打包和压缩文件

- 创建一个压缩包:

```
tar -czvf archive.tar.gz /path/to/directory
```

- 解压一个压缩包:

```
tar -xzvf archive.tar.gz
```

#### 6. **wget**: 从网络下载文件

- 下载一个文件:

```
wget http://example.com/file.txt
```

- 从命令行下载并保存为特定文件名:

```
wget -O newfilename http://example.com/file.txt
```

#### 7. **ssh**: 安全地登录到远程服务器

- 登录到远程服务器:

```
ssh username@remotehost
```

- 使用特定端口登录：

```
ssh -p port_number username@remotehost
```

#### 8. **scp**：安全地复制文件到远程服务器

- 复制文件到远程服务器：

```
scp localfile.txt username@remotehost:/path/to/destination/
```

- 从远程服务器复制文件到本地：

```
scp username@remotehost:/path/to/remotefile.txt /local/directory
```

#### 9. **df**：报告文件系统的磁盘空间使用情况

- 显示所有文件系统的磁盘空间使用情况：

```
df -h
```

- 只显示特定文件系统的磁盘空间使用情况：

```
df -h /dev/sda1
```

#### 10. **top**：实时显示系统进程

- 启动 **top** 命令查看系统进程：

```
top
```

- 显示特定用户的进程：

```
top -u username
```

这些命令覆盖了文件操作、系统管理、网络操作等多个方面，是Linux用户日常工作中经常使用的命令。

User: 请在上述命令之外给我推荐Linux的高频应用的一些重要命令，每个命令不少于 5个例子

Kimi: 当然，除了你提到的命令外，Linux 还提供了许多其他高频使用的命令。以下是一些额外的重要命令及其使用示例：

### 1. `ls`：列出目录内容

- 列出当前目录下的文件和目录：

```
ls
```

- 以长格式列出详细信息：

```
ls -l
```

- 显示隐藏文件：

```
ls -a
```

- 递归列出所有子目录的内容：

```
ls -R
```

- 按修改时间排序：

```
ls -lt
```

### 2. `cd`：改变当前目录

- 切换到用户的主目录：

```
cd ~
```

- 切换到父目录：

```
cd ..
```

- 切换到特定目录：

```
cd /path/to/directory
```

- 切换到上一个工作目录：

```
cd -
```

### 3. **echo**：显示文本或变量内容

- 显示文本：

```
echo "Hello, World!"
```

- 显示变量的值：

```
echo $PATH
```

- 创建新文件并写入内容：

```
echo "Some text" > filename.txt
```

- 追加文本到现有文件：

```
echo "More text" >> filename.txt
```

### 4. **sed**：流编辑器，用于文本替换

- 替换文件中所有出现的 "old" 为 "new"：

```
sed 's/old/new/g' filename.txt
```

- 删除文件中的空行：

```
sed '/^$/d' filename.txt
```

- 仅对第3行进行替换：

```
sed '3s/old/new/' filename.txt
```

- 打印文件中第5行：

```
sed -n '5p' filename.txt
```

## 5. **awk**：模式扫描和处理语言

- 打印文件的每一行：

```
awk '{print}' filename.txt
```

- 打印文件的第一列：

```
awk '{print $1}' filename.txt
```

- 打印第2列到最后一列：

```
awk '{print $2,$3,$4,$5,$6,$7,$8,$9}' filename.txt
```

- 计算文件中行数：

```
awk 'END{print NR}' filename.txt
```

## 6. **sort**：对文本文件的行进行排序

- 默认按字典顺序排序：

```
sort filename.txt
```

- 按数字排序：

```
sort -n filename.txt
```

- 逆序排序：

```
sort -r filename.txt
```



- 按第2列排序:

```
sort -k2 filename.txt
```

## 7. **uniq**: 报告或忽略重复的行

- 删除文件中的重复行:

```
sort filename.txt | uniq
```

- 只显示重复的行:

```
sort filename.txt | uniq -d
```

- 显示重复行的次数:

```
sort filename.txt | uniq -cd
```

## 8. **head**: 输出文件的开头部分

- 显示文件的前10行:

```
head filename.txt
```

- 显示文件的前20行:

```
head -n 20 filename.txt
```

- 显示文件的前一个字符:

```
head -c 1 filename.txt
```

## 9. **tail**: 输出文件的末尾部分

- 显示文件的最后10行:

```
tail filename.txt
```

- 显示文件的最后20行:

```
tail -n 20 filename.txt
```

- 显示文件的最后100个字符:

```
tail -c 100 filename.txt
```

#### 10. **chmod**: 更改文件或目录的权限

- 为所有用户添加读权限:

```
chmod a+r filename.txt
```

- 设置文件的权限为只读:

```
chmod 444 filename.txt
```

- 为文件所有者添加执行权限:

```
chmod u+x filename.txt
```

这些命令在处理文件、文本和系统管理任务时非常有用。掌握这些命令可以帮助你更高效地使用 Linux 系统。

- 我重点学习的命令: **sort**、**echo**、**sed**:

- **echo**:

```
root@Youer:~# touch example.txt
root@Youer:~# echo "Hello, World!" > example.txt
root@Youer:~# echo "This is another line." >> example.txt
root@Youer:~# cat example.txt
Hello, World!
This is another line.
root@Youer:~# echo "Hello, World!"
Hello, World!
root@Youer:~# echo "New line \n and tab \t characters."
New line \n and tab \t characters.
root@Youer:~# echo $PATH
```

```

/usr/local/sbin:/usr/local/bin:/usr/sbin:/usr/bin:/sbin:/bin:/usr/games
:/usr/local/games:/usr/lib/wsl/lib:/mnt/c/ProgramFiles/CommonFiles/Oracle/Java/javapath:/mnt/c/Windows/system32:/mnt/c/Windows:/mnt/c/Windows/System32/Wbem:/mnt/c/Windows/System32/WindowsPowerShell/v1.0:/mnt/c/Windows/System32/OpenSSH:/mnt/c/WINDOWS/system32:/mnt/c/WINDOWS:/mnt/c/WINDOWS/System32/Wbem:/mnt/c/WINDOWS/System32/WindowsPowerShell/v1.0:/mnt/c/WINDOWS/System32/OpenSSH:/mnt/d/git/Git/cmd:/mnt/c/ProgramFiles/Java/jdk-17/bin:/mnt/c/ProgramFiles/NVIDIA Corporation/NVIDIA NvDLISR:/mnt/c/ProgramFiles(x86)/NVIDIA Corporation/PhysX/Common:/mnt/c/ProgramFiles/dotnet:/mnt/c/ProgramFiles(x86)/WindowsKits/10/WindowsPerformanceToolkit:/mnt/c/ProgramFiles(x86)/MicrosoftSQLServer/160/Tools/Binn:/mnt/c/ProgramFiles/MicrosoftSQLServer/160/Tools/Binn:/mnt/c/ProgramFiles/MicrosoftSQLServer/ClientSDK/ODBC/170/Tools/Binn:/mnt/c/ProgramFiles/MicrosoftSQLServer/160/DTS/Binn:/mnt/c/ProgramFiles(x86)/MicrosoftSQLServer/160/DTS/Binn:/mnt/d/tomcat/apache-tomcat-9.0.93/bin:/mnt/c/Users/xlm20/AppData/Local/Microsoft/WindowsApps:/mnt/c/Users/xlm20/AppData/Local/Programs/MicrosoftVSCode/bin:/mnt/d/xampp/php:/mnt/d/ËýΛçÈíËp/modelsim_ase/win32aloem:/mnt/d/ËýΛçÈíËp/shudian/modelsim_ase/win32aloem:/mnt/c/Users/xlm20/AppData/Local/GitHubDesktop/bin:/mnt/d/nmap:/mnt/c/Users/xlm20/.dotnet/tools:/mnt/d/JDK22/bin:/snap/bin

```

#### ◦ sort:

```

root@Youer:~# sort --help
Usage: sort [OPTION]... [FILE]...
or: sort [OPTION]... --files0-from=F
Write sorted concatenation of all FILE(s) to standard output.

With no FILE, or when FILE is -, read standard input.

Mandatory arguments to long options are mandatory for short options too.
Ordering options:

-b, --ignore-leading-blanks  ignore leading blanks
-d, --dictionary-order       consider only blanks and alphanumeric
                              characters
-f, --ignore-case             fold lower case to upper case characters
-g, --general-numeric-sort   compare according to general numerical
                              value
-i, --ignore-nonprinting     consider only printable characters
-M, --month-sort              compare (unknown) < 'JAN' < ... < 'DEC'
-h, --human-numeric-sort     compare human readable numbers (e.g., 2K
                              1G)
-n, --numeric-sort            compare according to string numerical value
-R, --random-sort             shuffle, but group identical keys. See
shuf(1)

```

```

--random-source=FILE    get random bytes from FILE
-r, --reverse           reverse the result of comparisons
--sort=WORD             sort according to WORD:
                        general-numeric -g, human-numeric -h,
month -M,
                        numeric -n, random -R, version -V
-V, --version-sort      natural sort of (version) numbers within
text

Other options:

--batch-size=NMERGE     merge at most NMERGE inputs at once;
                        for more use temp files
-c, --check, --check=diagnose-first  check for sorted input; do not
sort
-C, --check=quiet, --check=silent    like -c, but do not report first bad
line
--compress-program=PROG  compress temporaries with PROG;
                        decompress them with PROG -d
--debug                  annotate the part of the line used to sort,
                        and warn about questionable usage to
stderr
--files0-from=F          read input from the files specified by
                        NUL-terminated names in file F;
                        If F is - then read names from standard
input
-k, --key=KEYDEF         sort via a key; KEYDEF gives location and
type
-m, --merge              merge already sorted files; do not sort
-o, --output=FILE        write result to FILE instead of standard
output
-s, --stable             stabilize sort by disabling last-resort
comparison
-S, --buffer-size=SIZE   use SIZE for main memory buffer
-t, --field-separator=SEP use SEP instead of non-blank to blank
transition
-T, --temporary-directory=DIR use DIR for temporaries, not $TMPDIR or
/tmp;

                        multiple options specify multiple
directories
--parallel=N            change the number of sorts run concurrently
to N
-u, --unique              with -c, check for strict ordering;
                        without -c, output only the first of an
equal run
-z, --zero-terminated    line delimiter is NUL, not newline
--help                  display this help and exit
--version                output version information and exit

```

KEYDEF is F[.C][OPTS][,F[.C][OPTS]] for start and stop position, where F is a field number and C a character position in the field; both are origin 1, and the stop position defaults to the line's end. If neither -t nor -b is

```
in
effect, characters in a field are counted from the beginning of the
preceding
whitespace. OPTS is one or more single-letter ordering options
[bdfgiMhnRrV],
which override global ordering options for that key. If no key is
given, use
the entire line as the key. Use --debug to diagnose incorrect key
usage.
```

```
SIZE may be followed by the following multiplicative suffixes:
% 1% of memory, b 1, K 1024 (default), and so on for M, G, T, P, E, Z,
Y.
```

```
*** WARNING ***
```

```
The locale specified by the environment affects sort order.
Set LC_ALL=C to get the traditional sort order that uses
native byte values.
```

```
GNU coreutils online help: <https://www.gnu.org/software/coreutils/>
Report any translation bugs to <https://translationproject.org/team/>
Full documentation <https://www.gnu.org/software/coreutils/sort/>
or available locally via: info '(coreutils) sort invocation'
```

```
root@Youer:~# cat example.txt
Hello, World!
This is another line.
root@Youer:~# sort example.txt
Hello, World!
This is another line.
root@Youer:~# sort -n example.txt
Hello, World!
This is another line.
root@Youer:~# sort -r example.txt
This is another line.
Hello, World!
root@Youer:~# sort -k2 example.txt
Hello, World!
This is another line.
```

- **sed:**

```
root@Youer:~# cat example.txt
Hello, World!
This is another line.
root@Youer:~# sed 's/line/new_line/g' example.txt
Hello, World!
This is another new_line.
root@Youer:~# echo "" >> example.txt
root@Youer:~# cat example.txt
Hello, World!
This is another line.
```

```
root@Youer:~# sed '/^$/d' example.txt
Hello, World!
This is another line.
root@Youer:~# sed -n '2p' example.txt
This is another line.
root@Youer:~# sed '1s/o/xlm/' example.txt
Hellxlm, World!
This is another line.

root@Youer:~# cat example.txt
Hello, World!
This is another line.

root@Youer:~# sed -i '/^$/d' example.txt
root@Youer:~# cat example.txt
Hello, World!
This is another line.
root@Youer:~# sed -i 's/line/new_line/g' example.txt
root@Youer:~# cat example.txt
Hello, World!
This is another new_line.
root@Youer:~#
```

- 总结：echo、sort和sed都与文本处理有关，其中echo主要用于输出和插入数据，sort功能专一，用于排序，sed可以进行替换、删除特殊字符等复杂的文本处理。