



Usage Guideline

CBPRPlus-camt.029.001.09_ResolutionOf- Investigation

CBPRPlus SR2026 (Combined)

This document describes a usage guideline restricting the base message **MX camt.029.001.09**. You can also consult [this information online](#).

Published by Cross Border Payments and Reporting Plus (CBPR+) and generated by [MyStandards](#).

20 February 2026

Table of Contents

Message Functionality

3

1 Restriction summary

5

2 Structure

7

3 ISO 20022 Rules

11

4 Message Building Blocks

13

5 Message Components

26

6 Message Datatypes

262

Legal Notices

319

Message Functionality

This Usage Guideline is based on the camt.029.001.09 message definition. In addition, Cross Border Payments and Reporting Plus (CBPR+) has defined usage of BusinessApplicationHeaderV02 as mandatory. The following section will be dealing with the camt.029.001.09 only.

Overview

Principles:

1. AGENTS IDENTIFICATION - Textual Rules:

-> If BICFI is present, then (Name & Postal Address) is NOT allowed (ClearingSystemMemberIdentification and LEI may complement) - However, in case of conflicting information, the BICFI will always take precedence.

-> If BICFI is absent, (Name & Postal Address) OR [(Name & Postal Address) and ClearingSystemMemberIdentification] must be present.

Exception: If BICFI is absent, whenever Debtor Agent, Creditor Agent and all agents in between are located within the same country, the clearing code only may be used.

Note: "Assigner" and "Assignee" must be identified with a BICFI - other elements are optional.

2. Character Set:

All proprietary and Text fields EXCLUDING Name and Address for all actors and Related Remittance Information and Remittance are limited to the FIN-X-Character set.

All Name and Address for all actors, Related Remittance Information and Remittance Information (structured and unstructured), Email Address where included as part of a proxy element are extended to support the following additional characters:

```
!#$%&*='^_ '{|}~";<>@[\\]
```

< is replaced with <

> is replaced with >

E-mail address/Proxy fields are extended to support the following additional characters: !#\$%&*='^_ '{|}~";<>@[\\]

3. CBPR_Agent_PointToPointOnSWIFT:

If the transaction is exchanged on the SWIFT network (ie if the instructing agent/sender and instructed agent/receiver of the message are on SWIFT), then BIC is mandatory and other elements are optional, eg LEI

Collection Description

This is the Cross Border Payment and Reporting Collection for SR2026.

These are FINAL usage guidelines.

The usage guidelines are available on the CBPR+ SR2026 Readiness Portal for testing.

The Collection contains:

30 Usage Guidelines that will be live on the network as of November 2026.

Outline

The CBPRPlus SR2026 (Combined) / CBPRPlus-camt.029.001.09_ResolutionOfInvestigation message is composed of 10 building blocks

a. Assignment

Identifies the assignment of an investigation case from an assigner to an assignee.

Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.

b. ResolvedCase

Identifies a resolved case.

c. Status

Indicates the status of the investigation.

d. CancellationDetails

Specifies the details of the underlying transactions being cancelled.

e. ModificationDetails

Specifies the details of the underlying transaction being modified.

f. ClaimNonReceiptDetails

Specifies the details of the underlying transaction for which a claim non receipt has been initiated.

g. StatementDetails

Details on the underlying statement entry.

h. CorrectionTransaction

References a transaction initiated to fix the case under investigation.

i. ResolutionRelatedInformation

Reference to fix the case under investigation as part of the resolution.

j. SupplementaryData

Additional information that cannot be captured in the structured elements and/or any other specific block.

1 Restriction summary

This Usage Guideline restricts the camt.029.001.09 message. This also includes the BusinessApplicationHeaderV02.

Restriction Type	See page
Removed elements	11, 11, 12, 12, 12, 17, 18, 20, 22, 23, 23, 24, 24, 25, 36, 37, 37, 37, 37, 37, 39, 44, 45, 46, 53, 66, 66, 66, 66, 66, 66, 66, 102, 103, 103, 103, 103, 103, 104, 104, 104, 104, 104, 104, 104, 104, 105, 105, 105, 105, 108, 125, 125, 126, 135, 135, 135, 136, 138, 138, 140, 140, 141, 141, 141, 142, 142, 160, 160, 160, 164, 164, 168, 168, 168, 168, 169, 169, 169, 170, 170, 170, 171, 171, 171, 171, 171, 172, 172, 172, 175, 178, 183, 185, 185, 186, 186, 187, 188, 205, 205, 210, 210, 210, 258, 258, 258, 259, 260, 268
Make mandatory	16, 21, 69, 69, 69, 69, 69, 69, 69, 101, 101, 101, 102, 102, 102, 120, 120, 123, 123, 179, 180, 181, 183, 214, 214, 214, 216, 216, 216, 261
Reduce Multiplicity	19, 21, 50, 137, 137, 184, 202, 203, 217, 217, 217, 261
Ignore	n.a.
Text rules	15, 19, 42, 43, 43, 49, 107, 144, 144, 145, 166, 167, 167, 167, 167, 174, 177, 181, 182, 182, 183
Conditional rules	n.a.
Formal rules	13, 13, 19, 38, 49, 49, 52, 166, 166, 179, 181, 184, 184
Fixed values	15, 16
Truncates	n.a.
Comments	n.a.
Annotations	n.a.
Changed datatypes	15, 17, 18, 42, 43, 43, 44, 45, 46, 50, 52, 53, 54, 69, 70, 70, 70, 70, 70, 70, 88, 88, 88, 89, 89, 90, 106, 119, 119, 120, 120, 122, 122, 123, 123, 124, 138, 138, 144, 145, 145, 173, 176, 179, 181, 182, 182, 182, 205, 205, 210, 210, 210, 211, 211, 211, 211, 211, 211, 211, 212, 212, 212, 212, 212, 212, 212, 213, 213, 213, 213, 213, 213, 213, 214, 214, 214, 214, 215, 215, 215,

Restriction Type	See page
	215, 215, 215, 215, 216, 216, 216, 216, 217, 217, 217
Extensions	n.a.
Synonyms	n.a.

2 Structure

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	<i>BusinessApplicationHeaderV02</i>	<AppHdr>		[1..1]		
	CharacterSet	<CharSet>		[0..1]		14
	From	<Fr>		[1..1]		14
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168
	To	<To>		[1..1]		14
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		15
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		15
	BusinessService	<BizSvc>		[0..1]	 	16
	MarketPractice	<MktPrctc>		[0..1]		16
	Registry	<Regy>		[1..1]		123
	Identification	<Id>		[1..1]		124
	CreationDate	<CreDt>		[1..1]		16
	BusinessProcessingDate	<BizPrctgDt>		[0..1]		17
	CopyDuplicate	<CpyDplct>		[0..1]		17
	PossibleDuplicate	<PssblDplct>		[0..1]		17
	Priority	<Prty>		[0..1]		18
	Signature	<Sgntr>		[0..1]		18
	Related	<Rltd>		[0..*]	 R[0..1]	18
	CharacterSet	<CharSet>		[0..1]		41
	From	<Fr>		[1..1]		41
	To	<To>		[1..1]		42
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		42
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		42
	BusinessService	<BizSvc>		[0..1]		43
	CreationDate	<CreDt>		[1..1]		43

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CopyDuplicate	<CpyDplct>		[0..1]		44
	PossibleDuplicate	<PssbldPlct>		[0..1]		44
	Priority	<Prty>		[0..1]		44
	Signature	<Sgntr>		[0..1]		45
	<i>ResolutionOfInvestigationV09</i>	<RsltnOfInvstgtn>		[1..1]		19
	Assignment	<Assgnmt>		[1..1]		20
	Identification	<Id>		[1..1]		53
	Assigner	<Assgnr>		[1..1]		53
	Assignee	<Assgne>		[1..1]		54
	CreationDateTime	<CreDtTm>		[1..1]		54
	ResolvedCase	<RslvdCase>		[0..1]		20
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51
	Status	<Sts>		[1..1]		20
	Confirmation	<Conf>	{Or	[1..1]		124
	RejectedModification	<RjctdMod>	Or	[1..*]		125
	DuplicateOf	<DplctOf>	Or	[1..1]		125
	AssignmentCancellationConfirmation	<AssgnmtCxlConf>	Or}	[1..1]		125
	CancellationDetails	<CxlDtls>		[0..*]	 R[1..1]	21
	OriginalGroupInformationAndStatus	<OrgnlGrpInfAndSts>		[0..1]		258
	OriginalPaymentInformationAndStatus	<OrgnlPmtInfAndSts>		[0..*]		259
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]	 R[1..1]	260
	ModificationDetails	<ModDtls>		[0..1]		21
	ModificationStatusIdentification	<ModStsId>		[0..1]		193
	ResolvedCase	<RslvdCase>		[0..1]		193
	OriginalGroupInformation	<OrgnlGrpInf>		[1..1]		193
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[0..1]		194
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		194
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		194
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		194

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalClearingSystemReference	<OrgnlClrSysRef>		[0..1]		194
	OriginalUETR	<OrgnlUETR>		[0..1]		195
	ModificationStatusReasonInformation	<ModStsRsnInf>		[0..*]		195
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]		195
	OriginalInterbankSettlementAmount	<OrgnlIntrBkSttlmAmt>		[0..1]		196
	OriginalInterbankSettlementDate	<OrgnlIntrBkSttlmDt>		[0..1]		196
	Assigner	<Assgnr>		[0..1]		196
	Assignee	<Assgne>		[0..1]		196
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		197
	ClaimNonReceiptDetails	<ClmNonRctDtls>		[0..1]	🚫	22
	Accepted	<Accptd>	{Or	[1..1]		64
	Rejected	<Rjctd>	Or}	[1..1]		64
	StatementDetails	<StmntDtls>		[0..1]	🚫	23
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		237
	OriginalStatementIdentification	<OrgnlStmntId>		[0..1]		237
	UETR	<UETR>		[0..1]		237
	AccountServicerReference	<AcctSvcrRef>		[0..1]		237
	CorrectedAmount	<CrrctdAmt>		[0..1]		237
	Charges	<Chrgs>		[0..*]		238
	Purpose	<Purp>		[0..1]		238
	CorrectionTransaction	<CrrctnTx>		[0..1]	🚫	23
	Initiation	<Initn>	{Or	[1..1]		82
	Interbank	<IntrBk>	Or}	[1..1]		82
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]	🚫	24
	EndToEndIdentification	<EndToEndId>		[0..1]		228
	TransactionIdentification	<TxId>		[0..1]		228
	UETR	<UETR>		[0..1]		228
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		229
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		229
	ClearingChannel	<ClrChanl>		[0..1]		229
	Compensation	<Compstn>		[0..1]		229

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Charges	<Chrgs>		[0..*]		229
	SupplementaryData	<SplmtryData>		[0..*]		24
	PlaceAndName	<PlcAndNm>		[0..1]		243
	Envelope	<Envlp>		[1..1]		243

3 ISO 20022 Rules

R1 **RelatedPresentWhenCopyDupl** ✓

Related MUST contain the relevant BusinessMessageHeader elements of the BusinessMessage to which this BusinessMessage relates.

If CopyDuplicate is present, then Related MUST be present.

Error handling:

- *Error severity:* Warning
- *Error Code:* H00001
- *Error Text:* Element Related is missing

R4 **PartialOrRejectedCancellationRule** ✓

If Status/Confirmation is present and equal to PECR or RJCR then CancellationDetails must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00095
- *Error Text:* Invalid message content for cancellation details.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/PartialOrRejectedCancellationRule) is removed.**

R5 **MessageOrGroupResolvedCaseRule** ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00113
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/MessageOrGroupResolvedCaseRule) is removed.**

R6 **MessageOrPaymentInformationResolvedCaseRule** ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal

- *Error Code:* X00114
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/MessageOrPaymentInformationResolvedCaseRule) is removed.**

R7 MessageOrInitiationTransactionResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/MessageOrInitiationTransactionResolvedCaseRule) is removed.**

R8 MessageOrInterbankTransactionResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00116
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/MessageOrInterbankTransactionResolvedCaseRule) is removed.**

4 Message Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.029.001.09_ResolutionOfInvestigation message definition.

Usage Guideline on Root Node

- on camt.029.001.09/fullmessage

- CBPR_From_To_Assigner_Assignee_BIC_1_FormalRule:

BAH "From" BIC must match "Assigner" BIC, except where BAH CopyDuplicate = COPY or = CODU

BAH "To" BIC must match "Assignee" BIC, except where BAH CopyDuplicate = COPY or = CODU

For each [Full Message], if
 for each [Full Message],
 every occurrence of [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] has value not included in the following list 'COPY' or 'CODU'
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/ResolutionOfInvestigationV09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/BICFI]
 and every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/ResolutionOfInvestigationV09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/BICFI]

- on camt.029.001.09/fullmessage

- CBPR_From_To_Assigner_Assignee_BIC_2_FormalRule:

BAH "From" BIC must match "Assigner" BIC if CopyDuplicate is absent.

BAH "To" BIC must match "Assignee" BIC if CopyDuplicate is absent.

For each [Full Message], if
 the following element(s) [Full Message/BusinessApplicationHeaderV02/CopyDuplicate] is (are) absent
 , then
 every occurrence of [Full Message/BusinessApplicationHeaderV02/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/ResolutionOfInvestigationV09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/BICFI]
 and every occurrence of [Full Message/BusinessApplicationHeaderV02/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI] must have the same value than every occurrence of [Full Message/Document/ResolutionOfInvestigationV09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/BICFI]

4.1 Header Building Blocks

Note The following chapter identifies the building blocks of the BusinessApplicationHeaderV02 definition.

4.1.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: ["UnicodeChartsCode" on page 317](#)

4.1.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype ["Party44Choice__1" on page 167](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168

4.1.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype ["Party44Choice__1" on page 167](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168

4.1.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/.header/BusinessMessageIdentifier

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on camt.029.001.09/.header/BusinessMessageIdentifier

– **CBPR_Business_Message_Identifier_TextualRule:**

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this field must contain the unique identifier of the Business Message instance.

4.1.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "Max35Text" on page 305

Usage Guideline details

- on camt.029.001.09/.header/MessageDefinitionIdentifier

Single value: camt.029.001.09

4.1.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "Max35Text" on page 305

Usage Guideline details

- on **camt.029.001.09/header/BusinessService**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on **camt.029.001.09/header/BusinessService**
Single value: swift.cbprplus.04

4.1.7 MarketPractice

XML Tag: MktPrctc

Presence: [0..1]

Definition: Specifies the market practice to which the message conforms. The market practices are a set of rules agreed between parties that restricts the usage of the messages in order to achieve better STP (Straight Through Processing) rates.

A market practice specification may also extend the underlying message specification by using extensions or supplementary data of this underlying message.

The **MktPrctc** block contains the following elements (see datatype "ImplementationSpecification1" on page 123 for details)

ⓧ Removed - ⓧ Partial Removed - ♦ Ignored - ♦ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		123
	Identification	<Id>		[1..1]		124

4.1.8 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Datatype: "CBPR_DateTime" on page 269

Usage Guideline details

- **on camt.029.001.09/.header/CreationDate**
Type changed to: [CBPR_DateTime on page 269](#)

4.1.9 BusinessProcessingDate

XML Tag: BizPrcgDt

Presence: [0..1]

Definition: Processing date and time indicated by the sender for the receiver of the business message. This date may be different from the date and time provided in the CreationDate.

Usage: Market practice or bilateral agreement should specify how this element should be used.

Datatype: ["ISODatetime" on page 301](#)

Usage Guideline details

- **This element(camt.029.001.09/.header/BusinessProcessingDate) is removed.**

4.1.10 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 276](#)

4.1.11 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 318](#)

4.1.12 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 311](#)

Usage Guideline details

- on **camt.029.001.09/.header/Priority**
Type changed to: [Priority2Code on page 311](#)

4.1.13 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(**camt.029.001.09/.header/Signature**) is removed.

4.1.14 Related

XML Tag: Rltd

Presence: [0..*]

Definition: Specifies the Business Application Header(s) of the Business Message(s) to which this Business Message relates.

Can be used when replying to a query; can also be used when canceling or amending.

The **Rltd** block contains the following elements (see datatype ["BusinessApplicationHeader5__1" on page 40](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		41
	From	<Fr>		[1..1]		41
	To	<To>		[1..1]		42

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]		42
	MessageDefinitionIdentifier	<MsgDefIdr>		[1..1]		42
	BusinessService	<BizSvc>		[0..1]		43
	CreationDate	<CreDt>		[1..1]		43
	CopyDuplicate	<CpyDplct>		[0..1]		44
	PossibleDuplicate	<PssblDplct>		[0..1]		44
	Priority	<Prty>		[0..1]		44
	Signature	<Sgntr>		[0..1]		45

Usage Guideline details

- **on camt.029.001.09/.header/Related**

This element has change repeatability, the maximum occurrence has been changed to : 1

- **on camt.029.001.09/.header/Related**

- **CBPR_Related_Business_Application_Header_TextualRule:**

If used, the Related BAH must transport the exact same information as in the BAH of the related message.

4.2 Payload Building Blocks

Note The following chapter identifies the building blocks of the CBPRPlus SR2026 (Combined) / CBPRPlus-camt.029.001.09_ResolutionOfInvestigation payload definition.

Usage Guideline on Root Node

- **on camt.029.001.09/**

- **CBPR_Cancellation_Reason_FormalRule:**

If Status/Confirmation =RJCR then CancellationStatus ReasonInformation/Reason is mandatory.

For each [Full Message/Document/ResolutionOfInvestigationV09], if every occurrence of [ResolutionOfInvestigationV09/Status/Confirmation] has value included in the following list 'RJCR', then at least one occurrence of the following element(s) [ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Reason] must be present

4.2.1 Assignment

XML Tag: Assgnmt

Presence: [1..1]

Definition: Identifies the assignment of an investigation case from an assigner to an assignee.

Usage: The assigner must be the sender of this confirmation and the assignee must be the receiver.

The **Assgnmt** block contains the following elements (see datatype "CaseAssignment5__1" on page 53 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		53
	Assigner	<Assgnr>		[1..1]		53
	Assignee	<Assgne>		[1..1]		54
	CreationDateTime	<CreDtTm>		[1..1]		54

4.2.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies a resolved case.

The **RslvdCase** block contains the following elements (see datatype "Case5" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

Usage Guideline details

- This element(camt.029.001.09/ResolvedCase) is removed.

4.2.3 Status

XML Tag: Sts

Presence: [1..1]

Definition: Indicates the status of the investigation.

The **Sts** block contains the following elements (see datatype "[InvestigationStatus5Choice__1](#)" on [page 124](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Confirmation	<Conf>	{Or	[1..1]	⚠	124
	RejectedModification	<RjctdMod>	Or	[1..*]	🚫	125
	DuplicateOf	<DplctOf>	Or	[1..1]	🚫	125
	AssignmentCancellationConfirmation	<AssgnmtCxlConf>	Or}	[1..1]	🚫	125

4.2.4 CancellationDetails

XML Tag: CxlDtIs

Presence: [0..*]

Definition: Specifies the details of the underlying transactions being cancelled.

The **CxlDtIs** block contains the following elements (see datatype "[UnderlyingTransaction22__1](#)" on [page 257](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformationAndStatus	<OrgnlGrpInfAndSts>		[0..1]	🚫	258
	OriginalPaymentInformationAndStatus	<OrgnlPmtInfAndSts>		[0..*]	🚫	259
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]	M R[1..1]	260

Usage Guideline details

- on camt.029.001.09/CancellationDetails

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

4.2.5 ModificationDetails

XML Tag: ModDtIs

Presence: [0..1]

Definition: Specifies the details of the underlying transaction being modified.

The **ModDtIs** block contains the following elements (see datatype "[PaymentTransaction107](#)" on [page 192](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ModificationStatusIdentification	<ModStsId>		[0..1]		193
	ResolvedCase	<RslvdCase>		[0..1]		193
	OriginalGroupInformation	<OrgnlGrpInf>		[1..1]		193
	OriginalPaymentInformationIdentification	<OrgnlPmtInflId>		[0..1]		194
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		194
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		194
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		194
	OriginalClearingSystemReference	<OrgnlClrSysRef>		[0..1]		194
	OriginalUETR	<OrgnlUETR>		[0..1]		195
	ModificationStatusReasonInformation	<ModStsRsnInf>		[0..*]		195
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]		195
	OriginalInterbankSettlementAmount	<OrgnlIntrBkSttlmAmt>		[0..1]		196
	OriginalInterbankSettlementDate	<OrgnlIntrBkSttlmDt>		[0..1]		196
	Assigner	<Assgnr>		[0..1]		196
	Assignee	<Assgnee>		[0..1]		196
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		197

Usage Guideline details

- This element(camt.029.001.09/ModificationDetails) is removed.

4.2.6 ClaimNonReceiptDetails

XML Tag: ClmNonRctDtls

Presence: [0..1]

Definition: Specifies the details of the underlying transaction for which a claim non receipt has been initiated.

The **ClmNonRctDtls** block contains the following elements (see datatype "[ClaimNonReceipt2Choice](#)" on page 64 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Accepted	<Accptd>	{Or	[1..1]		64
	Rejected	<Rjctd>	Or}	[1..1]		64

Usage Guideline details

- This element(camt.029.001.09/ClaimNonReceiptDetails) is removed.

4.2.7 StatementDetails

XML Tag: StmtDtls

Presence: [0..1]

Definition: Details on the underlying statement entry.

The **StmtDtls** block contains the following elements (see datatype "[StatementResolutionEntry4](#)" on page 236 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		237
	OriginalStatementIdentification	<OrgnlStmtId>		[0..1]		237
	UETR	<UETR>		[0..1]		237
	AccountServicerReference	<AcctSvcrRef>		[0..1]		237
	CorrectedAmount	<CrrctdAmt>		[0..1]		237
	Charges	<Chrgs>		[0..*]		238
	Purpose	<Purp>		[0..1]		238

Usage Guideline details

- This element(camt.029.001.09/StatementDetails) is removed.

4.2.8 CorrectionTransaction

XML Tag: CrrctnTx

Presence: [0..1]

Definition: References a transaction initiated to fix the case under investigation.

The **CrrctnTx** block contains the following elements (see datatype "[CorrectiveTransaction4Choice](#)" on page 81 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Initiation	<Initn>	{Or	[1..1]		82
	Interbank	<IntrBk>	Or}	[1..1]		82

Usage Guideline details

- This element(camt.029.001.09/CorrectionTransaction) is removed.

4.2.9 ResolutionRelatedInformation

XML Tag: RsltnRltdInf

Presence: [0..1]

Definition: Reference to fix the case under investigation as part of the resolution.

The **RsltnRltdInf** block contains the following elements (see datatype "ResolutionData1" on page 227 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EndToEndIdentification	<EndToEndId>		[0..1]		228
	TransactionIdentification	<TxId>		[0..1]		228
	UETR	<UETR>		[0..1]		228
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		229
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		229
	ClearingChannel	<ClrChanl>		[0..1]		229
	Compensation	<Compstn>		[0..1]		229
	Charges	<Chrgs>		[0..*]		229

Usage Guideline details

- This element(camt.029.001.09/ResolutionRelatedInformation) is removed.

4.2.10 SupplementaryData

XML Tag: SplmtryData

Presence: [0..*]

Definition: Additional information that cannot be captured in the structured elements and/or any other specific block.

The **SplmtryData** block contains the following elements (see datatype "SupplementaryData1" on page 242 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		243
	Envelope	<Envlp>		[1..1]		243

Usage Guideline details

- This element(camt.029.001.09/SupplementaryData) is removed.

5 Message Components

Note The following chapter identifies the message components.

5.1 AccountIdentification4Choice

Definition: Specifies the unique identification of an account as assigned by the account servicer.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		26
	Other	<Othr>	Or}	[1..1]		26

Used in element(s)

"Identification" on page 55

5.1.1 IBAN

XML Tag: IBAN

Presence: [1..1]

Definition: International Bank Account Number (IBAN) - identifier used internationally by financial institutions to uniquely identify the account of a customer. Further specifications of the format and content of the IBAN can be found in the standard ISO 13616 "Banking and related financial services - International Bank Account Number (IBAN)" version 1997-10-01, or later revisions.

Datatype: "IBAN2007Identifier" on page 300

5.1.2 Other

XML Tag: Othr

Presence: [1..1]

Definition: Unique identification of an account, as assigned by the account servicer, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericAccountIdentification1](#)" on page 114 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		115
	SchemeName	<SchmeNm>		[0..1]		115
	Issuer	<Issr>		[0..1]		115

5.2 AccountSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		27

Used in element(s)

"SchemeName" on page 115

5.2.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalAccountIdentification1Code" on page 282

5.2.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 305

5.3 AddressType3Choice

Definition: Choice of formats for the type of address.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		28

Used in element(s)

"AddressType" on page 206, "AddressType" on page 209

5.3.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of address expressed as a code.

Datatype: "AddressType2Code" on page 264

5.3.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of address expressed as a proprietary code.

The **Prtry** block contains the following elements (see datatype "GenericIdentification30" on page 117 for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		117
	Issuer	<Issr>		[1..1]		117
	SchemeName	<SchmeNm>		[0..1]		118

5.4 AmendmentInformationDetails13

Definition: Provides further details on the list of direct debit mandate elements that have been modified when the amendment indicator has been set.

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		29
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeId>		[0..1]		29
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		29
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		30
	OriginalDebtor	<OrgnlDbtr>		[0..1]		30
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		30
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		31
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		31
	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		32
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		32
	OriginalReason	<OrgnlRsn>		[0..1]		32

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		33

Used in element(s)

"AmendmentInformationDetails" on page 128

5.4.1 OriginalMandatIdentification

XML Tag: OrgnlMndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the original mandate.

Datatype: "Max35Text" on page 305

5.4.2 OriginalCreditorSchemeIdentification

XML Tag: OrgnlCdtrSchmeld

Presence: [0..1]

Definition: Original creditor scheme identification that has been modified.

The **OrgnlCdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.4.3 OriginalCreditorAgent

XML Tag: OrgnlCdtrAgt

Presence: [0..1]

Definition: Original creditor agent that has been modified.

The **OrgnlCdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.4.4 OriginalCreditorAgentAccount

XML Tag: OrgnlCdtrAgtAcct

Presence: [0..1]

Definition: Original creditor agent account that has been modified.

The **OrgnlCdtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.4.5 OriginalDebtor

XML Tag: OrgnlDbtr

Presence: [0..1]

Definition: Original debtor that has been modified.

The **OrgnlDbtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.4.6 OriginalDebtorAccount

XML Tag: OrgnlDbtrAcct

Presence: [0..1]

Definition: Original debtor account that has been modified.

The **OrgnlDbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 54](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.4.7 OriginalDebtorAgent

XML Tag: OrgnlDbtrAgt

Presence: [0..1]

Definition: Original debtor agent that has been modified.

The **OrgnlDbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on [page 34](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.4.8 OriginalDebtorAgentAccount

XML Tag: OrgnlDbtrAgtAcct

Presence: [0..1]

Definition: Original debtor agent account that has been modified.

The **OrgnlDbtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on [page 54](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.4.9 OriginalFinalCollectionDate

XML Tag: OrgnlFnIColltnDt

Presence: [0..1]

Definition: Original final collection date that has been modified.

Datatype: "ISODate" on page 301

5.4.10 OriginalFrequency

XML Tag: OrgnlFrqcy

Presence: [0..1]

Definition: Original frequency that has been modified.

The **OrgnlFrqcy** block contains the following elements (see datatype "Frequency36Choice" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		108
	Period	<Prd>	Or	[1..1]		108
	PointInTime	<PtInTm>	Or}	[1..1]		108

5.4.11 OriginalReason

XML Tag: OrgnlRsn

Presence: [0..1]

Definition: Original reason for the mandate to allow the user to distinguish between different mandates for the same creditor.

The **OrgnlRsn** block contains the following elements (see datatype "MandateSetupReason1Choice" on page 130 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		130
	Proprietary	<Prtry>	Or}	[1..1]		130

5.4.12 OriginalTrackingDays

XML Tag: OrgnlTrckgDays

Presence: [0..1]

Definition: Original number of tracking days that has been modified.

Datatype: "Exact2NumericText" on page 281

5.5 AmountType4Choice

Definition: Specifies the amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		33
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		33

Used in element(s)

"Amount" on page 150

5.5.1 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.5.2 EquivalentAmount

XML Tag: EqvtAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

The **EqvtAmt** block contains the following elements (see datatype "[EquivalentAmount2](#)" on page 97 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		97
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		97

5.6 BranchAndFinancialInstitutionIdentification6

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

Used in element(s)

"Agent" on page 60, "Agent" on page 62, "Agent" on page 163, "CreditorAgent" on page 71, "CreditorAgent" on page 156, "DebtorAgent" on page 71, "DebtorAgent" on page 155, "InstructedReimbursementAgent" on page 234, "InstructingReimbursementAgent" on page 234, "OriginalCreditorAgent" on page 29, "OriginalDebtorAgent" on page 31, "OriginalNextAgent" on page 63, "ThirdReimbursementAgent" on page 235

5.6.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "[FinancialInstitutionIdentification18](#)" on page 98 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		99
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		99
	LEI	<LEI>		[0..1]		99

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		99
	PostalAddress	<PstlAdr>		[0..1]		100
	Other	<Othr>		[0..1]		100

5.6.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 39 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		39
	LEI	<LEI>		[0..1]		39
	Name	<Nm>		[0..1]		39
	PostalAddress	<PstlAdr>		[0..1]		39

5.7 BranchAndFinancialInstitutionIdentification6__1

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		35
	BranchIdentification	<BrnchId>		[0..1]		36

Used in element(s)

"Agent" on page 164, "FinancialInstitutionIdentification" on page 168

5.7.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__1" on page 101 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]	M	101
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		102
	LEI	<LEI>		[0..1]		102
	Name	<Nm>		[0..1]	🚫	102
	PostalAddress	<PstlAdr>		[0..1]	🚫	103
	Other	<Othr>		[0..1]	🚫	104

5.7.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "BranchData3" on page 39 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		39
	LEI	<LEI>		[0..1]		39
	Name	<Nm>		[0..1]		39
	PostalAddress	<PstlAdr>		[0..1]		39

Usage Guideline details

- This element(camt.029.001.09/header/Related/To/FinancialInstitutionIdentification/BranchIdentification) is removed.

- This element(`camt.029.001.09/.header/To/FinancialInstitutionIdentification/BranchIdentification`) is removed.
- This element(`camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/BranchIdentification`) is removed.
- This element(`camt.029.001.09/.header/From/FinancialInstitutionIdentification/BranchIdentification`) is removed.
- This element(`camt.029.001.09/Assignment/Assigner/Agent/BranchIdentification`) is removed.
- This element(`camt.029.001.09/Assignment/Assignee/Agent/BranchIdentification`) is removed.

5.8 BranchAndFinancialInstitutionIdentification6__2

Definition: Unique and unambiguous identification of a financial institution or a branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		37
	BranchIdentification	<BrnchId>		[0..1]		38

Used in element(s)

"Agent" on page 166

5.8.1 FinancialInstitutionIdentification

XML Tag: FinInstnId

Presence: [1..1]

Definition: Unique and unambiguous identification of a financial institution, as assigned under an internationally recognised or proprietary identification scheme.

The **FinInstnId** block contains the following elements (see datatype "FinancialInstitutionIdentification18__2" on page 105 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		105
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		105
	LEI	<LEI>		[0..1]		106
	Name	<Nm>		[0..1]		106
	PostalAddress	<PstlAdr>		[0..1]		106

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Other	<Othr>		[0..1]		107

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification

– CBPR_Agent_Name_Postal_Address_FormaRule:

Name and Address must always be present together.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification],
 for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] must be present
 and for each [FinancialInstitutionIdentification], if
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/PostalAddress] is (are) present
 then
 at least one occurrence of the following element(s) [FinancialInstitutionIdentification/Name] must be present

5.8.2 BranchIdentification

XML Tag: BrnchId

Presence: [0..1]

Definition: Identifies a specific branch of a financial institution.

Usage: This component should be used in case the identification information in the financial institution component does not provide identification up to branch level.

The **BrnchId** block contains the following elements (see datatype "[BranchData3](#)" on page 39 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		39
	LEI	<LEI>		[0..1]		39
	Name	<Nm>		[0..1]		39
	PostalAddress	<PstlAdr>		[0..1]		39

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/BranchIdentification](#)) is removed.

5.9 BranchData3

Definition: Information that locates and identifies a specific branch of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		39
	LEI	<LEI>		[0..1]		39
	Name	<Nm>		[0..1]		39
	PostalAddress	<PstlAdr>		[0..1]		39

Used in element(s)

["BranchIdentification" on page 35](#),
 ["BranchIdentification" on page 36](#),
 ["BranchIdentification" on page 38](#)

5.9.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a branch of a financial institution.

Datatype: ["Max35Text" on page 305](#)

5.9.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification for the branch of the financial institution.

Datatype: ["LEIIdentifier" on page 302](#)

5.9.3 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: ["Max140Text" on page 303](#)

5.9.4 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 205 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		206
	Department	<Dept>		[0..1]		206
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		207
	Floor	<Flr>		[0..1]		207
	PostBox	<PstBx>		[0..1]		207
	Room	<Room>		[0..1]		207
	PostCode	<PstCd>		[0..1]		207
	TownName	<TwnNm>		[0..1]		208
	TownLocationName	<TwnLctnNm>		[0..1]		208
	DistrictName	<DstrctNm>		[0..1]		208
	CountrySubDivision	<CtrySubDvsn>		[0..1]		208
	Country	<Ctry>		[0..1]		208
	AddressLine	<AdrLine>		[0..7]		208

5.10 BusinessApplicationHeader5__1

Definition: Specifies the Business Application Header of the Business Message.

Can be used when replying to a query; can also be used when canceling or amending.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CharacterSet	<CharSet>		[0..1]		41
	From	<Fr>		[1..1]		41

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	To	<To>		[1..1]		42
	BusinessMessageIdentifier	<BizMsgIdr>		[1..1]	⚠	42
	MessageDefinitionIdentifier	<MsgDefldr>		[1..1]	⚠	42
	BusinessService	<BizSvc>		[0..1]	⚠	43
	CreationDate	<CreDt>		[1..1]	⚠	43
	CopyDuplicate	<CpyDplct>		[0..1]		44
	PossibleDuplicate	<PssblDplct>		[0..1]	⊘	44
	Priority	<Prty>		[0..1]	⚠	44
	Signature	<Sgntr>		[0..1]	⊘	45

Used in element(s)

"Related" on page 18

5.10.1 CharacterSet

XML Tag: CharSet

Presence: [0..1]

Definition: Contains the character set of the text-based elements used in the Business Message.

Datatype: "UnicodeChartsCode" on page 317

5.10.2 From

XML Tag: Fr

Presence: [1..1]

Definition: The sending MessagingEndpoint that has created this Business Message for the receiving MessagingEndpoint that will process this Business Message.

Note the sending MessagingEndpoint might be different from the sending address potentially contained in the transport header (as defined in the transport layer).

The **Fr** block contains the following elements (see datatype "Party44Choice__1" on page 167 for details)

⊘ Removed - ⊘ Partial Removed - ◇ Ignored - ◇ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	⊘	168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168

5.10.3 To

XML Tag: To

Presence: [1..1]

Definition: The MessagingEndpoint designated by the sending MessagingEndpoint to be the recipient who will ultimately process this Business Message.

Note the receiving MessagingEndpoint might be different from the receiving address potentially contained in the transport header (as defined in the transport layer).

The **To** block contains the following elements (see datatype "[Party44Choice__1](#)" on page 167 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168

5.10.4 BusinessMessageIdentifier

XML Tag: BizMsgIdr

Presence: [1..1]

Definition: Unambiguously identifies the Business Message to the MessagingEndpoint that has created the Business Message.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 272

Usage Guideline details

- on [camt.029.001.09/header/Related/BusinessMessageIdentifier](#)

Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 272

- on [camt.029.001.09/header/Related/BusinessMessageIdentifier](#)

– CBPR_Business_Message_Identifier_TextualRule:

The Business Message Identifier is the unique identifier of the Business Message instance that is being transported with this header, as defined by the sending application or system.

Must contain the Message Identification element from the Group Header of the underlying message, where available (as is typically the case with pacs, pain, and camt messages, for example). If Message Identification is not available in the underlying message, then this element must contain the unique identifier of the Business Message instance.

5.10.5 MessageDefinitionIdentifier

XML Tag: MsgDefIdr

Presence: [1..1]

Definition: Contains the MessageIdentifier that defines the BusinessMessage.

It must contain a MessageIdentifier published on the ISO 20022 website.

example camt.001.001.03.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- **on camt.029.001.09/.header/Related/MessageDefinitionIdentifier**
Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- **on camt.029.001.09/.header/Related/MessageDefinitionIdentifier**
 - **CBPR_Message_Definition_Identifier_TextualRule:**

The Message Definition Identifier of the Business Message instance that is being transported with this header. In general, it must be formatted exactly as it appears in the namespace of the Business Message instance.

5.10.6 BusinessService

XML Tag: BizSvc

Presence: [0..1]

Definition: Specifies the business service agreed between the two MessagingEndpoints under which rules this Business Message is exchanged.

To be used when there is a choice of processing services or processing service levels.

Example: E&I.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- **on camt.029.001.09/.header/Related/BusinessService**
Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- **on camt.029.001.09/.header/Related/BusinessService**
 - **CBPR_Related_BAH_Business_Service_TextualRule:**

If related BAH is present, it should transport the element Business Service.

5.10.7 CreationDate

XML Tag: CreDt

Presence: [1..1]

Definition: Date and time when this Business Message (header) was created.

Note Times must be normalized, using the "Z" annotation.

Datatype: ["CBPR_DateTime" on page 269](#)

Usage Guideline details

- on [camt.029.001.09/header/Related/CreationDate](#)
Type changed to: [CBPR_DateTime on page 269](#)

5.10.8 CopyDuplicate

XML Tag: CpyDplct

Presence: [0..1]

Definition: Indicates whether the message is a Copy, a Duplicate or a copy of a duplicate of a previously sent ISO 20022 Message.

Datatype: ["CopyDuplicate1Code" on page 276](#)

5.10.9 PossibleDuplicate

XML Tag: PssblDplct

Presence: [0..1]

Definition: Flag indicating if the Business Message exchanged between the MessagingEndpoints is possibly a duplicate.

If the receiving MessagingEndpoint did not receive the original, then this Business Message should be processed as if it were the original.

If the receiving MessagingEndpoint did receive the original, then it should perform necessary actions to avoid processing this Business Message again.

This will guarantee business idempotent behaviour.

NOTE: this is named "PossResend" in FIX - this is an application level resend not a network level re-transmission.

Datatype: ["YesNoIndicator" on page 318](#)

Usage Guideline details

- This element([camt.029.001.09/header/Related/PossibleDuplicate](#)) is removed.

5.10.10 Priority

XML Tag: Prty

Presence: [0..1]

Definition: Relative indication of the processing precedence of the message over a (set of) Business Messages with assigned priorities.

Datatype: ["Priority2Code" on page 311](#)

Usage Guideline details

- on **camt.029.001.09/.header/Related/Priority**
Type changed to: [Priority2Code on page 311](#)

5.10.11 Signature

XML Tag: Sgntr

Presence: [0..1]

Definition: Contains the digital signature of the Business Entity authorised to sign this Business Message.

Usage Guideline details

- This element(**camt.029.001.09/.header/Related/Signature**) is removed.

5.11 CancellationStatusReason3Choice

Definition: Specifies the reason for the transaction cancellation status.

❌ Removed -
 ❌ Partial Removed -
 ⬢ Ignored -
 ⬢ Partial Ignored -
 ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

Used in element(s)

["Reason" on page 47](#)

5.11.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the cancellation status, in a coded form.

Datatype: ["ExternalPaymentCancellationRejection1Code" on page 292](#)

5.11.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: ["Max35Text" on page 305](#)

5.12 CancellationStatusReason3Choice__1

Definition: Specifies the reason for the transaction cancellation status.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		46
	Proprietary	<Prtry>	Or}	[1..1]		46

Used in element(s)

["Reason" on page 49](#)

5.12.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the cancellation status, in a coded form.

Datatype: ["CBPR_CancellationStatusReasonCode" on page 267](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Reason/Code](#)

Type changed to: [CBPR_CancellationStatusReasonCode on page 268](#)

5.12.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: ["Max35Text" on page 305](#)

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Reason/Proprietary](#)) is removed.

5.13 CancellationStatusReason4

Definition: Provides further details on the status of the cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		47
	Reason	<Rsn>		[0..1]		47
	AdditionalInformation	<AddtlInf>		[0..*]		48

Used in element(s)

"CancellationStatusReasonInformation" on page 141, "CancellationStatusReasonInformation" on page 148, "CancellationStatusReasonInformation" on page 190

5.13.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation status.

The **Orgtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.13.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "[CancellationStatusReason3Choice](#)" on page 45 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		45
	Proprietary	<Prtry>	Or}	[1..1]		45

5.13.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the cancellation status reason.

Datatype: "Max105Text" on page 302

5.14 CancellationStatusReason4__1

Definition: Provides further details on the status of the cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		48
	Reason	<Rsn>		[0..1]		49
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	50

Used in element(s)

"CancellationStatusReasonInformation" on page 183

5.14.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation status.

The **Orgtr** block contains the following elements (see datatype "PartyIdentification135__2" on page 175 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		175
	PostalAddress	<PstlAdr>		[0..1]		176
	Identification	<Id>		[0..1]		177
	CountryOfResidence	<CtryOfRes>		[0..1]		177

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ContactDetails	<CtctDtls>		[0..1]		177

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator

- CBPR_Originator_Identification_TextualRule:

If AnyBIC is present in addition to any other optional elements, in case of conflicting information it will always take precedence.

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator

- CBPR_Party_Name_Postal_Address_FormaRule:

If Postal Address is present then Name is mandatory.

Recommendation: If present, the BIC (AnyBIC) will always take precedence in case of conflicting information.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator], if

at least one occurrence of the following element(s) [Originator/PostalAddress] is (are) present
, then

at least one occurrence of the following element(s) [Originator/Name] must be present

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator

- CBPR_Party_Name_Any_BIC_FormaRule:

If AnyBIC is absent Then Name is mandatory.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator], if

the following element(s) [Originator/Identification/OrganisationIdentification/AnyBIC] is (are) absent
, then

at least one occurrence of the following element(s) [Originator/Name] must be present

5.14.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "[CancellationStatusReason3Choice__1](#)" on page 46 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]	⚠	46
	Proprietary	<Prtry>	Or}	[1..1]	🚫	46

5.14.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the cancellation status reason.

Datatype: "[CBPR_RestrictedFINXMax105Text](#)" on page 270

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/AdditionalInformation](#)
This element has change repeatability, the maximum occurrence has been changed to : 2
- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/AdditionalInformation](#)
Type changed to: [CBPR_RestrictedFINXMax105Text](#) on page 270

5.15 Case5

Definition: Provides further details to identify an investigation case.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

Used in element(s)

["DuplicateOf"](#) on page 125, ["ResolvedCase"](#) on page 20, ["ResolvedCase"](#) on page 140, ["Resolved-Case"](#) on page 147, ["ResolvedCase"](#) on page 189, ["ResolvedCase"](#) on page 193

5.15.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case.

Datatype: "Max35Text" on page 305

5.15.2 Creator

XML Tag: Cretr

Presence: [1..1]

Definition: Party that created the investigation case.

The **Cretr** block contains the following elements (see datatype "Party40Choice" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.15.3 ReopenCaseIndication

XML Tag: ReopCaseIndctn

Presence: [0..1]

Definition: Indicates whether or not the case was previously closed and is now re-opened.

Datatype: "YesNoIndicator" on page 318

5.16 Case5__1

Definition: Provides further details to identify an investigation case.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		52
	Creator	<Cretr>		[1..1]		52
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		52

Used in element(s)

"ResolvedCase" on page 180

5.16.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 271

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/Resolved-Case/Identification**

Type changed to: CBPR_RestrictedFINXMax16Text on page 271

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/Resolved-Case/Identification**

– CBPR_Case_Identification_FormaRule:

For the Case/Identification, the below restrictions apply:

- The first one and the 16th one cannot be "/" and
- The string of 16 characters cannot contain "/"

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Identification], the value of every occurrence of [Identification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.16.2 Creator

XML Tag: Cretr

Presence: [1..1]

Definition: Party that created the investigation case.

The **Cretr** block contains the following elements (see datatype "Party40Choice__2" on page 165 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		165
	Agent	<Agt>	Or}	[1..1]		166

5.16.3 ReopenCaseIndication

XML Tag: ReopCaseIndctn

Presence: [0..1]

Definition: Indicates whether or not the case was previously closed and is now re-opened.

Datatype: ["YesNoIndicator" on page 318](#)

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/ReopenCaseIndication](#)) is removed.

5.17 CaseAssignment5__1

Definition: Represents the assignment of a case to a party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		53
	Assigner	<Assgnr>		[1..1]		53
	Assignee	<Assgne>		[1..1]		54
	CreationDateTime	<CreDtTm>		[1..1]		54

Used in element(s)

["Assignment" on page 20](#)

5.17.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Uniquely identifies the case assignment.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 272](#)

Usage Guideline details

- on [camt.029.001.09/Assignment/Identification](#)
Type changed to: [CBPR_RestrictedFINXMax35Text on page 272](#)

5.17.2 Assigner

XML Tag: Assgnr

Presence: [1..1]

Definition: Party who assigns the case.

Usage: This is also the sender of the message.

The **Assgnr** block contains the following elements (see datatype "[Party40Choice__1](#)" on page 164 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]	🚫	164
	Agent	<Agt>	Or}	[1..1]		164

5.17.3 Assignee

XML Tag: Assgne

Presence: [1..1]

Definition: Party to which the case is assigned.

Usage: This is also the receiver of the message.

The **Assgne** block contains the following elements (see datatype "[Party40Choice__1](#)" on page 164 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]	🚫	164
	Agent	<Agt>	Or}	[1..1]		164

5.17.4 CreationDateTime

XML Tag: CreDtTm

Presence: [1..1]

Definition: Date and time at which the assignment was created.

Datatype: "[CBPR_DateTime](#)" on page 269

Usage Guideline details

- on [camt.029.001.09/Assignment/CreationDateTime](#)
Type changed to: [CBPR_DateTime](#) on page 269

5.18 CashAccount38

Definition: Provides the details to identify an account.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

Used in element(s)

"CreditorAccount" on page 157, "CreditorAgentAccount" on page 157, "DebtorAccount" on page 155, "DebtorAgentAccount" on page 156, "InstructedReimbursementAgentAccount" on page 235, "InstructingReimbursementAgentAccount" on page 234, "OriginalCreditorAgentAccount" on page 30, "OriginalDebtorAccount" on page 30, "OriginalDebtorAgentAccount" on page 31, "SettlementAccount" on page 233, "ThirdReimbursementAgentAccount" on page 236

5.18.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification for the account between the account owner and the account servicer.

The **Id** block contains the following elements (see datatype "[AccountIdentification4Choice](#)" on page 26 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	IBAN	<IBAN>	{Or	[1..1]		26
	Other	<Othr>	Or}	[1..1]		26

5.18.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the nature, or use of the account.

The **Tp** block contains the following elements (see datatype "[CashAccountType2Choice](#)" on page 56 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		57

5.18.3 Currency

XML Tag: Ccy

Presence: [0..1]

Definition: Identification of the currency in which the account is held.

Usage: Currency should only be used in case one and the same account number covers several currencies

and the initiating party needs to identify which currency needs to be used for settlement on the account.

Datatype: ["ActiveOrHistoricCurrencyCode" on page 264](#)

5.18.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the account, as assigned by the account servicing institution, in agreement with the account owner in order to provide an additional means of identification of the account.

Usage: The account name is different from the account owner name. The account name is used in certain user communities to provide a means of identifying the account, in addition to the account owner's identity and the account number.

Datatype: ["Max70Text" on page 306](#)

5.18.5 Proxy

XML Tag: Prxy

Presence: [0..1]

Definition: Specifies an alternate assumed name for the identification of the account.

The **Prxy** block contains the following elements (see datatype ["ProxyAccountIdentification1" on page 217](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		218
	Identification	<Id>		[1..1]		218

5.19 CashAccountType2Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		57

Used in element(s)

["Type" on page 55](#)

5.19.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Account type, in a coded form.

Datatype: ["ExternalCashAccountType1Code" on page 282](#)

5.19.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Nature or use of the account in a proprietary form.

Datatype: ["Max35Text" on page 305](#)

5.20 CategoryPurpose1Choice

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		58

Used in element(s)

["CategoryPurpose" on page 199](#)

5.20.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Category purpose, as published in an external category purpose code list.

Datatype: ["ExternalCategoryPurpose1Code" on page 284](#)

5.20.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Category purpose, in a proprietary form.

Datatype: ["Max35Text" on page 305](#)

5.21 ChargeType3Choice

Definition: Specifies the charge type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]		58

Used in element(s)

["Type" on page 61](#)

5.21.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Charge type, in a coded form.

Datatype: ["ExternalChargeType1Code" on page 285](#)

5.21.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Type of charge in a proprietary form, as defined by the issuer.

The **Prtry** block contains the following elements (see datatype ["GenericIdentification3" on page 116](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		117

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Issuer	<Issr>		[0..1]		117

5.22 Charges6

Definition: Provides further details on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalChargesAndTaxAmount	<TtlChrgsAndTaxAmt>		[0..1]		59
	Record	<Rcrd>		[0..*]		59

Used in element(s)

["Charges" on page 238](#)

5.22.1 TotalChargesAndTaxAmount

XML Tag: TtlChrgsAndTaxAmt

Presence: [0..1]

Definition: Total of all charges and taxes applied to the entry.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.22.2 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Provides details of the individual charges record.

The **Rcrd** block contains the following elements (see datatype ["ChargesRecord3" on page 60](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		61
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		61
	ChargeIncludedIndicator	<ChrgInclInd>		[0..1]		61
	Type	<Tp>		[0..1]		61
	Rate	<Rate>		[0..1]		62
	Bearer	 		[0..1]		62

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Agent	<Agt>		[0..1]		62
	Tax	<Tax>		[0..1]		62

5.23 Charges7

Definition: Provides information on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		60
	Agent	<Agt>		[1..1]		60

Used in element(s)

"Charges" on page 229

5.23.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Transaction charges to be paid by the charge bearer.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.23.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Agent that takes the transaction charges or to which the transaction charges are due.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.24 ChargesRecord3

Definition: Provides further individual record details on the charges related to the payment transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		61
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		61
	ChargeIncludedIndicator	<ChrgInclInd>		[0..1]		61
	Type	<Tp>		[0..1]		61
	Rate	<Rate>		[0..1]		62
	Bearer	 		[0..1]		62
	Agent	<Agt>		[0..1]		62
	Tax	<Tax>		[0..1]		62

Used in element(s)

"Record" on page 59

5.24.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Transaction charges to be paid by the charge bearer.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.24.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Indicates whether the charges amount is a credit or a debit amount.

Usage: A zero amount is considered to be a credit.

Datatype: "CreditDebitCode" on page 277

5.24.3 ChargeIncludedIndicator

XML Tag: ChrgInclInd

Presence: [0..1]

Definition: Indicates whether the charge should be included in the amount or is added as pre-advice.

Datatype: "ChargeIncludedIndicator" on page 275

5.24.4 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of charge.

The **Tp** block contains the following elements (see datatype "[ChargeType3Choice](#)" on page 58 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		58
	Proprietary	<Prtry>	Or}	[1..1]		58

5.24.5 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the amount of the charge or fee.

Datatype: "[PercentageRate](#)" on page 310

5.24.6 Bearer

XML Tag: Br

Presence: [0..1]

Definition: Specifies which party/parties will bear the charges associated with the processing of the payment transaction.

Datatype: "[ChargeBearerType1Code](#)" on page 274

5.24.7 Agent

XML Tag: Agt

Presence: [0..1]

Definition: Agent that takes the transaction charges or to which the transaction charges are due.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.24.8 Tax

XML Tag: Tax

Presence: [0..1]

Definition: Provides details on the tax applied to charges.

The **Tax** block contains the following elements (see datatype "[TaxCharges2](#)" on page 246 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		247
	Rate	<Rate>		[0..1]		247
	Amount	<Amt>		[0..1]		247

5.25 ClaimNonReceipt2

Definition: Specifies details of a claim non receipt status advice.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateProcessed	<DtPrcd>		[1..1]		63
	OriginalNextAgent	<OrgnINxtAgt>		[0..1]		63

Used in element(s)

"Accepted" on page 64

5.25.1 DateProcessed

XML Tag: DtPrcd

Presence: [1..1]

Definition: Specifies the date the original payment instruction was processed.

Datatype: "ISODate" on page 301

5.25.2 OriginalNextAgent

XML Tag: OrgnINxtAgt

Presence: [0..1]

Definition: Specifies the next party the original payment instruction was sent to.

The **OrgnINxtAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.26 ClaimNonReceipt2Choice

Definition: Specifies whether the claim non receipt is accepted or rejected.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Accepted	<Accptd>	{Or	[1..1]		64
	Rejected	<Rjctd>	Or}	[1..1]		64

Used in element(s)

"ClaimNonReceiptDetails" on page 22

5.26.1 Accepted

XML Tag: Accptd

Presence: [1..1]

Definition: Claim non-receipt is accepted and processed by the agent.

The **Accptd** block contains the following elements (see datatype "ClaimNonReceipt2" on page 63 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateProcessed	<DtPrcd>		[1..1]		63
	OriginalNextAgent	<OrgnlNxtAgt>		[0..1]		63

5.26.2 Rejected

XML Tag: Rjctd

Presence: [1..1]

Definition: Specifies that the claim non receipt has been rejected and provides the reason for the rejection.

The **Rjctd** block contains the following elements (see datatype "ClaimNonReceiptRejectReason1Choice" on page 65 for details)

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		65
	Proprietary	<Prtry>	Or}	[1..1]		65

5.27 ClaimNonReceiptRejectReason1Choice

Definition: Specifies the rejection reason of a claim non receipt.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		65
	Proprietary	<Prtry>	Or}	[1..1]		65

Used in element(s)

"Rejected" on page 64

5.27.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the rejection, in a coded form.

Datatype: "ExternalClaimNonReceiptRejection1Code" on page 285

5.27.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the rejection, in a proprietary form.

Datatype: "Max35Text" on page 305

5.28 ClearingSystemIdentification2Choice

Definition: Choice of a clearing system identifier.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

Used in element(s)

["ClearingSystemIdentification" on page 67](#), ["ClearingSystemIdentification" on page 68](#)

5.28.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Identification of a clearing system, in a coded form as published in an external list.

Datatype: ["ExternalClearingSystemIdentification1Code" on page 286](#)

5.28.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Identification code for a clearing system, that has not yet been identified in the list of clearing systems.

Datatype: ["Max35Text" on page 305](#)

Usage Guideline details

- This element([camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.
- This element([camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification/Proprietary](#)) is removed.

5.29 ClearingSystemIdentification3Choice

Definition: Specifies the clearing system identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]		67

Used in element(s)

"ClearingSystem" on page 233

5.29.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Infrastructure through which the payment instruction is processed, as published in an external clearing system identification code list.

Datatype: "ExternalCashClearingSystem1Code" on page 283

5.29.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Clearing system identification in a proprietary form.

Datatype: "Max35Text" on page 305

5.30 ClearingSystemMemberIdentification2

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		67
	MemberIdentification	<Mmbld>		[1..1]		68

Used in element(s)

"ClearingSystemMemberIdentification" on page 99

5.30.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 65 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

5.30.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "[Max35Text](#)" on page 305

5.31 ClearingSystemMemberIdentification2__1

Definition: Unique identification, as assigned by a clearing system, to unambiguously identify a member of the clearing system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	68
	MemberIdentification	<Mmbld>		[1..1]	⚠	69

Used in element(s)

"[ClearingSystemMemberIdentification](#)" on page 102, "[ClearingSystemMemberIdentification](#)" on page 105

5.31.1 ClearingSystemIdentification

XML Tag: ClrSysId

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSysId** block contains the following elements (see datatype "[ClearingSystemIdentification2Choice](#)" on page 65 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		66
	Proprietary	<Prtry>	Or}	[1..1]		66

Usage Guideline details

- **on camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/ClearingSystemIdentification**
This element is now mandatory, the minimum occurrence has been changed to : 1

5.31.2 MemberIdentification

XML Tag: Mmbld

Presence: [1..1]

Definition: Identification of a member of a clearing system.

Datatype: "CBPR_RestrictedFINXMax28Text" on page 272

Usage Guideline details

- **on camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification**
Type changed to: CBPR_RestrictedFINXMax28Text on page 272

- on camt.029.001.09/header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)
- on camt.029.001.09/header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)
- on camt.029.001.09/header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)
- on camt.029.001.09/header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)
- on camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/ClearingSystemMemberIdentification/MemberIdentification
Type changed to: [CBPR_RestrictedFINXMax28Text on page 272](#)

5.32 Compensation2

Definition: Specifies the details of a payment compensation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		70
	DebtorAgent	<DbtrAgt>		[1..1]		71
	CreditorAgent	<CdtrAgt>		[1..1]		71
	Reason	<Rsn>		[1..1]		71

Used in element(s)

["Compensation" on page 229](#)

5.32.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be paid in compensation.

Datatype: "ActiveCurrencyAndAmount" on page 262

5.32.2 DebtorAgent

XML Tag: DbtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the debtor.

Usage: The debtor agent is the payer of the compensation amount.

The **DbtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.32.3 CreditorAgent

XML Tag: CdtrAgt

Presence: [1..1]

Definition: Financial institution servicing an account for the creditor.

Usage: The creditor agent is the payee of the compensation amount.

The **CdtrAgt** block contains the following elements (see datatype "BranchAndFinancialInstitutionIdentification6" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.32.4 Reason

XML Tag: Rsn

Presence: [1..1]

Definition: Reason for the payment compensation.

The **Rsn** block contains the following elements (see datatype "CompensationReason1Choice" on page 72 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		72
	Proprietary	<Prtry>	Or}	[1..1]		72

5.33 CompensationReason1Choice

Definition: Specifies the reason for the payment compensation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		72
	Proprietary	<Prtry>	Or}	[1..1]		72

Used in element(s)

"Reason" on page 71

5.33.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the payment compensation, in a coded form.

Datatype: "ExternalPaymentCompensationReason1Code" on page 293

5.33.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the payment compensation, in a proprietary form.

Datatype: "Max35Text" on page 305

5.34 Contact4

Definition: Specifies the details of the contact person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		73

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		73
	PhoneNumber	<PhneNb>		[0..1]		73
	MobileNumber	<MobNb>		[0..1]		73
	FaxNumber	<FaxNb>		[0..1]		74
	EmailAddress	<EmailAdr>		[0..1]		74
	EmailPurpose	<EmailPurp>		[0..1]		74
	JobTitle	<JobTitl>		[0..1]		74
	Responsibility	<Rspnsblty>		[0..1]		74
	Department	<Dept>		[0..1]		74
	Other	<Othr>		[0..*]		75
	PreferredMethod	<PrefrdMtd>		[0..1]		75

Used in element(s)

["ContactDetails" on page 171](#), ["ContactDetails" on page 174](#), ["ContactDetails" on page 177](#)

5.34.1 NamePrefix

XML Tag: NmPrfx

Presence: [0..1]

Definition: Specifies the terms used to formally address a person.

Datatype: ["NamePrefix2Code" on page 306](#)

5.34.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 303](#)

5.34.3 PhoneNumber

XML Tag: PhneNb

Presence: [0..1]

Definition: Collection of information that identifies a phone number, as defined by telecom services.

Datatype: ["PhoneNumber" on page 310](#)

5.34.4 MobileNumber

XML Tag: MobNb

Presence: [0..1]

Definition: Collection of information that identifies a mobile phone number, as defined by telecom services.

Datatype: "PhoneNumber" on page 310

5.34.5 FaxNumber

XML Tag: FaxNb

Presence: [0..1]

Definition: Collection of information that identifies a FAX number, as defined by telecom services.

Datatype: "PhoneNumber" on page 310

5.34.6 EmailAddress

XML Tag: EmailAdr

Presence: [0..1]

Definition: Address for electronic mail (e-mail).

Datatype: "Max2048Text" on page 304

5.34.7 EmailPurpose

XML Tag: EmailPurp

Presence: [0..1]

Definition: Purpose for which an email address may be used.

Datatype: "Max35Text" on page 305

5.34.8 JobTitle

XML Tag: JobTitl

Presence: [0..1]

Definition: Title of the function.

Datatype: "Max35Text" on page 305

5.34.9 Responsibility

XML Tag: Rspnsblty

Presence: [0..1]

Definition: Role of a person in an organisation.

Datatype: "Max35Text" on page 305

5.34.10 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 306

5.34.11 Other

XML Tag: Othr

Presence: [0..*]

Definition: Contact details in another form.

The **Othr** block contains the following elements (see datatype "OtherContact1" on page 159 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanTp>		[1..1]		159
	Identification	<Id>		[0..1]		159

5.34.12 PreferredMethod

XML Tag: PrefrdMtd

Presence: [0..1]

Definition: Preferred method used to reach the contact.

Datatype: "PreferredContactMethod1Code" on page 310

5.35 CorrectiveGroupInformation1

Definition: Set of elements used to provide information on the group of the corrective transaction, to which the resolution message refers.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		75
	MessageNameIdentification	<MsgNmId>		[1..1]		76
	CreationDateTime	<CreDtTm>		[0..1]		76

Used in element(s)

"GroupHeader" on page 77, "GroupHeader" on page 79

5.35.1 MessageIdentification

XML Tag: MsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the instructing party, and sent to the next party in the chain to unambiguously identify the message.

Usage: The instructing party has to make sure that 'MessageIdentification' is unique per instructed party for a pre-agreed period.

Datatype: "Max35Text" on page 305

5.35.2 MessageNameIdentification

XML Tag: MsgNmId

Presence: [1..1]

Definition: Specifies the message name identifier to which the message refers.

Datatype: "Max35Text" on page 305

5.35.3 CreationDateTime

XML Tag: CreDtTm

Presence: [0..1]

Definition: Date and time at which the message was created.

Datatype: "ISODateTime" on page 301

5.36 CorrectiveInterbankTransaction2

Definition: Provides information on the corrective interbank transaction, to which the resolution message refers.

🚫 Removed - 🚫 Partial Removed - 💡 Ignored - 💡 Partial Ignored - ⚠️ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupHeader	<GrpHdr>		[0..1]		77
	InstructionIdentification	<InstrId>		[0..1]		77
	EndToEndIdentification	<EndToEndId>		[0..1]		77
	TransactionIdentification	<TxId>		[0..1]		78
	UETR	<UETR>		[0..1]		78
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		78
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		78

Rules

R14 IdentificationRule ✓

Either InstructionIdentification, EndToEndIdentification, TransactionIdentification or any combination of the three must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00092
- *Error Text:* Invalid message content as no identification of transaction is present.

Used in element(s)

"Interbank" on page 82

5.36.1 GroupHeader

XML Tag: GrpHdr

Presence: [0..1]

Definition: Set of elements used to provide corrective information for the group header of the message under investigation.

The **GrpHdr** block contains the following elements (see datatype "[CorrectiveGroupInformation1](#)" on page 75 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		75
	MessageNameIdentification	<MsgNmId>		[1..1]		76
	CreationDateTime	<CreDtTm>		[0..1]		76

5.36.2 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "[Max35Text](#)" on page 305

5.36.3 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "Max35Text" on page 305

5.36.4 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the first instructing agent, to unambiguously identify the transaction that is passed on, unchanged, throughout the entire interbank chain.

Usage: The transaction identification can be used for reconciliation, tracking or to link tasks relating to the transaction on the interbank level.

Usage: The instructing agent has to make sure that the transaction identification is unique for a pre-agreed period.

Datatype: "Max35Text" on page 305

5.36.5 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 317

5.36.6 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [1..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.36.7 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [1..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 301

5.37 CorrectivePaymentInitiation4

Definition: Provides information on the corrective payment initiation transaction, to which the resolution message refers.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupHeader	<GrpHdr>		[0..1]		79
	PaymentInformationIdentification	<PmtInflId>		[0..1]		80
	InstructionIdentification	<InstrId>		[0..1]		80
	EndToEndIdentification	<EndToEndId>		[0..1]		80
	UETR	<UETR>		[0..1]		81
	InstructedAmount	<InstdAmt>		[1..1]		81
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		81
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		81

Rules

R15 IdentificationRule ✓

Either InstructionIdentification or EndToEndIdentification or both must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00092
- *Error Text:* Invalid message content as no identification of transaction is present.

R16 RequestedDateRule ✓

Either RequestedExecutionDate or RequestedCollectionDate must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00093
- *Error Text:* Invalid message content as no date of transaction is present.

Used in element(s)

"Initiation" on page 82

5.37.1 GroupHeader

XML Tag: GrpHdr

Presence: [0..1]

Definition: Set of elements used to provide corrective information for the group header of the message under investigation.

The **GrpHdr** block contains the following elements (see datatype "[CorrectiveGroupInformation1](#)" on page 75 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MessageIdentification	<MsgId>		[1..1]		75
	MessageNameIdentification	<MsgNmId>		[1..1]		76
	CreationDateTime	<CreDtTm>		[0..1]		76

5.37.2 PaymentInformationIdentification

XML Tag: PmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by a sending party, to unambiguously identify the payment information group within the message.

Datatype: "[Max35Text](#)" on page 305

5.37.3 InstructionIdentification

XML Tag: InstrId

Presence: [0..1]

Definition: Unique identification, as assigned by an instructing party for an instructed party, to unambiguously identify the instruction.

Usage: The instruction identification is a point to point reference that can be used between the instructing party and the instructed party to refer to the individual instruction. It can be included in several messages related to the instruction.

Datatype: "[Max35Text](#)" on page 305

5.37.4 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the initiating party, to unambiguously identify the transaction. This identification is passed on, unchanged, throughout the entire end-to-end chain.

Usage: The end-to-end identification can be used for reconciliation or to link tasks relating to the transaction. It can be included in several messages related to the transaction.

Usage: In case there are technical limitations to pass on multiple references, the end-to-end identification must be passed on throughout the entire end-to-end chain.

Datatype: "[Max35Text](#)" on page 305

5.37.5 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 317](#)

5.37.6 InstructedAmount

XML Tag: InstdAmt

Presence: [1..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.37.7 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [0..1]

Definition: Date or date time at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date or date time on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

The **ReqdExctnDt** block contains the following elements (see datatype ["DateAndDateTime2Choice" on page 85](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		86
	DateTime	<DtTm>	Or}	[1..1]		86

5.37.8 RequestedCollectionDate

XML Tag: ReqdColltnDt

Presence: [0..1]

Definition: Date at which the creditor requests the amount of money to be collected from the debtor.

Datatype: ["ISODate" on page 301](#)

5.38 CorrectiveTransaction4Choice

Definition: Specifies the corrective transaction on which the investigation is processed.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Initiation	<Initn>	{Or	[1..1]		82
	Interbank	<IntrBk>	Or}	[1..1]		82

Used in element(s)

"CorrectionTransaction" on page 23

5.38.1 Initiation

XML Tag: Initn

Presence: [1..1]

Definition: Set of elements used to reference the details of the corrective payment initiation.

The **Initn** block contains the following elements (see datatype "[CorrectivePaymentInitiation4](#)" on page 78 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupHeader	<GrpHdr>		[0..1]		79
	PaymentInformationIdentification	<PmtInflId>		[0..1]		80
	InstructionIdentification	<InstrId>		[0..1]		80
	EndToEndIdentification	<EndToEndId>		[0..1]		80
	UETR	<UETR>		[0..1]		81
	InstructedAmount	<InstAmt>		[1..1]		81
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		81
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		81

5.38.2 Interbank

XML Tag: IntrBk

Presence: [1..1]

Definition: Set of elements used to reference the details of the corrective interbank payment transaction.

The **IntrBk** block contains the following elements (see datatype "[CorrectiveInterbankTransaction2](#)" on page 76 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	GroupHeader	<GrpHdr>		[0..1]		77
	InstructionIdentification	<InstrId>		[0..1]		77
	EndToEndIdentification	<EndToEndId>		[0..1]		77
	TransactionIdentification	<TxId>		[0..1]		78
	UETR	<UETR>		[0..1]		78
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[1..1]		78
	InterbankSettlementDate	<IntrBkSttlmDt>		[1..1]		78

5.39 CreditorReferenceInformation2

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		83
	Reference	<Ref>		[0..1]		83

Used in element(s)

"CreditorReferenceInformation" on page 240

5.39.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of creditor reference.

The **Tp** block contains the following elements (see datatype "CreditorReferenceType2" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		85
	Issuer	<Issr>		[0..1]		85

5.39.2 Reference

XML Tag: Ref

Presence: [0..1]

Definition: Unique reference, as assigned by the creditor, to unambiguously refer to the payment transaction.

Usage: If available, the initiating party should provide this reference in the structured remittance information, to enable reconciliation by the creditor upon receipt of the amount of money.

If the business context requires the use of a creditor reference or a payment remit identification, and only one identifier can be passed through the end-to-end chain, the creditor's reference or payment remittance identification should be quoted in the end-to-end transaction identification.

Datatype: ["Max35Text" on page 305](#)

5.40 CreditorReferenceType1Choice

Definition: Specifies the type of document referred by the creditor.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		84
	Proprietary	<Prtry>	Or}	[1..1]		84

Used in element(s)

["CodeOrProprietary" on page 85](#)

5.40.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Type of creditor reference, in a coded form.

Datatype: ["DocumentType3Code" on page 278](#)

5.40.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Creditor reference type, in a proprietary form.

Datatype: ["Max35Text" on page 305](#)

5.41 CreditorReferenceType2

Definition: Specifies the type of creditor reference.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		85
	Issuer	<Issr>		[0..1]		85

Used in element(s)

"Type" on page 83

5.41.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Coded or proprietary format creditor reference type.

The **CdOrPrtry** block contains the following elements (see datatype "[CreditorReferenceType1Choice](#)" on page 84 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		84
	Proprietary	<Prtry>	Or}	[1..1]		84

5.41.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the credit reference type.

Datatype: "[Max35Text](#)" on page 305

5.42 DateAndDate2Choice

Definition: Choice between a date or a date and time format.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		86
	DateTime	<DtTm>	Or}	[1..1]		86

Used in element(s)

"OriginalRequestedExecutionDate" on page 190, "RequestedExecutionDate" on page 81, "RequestedExecutionDate" on page 151

5.42.1 Date

XML Tag: Dt

Presence: [1..1]

Definition: Specified date.

Datatype: "ISODate" on page 301

5.42.2 DateTime

XML Tag: DtTm

Presence: [1..1]

Definition: Specified date and time.

Datatype: "ISODateTime" on page 301

5.43 DateAndPlaceOfBirth1

Definition: Date and place of birth of a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -

📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		86
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		86
	CityOfBirth	<CityOfBirth>		[1..1]		87
	CountryOfBirth	<CtryOfBirth>		[1..1]		87

Used in element(s)

"DateAndPlaceOfBirth" on page 200

5.43.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "ISODate" on page 301

5.43.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["Max35Text" on page 305](#)

5.43.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["Max35Text" on page 305](#)

5.43.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 277](#)

5.44 DateAndPlaceOfBirth1__1

Definition: Date and place of birth of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		87
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		88
	CityOfBirth	<CityOfBirth>		[1..1]		88
	CountryOfBirth	<CtryOfBirth>		[1..1]		88

Used in element(s)

["DateAndPlaceOfBirth" on page 201](#)

5.44.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: ["CBPR_Date" on page 269](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/BirthDate](#)

Type changed to: [CBPR_Date](#) on page 269

5.44.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended"](#) on page 273

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/ProvinceOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended](#) on page 273

5.44.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended"](#) on page 273

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended](#) on page 273

5.44.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode"](#) on page 277

5.45 DateAndPlaceOfBirth1__2

Definition: Date and place of birth of a person.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		89
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		89
	CityOfBirth	<CityOfBirth>		[1..1]		89
	CountryOfBirth	<CtryOfBirth>		[1..1]		90

Used in element(s)

"DateAndPlaceOfBirth" on page 203

5.45.1 BirthDate

XML Tag: BirthDt

Presence: [1..1]

Definition: Date on which a person is born.

Datatype: "CBPR_Date" on page 269

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/Birth-Date

Type changed to: CBPR_Date on page 269

5.45.2 ProvinceOfBirth

XML Tag: PrvcOfBirth

Presence: [0..1]

Definition: Province where a person was born.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOf-Birth/ProvinceOfBirth

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.45.3 CityOfBirth

XML Tag: CityOfBirth

Presence: [1..1]

Definition: City where a person was born.

Datatype: ["CBPR_RestrictedFINXMax35Text" on page 272](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/DateAndPlaceOfBirth/CityOfBirth](#)

Type changed to: [CBPR_RestrictedFINXMax35Text on page 272](#)

5.45.4 CountryOfBirth

XML Tag: CtryOfBirth

Presence: [1..1]

Definition: Country where a person was born.

Datatype: ["CountryCode" on page 277](#)

5.46 DatePeriod2

Definition: Range of time defined by a start date and an end date.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		90
	ToDate	<ToDt>		[1..1]		90

Used in element(s)

["FromToDate" on page 253](#)

5.46.1 FromDate

XML Tag: FrDt

Presence: [1..1]

Definition: Start date of the range.

Datatype: ["ISODate" on page 301](#)

5.46.2 ToDate

XML Tag: ToDt

Presence: [1..1]

Definition: End date of the range.

Datatype: ["ISODate" on page 301](#)

5.47 DiscountAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		91
	Amount	<Amt>		[1..1]		91

Used in element(s)

["DiscountAppliedAmount" on page 223](#), ["DiscountAppliedAmount" on page 225](#)

5.47.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype ["DiscountAmountType1Choice" on page 91](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		92
	Proprietary	<Prtry>	Or}	[1..1]		92

5.47.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.48 DiscountAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		92
	Proprietary	<Prtry>	Or}	[1..1]		92

Used in element(s)

"Type" on page 91

5.48.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalDiscountAmountType1Code" on page 287

5.48.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 305

5.49 DocumentAdjustment1

Definition: Set of elements used to provide information on the amount and reason of the document adjustment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		92
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		93
	Reason	<Rsn>		[0..1]		93
	AdditionalInformation	<AddtlInf>		[0..1]		93

Used in element(s)

"AdjustmentAmountAndReason" on page 224, "AdjustmentAmountAndReason" on page 226

5.49.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money of the document adjustment.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.49.2 CreditDebitIndicator

XML Tag: CdtDbtInd

Presence: [0..1]

Definition: Specifies whether the adjustment must be subtracted or added to the total amount.

Datatype: ["CreditDebitCode" on page 277](#)

5.49.3 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the adjustment.

Datatype: ["Max4Text" on page 305](#)

5.49.4 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Provides further details on the document adjustment.

Datatype: ["Max140Text" on page 303](#)

5.50 DocumentLineIdentification1

Definition: Identifies the documents referred to in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		93
	Number	<Nb>		[0..1]		94
	RelatedDate	<RltdDt>		[0..1]		94

Used in element(s)

["Identification" on page 94](#)

5.50.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document line identification.

The **Tp** block contains the following elements (see datatype "[DocumentLineType1](#)" on page 95 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		96
	Issuer	<Issr>		[0..1]		96

5.50.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Identification of the type specified for the referred document line.

Datatype: "[Max35Text](#)" on page 305

5.50.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document line.

Datatype: "[ISODate](#)" on page 301

5.51 DocumentLineInformation1

Definition: Provides document line information.

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		94
	Description	<Desc>		[0..1]		95
	Amount	<Amt>		[0..1]		95

Used in element(s)

["LineDetails"](#) on page 220

5.51.1 Identification

XML Tag: Id

Presence: [1..*]

Definition: Provides identification of the document line.

The **Id** block contains the following elements (see datatype "[DocumentLineIdentification1](#)" on page 93 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		93
	Number	<Nb>		[0..1]		94
	RelatedDate	<RltdDt>		[0..1]		94

5.51.2 Description

XML Tag: Desc

Presence: [0..1]

Definition: Description associated with the document line.

Datatype: "[Max2048Text](#)" on page 304

5.51.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Provides details on the amounts of the document line.

The **Amt** block contains the following elements (see datatype "[RemittanceAmount3](#)" on page 224 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		225
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		225
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		225
	TaxAmount	<TaxAmt>		[0..*]		225
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		226
	RemittedAmount	<RmtdAmt>		[0..1]		226

5.52 DocumentLineType1

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		96
	Issuer	<Issr>		[0..1]		96

Used in element(s)

"Type" on page 93

5.52.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document line identification.

The **CdOrPrtry** block contains the following elements (see datatype "[DocumentLineType1Choice](#)" on page 96 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

5.52.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document line identificationtype.

Datatype: "[Max35Text](#)" on page 305

5.53 DocumentLineType1Choice

Definition: Specifies the type of the document line identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		97
	Proprietary	<Prtry>	Or}	[1..1]		97

Used in element(s)

"CodeOrProprietary" on page 96

5.53.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Line identification type in a coded form.

Datatype: ["ExternalDocumentLineType1Code" on page 288](#)

5.53.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: ["Max35Text" on page 305](#)

5.54 EquivalentAmount2

Definition: Amount of money to be moved between the debtor and creditor, expressed in the currency of the debtor's account, and the currency in which the amount is to be moved.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		97
	CurrencyOfTransfer	<CcyOfTrf>		[1..1]		97

Used in element(s)

["EquivalentAmount" on page 33](#)

5.54.1 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money to be moved between debtor and creditor, before deduction of charges, expressed in the currency of the debtor's account, and to be moved in a different currency.

Usage: The first agent will convert the equivalent amount into the amount to be moved.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.54.2 CurrencyOfTransfer

XML Tag: CcyOfTrf

Presence: [1..1]

Definition: Specifies the currency of the to be transferred amount, which is different from the currency of the debtor's account.

Datatype: "ActiveOrHistoricCurrencyCode" on page 264

5.55 FinancialIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		98
	Proprietary	<Prtry>	Or}	[1..1]		98

Used in element(s)

"SchemeName" on page 116

5.55.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalFinancialInstitutionIdentification1Code" on page 288

5.55.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 305

5.56 FinancialInstitutionIdentification18

Definition: Specifies the details to identify a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		99
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		99
	LEI	<LEI>		[0..1]		99
	Name	<Nm>		[0..1]		99
	PostalAddress	<PstlAdr>		[0..1]		100

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Other	<Othr>		[0..1]		100

Used in element(s)

"FinancialInstitutionIdentification" on page 34

5.56.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 266

5.56.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2" on page 67 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		67
	MemberIdentification	<Mmbld>		[1..1]		68

5.56.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 302

5.56.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 303

5.56.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24" on page 205 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		206
	Department	<Dept>		[0..1]		206
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		207
	Floor	<Flr>		[0..1]		207
	PostBox	<PstBx>		[0..1]		207
	Room	<Room>		[0..1]		207
	PostCode	<PstCd>		[0..1]		207
	TownName	<TwnNm>		[0..1]		208
	TownLocationName	<TwnLctnNm>		[0..1]		208
	DistrictName	<DstrctNm>		[0..1]		208
	CountrySubDivision	<CtrySubDvsn>		[0..1]		208
	Country	<Ctry>		[0..1]		208
	AddressLine	<AdrLine>		[0..7]		208

5.56.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 115 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		116
	SchemeName	<SchmeNm>		[0..1]		116
	Issuer	<Issr>		[0..1]		116

5.57 FinancialInstitutionIdentification18__1

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		101
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		102
	LEI	<LEI>		[0..1]		102
	Name	<Nm>		[0..1]		102
	PostalAddress	<PstlAdr>		[0..1]		103
	Other	<Othr>		[0..1]		104

Used in element(s)

"FinancialInstitutionIdentification" on page 35

5.57.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 266

Usage Guideline details

- on camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**
This element is now mandatory, the minimum occurrence has been changed to : 1
- on camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/BICFI**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.57.2 ClearingSystemMemberIdentification

XML Tag: **ClrSysMmbld**

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 68 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below - **M** Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]	M	68
	MemberIdentification	<Mmbld>		[1..1]	⚠	69

5.57.3 LEI

XML Tag: **LEI**

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 302

5.57.4 Name

XML Tag: **Nm**

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "Max140Text" on page 303

Usage Guideline details

- This element(**camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name**) is removed.

- This element(`camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/Name`) is removed.
- This element(`camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name`) is removed.
- This element(`camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name`) is removed.
- This element(`camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/Name`) is removed.
- This element(`camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Name`) is removed.

5.57.5 PostalAddress

XML Tag: `PstlAdr`

Presence: `[0..1]`

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "[PostalAddress24](#)" on [page 205](#) for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		206
	Department	<Dept>		[0..1]		206
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		207
	Floor	<Flr>		[0..1]		207
	PostBox	<PstBx>		[0..1]		207
	Room	<Room>		[0..1]		207
	PostCode	<PstCd>		[0..1]		207
	TownName	<TwnNm>		[0..1]		208
	TownLocationName	<TwnLctnNm>		[0..1]		208
	DistrictName	<DstrctNm>		[0..1]		208
	CountrySubDivision	<CtrySubDvsn>		[0..1]		208
	Country	<Ctry>		[0..1]		208

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressLine	<AdrLine>		[0..7]		208

Usage Guideline details

- This element(camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/PostalAddress) is removed.

5.57.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 115 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		116
	SchemeName	<SchmeNm>		[0..1]		116
	Issuer	<Issr>		[0..1]		116

Usage Guideline details

- This element(camt.029.001.09/.header/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other) is removed.
- This element(camt.029.001.09/Assignment/Assigner/Agent/FinancialInstitutionIdentification/Other) is removed.

- This element(`camt.029.001.09/.header/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.029.001.09/.header/Related/To/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.029.001.09/.header/Related/From/FinancialInstitutionIdentification/FinancialInstitutionIdentification/Other`) is removed.
- This element(`camt.029.001.09/Assignment/Assignee/Agent/FinancialInstitutionIdentification/Other`) is removed.

5.58 FinancialInstitutionIdentification18__2

Definition: Specifies the details to identify a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BICFI	<BICFI>		[0..1]		105
	ClearingSystemMemberIdentification	<ClrSysMmbld>		[0..1]		105
	LEI	<LEI>		[0..1]		106
	Name	<Nm>		[0..1]		106
	PostalAddress	<PstlAdr>		[0..1]		106
	Other	<Othr>		[0..1]		107

Used in element(s)

"FinancialInstitutionIdentification" on page 37

5.58.1 BICFI

XML Tag: BICFI

Presence: [0..1]

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362 "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Datatype: "BICFIDec2014Identifier" on page 266

5.58.2 ClearingSystemMemberIdentification

XML Tag: ClrSysMmbld

Presence: [0..1]

Definition: Information used to identify a member within a clearing system.

The **ClrSysMmbld** block contains the following elements (see datatype "ClearingSystemMemberIdentification2__1" on page 68 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingSystemIdentification	<ClrSysId>		[0..1]		68
	MemberIdentification	<MmbId>		[1..1]		69

5.58.3 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identifier of the financial institution.

Datatype: "LEIIdentifier" on page 302

5.58.4 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which an agent is known and which is usually used to identify that agent.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 271

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 271

5.58.5 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 209 for details)

Removed - Partial Removed - Ignored - Partial Ignored - Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		209
	Department	<Dept>		[0..1]		210
	SubDepartment	<SubDept>		[0..1]		210
	StreetName	<StrtNm>		[0..1]		211

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BuildingNumber	<BldgNb>		[0..1]		211
	BuildingName	<BldgNm>		[0..1]		212
	Floor	<Flr>		[0..1]		212
	PostBox	<PstBx>		[0..1]		213
	Room	<Room>		[0..1]		213
	PostCode	<PstCd>		[0..1]		214
	TownName	<TwnNm>		[0..1]	 	214
	TownLocationName	<TwnLctnNm>		[0..1]		215
	DistrictName	<DstrctNm>		[0..1]		215
	CountrySubDivision	<CtrySubDvsn>		[0..1]		216
	Country	<Ctry>		[0..1]		216
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	217

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress
 - CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.58.6 Other

XML Tag: Othr

Presence: [0..1]

Definition: Unique identification of an agent, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericFinancialIdentification1" on page 115 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		116
	SchemeName	<SchmeNm>		[0..1]		116
	Issuer	<Issr>		[0..1]		116

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/Other](#)) is removed.

5.59 Frequency36Choice

Definition: Choice of format for a frequency, for example, the frequency of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		108
	Period	<Prd>	Or	[1..1]		108
	PointInTime	<PtInTm>	Or}	[1..1]		108

Used in element(s)

"Frequency" on page 129, "OriginalFrequency" on page 32

5.59.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies a frequency in terms of a specified period type.

Datatype: "Frequency6Code" on page 298

5.59.2 Period

XML Tag: Prd

Presence: [1..1]

Definition: Specifies a frequency in terms of a count per period within a specified period type.

The **Prd** block contains the following elements (see datatype "FrequencyPeriod1" on page 109 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		110
	CountPerPeriod	<CntPerPrd>		[1..1]		110

5.59.3 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Specifies a frequency in terms of an exact point in time or moment within a specified period type.

The **PtInTm** block contains the following elements (see datatype "[FrequencyAndMoment1](#)" on [page 109](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		109
	PointInTime	<PtInTm>		[1..1]		109

5.60 FrequencyAndMoment1

Definition: Defines a frequency in terms a specific moment within a specified period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		109
	PointInTime	<PtInTm>		[1..1]		109

Used in element(s)

"[PointInTime](#)" on [page 108](#)

5.60.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: "[Frequency6Code](#)" on [page 298](#)

5.60.2 PointInTime

XML Tag: PtInTm

Presence: [1..1]

Definition: Further information on the exact point in time the event should take place.

Datatype: "[Exact2NumericText](#)" on [page 281](#)

5.61 FrequencyPeriod1

Definition: Defines a frequency in terms on counts per period for a specific period type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		110
	CountPerPeriod	<CntPerPrd>		[1..1]		110

Used in element(s)

"Period" on page 108

5.61.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Period for which the number of instructions are to be created and processed.

Datatype: "Frequency6Code" on page 298

5.61.2 CountPerPeriod

XML Tag: CntPerPrd

Presence: [1..1]

Definition: Number of instructions to be created and processed during the specified period.

Datatype: "DecimalNumber" on page 278

5.62 Garnishment3

Definition: Provides remittance information about a payment for garnishment-related purposes.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		111
	Garnishee	<Grnshee>		[0..1]		111
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		111
	ReferenceNumber	<RefNb>		[0..1]		112
	Date	<Dt>		[0..1]		112
	RemittedAmount	<RmtdAmt>		[0..1]		112
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrncInd>		[0..1]		112
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		112

Used in element(s)

"GarnishmentRemittance" on page 242

5.62.1 Type

XML Tag: Tp

Presence: [1..1]

Definition: Specifies the type of garnishment.

The **Tp** block contains the following elements (see datatype "GarnishmentType1" on page 113 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		113
	Issuer	<Issr>		[0..1]		113

5.62.2 Garnishee

XML Tag: Grnshee

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the garnisher.

The **Grnshee** block contains the following elements (see datatype "PartyIdentification135" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.62.3 GarnishmentAdministrator

XML Tag: GrnshmtAdmstr

Presence: [0..1]

Definition: Party on the credit side of the transaction who administers the garnishment on behalf of the ultimate beneficiary.

The **GrnshmtAdmstr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.62.4 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Reference information that is specific to the agency receiving the garnishment.

Datatype: "[Max140Text](#)" on page 303

5.62.5 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date of payment which garnishment was taken from.

Datatype: "[ISODate](#)" on page 301

5.62.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 263

5.62.7 FamilyMedicalInsuranceIndicator

XML Tag: FmlyMdclInsrncInd

Presence: [0..1]

Definition: Indicates if the person to whom the garnishment applies (that is, the ultimate debtor) has family medical insurance coverage available.

Datatype: "[TrueFalseIndicator](#)" on page 317

5.62.8 EmployeeTerminationIndicator

XML Tag: MplyeeTermntnInd

Presence: [0..1]

Definition: Indicates if the employment of the person to whom the garnishment applies (that is, the ultimate debtor) has been terminated.

Datatype: ["TrueFalseIndicator" on page 317](#)

5.63 GarnishmentType1

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		113
	Issuer	<Issr>		[0..1]		113

Used in element(s)

["Type" on page 111](#)

5.63.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the garnishment.

The **CdOrPrtry** block contains the following elements (see datatype ["GarnishmentType1Choice" on page 113](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

5.63.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the garnishment type.

Datatype: ["Max35Text" on page 305](#)

5.64 GarnishmentType1Choice

Definition: Specifies the type of garnishment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		114
	Proprietary	<Prtry>	Or}	[1..1]		114

Used in element(s)

"CodeOrProprietary" on page 113

5.64.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Garnishment type in a coded form.

Would suggest this to be an External Code List to contain:

GNCS Garnishment from a third party payer for Child Support

GNDP Garnishment from a Direct Payer for Child Support

GTPP Garnishment from a third party payer to taxing agency.

Datatype: "ExternalGarnishmentType1Code" on page 289

5.64.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of garnishment.

Datatype: "Max35Text" on page 305

5.65 GenericAccountIdentification1

Definition: Information related to a generic account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		115
	SchemeName	<SchmeNm>		[0..1]		115
	Issuer	<Issr>		[0..1]		115

Used in element(s)

"Other" on page 26

5.65.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "Max34Text" on page 304

5.65.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "AccountSchemeName1Choice" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		27

5.65.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 305

5.66 GenericFinancialIdentification1

Definition: Information related to an identification of a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		116
	SchemeName	<SchmeNm>		[0..1]		116
	Issuer	<Issr>		[0..1]		116

Used in element(s)

"Other" on page 100, "Other" on page 104, "Other" on page 107

5.66.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 305

5.66.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[FinancialIdentificationScheme-Name1Choice](#)" on page 98 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		98
	Proprietary	<Prtry>	Or}	[1..1]		98

5.66.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 305

5.67 GenericIdentification3

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		117
	Issuer	<Issr>		[0..1]		117

Used in element(s)

"Proprietary" on page 58

5.67.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Name or number assigned by an entity to enable recognition of that entity, for example, account identifier.

Datatype: "Max35Text" on page 305

5.67.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 305

5.68 GenericIdentification30

Definition: Information related to an identification, for example, party identification or account identification.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		117
	Issuer	<Issr>		[1..1]		117
	SchemeName	<SchmeNm>		[0..1]		118

Used in element(s)

"Proprietary" on page 28

5.68.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Proprietary information, often a code, issued by the data source scheme issuer.

Datatype: "Exact4AlphaNumericText" on page 281

5.68.2 Issuer

XML Tag: Issr

Presence: [1..1]

Definition: Entity that assigns the identification.

Datatype: ["Max35Text" on page 305](#)

5.68.3 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Short textual description of the scheme.

Datatype: ["Max35Text" on page 305](#)

5.69 GenericOrganisationIdentification1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		118
	SchemeName	<SchmeNm>		[0..1]		118
	Issuer	<Issr>		[0..1]		119

Used in element(s)

["Other" on page 135](#)

5.69.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: ["Max35Text" on page 305](#)

5.69.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype ["OrganisationIdentificationSchemeName1Choice" on page 137](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		137

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Proprietary	<Prtry>	Or}	[1..1]		137

5.69.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 305

5.70 GenericOrganisationIdentification1__1

Definition: Information related to an identification of an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		119
	SchemeName	<SchmeNm>		[0..1]		119
	Issuer	<Issr>		[0..1]		120

Used in element(s)

"Other" on page 136

5.70.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification assigned by an institution.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/OrganisationIdentification/Other/Identification
 Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other/Identification
 Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.70.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "[OrganisationIdentificationSchemeName1Choice__1](#)" on page 138 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		138
	Proprietary	<Prtry>	Or}	[1..1]	🚫 ⚠	138

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other/SchemeName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1
- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName](#)
This element is now mandatory, the minimum occurrence has been changed to : 1

5.70.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "[CBPR_RestrictedFINXMax35Text](#)" on page 272

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/OrganisationIdentification/Other/Issuer](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 272
- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other/Issuer](#)
Type changed to: [CBPR_RestrictedFINXMax35Text](#) on page 272

5.71 GenericPersonIdentification1

Definition: Information related to an identification of a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		121
	SchemeName	<SchmeNm>		[0..1]		121
	Issuer	<Issr>		[0..1]		121

Used in element(s)

"Other" on page 201

5.71.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "Max35Text" on page 305

5.71.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice" on page 203 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		204
	Proprietary	<Prtry>	Or}	[1..1]		204

5.71.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "Max35Text" on page 305

5.72 GenericPersonIdentification1__1

Definition: Information related to an identification of a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		122
	SchemeName	<SchmeNm>		[0..1]		122
	Issuer	<Issr>		[0..1]		123

Used in element(s)

"Other" on page 202, "Other" on page 203

5.72.1 Identification

XML Tag: Id

Presence: [1..1]

Definition: Unique and unambiguous identification of a person.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/Other/Identification
Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other/Identification
Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.72.2 SchemeName

XML Tag: SchmeNm

Presence: [0..1]

Definition: Name of the identification scheme.

The **SchmeNm** block contains the following elements (see datatype "PersonIdentificationScheme-Name1Choice_1" on page 204 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		204
	Proprietary	<Prtry>	Or}	[1..1]	 	205

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other/SchemeName**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.72.3 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Entity that assigns the identification.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/Other/Issuer**

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other/Issuer**

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.73 ImplementationSpecification1

Definition: Identifies the implementation specification to which the ISO 20022 message conforms.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Registry	<Regy>		[1..1]		123
	Identification	<Id>		[1..1]		124

Used in element(s)

"MarketPractice" on page 16

5.73.1 Registry

XML Tag: Regy

Presence: [1..1]

Definition: Name of the implementation specification registry in which the implementation specification of the ISO 20022 message is maintained.

For example, "MyStandards".

Datatype: "Max350Text" on page 304

5.73.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identifier which unambiguously identifies, within the implementation specification registry, the implementation specification to which the ISO 20022 message is compliant. This can be done via a URN. It can also contain a version number or date.

For instance, "2018-01-01 - Version 2" or "urn:uuid:6e8bc430-9c3a-11d9-9669-0800200c9a66".

Datatype: "Max2048Text" on page 304

5.74 InvestigationStatus5Choice__1

Definition: Specifies the status of an investigation case.

🚫 Removed - 🚫 Partial Removed - ⚠ Ignored - ⚠ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Confirmation	<Conf>	{Or	[1..1]	⚠	124
	RejectedModification	<RjctdMod>	Or	[1..*]	🚫	125
	DuplicateOf	<DplctOf>	Or	[1..1]	🚫	125
	AssignmentCancellationConfirmation	<AssgnmtCxlConf>	Or}	[1..1]	🚫	125

Used in element(s)

"Status" on page 20

5.74.1 Confirmation

XML Tag: Conf

Presence: [1..1]

Definition: Specifies the status of the investigation, in a coded form.

Datatype: "CBPR_CancellationStatus" on page 267

Usage Guideline details

- on camt.029.001.09/Status/Confirmation
Type changed to: CBPR_CancellationStatus on page 267

5.74.2 RejectedModification

XML Tag: RjctdMod

Presence: [1..*]

Definition: Reason for the rejection of a modification request, in a coded form.

The **RjctdMod** block contains the following elements (see datatype "[ModificationStatusReason1Choice](#)" on page 131 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		131
	Proprietary	<Prtry>	Or}	[1..1]		131

Usage Guideline details

- This element([camt.029.001.09/Status/RejectedModification](#)) is removed.

5.74.3 DuplicateOf

XML Tag: DplctOf

Presence: [1..1]

Definition: Indicates a duplicated case.

Usage: When present, the case identified in the message must be closed. The case identified as duplicated (in this component) will be pursued.

The **DplctOf** block contains the following elements (see datatype "[Case5](#)" on page 50 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - 🟡 Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

Usage Guideline details

- This element([camt.029.001.09/Status/DuplicateOf](#)) is removed.

5.74.4 AssignmentCancellationConfirmation

XML Tag: AssgnmtCxlConf

Presence: [1..1]

Definition: Indicates whether the cancellation of the assignment is confirmed or rejected.

Usage: If yes, the cancellation of the assignment is confirmed.

If no, the cancellation of the assignment is rejected and the investigation process will continue.

Datatype: ["YesNoIndicator" on page 318](#)

Usage Guideline details

- This element([camt.029.001.09/Status/AssignmentCancellationConfirmation](#)) is removed.

5.75 LocalInstrument2Choice

Definition: Set of elements that further identifies the type of local instruments being requested by the initiating party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		126
	Proprietary	<Prtry>	Or}	[1..1]		126

Used in element(s)

["LocalInstrument" on page 199](#)

5.75.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the local instrument, as published in an external local instrument code list.

Datatype: ["ExternalLocalInstrument1Code" on page 290](#)

5.75.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the local instrument, as a proprietary code.

Datatype: ["Max35Text" on page 305](#)

5.76 MandateRelatedInformation14

Definition: Provides further details related to a direct debit mandate signed between the creditor and the debtor.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		127
	DateOfSignature	<DtOfSgntr>		[0..1]		128
	AmendmentIndicator	<AmdmntInd>		[0..1]		128
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		128
	ElectronicSignature	<ElctrncSgntr>		[0..1]		129
	FirstCollectionDate	<FrstColltnDt>		[0..1]		129
	FinalCollectionDate	<FnlColltnDt>		[0..1]		129
	Frequency	<Frqcy>		[0..1]		129
	Reason	<Rsn>		[0..1]		129
	TrackingDays	<TrckgDays>		[0..1]		130

Rules

R19 AmendmentIndicatorTrueRule ✓

If AmendmentIndicator is true, then AmendmentInformationDetails must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00012
- *Error Text:* Invalid message content for true amendment indicator and details.

R20 AmendmentIndicatorFalseRule ✓

If AmendmentIndicator is false, then AmendmentInformationDetails is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00013
- *Error Text:* Invalid message content for false amendment indicator and details.

Used in element(s)

"MandateRelatedInformation" on page 153

5.76.1 MandateIdentification

XML Tag: MndtId

Presence: [0..1]

Definition: Unique identification, as assigned by the creditor, to unambiguously identify the mandate.

Datatype: ["Max35Text" on page 305](#)

5.76.2 DateOfSignature

XML Tag: DtOfSgntr

Presence: [0..1]

Definition: Date on which the direct debit mandate has been signed by the debtor.

Datatype: ["ISODate" on page 301](#)

5.76.3 AmendmentIndicator

XML Tag: AmdmntInd

Presence: [0..1]

Definition: Indicator notifying whether the underlying mandate is amended or not.

Datatype: ["TrueFalseIndicator" on page 317](#)

5.76.4 AmendmentInformationDetails

XML Tag: AmdmntInfDtls

Presence: [0..1]

Definition: List of mandate elements that have been modified.

The **AmdmntInfDtls** block contains the following elements (see datatype ["AmendmentInformationDetails13" on page 28](#) for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMandateIdentification	<OrgnlMndtId>		[0..1]		29
	OriginalCreditorSchemeIdentification	<OrgnlCdtrSchmeld>		[0..1]		29
	OriginalCreditorAgent	<OrgnlCdtrAgt>		[0..1]		29
	OriginalCreditorAgentAccount	<OrgnlCdtrAgtAcct>		[0..1]		30
	OriginalDebtor	<OrgnlDbtr>		[0..1]		30
	OriginalDebtorAccount	<OrgnlDbtrAcct>		[0..1]		30
	OriginalDebtorAgent	<OrgnlDbtrAgt>		[0..1]		31
	OriginalDebtorAgentAccount	<OrgnlDbtrAgtAcct>		[0..1]		31
	OriginalFinalCollectionDate	<OrgnlFnlColltnDt>		[0..1]		32
	OriginalFrequency	<OrgnlFrqcy>		[0..1]		32
	OriginalReason	<OrgnlRsn>		[0..1]		32
	OriginalTrackingDays	<OrgnlTrckgDays>		[0..1]		33

5.76.5 ElectronicSignature

XML Tag: ElctrncSgntr

Presence: [0..1]

Definition: Additional security provisions, such as a digital signature, as provided by the debtor.

Datatype: "Max1025Text" on page 302

5.76.6 FirstCollectionDate

XML Tag: FrstColltnDt

Presence: [0..1]

Definition: Date of the first collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 301

5.76.7 FinalCollectionDate

XML Tag: FnlColltnDt

Presence: [0..1]

Definition: Date of the final collection of a direct debit as per the mandate.

Datatype: "ISODate" on page 301

5.76.8 Frequency

XML Tag: Frqcy

Presence: [0..1]

Definition: Regularity with which direct debit instructions are to be created and processed.

The **Frqcy** block contains the following elements (see datatype "Frequency36Choice" on page 108 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>	{Or	[1..1]		108
	Period	<Prd>	Or	[1..1]		108
	PointInTime	<PtInTm>	Or}	[1..1]		108

5.76.9 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Reason for the direct debit mandate to allow the user to distinguish between different mandates for the same creditor.

The **Rsn** block contains the following elements (see datatype "[MandateSetupReason1Choice](#)" on page 130 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		130
	Proprietary	<Prtry>	Or}	[1..1]		130

5.76.10 TrackingDays

XML Tag: TrckgDays

Presence: [0..1]

Definition: Specifies the number of days the direct debit instruction must be tracked.

Datatype: "[Exact2NumericText](#)" on page 281

5.77 MandateSetupReason1Choice

Definition: Specifies the reason for the setup of the mandate.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		130
	Proprietary	<Prtry>	Or}	[1..1]		130

Used in element(s)

"[OriginalReason](#)" on page 32, "[Reason](#)" on page 129

5.77.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the mandate setup, as published in an external reason code list.

Datatype: "[ExternalMandateSetupReason1Code](#)" on page 291

5.77.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the mandate setup, in a proprietary form.

Datatype: "[Max70Text](#)" on page 306

5.78 ModificationStatusReason1Choice

Definition: Specifies the reason for the transaction modification status.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		131
	Proprietary	<Prtry>	Or}	[1..1]		131

Used in element(s)

"Reason" on page 132, "RejectedModification" on page 125

5.78.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Reason for the modification status, in a coded form.

Datatype: "ExternalPaymentModificationRejection1Code" on page 294

5.78.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Reason for the status, in a proprietary form.

Datatype: "Max35Text" on page 305

5.79 ModificationStatusReason2

Definition: Provides further details on the status of the cancellation request.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		131
	Reason	<Rsn>		[0..1]		132
	AdditionalInformation	<AddtlInf>		[0..*]		132

Used in element(s)

"ModificationStatusReasonInformation" on page 195

5.79.1 Originator

XML Tag: Orgtr

Presence: [0..1]

Definition: Party that issues the cancellation status.

The **Orgtr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.79.2 Reason

XML Tag: Rsn

Presence: [0..1]

Definition: Specifies the reason for the status report.

The **Rsn** block contains the following elements (see datatype "[ModificationStatusReason1Choice](#)" on page 131 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		131
	Proprietary	<Prtry>	Or}	[1..1]		131

5.79.3 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..*]

Definition: Further details on the cancellation status reason.

Datatype: "[Max105Text](#)" on page 302

5.80 NumberOfCancellationsPerStatus1

Definition: Set of elements used to provide detailed information on the number of transactions that are reported with a specific cancellation status.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		133
	DetailedStatus	<DtldSts>		[1..1]		133
	DetailedControlSum	<DtldCtrlSum>		[0..1]		133

Used in element(s)

"NumberOfTransactionsPerCancellationStatus" on page 148

5.80.1 DetailedNumberOfTransactions

XML Tag: DtldNbOfTxs

Presence: [1..1]

Definition: Number of individual cancellation requests contained in the message, detailed per status.

Datatype: "Max15NumericText" on page 303

5.80.2 DetailedStatus

XML Tag: DtldSts

Presence: [1..1]

Definition: Common cancellation request status for all individual cancellation requests reported.

Datatype: "CancellationIndividualStatus1Code" on page 274

5.80.3 DetailedControlSum

XML Tag: DtldCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies, detailed per status.

Datatype: "DecimalNumber" on page 278

5.81 NumberOfTransactionsPerStatus1

Definition: Set of additional elements to provide detailed information on the number of transactions that are reported with a specific transaction status.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		134
	DetailedStatus	<DtldSts>		[1..1]		134

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedControlSum	<DtldCtrlSum>		[0..1]		134

Used in element(s)

"NumberOfTransactionsPerCancellationStatus" on page 142

5.81.1 DetailedNumberOfTransactions

XML Tag: DtldNbOfTxS

Presence: [1..1]

Definition: Number of individual transactions contained in the message, detailed per status.

Datatype: "Max15NumericText" on page 303

5.81.2 DetailedStatus

XML Tag: DtldSts

Presence: [1..1]

Definition: Common transaction status for all individual transactions reported with the same status.

Datatype: "TransactionIndividualStatus1Code" on page 316

5.81.3 DetailedControlSum

XML Tag: DtldCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the message, irrespective of currencies, detailed per status.

Datatype: "DecimalNumber" on page 278

5.82 OrganisationIdentification29

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		135
	LEI	<LEI>		[0..1]		135
	Other	<Othr>		[0..*]		135

Used in element(s)

"OrganisationIdentification" on page 159

5.82.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: ["AnyBICDec2014Identifier" on page 266](#)

5.82.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: ["LEIIdentifier" on page 302](#)

Usage Guideline details

- This element([camt.029.001.09/Assignment/Assignee/Party/Identification/OrganisationIdentification/LEI](#)) is removed.

5.82.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype ["GenericOrganisationIdentification1" on page 118](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		118
	SchemeName	<SchmeNm>		[0..1]		118
	Issuer	<Issr>		[0..1]		119

Usage Guideline details

- This element([camt.029.001.09/.header/Related/To/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.
- This element([camt.029.001.09/.header/Related/From/OrganisationIdentification/Identification/OrganisationIdentification/Other](#)) is removed.

- This element(camt.029.001.09/Assignment/Assignee/Party/Identification/OrganisationIdentification/Other) is removed.

5.83 OrganisationIdentification29__1

Definition: Unique and unambiguous way to identify an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		136
	LEI	<LEI>		[0..1]		136
	Other	<Othr>		[0..*]	R[0..2] R[0..2]	136

Used in element(s)

"OrganisationIdentification" on page 161, "OrganisationIdentification" on page 162

5.83.1 AnyBIC

XML Tag: AnyBIC

Presence: [0..1]

Definition: Business identification code of the organisation.

Datatype: "AnyBICDec2014Identifier" on page 266

5.83.2 LEI

XML Tag: LEI

Presence: [0..1]

Definition: Legal entity identification as an alternate identification for a party.

Datatype: "LEIIdentifier" on page 302

5.83.3 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of an organisation, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericOrganisationIdentification1__1" on page 119 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		119
	SchemeName	<SchmeNm>		[0..1]		119
	Issuer	<Issr>		[0..1]		120

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other**
This element has change repeatability, the maximum occurrence has been changed to : 2

5.84 OrganisationIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		137
	Proprietary	<Prtry>	Or}	[1..1]		137

Used in element(s)

"SchemeName" on page 118

5.84.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 291

5.84.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 305

5.85 OrganisationIdentificationScheme-Name1Choice__1

Definition: Sets of elements to identify a name of the organisation identification scheme.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		138
	Proprietary	<Prtry>	Or}	[1..1]	 	138

Used in element(s)

"SchemeName" on page 119

5.85.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalOrganisationIdentification1Code" on page 291

5.85.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- This element(camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- This element(camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary) is removed.
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/Identification/OrganisationIdentification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/OrganisationIdentification/Other/SchemeName/Proprietary
Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.86 OriginalGroupHeader14

Definition: Provides the details on the original group, to which the message refers.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupCancellationIdentification	<OrgnlGrpCxIld>		[0..1]		139
	ResolvedCase	<RslvdCase>		[0..1]		140
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		140
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		140
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		141
	OriginalNumberOfTransactions	<OrgnlNbOfTxS>		[0..1]		141
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		141
	GroupCancellationStatus	<GrpCxISts>		[0..1]		141
	CancellationStatusReasonInformation	<CxIStsRsnInf>		[0..*]		141
	NumberOfTransactionsPerCancellationStatus	<NbOfTxSPerCxISts>		[0..*]		142

Rules

R22 CancellationStatusReasonInformationRule ✓

If GroupCancellationStatus is present and is different from RJCR or PNCR, then CancellationStatusReasonInformation/AdditionalInformation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00078
- *Error Text:* Invalid message content for additional cancellation status reason.

Guidelines

1. NumberOfTransactionsPerCancellationStatusGuideline

OriginalGroupInformationAndStatus/NumberOfTransactionsPerStatus should only be present if GroupCancellationStatus equals PACR.

Used in element(s)

"OriginalGroupInformationAndStatus" on page 258

5.86.1 OriginalGroupCancellationIdentification

XML Tag: OrgnlGrpCxIld

Presence: [0..1]

Definition: Unique identification, as assigned by the original assigner, to unambiguously identify the original group cancellation request.

Datatype: "Max35Text" on page 305

Usage Guideline details

- This element(**camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/OriginalGroupCancellationIdentification**) is removed.

5.86.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies the case.

The **RslvdCase** block contains the following elements (see datatype "Case5" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

Usage Guideline details

- This element(**camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/ResolvedCase**) is removed.

5.86.3 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference, as assigned by the original instructing party, to unambiguously identify the original message.

Datatype: "Max35Text" on page 305

5.86.4 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers.

Datatype: "Max35Text" on page 305

5.86.5 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Date and time at which the original message was created.

Datatype: ["ISODatetime" on page 301](#)

5.86.6 OriginalNumberOfTransactions

XML Tag: OrgnlNbOfTxS

Presence: [0..1]

Definition: Number of individual transactions contained in the original message.

Datatype: ["Max15NumericText" on page 303](#)

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/OriginalNumberOfTransactions](#)) is removed.

5.86.7 OriginalControlSum

XML Tag: OrgnlCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the original message, irrespective of currencies.

Datatype: ["DecimalNumber" on page 278](#)

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/OriginalControlSum](#)) is removed.

5.86.8 GroupCancellationStatus

XML Tag: GrpCxlSts

Presence: [0..1]

Definition: Specifies the status of a group cancellation request.

Datatype: ["GroupCancellationStatus1Code" on page 300](#)

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/GroupCancellationStatus](#)) is removed.

5.86.9 CancellationStatusReasonInformation

XML Tag: CxlStsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation status reason.

The **CxlStsRsnInf** block contains the following elements (see datatype "[CancellationStatusReason4](#)" on page 47 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		47
	Reason	<Rsn>		[0..1]		47
	AdditionalInformation	<AddtlInf>		[0..*]		48

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/CancellationStatusReasonInformation](#)) is removed.

5.86.10 NumberOfTransactionsPerCancellationStatus

XML Tag: NbOfTxPerCxlSts

Presence: [0..*]

Definition: Detailed information on the number of transactions for each identical cancellation status.

The **NbOfTxPerCxlSts** block contains the following elements (see datatype "[NumberOfTransactionsPerStatus1](#)" on page 133 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTx>		[1..1]		134
	DetailedStatus	<DtldSts>		[1..1]		134
	DetailedControlSum	<DtldCtrlSum>		[0..1]		134

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus/NumberOfTransactionsPerCancellationStatus](#)) is removed.

5.87 OriginalGroupInformation29

Definition: Unique and unambiguous identifier of the group of transactions as assigned by the original instructing party.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		143
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		143
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		143

Used in element(s)

"OriginalGroupInformation" on page 147, "OriginalGroupInformation" on page 193, "Original-GroupInformation" on page 237

5.87.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference assigned by the original instructing party to unambiguously identify the original message.

Datatype: "Max35Text" on page 305

5.87.2 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.

Datatype: "Max35Text" on page 305

5.87.3 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Original date and time at which the message was created.

Datatype: "ISODateTime" on page 301

5.88 OriginalGroupInformation29__1

Definition: Unique and unambiguous identifier of the group of transactions as assigned by the original instructing party.

🚫 Removed - 🚫 Partial Removed - ⚡ Ignored - ⚡ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		144
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		144
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		145

Used in element(s)

"OriginalGroupInformation" on page 180

5.88.1 OriginalMessageIdentification

XML Tag: OrgnlMsgId

Presence: [1..1]

Definition: Point to point reference assigned by the original instructing party to unambiguously identify the original message.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageIdentification

– **CBPR_Original_Message_Identification_2_TextualRule:**

This element should be only populated by the "Originator" otherwise can be populated with "NOTPROVIDED".

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageIdentification

– **CBPR_Original_Message_Identification_1_TextualRule:**

Original Message Identification should transport the Message Identification of the underlying payment (e.g. pacs.008/pacs.009)

5.88.2 OriginalMessageNameIdentification

XML Tag: OrgnlMsgNmId

Presence: [1..1]

Definition: Specifies the original message name identifier to which the message refers, for example, pacs.003.001.01 or MT103.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageNameIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalMessageNameIdentification

– **CBPR_Original_Message_Name_Identification_TextualRule:**

Original Message Name Identification should transport the Message Name Identification of the underlying payment (e.g. pacs.008/pacs.009)

5.88.3 OriginalCreationDateTime

XML Tag: OrgnlCreDtTm

Presence: [0..1]

Definition: Original date and time at which the message was created.

Datatype: "CBPR_DateTime" on page 269

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation/OriginalCreationDateTime

Type changed to: CBPR_DateTime on page 269

5.89 OriginalPaymentInstruction30

Definition: Provides the details on the reference and status of the original transactions, included in the original instruction, to which the cancellation request message applies.

🚫 Removed - 🚫 Partial Removed - ✦ Ignored - ✦ Partial Ignored - ⚠️ Details below -
 M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalPaymentInformationCancellationIdentification	<OrgnlPmtInfCxlId>		[0..1]		146
	ResolvedCase	<RslvdCase>		[0..1]		147
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[1..1]		147
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		147
	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]		147
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		148
	PaymentInformationCancellationStatus	<PmtInfCxlSts>		[0..1]		148

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationStatusReasonInformation	<CxIStsRsnInf>		[0..*]		148
	NumberOfTransactionsPerCancellationStatus	<NbOfTxPerCxISts>		[0..*]		148
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]		149

Rules

R23 CancellationStatusReasonInformationRule ✓

If PaymentInformationCancellationStatus is present and is different from RJCR (RejectedCancellationRequest) or PNCR (PendingCancellationRequest), then CancellationStatusReasonInformation/AdditionalInformation is not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00078
- *Error Text:* Invalid message content for additional cancellation status reason.

R24 PaymentInformationOrTransactionResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus level, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of resolved case.

Guidelines

1. NumberOfTransactionsPerCancellationStatusGuideline

OriginalGroupInformationAndStatus/NumberOfTransactionsPerStatus should only be present if GroupCancellationStatus equals PACR (PartialCancellationRequest).

Used in element(s)

"OriginalPaymentInformationAndStatus" on page 259

5.89.1 OriginalPaymentInformationCancellation-Identification

XML Tag: OrgnlPmtInfCxIId

Presence: [0..1]

Definition: Unique identification, as assigned by the original assigner, to unambiguously identify the original payment information cancellation request.

Datatype: "Max35Text" on page 305

5.89.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies the resolved case.

The **RslvdCase** block contains the following elements (see datatype "[Case5](#)" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

5.89.3 OriginalPaymentInformationIdentification

XML Tag: OrgnlPmtInfId

Presence: [1..1]

Definition: Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group.

Datatype: "[Max35Text](#)" on page 305

5.89.4 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [0..1]

Definition: Provides information on the original message.

The **OrgnlGrpInf** block contains the following elements (see datatype "[OriginalGroupInformation29](#)" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		143
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		143
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		143

5.89.5 OriginalNumberOfTransactions

XML Tag: OrgnlNbOfTx

Presence: [0..1]

Definition: Number of individual transactions contained in the original payment information group.

Datatype: "Max15NumericText" on page 303

5.89.6 OriginalControlSum

XML Tag: OrgnlCtrlSum

Presence: [0..1]

Definition: Total of all individual amounts included in the original payment information group, irrespective of currencies.

Datatype: "DecimalNumber" on page 278

5.89.7 PaymentInformationCancellationStatus

XML Tag: PmtInfCxlSts

Presence: [0..1]

Definition: Specifies the status of a cancellation request, related to a payment information group.

Datatype: "GroupCancellationStatus1Code" on page 300

5.89.8 CancellationStatusReasonInformation

XML Tag: CxlStsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation status reason.

The **CxlStsRsnInf** block contains the following elements (see datatype "CancellationStatusReason4" on page 47 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		47
	Reason	<Rsn>		[0..1]		47
	AdditionalInformation	<AddtlInf>		[0..*]		48

5.89.9 NumberOfTransactionsPerCancellationStatus

XML Tag: NbOfTxPerCxlSts

Presence: [0..*]

Definition: Detailed information on the number of transactions for each identical cancellation status.

The **NbOfTxPerCxlSts** block contains the following elements (see datatype "NumberOfCancellation-sPerStatus1" on page 132 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DetailedNumberOfTransactions	<DtldNbOfTxs>		[1..1]		133
	DetailedStatus	<DtldSts>		[1..1]		133
	DetailedControlSum	<DtldCtrlSum>		[0..1]		133

5.89.10 TransactionInformationAndStatus

XML Tag: TxInfAndSts

Presence: [0..*]

Definition: Provides information on the original transactions to which the cancellation request message refers.

The **TxInfAndSts** block contains the following elements (see datatype "[PaymentTransaction103](#)" on [page 188](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationStatusIdentification	<CxIStsId>		[0..1]		188
	ResolvedCase	<RslvdCase>		[0..1]		189
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		189
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		189
	UETR	<UETR>		[0..1]		189
	TransactionCancellationStatus	<TxCxISts>		[0..1]		190
	CancellationStatusReasonInformation	<CxIStsRsnInf>		[0..*]		190
	OriginalInstructedAmount	<OrgnlInstdAmt>		[0..1]		190
	OriginalRequestedExecutionDate	<OrgnlReqdExctnDt>		[0..1]		190
	OriginalRequestedCollectionDate	<OrgnlReqdColltnDt>		[0..1]		191
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		191

5.90 OriginalTransactionReference28

Definition: Key elements used to refer the original transaction.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		150

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[0..1]		150
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		151
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		151
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		151
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		152
	SettlementInformation	<SttlmInf>		[0..1]		152
	PaymentTypeInformation	<PmtTplnf>		[0..1]		153
	PaymentMethod	<PmtMtd>		[0..1]		153
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		153
	RemittanceInformation	<RmtInf>		[0..1]		154
	UltimateDebtor	<UltmtDbtr>		[0..1]		154
	Debtor	<Dbtr>		[0..1]		155
	DebtorAccount	<DbtrAcct>		[0..1]		155
	DebtorAgent	<DbtrAgt>		[0..1]		155
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		156
	CreditorAgent	<CdtrAgt>		[0..1]		156
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		157
	Creditor	<Cdtr>		[0..1]		157
	CreditorAccount	<CdtrAcct>		[0..1]		157
	UltimateCreditor	<UltmtCdtr>		[0..1]		158
	Purpose	<Purp>		[0..1]		158

Used in element(s)

"OriginalTransactionReference" on page 191, "OriginalTransactionReference" on page 197, "OriginalTransactionReference" on page 187

5.90.1 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.90.2 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money to be moved between the debtor and creditor, before deduction of charges, expressed in the currency as ordered by the initiating party.

The **Amt** block contains the following elements (see datatype "[AmountType4Choice](#)" on page 33 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedAmount	<InstdAmt>	{Or	[1..1]		33
	EquivalentAmount	<EqvtAmt>	Or}	[1..1]		33

5.90.3 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "[ISODate](#)" on page 301

5.90.4 RequestedCollectionDate

XML Tag: ReqdColltnDt

Presence: [0..1]

Definition: Date and time at which the creditor requests that the amount of money is to be collected from the debtor.

Datatype: "[ISODate](#)" on page 301

5.90.5 RequestedExecutionDate

XML Tag: ReqdExctnDt

Presence: [0..1]

Definition: Date at which the initiating party requests the clearing agent to process the payment.

Usage: This is the date on which the debtor's account is to be debited. If payment by cheque, the date when the cheque must be generated by the bank.

The **ReqdExctnDt** block contains the following elements (see datatype "[DateAndDateTime2Choice](#)" on page 85 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		86

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateTime	<DtTm>	Or}	[1..1]		86

5.90.6 CreditorSchemeldentification

XML Tag: CdtrSchmeld

Presence: [0..1]

Definition: Credit party that signs the mandate.

The **CdtrSchmeld** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.90.7 SettlementInformation

XML Tag: SttlmInf

Presence: [0..1]

Definition: Specifies the details on how the settlement of the original transaction(s) between the instructing agent and the instructed agent was completed.

The **SttlmInf** block contains the following elements (see datatype "[SettlementInstruction7](#)" on page 230 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		233
	SettlementAccount	<SttlmAcct>		[0..1]		233
	ClearingSystem	<ClrSys>		[0..1]		233
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		234
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		234
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		234

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		235
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		235
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		236

5.90.8 PaymentTypeInformation

XML Tag: PmtTpInf

Presence: [0..1]

Definition: Set of elements used to further specify the type of transaction.

The **PmtTpInf** block contains the following elements (see datatype "[PaymentTypeInformation27](#)" on page 198 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		198
	ClearingChannel	<ClrChanI>		[0..1]		198
	ServiceLevel	<SvcLvl>		[0..*]		199
	LocalInstrument	<LclInstrm>		[0..1]		199
	SequenceType	<SeqTp>		[0..1]		199
	CategoryPurpose	<CtgyPurp>		[0..1]		199

5.90.9 PaymentMethod

XML Tag: PmtMtd

Presence: [0..1]

Definition: Specifies the means of payment that will be used to move the amount of money.

Datatype: "[PaymentMethod4Code](#)" on page 307

5.90.10 MandateRelatedInformation

XML Tag: MndtRltdInf

Presence: [0..1]

Definition: Provides further details of the mandate signed between the creditor and the debtor.

The **MndtRltdInf** block contains the following elements (see datatype "[MandateRelatedInformation14](#)" on page 126 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MandateIdentification	<MndtId>		[0..1]		127
	DateOfSignature	<DtOfSgntr>		[0..1]		128
	AmendmentIndicator	<AmdmntInd>		[0..1]		128
	AmendmentInformationDetails	<AmdmntInfDtls>		[0..1]		128
	ElectronicSignature	<ElctrncSgntr>		[0..1]		129
	FirstCollectionDate	<FrstColltnDt>		[0..1]		129
	FinalCollectionDate	<FnIColltnDt>		[0..1]		129
	Frequency	<Frqcy>		[0..1]		129
	Reason	<Rsn>		[0..1]		129
	TrackingDays	<TrckgDays>		[0..1]		130

5.90.11 RemittanceInformation

XML Tag: RmtInf

Presence: [0..1]

Definition: Information supplied to enable the matching of an entry with the items that the transfer is intended to settle, such as commercial invoices in an accounts' receivable system.

The **RmtInf** block contains the following elements (see datatype "RemittanceInformation16" on page 226 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		227
	Structured	<Strd>		[0..*]		227

5.90.12 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor.

The **UltmtDbtr** block contains the following elements (see datatype "Party40Choice" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Agent	<Agt>	Or}	[1..1]		163

5.90.13 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Party that owes an amount of money to the (ultimate) creditor.

The **Dbtr** block contains the following elements (see datatype "[Party40Choice](#)" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.90.14 DebtorAccount

XML Tag: DbtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor to which a debit entry will be made as a result of the transaction.

The **DbtrAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.90.15 DebtorAgent

XML Tag: DbtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the debtor.

The **DbtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.90.16 DebtorAgentAccount

XML Tag: DbtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the debtor agent at its servicing agent in the payment chain.

The **DbtrAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.90.17 CreditorAgent

XML Tag: CdtrAgt

Presence: [0..1]

Definition: Financial institution servicing an account for the creditor.

The **CdtrAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.90.18 CreditorAgentAccount

XML Tag: CdtrAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor agent at its servicing agent to which a credit entry will be made as a result of the payment transaction.

The **CdtrAgtAcct** block contains the following elements (see datatype "CashAccount38" on page 54 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.90.19 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party to which an amount of money is due.

The **Cdtr** block contains the following elements (see datatype "Party40Choice" on page 162 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.90.20 CreditorAccount

XML Tag: CdtrAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the creditor to which a credit entry will be posted as a result of the payment transaction.

The **CdtrAcct** block contains the following elements (see datatype "CashAccount38" on page 54 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.90.21 UltimateCreditor

XML Tag: UltmtCdtr

Presence: [0..1]

Definition: Ultimate party to which an amount of money is due.

The **UltmtCdtr** block contains the following elements (see datatype "Party40Choice" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.90.22 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage:

Purpose is used by the end customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype "Purpose2Choice" on page 219 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		219
	Proprietary	<Prtry>	Or}	[1..1]		219

5.91 OtherContact1

Definition: Communication device number or electronic address used for communication.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ChannelType	<ChanlTp>		[1..1]		159
	Identification	<Id>		[0..1]		159

Used in element(s)

"Other" on page 75

5.91.1 ChannelType

XML Tag: ChanlTp

Presence: [1..1]

Definition: Method used to contact the financial institution's contact for the specific tax region.

Datatype: "Max4Text" on page 305

5.91.2 Identification

XML Tag: Id

Presence: [0..1]

Definition: Communication value such as phone number or email address.

Datatype: "Max128Text" on page 303

5.92 Party38Choice

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		159
	PrivateIdentification	<PrvtId>	Or}	[1..1]		160

Used in element(s)

"Identification" on page 170

5.92.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "[OrganisationIdentification29](#)" on page 134 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		135
	LEI	<LEI>		[0..1]	🚫	135
	Other	<Othr>		[0..*]	🚫	135

5.92.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "[PersonIdentification13](#)" on page 200 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		200
	Other	<Othr>		[0..*]		201

Usage Guideline details

- This element([camt.029.001.09/header/Related/From/OrganisationIdentification/Identification/PrivateIdentification](#)) is removed.
- This element([camt.029.001.09/header/Related/To/OrganisationIdentification/Identification/PrivateIdentification](#)) is removed.
- This element([camt.029.001.09/Assignment/Assignee/Party/Identification/PrivateIdentification](#)) is removed.

5.93 Party38Choice__1

Definition: Nature or use of the account.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		161
	PrivateIdentification	<PrvtId>	Or}	[1..1]		161

Used in element(s)

"Identification" on page 174

5.93.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29__1" on page 136 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		136
	LEI	<LEI>		[0..1]		136
	Other	<Othr>		[0..*]	R[0..2]	136

5.93.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13__1" on page 201 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		201
	Other	<Othr>		[0..*]	R[0..2]	202

5.94 Party38Choice__2

Definition: Nature or use of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		162
	PrivateIdentification	<PrvtId>	Or}	[1..1]		162

Used in element(s)

"Identification" on page 177

5.94.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Unique and unambiguous way to identify an organisation.

The **OrgId** block contains the following elements (see datatype "OrganisationIdentification29__1" on page 136 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AnyBIC	<AnyBIC>		[0..1]		136
	LEI	<LEI>		[0..1]		136
	Other	<Othr>		[0..*]	R[0..2]	136

5.94.2 PrivateIdentification

XML Tag: PrvtId

Presence: [1..1]

Definition: Unique and unambiguous identification of a person, for example a passport.

The **PrvtId** block contains the following elements (see datatype "PersonIdentification13__2" on page 202 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		203
	Other	<Othr>		[0..*]	R[0..2]	203

5.95 Party40Choice

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

Used in element(s)

"Assignee" on page 196, "Assignee" on page 186, "Assigner" on page 196, "Assigner" on page 186, "Creator" on page 51, "Creditor" on page 157, "Debtor" on page 155, "UltimateCreditor" on page 158, "UltimateDebtor" on page 154

5.95.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.95.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.96 Party40Choice__1

Definition: Identification of a person, an organisation or a financial institution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		164
	Agent	<Agt>	Or}	[1..1]		164

Used in element(s)

"Assignee" on page 54, "Assigner" on page 53

5.96.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

Usage Guideline details

- This element([camt.029.001.09/Assignment/Assigner/Party](#)) is removed.
- This element([camt.029.001.09/Assignment/Assignee/Party](#)) is removed.

5.96.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 35 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		35
	BranchIdentification	<BrnchId>		[0..1]	🚫	36

5.97 Party40Choice__2

Definition: Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]	⚠	165
	Agent	<Agt>	Or}	[1..1]	⚠	166

Used in element(s)

["Creator" on page 52](#)

5.97.1 Party

XML Tag: Pty

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **Pty** block contains the following elements (see datatype "[PartyIdentification135__1](#)" on page 172 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	⚠	172
	PostalAddress	<PstlAdr>		[0..1]	⚠	173
	Identification	<Id>		[0..1]		174
	CountryOfResidence	<CtryOfRes>		[0..1]		174
	ContactDetails	<CtctDtls>		[0..1]	🚫	174

Usage Guideline details

- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party**
 - **CBPR_Creator_Identification_TextualRule:**

If AnyBIC is present in addition to any other optional elements, in case of conflicting information it will always take precedence.
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party**
 - **CBPR_Party_Name_Any_BIC_FormaRule:**

If AnyBIC is Absent Then Name is mandatory.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party], if the following element(s) [Party/Identification/OrganisationIdentification/AnyBIC] is (are) absent, then at least one occurrence of the following element(s) [Party/Name] must be present
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party**
 - **CBPR_Party_Name_Postal_Address_FormaRule:**

If Postal Address is present then Name is mandatory.

Recommendation: If present, the BIC (AnyBIC) will always take precedence in case of conflicting information.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party], if at least one occurrence of the following element(s) [Party/PostalAddress] is (are) present, then at least one occurrence of the following element(s) [Party/Name] must be present

5.97.2 Agent

XML Tag: Agt

Presence: [1..1]

Definition: Identification of a financial institution.

The **Agt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__2](#)" on page 37 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]	⚠	37
	BranchIdentification	<BrnchId>		[0..1]	🚫	38

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent
 - CBPR_Agent_National_only_TextualRule:

Whenever Debtor Agent and Creditor Agent are located within the same country, the clearing code only may be used.
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent
 - CBPR_Agent_Option_1_TextualRule:

BICFI, complemented optionally with a LEI (preferred option)
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent
 - CBPR_Agent_Option_2_TextualRule:

(Clearing Code OR LEI) AND (Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent
 - CBPR_Agent_Option_3_TextualRule:

Name AND ([Structured postal address with minimum Town Name and Country] OR [Hybrid postal address with minimum Town Name and Country])). It is recommended to also add the post code when available.

5.98 Party44Choice__1

Definition: Identification of a person, an organisation or a financial institution.

🚫 Removed - 🚫 Partial Removed - ⬡ Ignored - ⬡ Partial Ignored - ⚠ Details below -
 📌 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]	🚫	168
	FinancialInstitutionIdentification	<FIId>	Or}	[1..1]		168

Used in element(s)

"From" on page 14, "From" on page 41, "To" on page 14, "To" on page 42

5.98.1 OrganisationIdentification

XML Tag: OrgId

Presence: [1..1]

Definition: Identification of a person or an organisation.

The **OrgId** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]	🚫	169
	PostalAddress	<PstlAdr>		[0..1]	🚫	169
	Identification	<Id>		[0..1]	🚫	170
	CountryOfResidence	<CtryOfRes>		[0..1]	🚫	171
	ContactDetails	<CtctDtls>		[0..1]	🚫	171

Usage Guideline details

- This element([camt.029.001.09/header/Related/From/OrganisationIdentification](#)) is removed.
- This element([camt.029.001.09/header/Related/To/OrganisationIdentification](#)) is removed.
- This element([camt.029.001.09/header/To/OrganisationIdentification](#)) is removed.
- This element([camt.029.001.09/header/From/OrganisationIdentification](#)) is removed.

5.98.2 FinancialInstitutionIdentification

XML Tag: FIId

Presence: [1..1]

Definition: Identification of a financial institution.

The **FIId** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6__1](#)" on page 35 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		35
	BranchIdentification	<BrnchId>		[0..1]	🚫	36

5.99 PartyIdentification135

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

Used in element(s)

["CreditorSchemeIdentification" on page 152](#),
 ["Garnishee" on page 111](#),
 ["GarnishmentAdministrator" on page 111](#),
 ["Invoicee" on page 241](#),
 ["Invoicer" on page 240](#),
 ["OrganisationIdentification" on page 168](#),
 ["OriginalCreditorSchemeIdentification" on page 29](#),
 ["OriginalDebtor" on page 30](#),
 ["Originator" on page 47](#),
 ["Originator" on page 131](#),
 ["Party" on page 163](#),
 ["Party" on page 164](#)

5.99.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: ["Max140Text" on page 303](#)

Usage Guideline details

- This element([camt.029.001.09/.header/Related/To/OrganisationIdentification/Name](#)) is removed.
- This element([camt.029.001.09/.header/Related/From/OrganisationIdentification/Name](#)) is removed.
- This element([camt.029.001.09/Assignment/Assignee/Party/Name](#)) is removed.

5.99.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype ["PostalAddress24" on page 205](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		206
	Department	<Dept>		[0..1]		206
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		207
	Floor	<Flr>		[0..1]		207
	PostBox	<PstBx>		[0..1]		207
	Room	<Room>		[0..1]		207
	PostCode	<PstCd>		[0..1]		207
	TownName	<TwnNm>		[0..1]		208
	TownLocationName	<TwnLctnNm>		[0..1]		208
	DistrictName	<DstrctNm>		[0..1]		208
	CountrySubDivision	<CtrySubDvsn>		[0..1]		208
	Country	<Ctry>		[0..1]		208
	AddressLine	<AdrLine>		[0..7]		208

Usage Guideline details

- This element(camt.029.001.09/.header/Related/To/OrganisationIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/.header/Related/From/OrganisationIdentification/PostalAddress) is removed.
- This element(camt.029.001.09/Assignment/Assignee/Party/PostalAddress) is removed.

5.99.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice" on page 159 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		159
	PrivateIdentification	<PrvtId>	Or}	[1..1]		160

Usage Guideline details

- This element([camt.029.001.09/header/Related/To/OrganisationIdentification/Identification](#)) is removed.
- This element([camt.029.001.09/header/Related/From/OrganisationIdentification/Identification](#)) is removed.

5.99.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: ["CountryCode" on page 277](#)

Usage Guideline details

- This element([camt.029.001.09/header/Related/To/OrganisationIdentification/CountryOfResidence](#)) is removed.
- This element([camt.029.001.09/header/Related/From/OrganisationIdentification/CountryOfResidence](#)) is removed.
- This element([camt.029.001.09/Assignment/Assignee/Party/CountryOfResidence](#)) is removed.

5.99.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype ["Contact4" on page 72](#) for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		73
	Name	<Nm>		[0..1]		73
	PhoneNumber	<PhneNb>		[0..1]		73

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	MobileNumber	<MobNb>		[0..1]		73
	FaxNumber	<FaxNb>		[0..1]		74
	EmailAddress	<EmailAdr>		[0..1]		74
	EmailPurpose	<EmailPurp>		[0..1]		74
	JobTitle	<JobTitl>		[0..1]		74
	Responsibility	<Rspnsblty>		[0..1]		74
	Department	<Dept>		[0..1]		74
	Other	<Othr>		[0..*]		75
	PreferredMethod	<PrefrdMtd>		[0..1]		75

Usage Guideline details

- This element(camt.029.001.09/.header/Related/To/OrganisationIdentification/ContactDetails) is removed.
- This element(camt.029.001.09/.header/Related/From/OrganisationIdentification/ContactDetails) is removed.
- This element(camt.029.001.09/Assignment/Assignee/Party/ContactDetails) is removed.

5.100 PartyIdentification135__1

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		172
	PostalAddress	<PstlAdr>		[0..1]		173
	Identification	<Id>		[0..1]		174
	CountryOfResidence	<CtryOfRes>		[0..1]		174
	ContactDetails	<CtctDtls>		[0..1]		174

Used in element(s)

"Party" on page 165

5.100.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 271

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 271

5.100.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 209 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		209
	Department	<Dept>		[0..1]		210
	SubDepartment	<SubDept>		[0..1]		210
	StreetName	<StrtNm>		[0..1]		211
	BuildingNumber	<BldgNb>		[0..1]		211
	BuildingName	<BldgNm>		[0..1]		212
	Floor	<Flr>		[0..1]		212
	PostBox	<PstBx>		[0..1]		213
	Room	<Room>		[0..1]		213
	PostCode	<PstCd>		[0..1]		214
	TownName	<TwnNm>		[0..1]	 	214
	TownLocationName	<TwnLctnNm>		[0..1]		215
	DistrictName	<DstrctNm>		[0..1]		215
	CountrySubDivision	<CtrySubDvsn>		[0..1]		216
	Country	<Ctry>		[0..1]		216
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	217

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.100.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "Party38Choice_1" on page 160 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		161
	PrivateIdentification	<PrvtId>	Or}	[1..1]		161

5.100.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "CountryCode" on page 277

5.100.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "Contact4" on page 72 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		73
	Name	<Nm>		[0..1]		73

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PhoneNumber	<PhneNb>		[0..1]		73
	MobileNumber	<MobNb>		[0..1]		73
	FaxNumber	<FaxNb>		[0..1]		74
	EmailAddress	<EmailAdr>		[0..1]		74
	EmailPurpose	<EmailPurp>		[0..1]		74
	JobTitle	<JobTitl>		[0..1]		74
	Responsibility	<Rspnsblty>		[0..1]		74
	Department	<Dept>		[0..1]		74
	Other	<Othr>		[0..*]		75
	PreferredMethod	<PrefrdMtd>		[0..1]		75

Usage Guideline details

- This element(camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/ContactDetails) is removed.

5.101 PartyIdentification135__2

Definition: Specifies the identification of a person or an organisation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		175
	PostalAddress	<PstlAdr>		[0..1]		176
	Identification	<Id>		[0..1]		177
	CountryOfResidence	<CtryOfRes>		[0..1]		177
	ContactDetails	<CtctDtls>		[0..1]		177

Used in element(s)

"Originator" on page 48

5.101.1 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name by which a party is known and which is usually used to identify that party.

Datatype: "CBPR_RestrictedFINXMax140Text_Extended" on page 271

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Name

Type changed to: CBPR_RestrictedFINXMax140Text_Extended on page 271

5.101.2 PostalAddress

XML Tag: PstlAdr

Presence: [0..1]

Definition: Information that locates and identifies a specific address, as defined by postal services.

The **PstlAdr** block contains the following elements (see datatype "PostalAddress24__1" on page 209 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		209
	Department	<Dept>		[0..1]		210
	SubDepartment	<SubDept>		[0..1]		210
	StreetName	<StrtNm>		[0..1]		211
	BuildingNumber	<BldgNb>		[0..1]		211
	BuildingName	<BldgNm>		[0..1]		212
	Floor	<Flr>		[0..1]		212
	PostBox	<PstBx>		[0..1]		213
	Room	<Room>		[0..1]		213
	PostCode	<PstCd>		[0..1]		214
	TownName	<TwnNm>		[0..1]	 	214
	TownLocationName	<TwnLctnNm>		[0..1]		215
	DistrictName	<DstrctNm>		[0..1]		215
	CountrySubDivision	<CtrySubDvsn>		[0..1]		216
	Country	<Ctry>		[0..1]		216
	AddressLine	<AdrLine>		[0..7]	 R[0..2]	217

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress

- CBPR_Duplication_Postal_Address_TextualRule:

Data present in structured elements within the Postal Address must not, under any circumstances be repeated in AddressLine.

5.101.3 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique and unambiguous identification of a party.

The **Id** block contains the following elements (see datatype "[Party38Choice_2](#)" on page 161 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OrganisationIdentification	<OrgId>	{Or	[1..1]		162
	PrivateIdentification	<PrvtId>	Or}	[1..1]		162

5.101.4 CountryOfResidence

XML Tag: CtryOfRes

Presence: [0..1]

Definition: Country in which a person resides (the place of a person's home). In the case of a company, it is the country from which the affairs of that company are directed.

Datatype: "[CountryCode](#)" on page 277

5.101.5 ContactDetails

XML Tag: CtctDtls

Presence: [0..1]

Definition: Set of elements used to indicate how to contact the party.

The **CtctDtls** block contains the following elements (see datatype "[Contact4](#)" on page 72 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	NamePrefix	<NmPrfx>		[0..1]		73
	Name	<Nm>		[0..1]		73

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PhoneNumber	<PhneNb>		[0..1]		73
	MobileNumber	<MobNb>		[0..1]		73
	FaxNumber	<FaxNb>		[0..1]		74
	EmailAddress	<EmailAdr>		[0..1]		74
	EmailPurpose	<EmailPurp>		[0..1]		74
	JobTitle	<JobTitl>		[0..1]		74
	Responsibility	<Rspnsblty>		[0..1]		74
	Department	<Dept>		[0..1]		74
	Other	<Othr>		[0..*]		75
	PreferredMethod	<PrefrdMtd>		[0..1]		75

Usage Guideline details

- This element(camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/ContactDetails) is removed.

5.102 PaymentTransaction102__1

Definition: Provides further details on the reference and status on the original transactions, included in the original instruction, to which the cancellation request message applies.

Removed -
 Partial Removed -
 Ignored -
 Partial Ignored -
 Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationStatusIdentification	<CxIStsId>		[0..1]		179
	ResolvedCase	<RslvdCase>		[0..1]		180
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		180
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		181
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		181
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		182
	OriginalClearingSystemReference	<OrgnlClrSysRef>		[0..1]		182
	OriginalUETR	<OrgnlUETR>		[0..1]		183
	TransactionCancellationStatus	<TxCxISts>		[0..1]		183
	CancellationStatusReasonInformation	<CxIStsRsnInf>		[0..*]	R[0..1]	183

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]		184
	OriginalInterbankSettlementAmount	<OrgnlIntrBkSttlmAmt>		[0..1]		185
	OriginalInterbankSettlementDate	<OrgnlIntrBkSttlmDt>		[0..1]		185
	Assigner	<Assgnr>		[0..1]		186
	Assignee	<Assgne>		[0..1]		186
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		187

Used in element(s)

"TransactionInformationAndStatus" on page 260

5.102.1 CancellationStatusIdentification

XML Tag: CxlStsId

Presence: [0..1]

Definition: Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner.

Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 271

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusIdentification

This element is now mandatory, the minimum occurrence has been changed to : 1

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusIdentification

Type changed to: CBPR_RestrictedFINXMax16Text on page 271

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusIdentification

– **CBPR_Cancellation_Status_Identification_FormalRule:**

For the Cancellation Status Identification, the below restrictions apply:

- The first one and the 16th one cannot be "/" and
- The string of 16 characters cannot contain "/"

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusIdentification],

the value of every occurrence of [CancellationStatusIdentification] must not comply with the following XML pattern : '(/.*)|(.*/)|(.*/.*)'

5.102.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies the resolved case.

The **RslvdCase** block contains the following elements (see datatype "Case5__1" on page 51 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		52
	Creator	<Cretr>		[1..1]		52
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		52

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase
This element is now mandatory, the minimum occurrence has been changed to : 1

5.102.3 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [0..1]

Definition: Provides information on the original message.

The **OrgnlGrpInf** block contains the following elements (see datatype "OriginalGroupInformation29__1" on page 143 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		144
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		144
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		145

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalGroupInformation**

This element is now mandatory, the minimum occurrence has been changed to : 1

5.102.4 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.

Datatype: "CBPR_RestrictedFINXMax16Text" on page 271

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalInstructionIdentification**

Type changed to: CBPR_RestrictedFINXMax16Text on page 271

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalInstructionIdentification**

- **CBPR_Original_Instruction_Identification_TextualRule:**

Should transport the Instruction Identification of the underlying transaction that is requested to be cancelled.

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalInstructionIdentification**

- **CBPR_Original_Instruction_Identification_FormalRule:**

This element must not start or end with a slash '/' and must not contain two consecutive slashes '//'.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/OriginalInstructionIdentification], the value of every occurrence of [OriginalInstructionIdentification] must not comply with the following XML pattern : `'(/.*)|(.*/)|(.*/.*)'`

5.102.5 OriginalEndToEndIdentification

XML Tag: OrgnlEndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalEnd-ToEndIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalEnd-ToEndIdentification

– **CBPR_Original_End_To_End_Identification_TextualRule:**

Should transport the EndToEnd Identification of the underlying transaction that is requested to be cancelled.

5.102.6 OriginalTransactionIdentification

XML Tag: OrgnlTxId

Presence: [0..1]

Definition: Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalTransactionIdentification

Type changed to: CBPR_RestrictedFINXMax35Text on page 272

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalTransactionIdentification

– **CBPR_Original_Transaction_Identification_TextualRule:**

Should transport the Transaction Identification of the underlying transaction that is requested to be cancelled.

5.102.7 OriginalClearingSystemReference

XML Tag: OrgnlClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalClearingSystemReference

Type changed to: [CBPR_RestrictedFINXMax35Text on page 272](#)

5.102.8 OriginalUETR

XML Tag: OrgnlUETR

Presence: [0..1]

Definition: Universally unique identifier to provide the original end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 317](#)

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalUETR**

This element is now mandatory, the minimum occurrence has been changed to : 1

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalUETR**

– **CBPR_Original_UETR_TextualRule:**

Must transport the UETR of the underlying transaction that is requested to be cancelled.

5.102.9 TransactionCancellationStatus

XML Tag: TxCxlSts

Presence: [0..1]

Definition: Specifies the status of the transaction cancellation request.

Datatype: ["CancellationIndividualStatus1Code" on page 274](#)

Usage Guideline details

- This element(**camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/TransactionCancellationStatus**) is removed.

5.102.10 CancellationStatusReasonInformation

XML Tag: CxlStsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation status reason.

The **CxlStsRsnInf** block contains the following elements (see datatype ["CancellationStatusReason4_1" on page 48](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		48
	Reason	<Rsn>		[0..1]		49
	AdditionalInformation	<AddtlInf>		[0..*]	 R[0..2]	50

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation

This element has change repeatability, the maximum occurrence has been changed to : 1

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation

– CBPR_Reason_Code_ARDT_AdditionalInformation_FormalRule:

If Reason code = Already Returned (ARDT), then the element AdditionalInformation must include the UETR of the returned payment.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation], if every occurrence of [CancellationStatusReasonInformation/Reason/Code] has value included in the following list 'ARDT', then
at least one occurrence of the following element(s) [CancellationStatusReasonInformation/AdditionalInformation] must be present

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation

– CBPR_Reason_Code_PTNA_AdditionalInformation_FormalRule:

If Reason/Code = PTNA, then the element AdditionalInformation, if present, must be exactly a BIC8 or BIC11.

For each [Full Message/Document/ResolutionOfInvestigationV09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation], if every occurrence of [CancellationStatusReasonInformation/Reason/Code] has value included in the following list 'PTNA', then
the value of every occurrence of [CancellationStatusReasonInformation/AdditionalInformation] must comply with the following XML pattern : '[A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}'

5.102.11 ResolutionRelatedInformation

XML Tag: RsltnRltdInf

Presence: [0..1]

Definition: Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution.

The **RsltnRltdInf** block contains the following elements (see datatype "[ResolutionData1](#)" on page 227 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EndToEndIdentification	<EndToEndId>		[0..1]		228
	TransactionIdentification	<TxId>		[0..1]		228
	UETR	<UETR>		[0..1]		228
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		229
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		229
	ClearingChannel	<ClrChanl>		[0..1]		229
	Compensation	<Compstn>		[0..1]		229
	Charges	<Chrgs>		[0..*]		229

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolutionRelatedInformation](#)) is removed.

5.102.12 OriginalInterbankSettlementAmount

XML Tag: OrgnlIntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on page 263

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalInterbankSettlementAmount](#)) is removed.

5.102.13 OriginalInterbankSettlementDate

XML Tag: OrgnlIntrBkSttlmDt

Presence: [0..1]

Definition: Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 301

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/OriginalInterbankSettlementDate](#)) is removed.

5.102.14 Assigner

XML Tag: Assgnr

Presence: [0..1]

Definition: Party who assigns the case.

Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s).

The **Assgnr** block contains the following elements (see datatype "[Party40Choice](#)" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/Assigner](#)) is removed.

5.102.15 Assignee

XML Tag: Assgne

Presence: [0..1]

Definition: Party to which the case is assigned.

Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s).

The **Assgne** block contains the following elements (see datatype "[Party40Choice](#)" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Agent	<Agt>	Or}	[1..1]		163

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/As-signee](#)) is removed.

5.102.16 OriginalTransactionReference

XML Tag: OrgnlTxRef

Presence: [0..1]

Definition: Key elements used to identify the original transaction that is being referred to.

The **OrgnlTxRef** block contains the following elements (see datatype "[OriginalTransactionReference28](#)" on page 149 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		150
	Amount	<Amt>		[0..1]		150
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		151
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		151
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		151
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		152
	SettlementInformation	<SttlmInf>		[0..1]		152
	PaymentTypeInformation	<PmtTplnf>		[0..1]		153
	PaymentMethod	<PmtMtd>		[0..1]		153
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		153
	RemittanceInformation	<RmtInf>		[0..1]		154
	UltimateDebtor	<UltmtDbtr>		[0..1]		154
	Debtor	<Dbtr>		[0..1]		155
	DebtorAccount	<DbtrAcct>		[0..1]		155
	DebtorAgent	<DbtrAgt>		[0..1]		155
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		156
	CreditorAgent	<CdtrAgt>		[0..1]		156

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		157
	Creditor	<Cdtr>		[0..1]		157
	CreditorAccount	<CdtrAcct>		[0..1]		157
	UltimateCreditor	<UltmtCdtr>		[0..1]		158
	Purpose	<Purp>		[0..1]		158

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/Original-TransactionReference](#)) is removed.

5.103 PaymentTransaction103

Definition: Provides reference and status information on the original transactions, included in the original instruction, to which the cancellation request message applies.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationStatusIdentification	<CxIStsId>		[0..1]		188
	ResolvedCase	<RslvdCase>		[0..1]		189
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		189
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		189
	UETR	<UETR>		[0..1]		189
	TransactionCancellationStatus	<TxCxISts>		[0..1]		190
	CancellationStatusReasonInformation	<CxIStsRsnInf>		[0..*]		190
	OriginalInstructedAmount	<OrgnlInstdAmt>		[0..1]		190
	OriginalRequestedExecutionDate	<OrgnlReqdExctnDt>		[0..1]		190
	OriginalRequestedCollectionDate	<OrgnlReqdColltnDt>		[0..1]		191
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		191

Used in element(s)

["TransactionInformationAndStatus"](#) on page 149

5.103.1 CancellationStatusIdentification

XML Tag: CxIStsId

Presence: [0..1]

Definition: Unique and unambiguous identifier of a cancellation request status, as assigned by the assigner.

Usage: The cancellation status identification can be used for reconciliation or to link tasks relating to the cancellation request.

Datatype: "Max35Text" on page 305

5.103.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies the resolved case.

The **RslvdCase** block contains the following elements (see datatype "Case5" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

5.103.3 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party to unambiguously identify the original instruction.

Datatype: "Max35Text" on page 305

5.103.4 OriginalEndToEndIdentification

XML Tag: OrgnlEndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "Max35Text" on page 305

5.103.5 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 317](#)

5.103.6 TransactionCancellationStatus

XML Tag: TxCxlSts

Presence: [0..1]

Definition: Specifies the status of the transaction cancellation request.

Datatype: ["CancellationIndividualStatus1Code" on page 274](#)

5.103.7 CancellationStatusReasonInformation

XML Tag: CxlStsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the cancellation status reason.

The **CxlStsRsnInf** block contains the following elements (see datatype ["CancellationStatusReason4" on page 47](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		47
	Reason	<Rsn>		[0..1]		47
	AdditionalInformation	<AddtlInf>		[0..*]		48

5.103.8 OriginalInstructedAmount

XML Tag: OrgnlInstdAmt

Presence: [0..1]

Definition: Amount of money, as provided in the original transaction, to be moved between the debtor and the creditor, before deduction of charges, expressed in the currency, as ordered by the original initiating party.

Usage: This amount has to be transported unchanged through the transaction chain.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.103.9 OriginalRequestedExecutionDate

XML Tag: OrgnlReqdExctnDt

Presence: [0..1]

Definition: Date at which the initiating party originally requested the clearing agent to process the payment.

The **OrgnlReqdExctnDt** block contains the following elements (see datatype ["DateAndDate-Time2Choice" on page 85](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Date	<Dt>	{Or	[1..1]		86
	DateTime	<DtTm>	Or}	[1..1]		86

5.103.10 OriginalRequestedCollectionDate

XML Tag: OrgnlReqdColltnDt

Presence: [0..1]

Definition: Date at which the creditor originally requested the collection of the amount of money from the debtor.

Datatype: "ISODate" on page 301

5.103.11 OriginalTransactionReference

XML Tag: OrgnlTxRef

Presence: [0..1]

Definition: Key elements used to identify the original transaction that is being referred to.

The **OrgnlTxRef** block contains the following elements (see datatype "OriginalTransactionReference28" on page 149 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		150
	Amount	<Amt>		[0..1]		150
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		151
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		151
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		151
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		152
	SettlementInformation	<SttlmInf>		[0..1]		152
	PaymentTypeInformation	<PmtTpInf>		[0..1]		153
	PaymentMethod	<PmtMtd>		[0..1]		153
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		153
	RemittanceInformation	<RmtInf>		[0..1]		154
	UltimateDebtor	<UltmtDbtr>		[0..1]		154
	Debtor	<Dbtr>		[0..1]		155

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebtorAccount	<DbtrAcct>		[0..1]		155
	DebtorAgent	<DbtrAgt>		[0..1]		155
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		156
	CreditorAgent	<CdtrAgt>		[0..1]		156
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		157
	Creditor	<Cdtr>		[0..1]		157
	CreditorAccount	<CdtrAcct>		[0..1]		157
	UltimateCreditor	<UltmtCdtr>		[0..1]		158
	Purpose	<Purp>		[0..1]		158

5.104 PaymentTransaction107

Definition: Provides further details on the reference and status on the original transactions, included in the original instruction, to which the cancellation request message applies.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ModificationStatusIdentification	<ModStsId>		[0..1]		193
	ResolvedCase	<RslvdCase>		[0..1]		193
	OriginalGroupInformation	<OrgnlGrpInf>		[1..1]		193
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[0..1]		194
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		194
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		194
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		194
	OriginalClearingSystemReference	<OrgnlClrSysRef>		[0..1]		194
	OriginalUETR	<OrgnlUETR>		[0..1]		195
	ModificationStatusReasonInformation	<ModStsRsnInf>		[0..*]		195
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]		195
	OriginalInterbankSettlementAmount	<OrgnlIntrBkSttlmAmt>		[0..1]		196
	OriginalInterbankSettlementDate	<OrgnlIntrBkSttlmDt>		[0..1]		196
	Assigner	<Assgnr>		[0..1]		196

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Assignee	<Assgne>		[0..1]		196
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		197

Used in element(s)

"ModificationDetails" on page 21

5.104.1 ModificationStatusIdentification

XML Tag: ModStsId

Presence: [0..1]

Definition: Unique and unambiguous identifier of a modification request status, as assigned by the assigner.

Usage: The modification status identification can be used for reconciliation or to link tasks relating to the modification request.

Datatype: "Max35Text" on page 305

5.104.2 ResolvedCase

XML Tag: RslvdCase

Presence: [0..1]

Definition: Identifies the resolved case.

The **RslvdCase** block contains the following elements (see datatype "Case5" on page 50 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		51
	Creator	<Cretr>		[1..1]		51
	ReopenCaseIndication	<ReopCaseIndctn>		[0..1]		51

5.104.3 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [1..1]

Definition: Provides information on the original message.

The **OrgnlGrpInf** block contains the following elements (see datatype "OriginalGroupInformation29" on page 142 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		143
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		143
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		143

5.104.4 OriginalPaymentInformationIdentification

XML Tag: OrgnlPmtInfId

Presence: [0..1]

Definition: Unique identification, as assigned by the original sending party, to unambiguously identify the original payment information group.

Datatype: "Max35Text" on page 305

5.104.5 OriginalInstructionIdentification

XML Tag: OrgnlInstrId

Presence: [0..1]

Definition: Unique identification, as assigned by the original instructing party for the original instructed party, to unambiguously identify the original instruction.

Datatype: "Max35Text" on page 305

5.104.6 OriginalEndToEndIdentification

XML Tag: OrgnlEndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "Max35Text" on page 305

5.104.7 OriginalTransactionIdentification

XML Tag: OrgnlTxId

Presence: [0..1]

Definition: Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.

Datatype: "Max35Text" on page 305

5.104.8 OriginalClearingSystemReference

XML Tag: OrgnlClrSysRef

Presence: [0..1]

Definition: Unique reference, as assigned by the original clearing system, to unambiguously identify the original instruction.

Datatype: "Max35Text" on page 305

5.104.9 OriginalUETR

XML Tag: OrgnlUETR

Presence: [0..1]

Definition: Universally unique identifier to provide the original end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 317

5.104.10 ModificationStatusReasonInformation

XML Tag: ModStsRsnInf

Presence: [0..*]

Definition: Provides detailed information on the modification status reason.

The **ModStsRsnInf** block contains the following elements (see datatype "ModificationStatusReason2" on page 131 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Originator	<Orgtr>		[0..1]		131
	Reason	<Rsn>		[0..1]		132
	AdditionalInformation	<AddtlInf>		[0..*]		132

5.104.11 ResolutionRelatedInformation

XML Tag: RsltnRltdInf

Presence: [0..1]

Definition: Reference of a return or a reversal transaction that is initiated to fix the case under investigation as part of the resolution.

The **RsltnRltdInf** block contains the following elements (see datatype "ResolutionData1" on page 227 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EndToEndIdentification	<EndToEndId>		[0..1]		228
	TransactionIdentification	<TxId>		[0..1]		228
	UETR	<UETR>		[0..1]		228
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		229
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		229

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ClearingChannel	<ClrChanl>		[0..1]		229
	Compensation	<Compstn>		[0..1]		229
	Charges	<Chrgs>		[0..*]		229

5.104.12 OriginalInterbankSettlementAmount

XML Tag: OrgnlIntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent, as provided in the original instruction.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.104.13 OriginalInterbankSettlementDate

XML Tag: OrgnlIntrBkSttlmDt

Presence: [0..1]

Definition: Date, as provided in the original transaction, on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 301

5.104.14 Assigner

XML Tag: Assgnr

Presence: [0..1]

Definition: Party who assigns the case.

Usage: This is also the agent that instructs the next party in the chain to carry out the (set of) cancellation request(s).

The **Assgnr** block contains the following elements (see datatype "Party40Choice" on page 162 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.104.15 Assignee

XML Tag: Assgne

Presence: [0..1]

Definition: Party to which the case is assigned.

Usage: This is also the agent that is instructed by the previous party in the chain to carry out the (set of) cancellation request(s).

The **Assgne** block contains the following elements (see datatype "[Party40Choice](#)" on page 162 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Party	<Pty>	{Or	[1..1]		163
	Agent	<Agt>	Or}	[1..1]		163

5.104.16 OriginalTransactionReference

XML Tag: OrgnlTxRef

Presence: [0..1]

Definition: Key elements used to identify the original transaction that is being referred to.

The **OrgnlTxRef** block contains the following elements (see datatype "[OriginalTransactionReference28](#)" on page 149 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		150
	Amount	<Amt>		[0..1]		150
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		151
	RequestedCollectionDate	<ReqdColltnDt>		[0..1]		151
	RequestedExecutionDate	<ReqdExctnDt>		[0..1]		151
	CreditorSchemeIdentification	<CdtrSchmeld>		[0..1]		152
	SettlementInformation	<SttlmInf>		[0..1]		152
	PaymentTypeInformation	<PmtTplnf>		[0..1]		153
	PaymentMethod	<PmtMtd>		[0..1]		153
	MandateRelatedInformation	<MndtRltdInf>		[0..1]		153
	RemittanceInformation	<RmtInf>		[0..1]		154
	UltimateDebtor	<UltmtDbtr>		[0..1]		154
	Debtor	<Dbtr>		[0..1]		155
	DebtorAccount	<DbtrAcct>		[0..1]		155
	DebtorAgent	<DbtrAgt>		[0..1]		155

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DebtorAgentAccount	<DbtrAgtAcct>		[0..1]		156
	CreditorAgent	<CdtrAgt>		[0..1]		156
	CreditorAgentAccount	<CdtrAgtAcct>		[0..1]		157
	Creditor	<Cdtr>		[0..1]		157
	CreditorAccount	<CdtrAcct>		[0..1]		157
	UltimateCreditor	<UltmtCdtr>		[0..1]		158
	Purpose	<Purp>		[0..1]		158

5.105 PaymentTypeInformation27

Definition: Provides further details of the type of payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	InstructionPriority	<InstrPrty>		[0..1]		198
	ClearingChannel	<ClrChanl>		[0..1]		198
	ServiceLevel	<SvcLvl>		[0..*]		199
	LocalInstrument	<LclInstrm>		[0..1]		199
	SequenceType	<SeqTp>		[0..1]		199
	CategoryPurpose	<CtgyPurp>		[0..1]		199

Used in element(s)

"PaymentTypeInformation" on page 153

5.105.1 InstructionPriority

XML Tag: InstrPrty

Presence: [0..1]

Definition: Indicator of the urgency or order of importance that the instructing party would like the instructed party to apply to the processing of the instruction.

Datatype: "Priority2Code" on page 311

5.105.2 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: ["ClearingChannel2Code" on page 275](#)

5.105.3 ServiceLevel

XML Tag: SvcLvl

Presence: [0..*]

Definition: Agreement under which or rules under which the transaction should be processed.

The **SvcLvl** block contains the following elements (see datatype ["ServiceLevel8Choice" on page 230](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		230
	Proprietary	<Prtry>	Or}	[1..1]		230

5.105.4 LocalInstrument

XML Tag: LclInstrm

Presence: [0..1]

Definition: User community specific instrument.

Usage: This element is used to specify a local instrument, local clearing option and/or further qualify the service or service level.

The **LclInstrm** block contains the following elements (see datatype ["LocalInstrument2Choice" on page 126](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		126
	Proprietary	<Prtry>	Or}	[1..1]		126

5.105.5 SequenceType

XML Tag: SeqTp

Presence: [0..1]

Definition: Identifies the direct debit sequence, such as first, recurrent, final or one-off.

Datatype: ["SequenceType3Code" on page 312](#)

5.105.6 CategoryPurpose

XML Tag: CtgyPurp

Presence: [0..1]

Definition: Specifies the high level purpose of the instruction based on a set of pre-defined categories.

Usage: This is used by the initiating party to provide information concerning the processing of the payment. It is likely to trigger special processing by any of the agents involved in the payment chain.

The **CtgyPurp** block contains the following elements (see datatype "[CategoryPurpose1Choice](#)" on page 57 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		57
	Proprietary	<Prtry>	Or}	[1..1]		58

5.106 PersonIdentification13

Definition: Unique and unambiguous way to identify a person.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		200
	Other	<Othr>		[0..*]		201

Used in element(s)

"[PrivateIdentification](#)" on page 160

5.106.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1](#)" on page 86 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		86
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		86
	CityOfBirth	<CityOfBirth>		[1..1]		87

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CountryOfBirth	<CtryOfBirth>		[1..1]		87

5.106.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1](#)" on page 120 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		121
	SchemeName	<SchmeNm>		[0..1]		121
	Issuer	<Issr>		[0..1]		121

5.107 PersonIdentification13__1

Definition: Unique and unambiguous way to identify a person.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		201
	Other	<Othr>		[0..*]	R[0..2]	202

Used in element(s)

"[PrivateIdentification](#)" on page 161

5.107.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1__1](#)" on page 87 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		87
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		88
	CityOfBirth	<CityOfBirth>		[1..1]		88
	CountryOfBirth	<CtryOfBirth>		[1..1]		88

5.107.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "GenericPersonIdentification1__1" on page 121 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		122
	SchemeName	<SchmeNm>		[0..1]		122
	Issuer	<Issr>		[0..1]		123

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other

This element has change repeatability, the maximum occurrence has been changed to : 2

5.108 PersonIdentification13__2

Definition: Unique and unambiguous way to identify a person.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DateAndPlaceOfBirth	<DtAndPlcOfBirth>		[0..1]		203
	Other	<Othr>		[0..*]	R[0..2]	203

Used in element(s)

"PrivateIdentification" on page 162

5.108.1 DateAndPlaceOfBirth

XML Tag: DtAndPlcOfBirth

Presence: [0..1]

Definition: Date and place of birth of a person.

The **DtAndPlcOfBirth** block contains the following elements (see datatype "[DateAndPlaceOfBirth1__2](#)" on [page 88](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	BirthDate	<BirthDt>		[1..1]		89
	ProvinceOfBirth	<PrvcOfBirth>		[0..1]		89
	CityOfBirth	<CityOfBirth>		[1..1]		89
	CountryOfBirth	<CtryOfBirth>		[1..1]		90

5.108.2 Other

XML Tag: Othr

Presence: [0..*]

Definition: Unique identification of a person, as assigned by an institution, using an identification scheme.

The **Othr** block contains the following elements (see datatype "[GenericPersonIdentification1__1](#)" on [page 121](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		122
	SchemeName	<SchmeNm>		[0..1]		122
	Issuer	<Issr>		[0..1]		123

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/Identification/PrivateIdentification/Other](#)

This element has change repeatability, the maximum occurrence has been changed to : 2

5.109 PersonIdentificationSchemeName1Choice

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		204
	Proprietary	<Prtry>	Or}	[1..1]		204

Used in element(s)

"SchemeName" on page 121

5.109.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 294

5.109.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 305

5.110 PersonIdentificationSchemeName1Choice__1

Definition: Sets of elements to identify a name of the identification scheme.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		204
	Proprietary	<Prtry>	Or}	[1..1]	 	205

Used in element(s)

"SchemeName" on page 122

5.110.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: "ExternalPersonIdentification1Code" on page 294

5.110.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "CBPR_RestrictedFINXMax35Text" on page 272

Usage Guideline details

- This element(**camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other/SchemeName/Proprietary**) is removed.
- This element(**camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary**) is removed.
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/Identification/PrivateIdentification/Other/SchemeName/Proprietary**
Type changed to: CBPR_RestrictedFINXMax35Text on page 272
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/Identification/PrivateIdentification/Other/SchemeName/Proprietary**
Type changed to: CBPR_RestrictedFINXMax35Text on page 272

5.111 PostalAddress24

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		206
	Department	<Dept>		[0..1]		206
	SubDepartment	<SubDept>		[0..1]		206
	StreetName	<StrtNm>		[0..1]		207
	BuildingNumber	<BldgNb>		[0..1]		207
	BuildingName	<BldgNm>		[0..1]		207
	Floor	<Flr>		[0..1]		207
	PostBox	<PstBx>		[0..1]		207
	Room	<Room>		[0..1]		207
	PostCode	<PstCd>		[0..1]		207

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TownName	<TwnNm>		[0..1]		208
	TownLocationName	<TwnLctnNm>		[0..1]		208
	DistrictName	<DstrctNm>		[0..1]		208
	CountrySubDivision	<CtrySubDvsn>		[0..1]		208
	Country	<Ctry>		[0..1]		208
	AddressLine	<AdrLine>		[0..7]		208

Used in element(s)

"PostalAddress" on page 39, "PostalAddress" on page 100, "PostalAddress" on page 169,
 "PostalAddress" on page 103

5.111.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 27 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		28

5.111.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: "Max70Text" on page 306

5.111.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: "Max70Text" on page 306

5.111.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: "Max70Text" on page 306

5.111.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: "Max16Text" on page 303

5.111.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: "Max35Text" on page 305

5.111.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: "Max70Text" on page 306

5.111.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: "Max16Text" on page 303

5.111.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: "Max70Text" on page 306

5.111.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: "Max16Text" on page 303

5.111.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: "Max35Text" on page 305

5.111.12 TownLocationName

XML Tag: TwnLctnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: "Max35Text" on page 305

5.111.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: "Max35Text" on page 305

5.111.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: "Max35Text" on page 305

5.111.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: "CountryCode" on page 277

5.111.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "Max70Text" on page 306

5.112 PostalAddress24__1

Definition: Information that locates and identifies a specific address, as defined by postal services.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	AddressType	<AdrTp>		[0..1]		209
	Department	<Dept>		[0..1]		210
	SubDepartment	<SubDept>		[0..1]		210
	StreetName	<StrtNm>		[0..1]		211
	BuildingNumber	<BldgNb>		[0..1]		211
	BuildingName	<BldgNm>		[0..1]		212
	Floor	<Flr>		[0..1]		212
	PostBox	<PstBx>		[0..1]		213
	Room	<Room>		[0..1]		213
	PostCode	<PstCd>		[0..1]		214
	TownName	<TwnNm>		[0..1]	 	214
	TownLocationName	<TwnLctnNm>		[0..1]		215
	DistrictName	<DstrctNm>		[0..1]		215
	CountrySubDivision	<CtrySubDvsn>		[0..1]		216
	Country	<Ctry>		[0..1]		216
	AddressLine	<AdrLine>		[0..7]	 R[0..2] R[0..2] R[0..2]	217

Used in element(s)

"PostalAddress" on page 173, "PostalAddress" on page 106, "PostalAddress" on page 176

5.112.1 AddressType

XML Tag: AdrTp

Presence: [0..1]

Definition: Identifies the nature of the postal address.

The **AdrTp** block contains the following elements (see datatype "AddressType3Choice" on page 27 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		27
	Proprietary	<Prtry>	Or}	[1..1]		28

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/AddressType](#)) is removed.
- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/AddressType](#)) is removed.
- This element([camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/PostalAddress/AddressType](#)) is removed.

5.112.2 Department

XML Tag: Dept

Presence: [0..1]

Definition: Identification of a division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 273

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Originator/PostalAddress/Department](#)
 Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/Department](#)
 Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Department](#)
 Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273

5.112.3 SubDepartment

XML Tag: SubDept

Presence: [0..1]

Definition: Identification of a sub-division of a large organisation or building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 273

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/SubDepartment**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/SubDepartment**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/SubDepartment**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273

5.112.4 StreetName

XML Tag: StrtNm

Presence: [0..1]

Definition: Name of a street or thoroughfare.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended"](#) on page 273

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273
- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/StreetName**
Type changed to: [CBPR_RestrictedFINXMax70Text_Extended](#) on page 273

5.112.5 BuildingNumber

XML Tag: BldgNb

Presence: [0..1]

Definition: Number that identifies the position of a building on a street.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended"](#) on page 271

Usage Guideline details

- on **camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/BuildingNumber**

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingNumber](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

5.112.6 BuildingName

XML Tag: BldgNm

Presence: [0..1]

Definition: Name of the building or house.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/BuildingName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

5.112.7 Floor

XML Tag: Flr

Presence: [0..1]

Definition: Floor or storey within a building.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/Floor](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

5.112.8 PostBox

XML Tag: PstBx

Presence: [0..1]

Definition: Numbered box in a post office, assigned to a person or organisation, where letters are kept until called for.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 271](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/PostBox](#)

Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

5.112.9 Room

XML Tag: Room

Presence: [0..1]

Definition: Building room number.

Datatype: ["CBPR_RestrictedFINXMax70Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/Room](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/Room](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Room](#)

Type changed to: [CBPR_RestrictedFINXMax70Text_Extended on page 273](#)

5.112.10 PostCode

XML Tag: PstCd

Presence: [0..1]

Definition: Identifier consisting of a group of letters and/or numbers that is added to a postal address to assist the sorting of mail.

Datatype: ["CBPR_RestrictedFINXMax16Text_Extended" on page 271](#)

Usage Guideline details

- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/PostCode**
Type changed to: [CBPR_RestrictedFINXMax16Text_Extended on page 271](#)

5.112.11 TownName

XML Tag: TwnNm

Presence: [0..1]

Definition: Name of a built-up area, with defined boundaries, and a local government.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 273](#)

Usage Guideline details

- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownName**
This element is now mandatory, the minimum occurrence has been changed to : 1
- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/TownName**

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/TownName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

5.112.12 TownLocationName

XML Tag: TwNLCtnNm

Presence: [0..1]

Definition: Specific location name within the town.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/TownLocationName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

5.112.13 DistrictName

XML Tag: DstrctNm

Presence: [0..1]

Definition: Identifies a subdivision within a country sub-division.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/DistrictName](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

5.112.14 CountrySubDivision

XML Tag: CtrySubDvsn

Presence: [0..1]

Definition: Identifies a subdivision of a country such as state, region, county.

Datatype: ["CBPR_RestrictedFINXMax35Text_Extended" on page 273](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/CountrySubDivision](#)

Type changed to: [CBPR_RestrictedFINXMax35Text_Extended on page 273](#)

5.112.15 Country

XML Tag: Ctry

Presence: [0..1]

Definition: Nation with its own government.

Datatype: ["CountryCode" on page 277](#)

Usage Guideline details

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/Country](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/Country](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

- on [camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/Country](#)

This element is now mandatory, the minimum occurrence has been changed to : 1

5.112.16 AddressLine

XML Tag: AdrLine

Presence: [0..7]

Definition: Information that locates and identifies a specific address, as defined by postal services, presented in free format text.

Datatype: "CBPR_RestrictedFINXMax70Text_Extended" on page 273

Usage Guideline details

- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/AddressLine
This element has change repeatability, the maximum occurrence has been changed to : 2
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Agent/FinancialInstitutionIdentification/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 273
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/ResolvedCase/Creator/Party/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 273
- on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatus-ReasonInformation/Originator/PostalAddress/AddressLine
Type changed to: CBPR_RestrictedFINXMax70Text_Extended on page 273

5.113 ProxyAccountIdentification1

Definition: Information related to a proxy identification of the account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		218
	Identification	<Id>		[1..1]		218

Used in element(s)

["Proxy" on page 56](#)

5.113.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Type of the proxy identification.

The **Tp** block contains the following elements (see datatype ["ProxyAccountType1Choice"](#) on page 218 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		218
	Proprietary	<Prtry>	Or}	[1..1]		219

5.113.2 Identification

XML Tag: Id

Presence: [1..1]

Definition: Identification used to indicate the account identification under another specified name.

Datatype: ["Max2048Text"](#) on page 304

5.114 ProxyAccountType1Choice

Definition: Specifies the scheme used for the identification of an account alias.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		218
	Proprietary	<Prtry>	Or}	[1..1]		219

Used in element(s)

["Type" on page 218](#)

5.114.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Name of the identification scheme, in a coded form as published in an external list.

Datatype: ["ExternalProxyAccountType1Code"](#) on page 295

5.114.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Name of the identification scheme, in a free text form.

Datatype: "Max35Text" on page 305

5.115 Purpose2Choice

Definition: Specifies the underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		219
	Proprietary	<Prtry>	Or}	[1..1]		219

Used in element(s)

"Purpose" on page 158, "Purpose" on page 238

5.115.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Underlying reason for the payment transaction, as published in an external purpose code list.

Datatype: "ExternalPurpose1Code" on page 296

5.115.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Purpose, in a proprietary form.

Datatype: "Max35Text" on page 305

5.116 ReferredDocumentInformation7

Definition: Set of elements used to identify the documents referred to in the remittance information.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		220
	Number	<Nb>		[0..1]		220
	RelatedDate	<RltdDt>		[0..1]		220
	LineDetails	<LineDtls>		[0..*]		220

Used in element(s)

"ReferredDocumentInformation" on page 239

5.116.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of referred document.

The **Tp** block contains the following elements (see datatype "ReferredDocumentType4" on page 221 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		222
	Issuer	<Issr>		[0..1]		222

5.116.2 Number

XML Tag: Nb

Presence: [0..1]

Definition: Unique and unambiguous identification of the referred document.

Datatype: "Max35Text" on page 305

5.116.3 RelatedDate

XML Tag: RltdDt

Presence: [0..1]

Definition: Date associated with the referred document.

Datatype: "ISODate" on page 301

5.116.4 LineDetails

XML Tag: LineDtls

Presence: [0..*]

Definition: Set of elements used to provide the content of the referred document line.

The **LineDtIs** block contains the following elements (see datatype "[DocumentLineInformation1](#)" on [page 94](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..*]		94
	Description	<Desc>		[0..1]		95
	Amount	<Amt>		[0..1]		95

5.117 ReferredDocumentType3Choice

Definition: Specifies the type of the document referred in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		221
	Proprietary	<Prtry>	Or}	[1..1]		221

Used in element(s)

"[CodeOrProprietary](#)" on [page 222](#)

5.117.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Document type in a coded form.

Datatype: "[DocumentType6Code](#)" on [page 279](#)

5.117.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Proprietary identification of the type of the remittance document.

Datatype: "[Max35Text](#)" on [page 305](#)

5.118 ReferredDocumentType4

Definition: Specifies the type of the document referred in the remittance information.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CodeOrProprietary	<CdOrPrtry>		[1..1]		222
	Issuer	<Issr>		[0..1]		222

Used in element(s)

"Type" on page 220

5.118.1 CodeOrProprietary

XML Tag: CdOrPrtry

Presence: [1..1]

Definition: Provides the type details of the referred document.

The **CdOrPrtry** block contains the following elements (see datatype "[ReferredDocumentType3Choice](#)" on page 221 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		221
	Proprietary	<Prtry>	Or}	[1..1]		221

5.118.2 Issuer

XML Tag: Issr

Presence: [0..1]

Definition: Identification of the issuer of the reference document type.

Datatype: "[Max35Text](#)" on page 305

5.119 RemittanceAmount2

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		223
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		223

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		223
	TaxAmount	<TaxAmt>		[0..*]		223
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		224
	RemittedAmount	<RmtdAmt>		[0..1]		224

Used in element(s)

"ReferredDocumentAmount" on page 239

5.119.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.119.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount specified for the referred document is the amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "DiscountAmountAndType1" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		91
	Amount	<Amt>		[1..1]		91

5.119.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount specified for the referred document is the amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.119.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Quantity of cash resulting from the calculation of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on [page 244](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		245
	Amount	<Amt>		[1..1]		245

5.119.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the document adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on [page 92](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		92
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		93
	Reason	<Rsn>		[0..1]		93
	AdditionalInformation	<AddtlInf>		[0..1]		93

5.119.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted for the referred document.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on [page 263](#)

5.120 RemittanceAmount3

Definition: Nature of the amount and currency on a document referred to in the remittance section, typically either the original amount due/payable or the amount actually remitted for the referenced document.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		225
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		225
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		225
	TaxAmount	<TaxAmt>		[0..*]		225
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		226
	RemittedAmount	<RmtdAmt>		[0..1]		226

Used in element(s)

"Amount" on page 95

5.120.1 DuePayableAmount

XML Tag: DuePyblAmt

Presence: [0..1]

Definition: Amount specified is the exact amount due and payable to the creditor.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.120.2 DiscountAppliedAmount

XML Tag: DscntApldAmt

Presence: [0..*]

Definition: Amount of discount to be applied to the amount due and payable to the creditor.

The **DscntApldAmt** block contains the following elements (see datatype "DiscountAmountAndType1" on page 91 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		91
	Amount	<Amt>		[1..1]		91

5.120.3 CreditNoteAmount

XML Tag: CdtNoteAmt

Presence: [0..1]

Definition: Amount of a credit note.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.120.4 TaxAmount

XML Tag: TaxAmt

Presence: [0..*]

Definition: Amount of the tax.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmountAndType1](#)" on [page 244](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		245
	Amount	<Amt>		[1..1]		245

5.120.5 AdjustmentAmountAndReason

XML Tag: AdjstmntAmtAndRsn

Presence: [0..*]

Definition: Specifies detailed information on the amount and reason of the adjustment.

The **AdjstmntAmtAndRsn** block contains the following elements (see datatype "[DocumentAdjustment1](#)" on [page 92](#) for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		92
	CreditDebitIndicator	<CdtDbtInd>		[0..1]		93
	Reason	<Rsn>		[0..1]		93
	AdditionalInformation	<AddtlInf>		[0..1]		93

5.120.6 RemittedAmount

XML Tag: RmtdAmt

Presence: [0..1]

Definition: Amount of money remitted.

Datatype: "[ActiveOrHistoricCurrencyAndAmount](#)" on [page 263](#)

5.121 RemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Unstructured	<Ustrd>		[0..*]		227
	Structured	<Strd>		[0..*]		227

Used in element(s)

"RemittanceInformation" on page 154

5.121.1 Unstructured

XML Tag: Ustrd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in an unstructured form.

Datatype: "Max140Text" on page 303

5.121.2 Structured

XML Tag: Strd

Presence: [0..*]

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

The **Strd** block contains the following elements (see datatype "[StructuredRemittanceInformation16](#)" on page 238 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		239
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		239
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		240
	Invoicer	<Invcr>		[0..1]		240
	Invoicee	<Invcee>		[0..1]		241
	TaxRemittance	<TaxRmt>		[0..1]		241
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		242
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		242

5.122 ResolutionData1

Definition: Specifies additional information as expected by the party that the investigation performs the expected actions for its resolution.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	EndToEndIdentification	<EndToEndId>		[0..1]		228
	TransactionIdentification	<TxId>		[0..1]		228
	UETR	<UETR>		[0..1]		228
	InterbankSettlementAmount	<IntrBkSttlmAmt>		[0..1]		229
	InterbankSettlementDate	<IntrBkSttlmDt>		[0..1]		229
	ClearingChannel	<ClrChanl>		[0..1]		229
	Compensation	<Compstn>		[0..1]		229
	Charges	<Chrgs>		[0..*]		229

Used in element(s)

"ResolutionRelatedInformation" on page 24, "ResolutionRelatedInformation" on page 195, "ResolutionRelatedInformation" on page 184

5.122.1 EndToEndIdentification

XML Tag: EndToEndId

Presence: [0..1]

Definition: Unique identification, as assigned by the original initiating party, to unambiguously identify the original transaction.

Datatype: "Max35Text" on page 305

5.122.2 TransactionIdentification

XML Tag: TxId

Presence: [0..1]

Definition: Unique identification, as assigned by the original first instructing agent, to unambiguously identify the transaction.

Datatype: "Max35Text" on page 305

5.122.3 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: "UUIDv4Identifier" on page 317

5.122.4 InterbankSettlementAmount

XML Tag: IntrBkSttlmAmt

Presence: [0..1]

Definition: Amount of money moved between the instructing agent and the instructed agent.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.122.5 InterbankSettlementDate

XML Tag: IntrBkSttlmDt

Presence: [0..1]

Definition: Date on which the amount of money ceases to be available to the agent that owes it and when the amount of money becomes available to the agent to which it is due.

Datatype: "ISODate" on page 301

5.122.6 ClearingChannel

XML Tag: ClrChanl

Presence: [0..1]

Definition: Specifies the clearing channel to be used to process the payment instruction.

Datatype: "ClearingChannel2Code" on page 275

5.122.7 Compensation

XML Tag: Compstn

Presence: [0..1]

Definition: Provides the details of the compensation made due to the modification or cancellation of a previous payment.

The **Compstn** block contains the following elements (see datatype "Compensation2" on page 70 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		70
	DebtorAgent	<DbtrAgt>		[1..1]		71
	CreditorAgent	<CdtrAgt>		[1..1]		71
	Reason	<Rsn>		[1..1]		71

5.122.8 Charges

XML Tag: Chrgs

Presence: [0..*]

Definition: Provides information on the charges to be paid by the charge bearer(s) related to the payment transaction.

The **Chrgs** block contains the following elements (see datatype "[Charges7](#)" on page 60 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Amount	<Amt>		[1..1]		60
	Agent	<Agt>		[1..1]		60

5.123 ServiceLevel8Choice

Definition: Specifies the service level of the transaction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		230
	Proprietary	<Prtry>	Or}	[1..1]		230

Used in element(s)

"[ServiceLevel](#)" on page 199

5.123.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as published in an external service level code list.

Datatype: "[ExternalServiceLevel1Code](#)" on page 297

5.123.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies a pre-agreed service or level of service between the parties, as a proprietary code.

Datatype: "[Max35Text](#)" on page 305

5.124 SettlementInstruction7

Definition: Provides further details on the settlement of the instruction.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	SettlementMethod	<SttlmMtd>		[1..1]		233
	SettlementAccount	<SttlmAcct>		[0..1]		233
	ClearingSystem	<ClrSys>		[0..1]		233
	InstructingReimbursementAgent	<InstgRmbrsmntAgt>		[0..1]		234
	InstructingReimbursementAgentAccount	<InstgRmbrsmntAgtAcct>		[0..1]		234
	InstructedReimbursementAgent	<InstdRmbrsmntAgt>		[0..1]		234
	InstructedReimbursementAgentAccount	<InstdRmbrsmntAgtAcct>		[0..1]		235
	ThirdReimbursementAgent	<ThrdRmbrsmntAgt>		[0..1]		235
	ThirdReimbursementAgentAccount	<ThrdRmbrsmntAgtAcct>		[0..1]		236

Rules

R25 ThirdReimbursementAgentRule ✓

If ThirdReimbursementAgent is present, then InstructingReimbursementAgent and InstructedReimbursementAgent must both be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00040
- *Error Text:* Invalid message content for third reimbursement agent.

R26 SettlementMethodAgentRule ✓

If SettlementMethod is equal to INDA or INGA, then ReimbursementAgent(s) and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00018
- *Error Text:* Invalid message content for settlement method INGA or INDA.

R27 SettlementMethodCoverRule ✓

If SettlementMethod is equal to COVE, then SettlementAccount and ClearingSystem are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00075
- *Error Text:* Invalid message content for cover settlement method with settlement account and clearing system.

R28 SettlementMethodCoverAgentRule ✓

If SettlementMethod is equal to COVE, then InstructedReimbursementAgent or InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00076
- *Error Text:* Invalid message content for cover settlement method and reimbursement agents.

R29 SettlementMethodClearingRule ✓

If SettlementMethod is equal to CLRG, then SettlementAccount and ReimbursementAgent(s) are not allowed.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00019
- *Error Text:* Invalid message content for settlement method CLRG.

R30 InstructingReimbursementAgentAccountRule ✓

If InstructingReimbursementAgentAccount is present, then InstructingReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00038
- *Error Text:* Invalid message content for instructing reimbursement agent account.

R31 InstructedReimbursementAgentAccountRule ✓

If InstructedReimbursementAgentAccount is present, then InstructedReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00037
- *Error Text:* Invalid message content for instructed reimbursement agent account.

R32 ThirdReimbursementAgentAccountRule ✓

If ThirdReimbursementAgentAccount is present, then ThirdReimbursementAgent must be present.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00039
- *Error Text:* Invalid message content for third reimbursement agent account.

Used in element(s)

["SettlementInformation" on page 152](#)

5.124.1 SettlementMethod

XML Tag: SttlmMtd

Presence: [1..1]

Definition: Method used to settle the (batch of) payment instructions.

Datatype: ["SettlementMethod1Code" on page 313](#)

5.124.2 SettlementAccount

XML Tag: SttlmAcct

Presence: [0..1]

Definition: A specific purpose account used to post debit and credit entries as a result of the transaction.

The **SttlmAcct** block contains the following elements (see datatype ["CashAccount38" on page 54](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.124.3 ClearingSystem

XML Tag: ClrSys

Presence: [0..1]

Definition: Specification of a pre-agreed offering between clearing agents or the channel through which the payment instruction is processed.

The **ClrSys** block contains the following elements (see datatype ["ClearingSystemIdentification3Choice" on page 66](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		67
	Proprietary	<Prtry>	Or}	[1..1]		67

5.124.4 InstructingReimbursementAgent

XML Tag: InstgRmbrsmntAgt

Presence: [0..1]

Definition: Agent through which the instructing agent will reimburse the instructed agent.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstgRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.124.5 InstructingReimbursementAgentAccount

XML Tag: InstgRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructing reimbursement agent account at its servicing agent in the payment chain.

The **InstgRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.124.6 InstructedReimbursementAgent

XML Tag: InstdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If InstructedReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

Usage: If InstructingAgent and InstructedAgent have the same reimbursement agent, then only InstructingReimbursementAgent must be used.

The **InstdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.124.7 InstructedReimbursementAgentAccount

XML Tag: InstdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the instructed reimbursement agent account at its servicing agent in the payment chain.

The **InstdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.124.8 ThirdReimbursementAgent

XML Tag: ThrdRmbrsmntAgt

Presence: [0..1]

Definition: Agent at which the instructed agent will be reimbursed.

Usage: If ThirdReimbursementAgent contains a branch of the InstructedAgent, then the party in InstructedAgent will claim reimbursement from that branch/will be paid by that branch.

The **ThrdRmbrsmntAgt** block contains the following elements (see datatype "[BranchAndFinancialInstitutionIdentification6](#)" on page 34 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FinancialInstitutionIdentification	<FinInstnId>		[1..1]		34
	BranchIdentification	<BrnchId>		[0..1]		35

5.124.9 ThirdReimbursementAgentAccount

XML Tag: ThrdRmbrsmntAgtAcct

Presence: [0..1]

Definition: Unambiguous identification of the account of the third reimbursement agent account at its servicing agent in the payment chain.

The **ThrdRmbrsmntAgtAcct** block contains the following elements (see datatype "[CashAccount38](#)" on page 54 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[1..1]		55
	Type	<Tp>		[0..1]		55
	Currency	<Ccy>		[0..1]		56
	Name	<Nm>		[0..1]		56
	Proxy	<Prxy>		[0..1]		56

5.125 StatementResolutionEntry4

Definition: Provides further details on the statement entry for the resolution of the investigation.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		237
	OriginalStatementIdentification	<OrgnlStmntId>		[0..1]		237
	UETR	<UETR>		[0..1]		237
	AccountServicerReference	<AcctSvcrRef>		[0..1]		237
	CorrectedAmount	<CrrctdAmt>		[0..1]		237
	Charges	<Chrgs>		[0..*]		238
	Purpose	<Purp>		[0..1]		238

Used in element(s)

["StatementDetails" on page 23](#)

5.125.1 OriginalGroupInformation

XML Tag: OrgnlGrpInf

Presence: [0..1]

Definition: Provides information on the original message.

The **OrgnlGrpInf** block contains the following elements (see datatype ["OriginalGroupInformation29" on page 142](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		143
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		143
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		143

5.125.2 OriginalStatementIdentification

XML Tag: OrgnlStmtd

Presence: [0..1]

Definition: Unique identification, as assigned by the account servicer, to unambiguously identify the original statement.

Datatype: ["Max35Text" on page 305](#)

5.125.3 UETR

XML Tag: UETR

Presence: [0..1]

Definition: Universally unique identifier to provide an end-to-end reference of a payment transaction.

Datatype: ["UUIDv4Identifier" on page 317](#)

5.125.4 AccountServicerReference

XML Tag: AcctSvcrRef

Presence: [0..1]

Definition: Unique reference, as assigned by the account servicing institution, to unambiguously identify the entry.

Datatype: ["Max35Text" on page 305](#)

5.125.5 CorrectedAmount

XML Tag: CrrctdAmt

Presence: [0..1]

Definition: Corrected debit or credit amount, compared to the original entry where the amount is incorrect.

Usage: This amount may only be present if an incorrect statement entry has been reported.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.125.6 Charges

XML Tag: Chrgs

Presence: [0..*]

Definition: Provides information on the charges included in the original entry amount.

The **Chrgs** block contains the following elements (see datatype ["Charges6" on page 59](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TotalChargesAndTaxAmount	<TtlChrgsAndTaxAmt>		[0..1]		59
	Record	<Rcrd>		[0..*]		59

5.125.7 Purpose

XML Tag: Purp

Presence: [0..1]

Definition: Underlying reason for the payment transaction.

Usage: Purpose is used by the end-customers, that is initiating party, (ultimate) debtor, (ultimate) creditor to provide information concerning the nature of the payment. Purpose is a content element, which is not used for processing by any of the agents involved in the payment chain.

The **Purp** block contains the following elements (see datatype ["Purpose2Choice" on page 219](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		219
	Proprietary	<Prtry>	Or}	[1..1]		219

5.126 StructuredRemittanceInformation16

Definition: Information supplied to enable the matching/reconciliation of an entry with the items that the payment is intended to settle, such as commercial invoices in an accounts' receivable system, in a structured form.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ReferredDocumentInformation	<RfrdDocInf>		[0..*]		239
	ReferredDocumentAmount	<RfrdDocAmt>		[0..1]		239
	CreditorReferenceInformation	<CdtrRefInf>		[0..1]		240
	Invoicer	<Invcr>		[0..1]		240
	Invoicee	<Invcee>		[0..1]		241
	TaxRemittance	<TaxRmt>		[0..1]		241
	GarnishmentRemittance	<GrnshmtRmt>		[0..1]		242
	AdditionalRemittanceInformation	<AddtlRmtInf>		[0..3]		242

Used in element(s)

"Structured" on page 227

5.126.1 ReferredDocumentInformation

XML Tag: RfrdDocInf

Presence: [0..*]

Definition: Provides the identification and the content of the referred document.

The **RfrdDocInf** block contains the following elements (see datatype "[ReferredDocumentInformation7](#)" on page 219 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		220
	Number	<Nb>		[0..1]		220
	RelatedDate	<RltdDt>		[0..1]		220
	LineDetails	<LineDtls>		[0..*]		220

5.126.2 ReferredDocumentAmount

XML Tag: RfrdDocAmt

Presence: [0..1]

Definition: Provides details on the amounts of the referred document.

The **RfrdDocAmt** block contains the following elements (see datatype "[RemittanceAmount2](#)" on page 222 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	DuePayableAmount	<DuePyblAmt>		[0..1]		223
	DiscountAppliedAmount	<DscntApldAmt>		[0..*]		223
	CreditNoteAmount	<CdtNoteAmt>		[0..1]		223
	TaxAmount	<TaxAmt>		[0..*]		223
	AdjustmentAmountAndReason	<AdjstmntAmtAndRsn>		[0..*]		224
	RemittedAmount	<RmtdAmt>		[0..1]		224

5.126.3 CreditorReferenceInformation

XML Tag: CdtrRefInf

Presence: [0..1]

Definition: Reference information provided by the creditor to allow the identification of the underlying documents.

The **CdtrRefInf** block contains the following elements (see datatype "[CreditorReferenceInformation2](#)" on page 83 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		83
	Reference	<Ref>		[0..1]		83

5.126.4 Invoicer

XML Tag: Invcr

Presence: [0..1]

Definition: Identification of the organisation issuing the invoice, when it is different from the creditor or ultimate creditor.

The **Invcr** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.126.5 Invoicee

XML Tag: Invcee

Presence: [0..1]

Definition: Identification of the party to whom an invoice is issued, when it is different from the debtor or ultimate debtor.

The **Invcee** block contains the following elements (see datatype "[PartyIdentification135](#)" on page 169 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Name	<Nm>		[0..1]		169
	PostalAddress	<PstlAdr>		[0..1]		169
	Identification	<Id>		[0..1]		170
	CountryOfResidence	<CtryOfRes>		[0..1]		171
	ContactDetails	<CtctDtls>		[0..1]		171

5.126.6 TaxRemittance

XML Tag: TaxRmt

Presence: [0..1]

Definition: Provides remittance information about a payment made for tax-related purposes.

The **TaxRmt** block contains the following elements (see datatype "[TaxInformation7](#)" on page 247 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		248
	Debtor	<Dbtr>		[0..1]		248
	UltimateDebtor	<UltmtDbtr>		[0..1]		249
	AdministrationZone	<AdmstnZone>		[0..1]		249
	ReferenceNumber	<RefNb>		[0..1]		249

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Method	<Mtd>		[0..1]		249
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		250
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		250
	Date	<Dt>		[0..1]		250
	SequenceNumber	<SeqNb>		[0..1]		250
	Record	<Rcrd>		[0..*]		250

5.126.7 GarnishmentRemittance

XML Tag: GrnshmtRmt

Presence: [0..1]

Definition: Provides remittance information about a payment for garnishment-related purposes.

The **GrnshmtRmt** block contains the following elements (see datatype "[Garnishment3](#)" on page 110 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[1..1]		111
	Garnishee	<Grnshee>		[0..1]		111
	GarnishmentAdministrator	<GrnshmtAdmstr>		[0..1]		111
	ReferenceNumber	<RefNb>		[0..1]		112
	Date	<Dt>		[0..1]		112
	RemittedAmount	<RmtdAmt>		[0..1]		112
	FamilyMedicalInsuranceIndicator	<FmlyMdclInsrnclnd>		[0..1]		112
	EmployeeTerminationIndicator	<MplyeeTermntnInd>		[0..1]		112

5.126.8 AdditionalRemittanceInformation

XML Tag: AddtlRmtInf

Presence: [0..3]

Definition: Additional information, in free text form, to complement the structured remittance information.

Datatype: "[Max140Text](#)" on page 303

5.127 SupplementaryData1

Definition: Additional information that can not be captured in the structured fields and/or any other specific block.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	PlaceAndName	<PlcAndNm>		[0..1]		243
	Envelope	<Envlp>		[1..1]		243

Rules

R33 SupplementaryDataRule

This component may not be used without the explicit approval of a SEG and submission to the RA of ISO 20022 compliant structure(s) to be used in the Envelope element.

Error handling: Undefined

Used in element(s)

"SupplementaryData" on page 24

5.127.1 PlaceAndName

XML Tag: PlcAndNm

Presence: [0..1]

Definition: Unambiguous reference to the location where the supplementary data must be inserted in the message instance.

In the case of XML, this is expressed by a valid XPath.

Datatype: "Max350Text" on page 304

5.127.2 Envelope

XML Tag: Envlp

Presence: [1..1]

Definition: Technical element wrapping the supplementary data.

5.128 TaxAmount2

Definition: Set of elements used to provide information on the tax amount(s) of tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		244
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		244
	TotalAmount	<TtlAmt>		[0..1]		244
	Details	<Dtls>		[0..*]		244

Used in element(s)

"TaxAmount" on page 256

5.128.1 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: "PercentageRate" on page 310

5.128.2 TaxableBaseAmount

XML Tag: TaxblBaseAmt

Presence: [0..1]

Definition: Amount of money on which the tax is based.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.128.3 TotalAmount

XML Tag: TtlAmt

Presence: [0..1]

Definition: Total amount that is the result of the calculation of the tax for the record.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.128.4 Details

XML Tag: Dtls

Presence: [0..*]

Definition: Set of elements used to provide details on the tax period and amount.

The **Dtls** block contains the following elements (see datatype "TaxRecordDetails2" on page 256 for details)

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		257
	Amount	<Amt>		[1..1]		257

5.129 TaxAmountAndType1

Definition: Specifies the amount with a specific type.

 Removed -  Partial Removed -  Ignored -  Partial Ignored -  Details below -

 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		245
	Amount	<Amt>		[1..1]		245

Used in element(s)

["TaxAmount" on page 223](#), ["TaxAmount" on page 225](#)

5.129.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: Specifies the type of the amount.

The **Tp** block contains the following elements (see datatype ["TaxAmountType1Choice" on page 245](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		246
	Proprietary	<Prtry>	Or}	[1..1]		246

5.129.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Amount of money, which has been typed.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.130 TaxAmountType1Choice

Definition: Specifies the amount type.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Code	<Cd>	{Or	[1..1]		246
	Proprietary	<Prtry>	Or}	[1..1]		246

Used in element(s)

["Type" on page 245](#)

5.130.1 Code

XML Tag: Cd

Presence: [1..1]

Definition: Specifies the amount type, in a coded form.

Datatype: "ExternalTaxAmountType1Code" on page 297

5.130.2 Proprietary

XML Tag: Prtry

Presence: [1..1]

Definition: Specifies the amount type, in a free-text form.

Datatype: "Max35Text" on page 305

5.131 TaxAuthorisation1

Definition: Details of the authorised tax paying party.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		246
	Name	<Nm>		[0..1]		246

Used in element(s)

"Authorisation" on page 252

5.131.1 Title

XML Tag: Titl

Presence: [0..1]

Definition: Title or position of debtor or the debtor's authorised representative.

Datatype: "Max35Text" on page 305

5.131.2 Name

XML Tag: Nm

Presence: [0..1]

Definition: Name of the debtor or the debtor's authorised representative.

Datatype: "Max140Text" on page 303

5.132 TaxCharges2

Definition: Amount of money due to the government or tax authority, according to various pre-defined parameters such as thresholds or income.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Identification	<Id>		[0..1]		247
	Rate	<Rate>		[0..1]		247
	Amount	<Amt>		[0..1]		247

Used in element(s)

["Tax" on page 62](#)

5.132.1 Identification

XML Tag: Id

Presence: [0..1]

Definition: Unique reference to unambiguously identify the nature of the tax levied, such as Value Added Tax (VAT).

Datatype: ["Max35Text" on page 305](#)

5.132.2 Rate

XML Tag: Rate

Presence: [0..1]

Definition: Rate used to calculate the tax.

Datatype: ["PercentageRate" on page 310](#)

5.132.3 Amount

XML Tag: Amt

Presence: [0..1]

Definition: Amount of money resulting from the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.133 TaxInformation7

Definition: Details about tax paid, or to be paid, to the government in accordance with the law, including pre-defined parameters such as thresholds and type of account.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Creditor	<Cdtr>		[0..1]		248
	Debtor	<Dbtr>		[0..1]		248
	UltimateDebtor	<UltmtDbtr>		[0..1]		249
	AdministrationZone	<AdmstnZone>		[0..1]		249
	ReferenceNumber	<RefNb>		[0..1]		249
	Method	<Mtd>		[0..1]		249
	TotalTaxableBaseAmount	<TtlTaxblBaseAmt>		[0..1]		250
	TotalTaxAmount	<TtlTaxAmt>		[0..1]		250
	Date	<Dt>		[0..1]		250
	SequenceNumber	<SeqNb>		[0..1]		250
	Record	<Rcrd>		[0..*]		250

Used in element(s)

"TaxRemittance" on page 241

5.133.1 Creditor

XML Tag: Cdtr

Presence: [0..1]

Definition: Party on the credit side of the transaction to which the tax applies.

The **Cdtr** block contains the following elements (see datatype "TaxParty1" on page 251 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		251
	RegistrationIdentification	<RegnId>		[0..1]		251
	TaxType	<TaxTp>		[0..1]		251

5.133.2 Debtor

XML Tag: Dbtr

Presence: [0..1]

Definition: Identifies the party on the debit side of the transaction to which the tax applies.

The **Dbtr** block contains the following elements (see datatype "TaxParty2" on page 252 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		252
	RegistrationIdentification	<RegnId>		[0..1]		252
	TaxType	<TaxTp>		[0..1]		252
	Authorisation	<Authstn>		[0..1]		252

5.133.3 UltimateDebtor

XML Tag: UltmtDbtr

Presence: [0..1]

Definition: Ultimate party that owes an amount of money to the (ultimate) creditor, in this case, to the taxing authority.

The **UltmtDbtr** block contains the following elements (see datatype "[TaxParty2](#)" on page 252 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
 Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		252
	RegistrationIdentification	<RegnId>		[0..1]		252
	TaxType	<TaxTp>		[0..1]		252
	Authorisation	<Authstn>		[0..1]		252

5.133.4 AdministrationZone

XML Tag: AdmstnZone

Presence: [0..1]

Definition: Territorial part of a country to which the tax payment is related.

Datatype: "[Max35Text](#)" on page 305

5.133.5 ReferenceNumber

XML Tag: RefNb

Presence: [0..1]

Definition: Tax reference information that is specific to a taxing agency.

Datatype: "[Max140Text](#)" on page 303

5.133.6 Method

XML Tag: Mtd

Presence: [0..1]

Definition: Method used to indicate the underlying business or how the tax is paid.

Datatype: ["Max35Text" on page 305](#)

5.133.7 TotalTaxableBaseAmount

XML Tag: TtlTaxblBaseAmt

Presence: [0..1]

Definition: Total amount of money on which the tax is based.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.133.8 TotalTaxAmount

XML Tag: TtlTaxAmt

Presence: [0..1]

Definition: Total amount of money as result of the calculation of the tax.

Datatype: ["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

5.133.9 Date

XML Tag: Dt

Presence: [0..1]

Definition: Date by which tax is due.

Datatype: ["ISODate" on page 301](#)

5.133.10 SequenceNumber

XML Tag: SeqNb

Presence: [0..1]

Definition: Sequential number of the tax report.

Datatype: ["Number" on page 307](#)

5.133.11 Record

XML Tag: Rcrd

Presence: [0..*]

Definition: Record of tax details.

The **Rcrd** block contains the following elements (see datatype ["TaxRecord2" on page 254](#) for details)

❌ Removed - ❌ Partial Removed - ❖ Ignored - ❖ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		254
	Category	<Ctgy>		[0..1]		254

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CategoryDetails	<CtgyDtls>		[0..1]		255
	DebtorStatus	<DbtrSts>		[0..1]		255
	CertificateIdentification	<CertId>		[0..1]		255
	FormsCode	<FrmsCd>		[0..1]		255
	Period	<Prd>		[0..1]		255
	TaxAmount	<TaxAmt>		[0..1]		256
	AdditionalInformation	<AddtlInf>		[0..1]		256

5.134 TaxParty1

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory -
 R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		251
	RegistrationIdentification	<RegnId>		[0..1]		251
	TaxType	<TaxTp>		[0..1]		251

Used in element(s)

"Creditor" on page 248

5.134.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the creditor.

Datatype: "Max35Text" on page 305

5.134.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: "Max35Text" on page 305

5.134.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 305](#)

5.135 TaxParty2

Definition: Details about the entity involved in the tax paid or to be paid.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	TaxIdentification	<TaxId>		[0..1]		252
	RegistrationIdentification	<RegnId>		[0..1]		252
	TaxType	<TaxTp>		[0..1]		252
	Authorisation	<Authstn>		[0..1]		252

Used in element(s)

["Debtor" on page 248](#), ["UltimateDebtor" on page 249](#)

5.135.1 TaxIdentification

XML Tag: TaxId

Presence: [0..1]

Definition: Tax identification number of the debtor.

Datatype: ["Max35Text" on page 305](#)

5.135.2 RegistrationIdentification

XML Tag: RegnId

Presence: [0..1]

Definition: Unique identification, as assigned by an organisation, to unambiguously identify a party.

Datatype: ["Max35Text" on page 305](#)

5.135.3 TaxType

XML Tag: TaxTp

Presence: [0..1]

Definition: Type of tax payer.

Datatype: ["Max35Text" on page 305](#)

5.135.4 Authorisation

XML Tag: Authstn

Presence: [0..1]

Definition: Details of the authorised tax paying party.

The **Authstn** block contains the following elements (see datatype "[TaxAuthorisation1](#)" on page 246 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Title	<Titl>		[0..1]		246
	Name	<Nm>		[0..1]		246

5.136 TaxPeriod2

Definition: Period of time details related to the tax payment.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		253
	Type	<Tp>		[0..1]		253
	FromDate	<FrToDt>		[0..1]		253

Used in element(s)

"Period" on page 255, "Period" on page 257

5.136.1 Year

XML Tag: Yr

Presence: [0..1]

Definition: Year related to the tax payment.

Datatype: "[ISODate](#)" on page 301

5.136.2 Type

XML Tag: Tp

Presence: [0..1]

Definition: Identification of the period related to the tax payment.

Datatype: "[TaxRecordPeriod1Code](#)" on page 314

5.136.3 FromToDate

XML Tag: FrToDt

Presence: [0..1]

Definition: Range of time between a start date and an end date for which the tax report is provided.

The **FrToDt** block contains the following elements (see datatype "[DatePeriod2](#)" on page 90 for details)

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	FromDate	<FrDt>		[1..1]		90
	ToDate	<ToDt>		[1..1]		90

5.137 TaxRecord2

Definition: Set of elements used to define the tax record.

🚫 Removed - 🚫 Partial Removed - ⬜ Ignored - ⬜ Partial Ignored - ⚠ Details below -
M Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Type	<Tp>		[0..1]		254
	Category	<Ctgy>		[0..1]		254
	CategoryDetails	<CtgyDtls>		[0..1]		255
	DebtorStatus	<DbtrSts>		[0..1]		255
	CertificateIdentification	<CertId>		[0..1]		255
	FormsCode	<FrmsCd>		[0..1]		255
	Period	<Prd>		[0..1]		255
	TaxAmount	<TaxAmt>		[0..1]		256
	AdditionalInformation	<AddtlInf>		[0..1]		256

Used in element(s)

"Record" on page 250

5.137.1 Type

XML Tag: Tp

Presence: [0..1]

Definition: High level code to identify the type of tax details.

Datatype: "[Max35Text](#)" on page 305

5.137.2 Category

XML Tag: CtgY

Presence: [0..1]

Definition: Specifies the tax code as published by the tax authority.

Datatype: ["Max35Text" on page 305](#)

5.137.3 CategoryDetails

XML Tag: CtgYDtIs

Presence: [0..1]

Definition: Provides further details of the category tax code.

Datatype: ["Max35Text" on page 305](#)

5.137.4 DebtorStatus

XML Tag: DbtrSts

Presence: [0..1]

Definition: Code provided by local authority to identify the status of the party that has drawn up the settlement document.

Datatype: ["Max35Text" on page 305](#)

5.137.5 CertificateIdentification

XML Tag: CertId

Presence: [0..1]

Definition: Identification number of the tax report as assigned by the taxing authority.

Datatype: ["Max35Text" on page 305](#)

5.137.6 FormsCode

XML Tag: FrmsCd

Presence: [0..1]

Definition: Identifies, in a coded form, on which template the tax report is to be provided.

Datatype: ["Max35Text" on page 305](#)

5.137.7 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype ["TaxPeriod2" on page 253](#) for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		253
	Type	<Tp>		[0..1]		253
	FromToDate	<FrToDt>		[0..1]		253

5.137.8 TaxAmount

XML Tag: TaxAmt

Presence: [0..1]

Definition: Set of elements used to provide information on the amount of the tax record.

The **TaxAmt** block contains the following elements (see datatype "[TaxAmount2](#)" on page 243 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Rate	<Rate>		[0..1]		244
	TaxableBaseAmount	<TaxblBaseAmt>		[0..1]		244
	TotalAmount	<TtlAmt>		[0..1]		244
	Details	<Dtls>		[0..*]		244

5.137.9 AdditionalInformation

XML Tag: AddtlInf

Presence: [0..1]

Definition: Further details of the tax record.

Datatype: "[Max140Text](#)" on page 303

5.138 TaxRecordDetails2

Definition: Provides information on the individual tax amount(s) per period of the tax record.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Period	<Prd>		[0..1]		257
	Amount	<Amt>		[1..1]		257

Used in element(s)

"Details" on page 244

5.138.1 Period

XML Tag: Prd

Presence: [0..1]

Definition: Set of elements used to provide details on the period of time related to the tax payment.

The **Prd** block contains the following elements (see datatype "TaxPeriod2" on page 253 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	Year	<Yr>		[0..1]		253
	Type	<Tp>		[0..1]		253
	FromDate	<FrToDt>		[0..1]		253

5.138.2 Amount

XML Tag: Amt

Presence: [1..1]

Definition: Underlying tax amount related to the specified period.

Datatype: "ActiveOrHistoricCurrencyAndAmount" on page 263

5.139 UnderlyingTransaction22__1

Definition: Identifies the underlying (group of) transaction(s) to which the resolution of investigation applies.

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupInformationAndStatus	<OrgnlGrpInfAndSts>		[0..1]		258
	OriginalPaymentInformationAndStatus	<OrgnlPmtInfAndSts>		[0..*]		259
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]	 R[1..1]	260

Rules

R34 GroupOrPaymentInformationResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus level, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

– Error severity: Fatal

- *Error Code:* X00114
- *Error Text:* Invalid message content for unique resolved case element.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/CancellationDetails/GroupOrPaymentInformationResolvedCaseRule) is removed.**

R35 GroupOrInitiationTransactionResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus level, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00115
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/CancellationDetails/GroupOrInitiationTransactionResolvedCaseRule) is removed.**

R36 GroupOrInterbankTransactionResolvedCaseRule ✓

ResolvedCase may be present at either ResolvedCase, OriginalGroupInformationAndStatus level, OriginalPaymentInformationAndStatus or TransactionInformationAndStatus level.

Error handling:

- *Error severity:* Fatal
- *Error Code:* X00116
- *Error Text:* Invalid message content for uniqueness of resolved case.

Usage Guideline restrictions for this element

- **This rule(camt.029.001.09/CancellationDetails/GroupOrInterbankTransactionResolvedCaseRule) is removed.**

Used in element(s)

"CancellationDetails" on page 21

5.139.1 OriginalGroupInformationAndStatus

XML Tag: OrgnlGrpInfAndSts

Presence: [0..1]

Definition: Provides information on the original cancellation message, to which the resolution refers.

The **OrgnlGrpInfAndSts** block contains the following elements (see datatype "OriginalGroupHeader14" on page 139 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalGroupCancellationIdentification	<OrgnlGrpCxlId>		[0..1]		139
	ResolvedCase	<RslvdCase>		[0..1]		140
	OriginalMessageIdentification	<OrgnlMsgId>		[1..1]		140
	OriginalMessageNameIdentification	<OrgnlMsgNmId>		[1..1]		140
	OriginalCreationDateTime	<OrgnlCreDtTm>		[0..1]		141
	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]		141
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		141
	GroupCancellationStatus	<GrpCxlSts>		[0..1]		141
	CancellationStatusReasonInformation	<CxlStsRsnInf>		[0..*]		141
	NumberOfTransactionsPerCancellationStatus	<NbOfTxPerCxlSts>		[0..*]		142

Usage Guideline details

- This element([camt.029.001.09/CancellationDetails/OriginalGroupInformationAndStatus](#)) is removed.

5.139.2 OriginalPaymentInformationAndStatus

XML Tag: OrgnlPmtInfAndSts

Presence: [0..*]

Definition: Provides information on the original (group of) transactions, to which the cancellation status refers.

The **OrgnlPmtInfAndSts** block contains the following elements (see datatype "[OriginalPaymentInstruction30](#)" on page 145 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalPaymentInformationCancellationIdentification	<OrgnlPmtInfCxlId>		[0..1]		146
	ResolvedCase	<RslvdCase>		[0..1]		147
	OriginalPaymentInformationIdentification	<OrgnlPmtInfId>		[1..1]		147
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		147

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	OriginalNumberOfTransactions	<OrgnlNbOfTx>		[0..1]		147
	OriginalControlSum	<OrgnlCtrlSum>		[0..1]		148
	PaymentInformationCancellationStatus	<PmtInfCxlSts>		[0..1]		148
	CancellationStatusReasonInformation	<CxlStsRsnInf>		[0..*]		148
	NumberOfTransactionsPerCancellationStatus	<NbOfTxPerCxlSts>		[0..*]		148
	TransactionInformationAndStatus	<TxInfAndSts>		[0..*]		149

Usage Guideline details

- This element(camt.029.001.09/CancellationDetails/OriginalPaymentInformationAndStatus) is removed.

5.139.3 TransactionInformationAndStatus

XML Tag: TxInfAndSts

Presence: [0..*]

Definition: Provides details on the original transactions to which the cancellation request message refers.

The **TxInfAndSts** block contains the following elements (see datatype "PaymentTransaction102__1" on page 178 for details)

 Removed -
  Partial Removed -
  Ignored -
  Partial Ignored -
  Details below -
  Mandatory - R[x..x] Repeatability[details]

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	CancellationStatusIdentification	<CxlStsId>		[0..1]	 	179
	ResolvedCase	<RslvdCase>		[0..1]		180
	OriginalGroupInformation	<OrgnlGrpInf>		[0..1]		180
	OriginalInstructionIdentification	<OrgnlInstrId>		[0..1]		181
	OriginalEndToEndIdentification	<OrgnlEndToEndId>		[0..1]		181
	OriginalTransactionIdentification	<OrgnlTxId>		[0..1]		182
	OriginalClearingSystemReference	<OrgnlClrSysRef>		[0..1]		182
	OriginalUETR	<OrgnlUETR>		[0..1]	 	183
	TransactionCancellationStatus	<TxCxlSts>		[0..1]		183
	CancellationStatusReasonInformation	<CxlStsRsnInf>		[0..*]	 R[0..1]	183

Index	Message Item	<XML Tag>	Or	Mult.	Usage Guidelines	Page
	ResolutionRelatedInformation	<RsltnRltdInf>		[0..1]		184
	OriginalInterbankSettlementAmount	<OrgnlIntrBkSttlmAmt>		[0..1]		185
	OriginalInterbankSettlementDate	<OrgnlIntrBkSttlmDt>		[0..1]		185
	Assigner	<Assgnr>		[0..1]		186
	Assignee	<Assgne>		[0..1]		186
	OriginalTransactionReference	<OrgnlTxRef>		[0..1]		187

Usage Guideline details

- **on camt.029.001.09/CancellationDetails/TransactionInformationAndStatus**

This element is now mandatory, the minimum occurrence has been changed to : 1

This element has change repeatability, the maximum occurrence has been changed to : 1

6 Message Datatypes

Note The following chapter identifies the datatypes that are used in the message.

6.1 ActiveCurrencyAndAmount

Definition: A number of monetary units specified in an active currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveCurrencyCode" on page 262

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules

R12 CurrencyAmount ✓

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

"Amount" on page 70

6.2 ActiveCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Rules**R13 ActiveCurrency ✓**

The currency code must be a valid active currency code, not yet withdrawn on the day the message containing the currency is exchanged. Valid active currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and are not yet withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00005
- *Error Text:* Invalid currency code

Used in attribute(s)

"ActiveCurrencyAndAmount" on page 262

Restricts

"ParentCurrencyCode" on page 307

6.3 ActiveOrHistoricCurrencyAndAmount

Definition: A number of monetary units specified in an active or a historic currency where the unit of currency is explicit and compliant with ISO 4217.

Type: Amount

This data type must be used with the following XML Attributes:

Attribute	Tag	Datatype
Currency	Ccy	"ActiveOrHistoricCurrencyCode" on page 264

Format

fractionDigits	5
minInclusive	0
totalDigits	18

Rules**R10 CurrencyAmount ✓**

The number of fractional digits (or minor unit of currency) must comply with ISO 4217.

Note: The decimal separator is a dot.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00007
- *Error Text:* Invalid currency code or too many decimal digits.

Used in element(s)

["Amount" on page 60](#), ["Amount" on page 61](#), ["Amount" on page 91](#), ["Amount" on page 92](#), ["Amount" on page 97](#), ["Amount" on page 245](#), ["Amount" on page 247](#), ["Amount" on page 257](#), ["CorrectedAmount" on page 237](#), ["CreditNoteAmount" on page 223](#), ["CreditNoteAmount" on page 225](#), ["DuePayableAmount" on page 223](#), ["DuePayableAmount" on page 225](#), ["InstructedAmount" on page 33](#), ["InstructedAmount" on page 81](#), ["InterbankSettlementAmount" on page 78](#), ["InterbankSettlementAmount" on page 150](#), ["InterbankSettlementAmount" on page 229](#), ["OriginalInstructedAmount" on page 190](#), ["OriginalInterbankSettlementAmount" on page 196](#), ["OriginalInterbankSettlementAmount" on page 185](#), ["RemittedAmount" on page 112](#), ["RemittedAmount" on page 224](#), ["RemittedAmount" on page 226](#), ["TaxableBaseAmount" on page 244](#), ["TotalAmount" on page 244](#), ["TotalChargesAndTaxAmount" on page 59](#), ["TotalTaxAmount" on page 250](#), ["TotalTaxableBaseAmount" on page 250](#)

6.4 ActiveOrHistoricCurrencyCode

Definition: A code allocated to a currency by a Maintenance Agency under an international identification scheme, as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds".

Type: CodeSet

Format

pattern [A-Z]{3,3}

Rules**R11 ActiveOrHistoricCurrency ✓**

The Currency Code must be registered, or have already been registered. Valid active or historic currency codes are registered with the ISO 4217 Maintenance Agency, consist of three (3) contiguous letters, and may be or not be withdrawn on the day the message containing the Currency is exchanged.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00006
- *Error Text:* Invalid currency code.

Used in element(s)

["Currency" on page 56](#), ["CurrencyOfTransfer" on page 97](#)

Used in attribute(s)

["ActiveOrHistoricCurrencyAndAmount" on page 263](#)

Restricts

["ParentCurrencyCode" on page 307](#)

6.5 AddressType2Code

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Used in element(s)

["Code" on page 27](#)

Restricts

["AddressTypeCode" on page 265](#)

6.6 AddressTypeCode

Definition: Specifies the type of address.

Type: CodeSet

Code	Name	Definition
ADDR	Postal	Address is the complete postal address.
BIZZ	Business	Address is the business address.
DLVY	DeliveryTo	Address is the address to which delivery is to take place.
HOME	Residential	Address is the home address.
MLTO	MailTo	Address is the address to which mail is sent.
PBOX	POBox	Address is a postal office (PO) box.

Is restricted by

["AddressType2Code" on page 264](#)

6.7 AmountDirectionCode

Definition: Specifies if an operation is an increase or a decrease or the result of a reversal operation.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Code	Name	Definition
RVCD	ReversalCredit	Debit entry used to reverse a previously booked credit entry.
RVDB	ReversalDebit	Credit entry used to reverse a previously booked debit entry.

Is restricted by

"CreditDebitCode" on page 277

6.8 AnyBICDec2014Identifier

Definition: Code allocated to a financial or non-financial institution by the ISO 9362 Registration Authority, as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R21 AnyBIC ✓

Only a valid Business identifier code is allowed. Business identifier codes for financial or non-financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consists of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00008
- *Error Text:* Invalid BIC.

Used in element(s)

"AnyBIC" on page 135, "AnyBIC" on page 136

6.9 BICFIDec2014Identifier

Definition: Code allocated to a financial institution by the ISO 9362 Registration Authority as described in ISO 9362: 2014 - "Banking - Banking telecommunication messages - Business identifier code (BIC)".

Type: IdentifierSet

Format

pattern [A-Z0-9]{4,4}[A-Z]{2,2}[A-Z0-9]{2,2}([A-Z0-9]{3,3}){0,1}

Rules

R18 BICFI ✓

Valid BICs for financial institutions are registered and published by the ISO 9362 Registration Authority in the ISO directory of BICs, and consist of eight (8) or eleven (11) contiguous characters.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00001
- *Error Text:* Invalid FI BIC.

Used in element(s)

["BICFI" on page 99](#), ["BICFI" on page 101](#), ["BICFI" on page 105](#)

6.10 CBPR_CancellationStatus

Definition: Specifies the status of the investigation, in a coded form.

This datatype has been created by the Publisher of this Usage Guideline.

Type: CodeSet

Code	Name	Definition
CNCL	Cancelled	A final response confirming the payment is cancelled as requested and the return of funds will be initiated.
PDCR	Pending	Interim status which acknowledges the cancellation request, where further work is required before a final response (CNCL or RJCR) is provided to this cancellation request. This is the case where the investigation will not be finalized within the same day (for example, where debit authority is required from the creditor). When a pending response is provided (/PDCR/) it may optionally be followed by an additional reason code.
RJCR	Rejected	A final response rejecting the request to cancel. In this case, an additional reason is required.

Used in element(s)

["Confirmation" on page 124](#)

6.11 CBPR_CancellationStatusReasonCode

Definition: Reason for the cancellation status, in a coded form.

Type: CodeSet

Code	Name	Definition
AC04	ClosedAccountNumber	Account number specified has been closed on the receiver's books.
AGNT	AgentDecision	Reported when the cancellation cannot be accepted because an agent refuses to cancel.
AM04	InsufficientFunds	Amount of funds available to cover specified message amount is insufficient.
ARDT	AlreadyReturned	Cancellation not accepted as the transaction has already been returned.
CUST	CustomerDecision	Reported when the cancellation cannot be accepted because of a customer's decision (creditor).
INDM	Indemnity	Cancellation Indemnity Required.
LEGL	LegalDecision	Reported when the cancellation cannot be accepted for regulatory reasons.
NARR	Narrative	Reason is provided as narrative information in the additional reason information. Usage Guideline restrictions for this code • This code(camt.029.001.09/CancellationDetails/TransactionInformationAndStatus/CancellationStatusReasonInformation/Reason/Code/Narrative) is removed.
NOAS	NoAnswerFromCustomer	No response from beneficiary (to the cancellation request).
NOOR	NoOriginalTransactionReceived	Original transaction (subject to cancellation) never received.
PTNA	PassedToTheNextAgent	The cancellation has been forwarded to the next agent in the payment chain.
RQDA	RequestingDebitAuthority	Requested Debit Authority when authority is required by the creditor to return the payment.

Used in element(s)

"Code" on page 46

6.12 CBPR_CancellationStatusReasonCode

Definition: Reason for the cancellation status, in a coded form.

This datatype has been created by the Publisher of this Usage Guideline.

Type: CodeSet

Code	Name	Definition
AC04	ClosedAccountNumber	Account number specified has been closed on the receiver's books.
AGNT	AgentDecision	Reported when the cancellation cannot be accepted because an agent refuses to cancel.
AM04	InsufficientFunds	Amount of funds available to cover specified message amount is insufficient.
ARDT	AlreadyReturned	Cancellation not accepted as the transaction has already been returned.
CUST	CustomerDecision	Reported when the cancellation cannot be accepted because of a customer's decision (creditor).
INDM	Indemnity	Cancellation Indemnity Required.
LEGL	LegalDecision	Reported when the cancellation cannot be accepted for regulatory reasons.
NARR	Narrative	Reason is provided as narrative information in the additional reason information.
NOAS	NoAnswerFromCustomer	No response from beneficiary (to the cancellation request).
NOOR	NoOriginalTransactionReceived	Original transaction (subject to cancellation) never received.
PTNA	PassedToTheNextAgent	The cancellation has been forwarded to the next agent in the payment chain.
RQDA	RequestingDebitAuthority	Requested Debit Authority when authority is required by the creditor to return the payment.

6.13 CBPR_Date

Definition: This Type restricts the base ISODate to YYYY (exactly 4 digits for the Year) and does not allow use of UTC offset or Zulu indicator with a date.

This datatype has been created by the Publisher of this Usage Guideline.

Type: Date

Format

pattern [0-9]{4}-[0-9]{2}-[0-9]{2}

Used in element(s)

"BirthDate" on page 87, "BirthDate" on page 89

6.14 CBPR_DateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm-m).

This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Example: 2020-07-16T19:20:30.45+01:00

This datatype has been created by the Publisher of this Usage Guideline.

Type: DateTime

Format

pattern .*(\+|-)((0[0-9])|(1[0-4])):[0-5][0-9]

Used in element(s)

"CreationDate" on page 43, "CreationDateTime" on page 54, "OriginalCreationDateTime" on page 145

6.15 CBPR_RestrictedFINXMax105Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 105 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	105
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,'\+]+

Used in element(s)

["AdditionalInformation" on page 50](#)

6.16 CBPR_RestrictedFINXMax140Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 140 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	140
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*='^_`{ }\~";<>@[\\]]+

Used in element(s)

["Name" on page 172](#), ["Name" on page 106](#), ["Name" on page 175](#)

6.17 CBPR_RestrictedFINXMax16Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

["CancellationStatusIdentification" on page 179](#), ["Identification" on page 52](#), ["OriginalInstructionIdentification" on page 181](#)

6.18 CBPR_RestrictedFINXMax16Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 16 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	16
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*=-^_`{\ \}~";<>@\[\]\]]+

Used in element(s)

"BuildingNumber" on page 211, "PostBox" on page 213, "PostCode" on page 214

6.19 CBPR_RestrictedFINXMax28Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 28 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	28
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

"MemberIdentification" on page 69

6.20 CBPR_RestrictedFINXMax35Text

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + .

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+]+

Used in element(s)

["BusinessMessageIdentifier" on page 42](#), ["BusinessService" on page 43](#), ["CityOfBirth" on page 89](#), ["Identification" on page 53](#), ["Identification" on page 119](#), ["Identification" on page 122](#), ["Issuer" on page 120](#), ["Issuer" on page 123](#), ["MessageDefinitionIdentifier" on page 42](#), ["OriginalClearingSystemReference" on page 182](#), ["OriginalEndToEndIdentification" on page 181](#), ["OriginalMessageIdentification" on page 144](#), ["OriginalMessageNameIdentification" on page 144](#), ["OriginalTransactionIdentification" on page 182](#), ["Proprietary" on page 138](#), ["Proprietary" on page 205](#), ["ProvinceOfBirth" on page 89](#)

6.21 CBPR_RestrictedFINXMax35Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 35 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	35
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

["BuildingName" on page 212](#), ["CityOfBirth" on page 88](#), ["CountrySubDivision" on page 216](#), ["District-Name" on page 215](#), ["ProvinceOfBirth" on page 88](#), ["TownLocationName" on page 215](#), ["TownName" on page 214](#)

6.22 CBPR_RestrictedFINXMax70Text_Extended

Definition: Specifies a character string with a minimum length of 1, and a maximum length of 70 characters, and limited to character set X, that is, 0-9 a-z A-Z / - ? : () . , ' + . that is extended to support the following additional characters !#\$%&*='^_`{|}~";<>@[\\]

This datatype has been created by the Publisher of this Usage Guideline.

Type: Text

Format

maxLength	70
minLength	1
pattern	[0-9a-zA-Z/\-!\?:\(\)\.,\'+ !#\$%&!*='^_`{ }\}~";<>@[\\]]+

Used in element(s)

["AddressLine" on page 217](#), ["Department" on page 210](#), ["Floor" on page 212](#), ["Room" on page 213](#), ["StreetName" on page 211](#), ["SubDepartment" on page 210](#)

6.23 CancellationIndividualStatus1Code

Definition: Specifies the status of a cancellation request.

Type: CodeSet

Code	Name	Definition
ACCR	AcceptedCancellationRequest	Cancellation is accepted.
PDCR	PendingCancellationRequest	Cancellation request is pending.
RJCR	RejectedCancellationRequest	Cancellation request is rejected

Used in element(s)

"DetailedStatus" on page 133, "TransactionCancellationStatus" on page 190, "TransactionCancellationStatus" on page 183

Restricts

"PaymentStatusCode" on page 308

6.24 ChargeBearerType1Code

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Used in element(s)

"Bearer" on page 62

Restricts

"ChargeBearerTypeCode" on page 274

6.25 ChargeBearerTypeCode

Definition: Specifies which party(ies) will pay charges due for processing of the instruction.

Type: CodeSet

Code	Name	Definition
CRED	BorneByCreditor	All transaction charges are to be borne by the creditor.
DEBT	BorneByDebtor	All transaction charges are to be borne by the debtor.
SHAR	Shared	In a credit transfer context, means that transaction charges on the sender side are to be borne by the debtor, transaction charges on the receiver side are to be borne by the creditor. In a direct debit context, means that transaction charges on the sender side are to be borne by the creditor, transaction charges on the receiver side are to be borne by the debtor.
SLEV	FollowingServiceLevel	Charges are to be applied following the rules agreed in the service level and/or scheme.

Is restricted by

"ChargeBearerType1Code" on page 274

6.26 ChargeIncludedIndicator

Definition: Indicates whether charges have already been included.

Type: Indicator

Meaning When True: Included

Meaning When False: Pre-advised

Used in element(s)

"ChargeIncludedIndicator" on page 61

6.27 ClearingChannel2Code

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Used in element(s)

["ClearingChannel" on page 198](#), ["ClearingChannel" on page 229](#)

Restricts

["ClearingChannelCode" on page 276](#)

6.28 ClearingChannelCode

Definition: Specifies the clearing channel for the routing of the transaction, as part of the payment type identification.

Type: CodeSet

Code	Name	Definition
BOOK	BookTransfer	Payment through internal book transfer.
MPNS	MassPaymentNetSystem	Clearing channel is a mass payment net settlement system.
RTGS	RealTimeGrossSettlementSystem	Clearing channel is a real-time gross settlement system.
RTNS	RealTimeNetSettlementSystem	Clearing channel is a real-time net settlement system.

Is restricted by

["ClearingChannel2Code" on page 275](#)

6.29 CopyDuplicate1Code

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Used in element(s)

["CopyDuplicate" on page 44](#)

Restricts

["CopyDuplicateCode" on page 277](#)

6.30 CopyDuplicateCode

Definition: Specifies if this document is a copy, a duplicate, or a duplicate of a copy.

Type: CodeSet

Code	Name	Definition
CODU	CopyDuplicate	Message is being sent as a copy to a party other than the account owner, for information purposes and the message is a duplicate of a message previously sent.
COPY	Copy	Message is being sent as a copy to a party other than the account owner, for information purposes.
DUPL	Duplicate	Message is for information/confirmation purposes. It is a duplicate of a message previously sent.

Is restricted by

"CopyDuplicate1Code" on page 276

6.31 CountryCode

Definition: Code to identify a country, a dependency, or another area of particular geopolitical interest, on the basis of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Type: CodeSet

Format

pattern [A-Z]{2,2}

Rules

R17 Country ✓

The code is checked against the list of country names obtained from the United Nations (ISO 3166, Alpha-2 code).

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00004
- *Error Text:* Invalid Country Code.

Used in element(s)

"Country" on page 208, "Country" on page 216, "CountryOfBirth" on page 87, "CountryOfBirth" on page 88, "CountryOfBirth" on page 90, "CountryOfResidence" on page 171, "CountryOfResidence" on page 174, "CountryOfResidence" on page 177

6.32 CreditDebitCode

Definition: Specifies if an operation is an increase or a decrease.

Type: CodeSet

Code	Name	Definition
CRDT	Credit	Operation is an increase.
DBIT	Debit	Operation is a decrease.

Used in element(s)

"CreditDebitIndicator" on page 61, "CreditDebitIndicator" on page 93

Restricts

"AmountDirectionCode" on page 265

6.33 DecimalNumber

Definition: Number of objects represented as a decimal number, for example 0.75 or 45.6.

Type: Quantity

Format

fractionDigits	17
totalDigits	18

Used in element(s)

"CountPerPeriod" on page 110, "DetailedControlSum" on page 133, "DetailedControlSum" on page 134, "OriginalControlSum" on page 141, "OriginalControlSum" on page 148

6.34 DocumentType3Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
DISP	DispatchAdvice	Document is a dispatch advice.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
PUOR	PurchaseOrder	Document is a purchase order.
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.

Used in element(s)

["Code" on page 84](#)

Restricts

["DocumentTypeCode" on page 280](#)

6.35 DocumentType6Code

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Used in element(s)"Code" on page 221**Restricts**"DocumentTypeCode" on page 280

6.36 DocumentTypeCode

Definition: Specifies a type of financial or commercial document.

Type: CodeSet

Code	Name	Definition
AROI	AccountReceivableOpenItem	Document is a payment that applies to a specific source document.
BOLD	BillOfLading	Document is a shipping notice.
CINV	CommercialInvoice	Document is an invoice.
CMCN	CommercialContract	Document is an agreement between the parties, stipulating the terms and conditions of the delivery of goods or services.
CNFA	CreditNoteRelatedToFinancialAdjustment	Document is a credit note for the final amount settled for a commercial transaction.
CRCP	CustomerReceipt	When the Sale System requires the POI system to print the Customer receipt.
CREN	CreditNote	Document is a credit note.
DEBN	DebitNote	Document is a debit note.
DISP	DispatchAdvice	Document is a dispatch advice.
DNFA	DebitNoteRelatedToFinancialAdjustment	Document is a debit note for the final amount settled for a commercial transaction.
FXDR	ForeignExchangeDealReference	Document is a pre-agreed or pre-arranged foreign exchange transaction to which the payment transaction refers.
HIRI	HireInvoice	Document is an invoice for the hiring of human resources or renting goods or equipment.
HRCP	CashierReceipt	When the Sale system print the Cashier copy of the Payment receipt.
JNRL	Journal	When the POI or the Sale System wants to store a message on the journal printer or electronic journal of the Sale Terminal (it is sometimes a Sale Logging/Journal Printer).
MSIN	MeteredServiceInvoice	Document is an invoice claiming payment for the supply of metered services, for example gas or electricity supplied to a fixed meter.
PUOR	PurchaseOrder	Document is a purchase order.

Code	Name	Definition
RADM	RemittanceAdviceMessage	Document is a remittance advice sent separately from the current transaction.
RPIN	RelatedPaymentInstruction	Document is a linked payment instruction to which the current payment instruction is related, for example, in a cover scenario.
SBIN	SelfBilledInvoice	Document is an invoice issued by the debtor.
SCOR	StructuredCommunicationReference	Document is a structured communication reference provided by the creditor to identify the referred transaction.
SOAC	StatementOfAccount	Document is a statement of the transactions posted to the debtor's account at the supplier.
SRCP	SaleReceipt	When the Sale System requires the POI system to print the Sale receipt.
TSUT	TradeServicesUtilityTransaction	Document is a transaction identifier as assigned by the Trade Services Utility.
VCHR	Voucher	Document is an electronic payment document.

Is restricted by

["DocumentType3Code" on page 278](#), ["DocumentType6Code" on page 279](#)

6.37 Exact2NumericText

Definition: Specifies a numeric string with an exact length of 2 digits.

Type: Text

Format

pattern [0-9]{2}

Used in element(s)

["OriginalTrackingDays" on page 33](#), ["PointInTime" on page 109](#), ["TrackingDays" on page 130](#)

6.38 Exact4AlphaNumericText

Definition: Specifies an alphanumeric string with a length of 4 characters.

Type: Text

Format

pattern [a-zA-Z0-9]{4}

Used in element(s)

["Identification" on page 117](#)

6.39 ExternalAccountIdentification1Code

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 27](#)

Restricts

["ExternalAccountIdentificationCode" on page 282](#)

6.40 ExternalAccountIdentificationCode

Definition: Specifies the external account identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalAccountIdentification1Code" on page 282](#)

6.41 ExternalCashAccountType1Code

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 57

Restricts

"ExternalCashAccountTypeCode" on page 283

6.42 ExternalCashAccountTypeCode

Definition: Specifies the nature, or use, of the cash account in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashAccountType1Code" on page 282

6.43 ExternalCashClearingSystem1Code

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	3
minLength	1

Used in element(s)

"Code" on page 67

Restricts

"ExternalCashClearingSystemCode" on page 284

6.44 ExternalCashClearingSystemCode

Definition: Specifies the cash clearing system, as published in an external cash clearing system code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCashClearingSystem1Code" on page 283

6.45 ExternalCategoryPurpose1Code

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 57

Restricts

"ExternalCategoryPurposeCode" on page 284

6.46 ExternalCategoryPurposeCode

Definition: Specifies the category purpose, as published in an external category purpose code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalCategoryPurpose1Code" on page 284

6.47 ExternalChargeType1Code

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 58

Restricts

"ExternalChargeTypeCode" on page 285

6.48 ExternalChargeTypeCode

Definition: Specifies the nature, or use, of the charges in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code set published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalChargeType1Code" on page 285

6.49 ExternalClaimNonReceiptRejection1Code

Definition: Specifies the reason for the rejection of a claim non receipt, as published in an external claim non receipt rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 65](#)

Restricts

["ExternalClaimNonReceiptRejectionCode" on page 286](#)

6.50 ExternalClaimNonReceiptRejectionCode

Definition: Specifies the reason for the rejection of a claim non receipt, as published in an external claim non receipt rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalClaimNonReceiptRejection1Code" on page 285](#)

6.51 ExternalClearingSystemIdentification1Code

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Used in element(s)

["Code" on page 66](#)

Restricts

["ExternalClearingSystemIdentificationCode" on page 286](#)

6.52 ExternalClearingSystemIdentificationCode

Definition: Specifies the clearing system identification code, as published in an external clearing system identification code list.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	5
minLength	1

Is restricted by

"ExternalClearingSystemIdentification1Code" on page 286

6.53 ExternalDiscountAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 92

Restricts

"ExternalDiscountAmountTypeCode" on page 287

6.54 ExternalDiscountAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDiscountAmountType1Code" on page 287

6.55 ExternalDocumentLineType1Code

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 97

Restricts

"ExternalDocumentLineTypeCode" on page 288

6.56 ExternalDocumentLineTypeCode

Definition: Specifies the document line type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalDocumentLineType1Code" on page 288

6.57 ExternalFinancialInstitutionIdentification1Code

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 98](#)

Restricts

["ExternalFinancialInstitutionIdentificationCode" on page 289](#)

6.58 ExternalFinancialInstitutionIdentificationCode

Definition: Specifies the external financial institution identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalFinancialInstitutionIdentification1Code" on page 288](#)

6.59 ExternalGarnishmentType1Code

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 114](#)

Restricts

["ExternalGarnishmentTypeCode" on page 289](#)

6.60 ExternalGarnishmentTypeCode

Definition: Specifies the garnishment type as published in an external document type code list.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalGarnishmentType1Code" on page 289

6.61 ExternalLocalInstrument1Code

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Used in element(s)

"Code" on page 126

Restricts

"ExternalLocalInstrumentCode" on page 290

6.62 ExternalLocalInstrumentCode

Definition: Specifies the external local instrument code in the format of character string with a maximum length of 35 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	35
minLength	1

Is restricted by

"ExternalLocalInstrument1Code" on page 290

6.63 ExternalMandateSetupReason1Code

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 130

Restricts

"ExternalMandateSetupReasonCode" on page 291

6.64 ExternalMandateSetupReasonCode

Definition: Specifies the external mandate setup reason code in the format of character string with a maximum length of 4 characters.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalMandateSetupReason1Code" on page 291

6.65 ExternalOrganisationIdentification1Code

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
-----------	---

minLength	1
-----------	---

Used in element(s)

["Code" on page 137](#), ["Code" on page 138](#)

Restricts

["ExternalOrganisationIdentificationCode" on page 292](#)

6.66 ExternalOrganisationIdentificationCode

Definition: Specifies the external organisation identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalOrganisationIdentification1Code" on page 291](#)

6.67 ExternalPaymentCancellationRejection1Code

Definition: Specifies the reason for the rejection of a cancellation, as published in an external payment cancellation rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 45](#)

Restricts

["ExternalPaymentCancellationRejectionCode" on page 292](#)

6.68 ExternalPaymentCancellationRejectionCode

Definition: Specifies the reason for the rejection of a cancellation, as published in an external payment cancellation rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPaymentCancellationRejection1Code" on page 292

6.69 ExternalPaymentCompensationReason1Code

Definition: Specifies the reason for compensation for the processing of a payment, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 72

Restricts

"ExternalPaymentCompensationReasonCode" on page 293

6.70 ExternalPaymentCompensationReasonCode

Definition: Specifies the reason for compensation for the processing of a payment, as published in an external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPaymentCompensationReason1Code" on page 293

6.71 ExternalPaymentModificationRejection1Code

Definition: Specifies the reason for the rejection of a modification, as published in an external payment modification rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 131

Restricts

"ExternalPaymentModificationRejectionCode" on page 294

6.72 ExternalPaymentModificationRejectionCode

Definition: Specifies the reason for the rejection of a modification, as published in an external payment modification rejection code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPaymentModificationRejection1Code" on page 294

6.73 ExternalPersonIdentification1Code

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
-----------	---

minLength	1
-----------	---

Used in element(s)

["Code" on page 204](#), ["Code" on page 204](#)

Restricts

["ExternalPersonIdentificationCode" on page 295](#)

6.74 ExternalPersonIdentificationCode

Definition: Specifies the external person identification scheme name code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalPersonIdentification1Code" on page 294](#)

6.75 ExternalProxyAccountType1Code

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 218](#)

Restricts

["ExternalProxyAccountTypeCode" on page 295](#)

6.76 ExternalProxyAccountTypeCode

Definition: Specifies the external proxy account type code, as published in the proxy account type external code set.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalProxyAccountType1Code" on page 295

6.77 ExternalPurpose1Code

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 219

Restricts

"ExternalPurposeCode" on page 296

6.78 ExternalPurposeCode

Definition: Specifies the external purpose code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalPurpose1Code" on page 296

6.79 ExternalServiceLevel1Code

Definition: Specifies the external service level code in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

"Code" on page 230

Restricts

"ExternalServiceLevelCode" on page 297

6.80 ExternalServiceLevelCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

"ExternalServiceLevel1Code" on page 297

6.81 ExternalTaxAmountType1Code

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Used in element(s)

["Code" on page 246](#)

Restricts

["ExternalTaxAmountTypeCode" on page 298](#)

6.82 ExternalTaxAmountTypeCode

Definition: Specifies the nature, or use, of the amount in the format of character string with a maximum length of 4 characters.

The list of valid codes is an external code list published separately.

External code sets can be downloaded from www.iso20022.org.

Type: CodeSet

Format

maxLength	4
minLength	1

Is restricted by

["ExternalTaxAmountType1Code" on page 297](#)

6.83 Frequency6Code

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
DAIL	Daily	Event takes place every day.
FRTN	Fortnightly	Event takes place every two weeks.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.

Code	Name	Definition
QURT	Quarterly	Event takes place every three months or four times a year.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Used in element(s)

["Type" on page 108](#), ["Type" on page 109](#), ["Type" on page 110](#)

Restricts

["FrequencyCode" on page 299](#)

6.84 FrequencyCode

Definition: Specifies the regularity of an event.

Type: CodeSet

Code	Name	Definition
ADHO	Adhoc	Event takes place on request or as necessary.
BIMN	Bimonthly	Event takes place every two months or six times a year.
CRED	OnCreditEvent	Event occurs due to a credit event occurring for an issuer.
DAIL	Daily	Event takes place every day.
EXPI	OnExpiry	Event occurs on expiry of a financial contract.
FRTN	Fortnightly	Event takes place every two weeks.
HOUL	Hourly	Event takes place every hours.
INDA	IntraDay	Event takes place several times a day.
MIAN	SemiAnnual	Event takes place every six months or two times a year.
MNTH	Monthly	Event takes place every month or once a month.
MOVE	TriggeredByMovement	Event takes place at the end of the day if there was a movement on the account, otherwise nothing is sent that day.
NEVR	Never	Event does never take place.
ODMD	OnDemand	Event takes place on demand.
OVNG	Overnight	Event takes place overnight.
QURT	Quarterly	Event takes place every three months or four times a year.

Code	Name	Definition
RATE	Rate	Event takes place based on a change of a rate.
SHFT	Shift	Event associated with a shift.
TEND	TenDays	Event takes place every ten business days.
TRIL	TriAnnual	Event takes place every four months or three times a year.
TWWK	TwiceAWeek	Two times a week
UPFR	Upfront	Event that takes place at the initiation of a trade or agreement.
WEEK	Weekly	Event takes place once a week.
YEAR	Annual	Event takes place every year or once a year.

Is restricted by

"Frequency6Code" on page 298

6.85 GroupCancellationStatus1Code

Definition: Specifies the status of a group of cancellation requests.

Type: CodeSet

Code	Name	Definition
ACCR	AcceptedCancellationRequest	Cancellation is accepted.
PACR	PartiallyAcceptedCancellationRequest	Cancellation is partially accepted.
PDCR	PendingCancellationRequest	Cancellation request is pending.
RJCR	RejectedCancellationRequest	Cancellation request is rejected

Used in element(s)

"GroupCancellationStatus" on page 141, "PaymentInformationCancellationStatus" on page 148

Restricts

"PaymentStatusCode" on page 308

6.86 IBAN2007Identifier

Definition: The International Bank Account Number is a code used internationally by financial institutions to uniquely identify the account of a customer at a financial institution as described in the 2007 edition of the ISO 13616 standard "Banking and related financial services - International Bank Account Number (IBAN)" and replaced by the more recent edition of the standard.

Type: IdentifierSet

Format

pattern [A-Z]{2,2}[0-9]{2,2}[a-zA-Z0-9]{1,30}

Rules**R9 IBAN ✓**

A valid IBAN consists of all three of the following components: Country Code, check digits and BBAN.

Error handling:

- *Error severity:* Fatal
- *Error Code:* D00003
- *Error Text:* Invalid IBAN format or invalid check digits.

Used in element(s)

"IBAN" on page 26

6.87 ISODate

Definition: A particular point in the progression of time in a calendar year expressed in the YYYY-MM-DD format. This representation is defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Type: Date

Used in element(s)

"BirthDate" on page 86, "Date" on page 86, "Date" on page 112, "Date" on page 250, "DateOfSignature" on page 128, "DateProcessed" on page 63, "FinalCollectionDate" on page 129, "FirstCollectionDate" on page 129, "FromDate" on page 90, "InterbankSettlementDate" on page 78, "InterbankSettlementDate" on page 151, "InterbankSettlementDate" on page 229, "OriginalFinalCollectionDate" on page 32, "OriginalInterbankSettlementDate" on page 196, "OriginalInterbankSettlementDate" on page 185, "OriginalRequestedCollectionDate" on page 191, "RelatedDate" on page 94, "RelatedDate" on page 220, "RequestedCollectionDate" on page 81, "RequestedCollectionDate" on page 151, "ToDate" on page 90, "Year" on page 253

6.88 ISODateTime

Definition: A particular point in the progression of time defined by a mandatory date and a mandatory time component, expressed in either UTC time format (YYYY-MM-DDThh:mm:ss.sssZ), local time with UTC offset format (YYYY-MM-DDThh:mm:ss.sss+/-hh:mm), or local time format (YYYY-MM-DDThh:mm:ss.sss). These representations are defined in "XML Schema Part 2: Datatypes Second Edition - W3C Recommendation 28 October 2004" which is aligned with ISO 8601.

Note on the time format:

1) beginning / end of calendar day

00:00:00 = the beginning of a calendar day

24:00:00 = the end of a calendar day

2) fractions of second in time format

Decimal fractions of seconds may be included. In this case, the involved parties shall agree on the maximum number of digits that are allowed.

Type: DateTime

Used in element(s)

"CreationDateTime" on page 76, "DateTime" on page 86, "OriginalCreationDateTime" on page 141, "OriginalCreationDateTime" on page 143

6.89 LEIIdentifier

Definition: Legal Entity Identifier is a code allocated to a party as described in ISO 17442 "Financial Services - Legal Entity Identifier (LEI)".

Type: IdentifierSet

Format

pattern	[A-Z0-9]{18,18}[0-9]{2,2}
---------	---------------------------

Used in element(s)

"LEI" on page 39, "LEI" on page 99, "LEI" on page 135, "LEI" on page 102, "LEI" on page 136, "LEI" on page 106

6.90 Max1025Text

Definition: Specifies a character string with a maximum length of 1025 characters.

Type: Text

Format

maxLength	1025
minLength	1

Used in element(s)

"ElectronicSignature" on page 129

6.91 Max105Text

Definition: Specifies a character string with a maximum length of 105 characters.

Type: Text

Format

maxLength	105
minLength	1

Used in element(s)

["AdditionalInformation" on page 48](#), ["AdditionalInformation" on page 132](#)

6.92 Max128Text

Definition: Specifies a character string with a maximum length of 128 characters.

Type: Text

Format

maxLength	128
minLength	1

Used in element(s)

["Identification" on page 159](#)

6.93 Max140Text

Definition: Specifies a character string with a maximum length of 140 characters.

Type: Text

Format

maxLength	140
minLength	1

Used in element(s)

["AdditionalInformation" on page 93](#), ["AdditionalInformation" on page 256](#), ["AdditionalRemittanceInformation" on page 242](#), ["Name" on page 39](#), ["Name" on page 73](#), ["Name" on page 99](#), ["Name" on page 169](#), ["Name" on page 246](#), ["Name" on page 102](#), ["ReferenceNumber" on page 112](#), ["ReferenceNumber" on page 249](#), ["Unstructured" on page 227](#)

6.94 Max15NumericText

Definition: Specifies a numeric string with a maximum length of 15 digits.

Type: Text

Format

pattern	[0-9]{1,15}
---------	-------------

Used in element(s)

["DetailedNumberOfTransactions" on page 133](#), ["DetailedNumberOfTransactions" on page 134](#), ["OriginalNumberOfTransactions" on page 141](#), ["OriginalNumberOfTransactions" on page 147](#)

6.95 Max16Text

Definition: Specifies a character string with a maximum length of 16 characters.

Type: Text

Format

maxLength	16
minLength	1

Used in element(s)

"BuildingNumber" on page 207, "PostBox" on page 207, "PostCode" on page 207

6.96 Max2048Text

Definition: Specifies a character string with a maximum length of 2048 characters.

Type: Text

Format

maxLength	2048
minLength	1

Used in element(s)

"Description" on page 95, "EmailAddress" on page 74, "Identification" on page 124, "Identification" on page 218

6.97 Max34Text

Definition: Specifies a character string with a maximum length of 34 characters.

Type: Text

Format

maxLength	34
minLength	1

Used in element(s)

"Identification" on page 115

6.98 Max350Text

Definition: Specifies a character string with a maximum length of 350 characters.

Type: Text

Format

maxLength	350
minLength	1

Used in element(s)

["PlaceAndName" on page 243](#), ["Registry" on page 123](#)

6.99 Max35Text

Definition: Specifies a character string with a maximum length of 35 characters.

Type: Text

Format

maxLength	35
minLength	1

Used in element(s)

["AccountServicerReference" on page 237](#), ["AdministrationZone" on page 249](#), ["BuildingName" on page 207](#), ["CancellationStatusIdentification" on page 188](#), ["Category" on page 254](#), ["CategoryDetails" on page 255](#), ["CertificateIdentification" on page 255](#), ["CityOfBirth" on page 87](#), ["CountrySubDivision" on page 208](#), ["DebtorStatus" on page 255](#), ["DistrictName" on page 208](#), ["EmailPurpose" on page 74](#), ["EndToEndIdentification" on page 77](#), ["EndToEndIdentification" on page 80](#), ["EndToEndIdentification" on page 228](#), ["FormsCode" on page 255](#), ["Identification" on page 39](#), ["Identification" on page 51](#), ["Identification" on page 116](#), ["Identification" on page 117](#), ["Identification" on page 118](#), ["Identification" on page 121](#), ["Identification" on page 247](#), ["InstructionIdentification" on page 77](#), ["InstructionIdentification" on page 80](#), ["Issuer" on page 85](#), ["Issuer" on page 96](#), ["Issuer" on page 113](#), ["Issuer" on page 115](#), ["Issuer" on page 116](#), ["Issuer" on page 117](#), ["Issuer" on page 117](#), ["Issuer" on page 119](#), ["Issuer" on page 121](#), ["Issuer" on page 222](#), ["JobTitle" on page 74](#), ["MandatIdentification" on page 127](#), ["MemberIdentification" on page 68](#), ["MessageIdentification" on page 75](#), ["MessageNameIdentification" on page 76](#), ["Method" on page 249](#), ["ModificationStatusIdentification" on page 193](#), ["Number" on page 94](#), ["Number" on page 220](#), ["OriginalClearingSystemReference" on page 194](#), ["OriginalEndToEndIdentification" on page 189](#), ["OriginalEndToEndIdentification" on page 194](#), ["OriginalGroupCancellationIdentification" on page 139](#), ["OriginalInstructionIdentification" on page 189](#), ["OriginalInstructionIdentification" on page 194](#), ["OriginalMandatIdentification" on page 29](#), ["OriginalMessageIdentification" on page 140](#), ["OriginalMessageIdentification" on page 143](#), ["OriginalMessageNameIdentification" on page 140](#), ["OriginalMessageNameIdentification" on page 143](#), ["OriginalPaymentInformationCancellationIdentification" on page 146](#), ["OriginalPaymentInformationIdentification" on page 147](#), ["OriginalPaymentInformationIdentification" on page 194](#), ["OriginalStatementIdentification" on page 237](#), ["OriginalTransactionIdentification" on page 194](#), ["PaymentInformationIdentification" on page 80](#), ["Proprietary" on page 27](#), ["Proprietary" on page 45](#), ["Proprietary" on page 57](#), ["Proprietary" on page 58](#), ["Proprietary" on page 65](#), ["Proprietary" on page 66](#), ["Proprietary" on page 67](#), ["Proprietary" on page 72](#), ["Proprietary" on page 84](#), ["Proprietary" on page 92](#), ["Proprietary" on page 97](#), ["Proprietary" on page 98](#), ["Proprietary" on page 114](#), ["Proprietary" on page 126](#), ["Proprietary" on page 131](#), ["Proprietary" on page 137](#), ["Proprietary" on page 204](#), ["Proprietary" on page 219](#), ["Proprietary" on page 219](#), ["Proprietary" on page 221](#), ["Proprietary" on page 230](#), ["Proprietary" on page 246](#), ["Proprietary" on page 46](#), ["ProvinceOfBirth" on page 86](#), ["Reference" on page 83](#), ["RegistrationIdentification" on page 251](#), ["RegistrationIdentification" on page 252](#), ["Responsibility" on page 74](#), ["SchemeName" on page 118](#), ["TaxIdentification" on page 251](#), ["TaxIdentification" on page 252](#), ["TaxType" on page 251](#), ["TaxType" on page 252](#), ["Title" on page 246](#), ["TownLocationName" on page 208](#), ["TownName" on page 208](#), ["TransactionIdentification" on page 78](#), ["TransactionIdentification" on page 228](#), ["Type" on page 254](#)

6.100 Max4Text

Definition: Specifies a character string with a maximum length of 4 characters.

Type: Text

Format

maxLength	4
minLength	1

Used in element(s)

"ChannelType" on page 159, "Reason" on page 93

6.101 Max70Text

Definition: Specifies a character string with a maximum length of 70characters.

Type: Text

Format

maxLength	70
minLength	1

Used in element(s)

"AddressLine" on page 208, "Department" on page 74, "Department" on page 206, "Floor" on page 207, "Name" on page 56, "Proprietary" on page 130, "Room" on page 207, "StreetName" on page 207, "Sub-Department" on page 206

6.102 NamePrefix2Code

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Used in element(s)

"NamePrefix" on page 73

Restricts

"NamePrefixCode" on page 306

6.103 NamePrefixCode

Definition: Specifies the terms used to formally address a person.

Type: CodeSet

Code	Name	Definition
DOCT	Doctor	Title of the person is Doctor or Dr.
MADM	Madam	Title of the person is Madam.
MIKS	GenderNeutral	Title of the person is gender neutral (Mx).
MISS	Miss	Title of the person is Miss.
MIST	Mister	Title of the person is Mister or Mr.

Is restricted by

"NamePrefix2Code" on page 306

6.104 Number

Definition: Number of objects represented as an integer.

Type: Quantity

Format

fractionDigits	0
totalDigits	18

Used in element(s)

"SequenceNumber" on page 250

6.105 ParentCurrencyCode

Definition: Code allocated to a currency, by a maintenance agency, under an international identification scheme as described in the latest edition of the international standard ISO 4217 "Codes for the representation of currencies and funds". Valid currency codes are registered with the ISO 4217 Maintenance Agency, and consist of three contiguous letters.

Type: CodeSet

Format

pattern	[A-Z]{3,3}
---------	------------

Is restricted by

"ActiveCurrencyCode" on page 262, "ActiveOrHistoricCurrencyCode" on page 264

6.106 PaymentMethod4Code

Definition: Specifies the transfer method that will be used to transfer an amount of money.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Used in element(s)

"PaymentMethod" on page 153

Restricts

"PaymentMethodCode" on page 308

6.107 PaymentMethodCode

Definition: Specifies the transfer method that will be used to transfer the cash.

Type: CodeSet

Code	Name	Definition
CHK	Cheque	Written order to a bank to pay a certain amount of money from one person to another person.
CLAS	Classical	Classical method.
DD	DirectDebit	Collection of an amount of money from the debtor's bank account by the creditor. The amount of money and dates of collections may vary.
DIRE	Direct	Direct method.
TRA	TransferAdvice	Transfer of an amount of money in the books of the account servicer. An advice should be sent back to the account owner.
TRF	CreditTransfer	Transfer of an amount of money in the books of the account servicer.

Is restricted by

"PaymentMethod4Code" on page 307

6.108 PaymentStatusCode

Definition: Indicates the status of a single payment transaction or of a group of payment transactions.

Type: CodeSet

Code	Name	Definition
ACCC	AcceptedCreditSettlementCompleted	Settlement on the creditor's account has been completed.
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACCR	AcceptedCancellationRequest	Cancellation is accepted.
ACPT	Accepted	Request is accepted.
ACSC	AcceptedSettlementCompleted	Settlement on the debtor's account has been completed. Usage : this can be used by the first agent to report to the debtor that the transaction has been completed. Warning : this status is provided for transaction status reasons, not for financial information. It can only be used after bilateral agreement
ACSP	AcceptedSettlementInProgress	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACTC	AcceptedTechnicalValidation	Authentication and syntactical and semantical validation are successful.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.
CNCL	PaymentCancelled	Payment is cancelled.
NULL	NoCancellationProcess	There is no cancellation process ongoing
PACR	PartiallyAcceptedCancellationRequest	Cancellation is partially accepted.
PART	PartiallyAccepted	A number of transactions have been accepted, whereas another number of transactions have not yet achieved 'accepted' status.
PDCR	PendingCancellationRequest	Cancellation request is pending.
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RCVD	Received	Payment initiation has been received by the receiving agent.
RJCR	RejectedCancellationRequest	Cancellation request is rejected
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

Is restricted by

["CancellationIndividualStatus1Code" on page 274](#), ["GroupCancellationStatus1Code" on page 300](#),
["TransactionIndividualStatus1Code" on page 316](#)

6.109 PercentageRate

Definition: Rate expressed as a percentage, that is, in hundredths, for example, 0.7 is 7/10 of a percent, and 7.0 is 7%.

Type: Rate

Format

fractionDigits	10
totalDigits	11

Used in element(s)

["Rate" on page 62](#), ["Rate" on page 244](#), ["Rate" on page 247](#)

6.110 PhoneNumber

Definition: The collection of information which identifies a specific phone or FAX number as defined by telecom services.

It consists of a "+" followed by the country code (from 1 to 3 characters) then a "-" and finally, any combination of numbers, "(", ")", "+", and "-" (up to 30 characters).

Type: Text

Format

pattern	\+[0-9]{1,3}-[0-9()+-]{1,30}
---------	------------------------------

Used in element(s)

["FaxNumber" on page 74](#), ["MobileNumber" on page 73](#), ["PhoneNumber" on page 73](#)

6.111 PreferredContactMethod1Code

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.

Code	Name	Definition
PHON	Phone	Preferred method used to reach the contact is per phone.

Used in element(s)

["PreferredMethod" on page 75](#)

Restricts

["PreferredContactMethodCode" on page 311](#)

6.112 PreferredContactMethodCode

Definition: Preferred method used to reach the individual contact within an organisation.

Type: CodeSet

Code	Name	Definition
CELL	MobileOrCellPhone	Preferred method used to reach the contact is per mobile or cell phone.
FAXX	Fax	Preferred method used to reach the contact is per fax.
LETT	Letter	Preferred method used to reach the contact is per letter.
MAIL	Email	Preferred method used to reach the contact is per email.
ONLI	Online	Preferred method used to reach the contact is online.
PHON	Phone	Preferred method used to reach the contact is per phone.

Is restricted by

["PreferredContactMethod1Code" on page 310](#)

6.113 Priority2Code

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
NORM	Normal	Priority level is normal.

Used in element(s)

["InstructionPriority" on page 198](#), ["Priority" on page 44](#)

Restricts

["PriorityCode" on page 312](#)

6.114 PriorityCode

Definition: Specifies the priority level of an event.

Type: CodeSet

Code	Name	Definition
HIGH	High	Priority level is high.
LOWW	Low	Priority level is low.
NORM	Normal	Priority level is normal.
URGT	Urgent	Priority level is urgent (highest priority possible).

Is restricted by

["Priority2Code" on page 311](#)

6.115 SequenceType3Code

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Used in element(s)

["SequenceType" on page 199](#)

Restricts

["SequenceTypeCode" on page 312](#)

6.116 SequenceTypeCode

Definition: Specifies the type of the current transaction that belongs to a sequence of transactions.

Type: CodeSet

Code	Name	Definition
FNAL	Final	Final collection of a series of direct debit instructions.
FRST	First	First collection of a series of direct debit instructions.
OOFF	OneOff	Direct debit instruction where the debtor's authorisation is used to initiate one single direct debit transaction.
RCUR	Recurring	Direct debit instruction where the debtor's authorisation is used for regular direct debit transactions initiated by the creditor.
RPRE	Represented	Collection used to re-present previously reversed or returned direct debit transactions.

Is restricted by

"SequenceType3Code" on page 312

6.117 SettlementMethod1Code

Definition: Specifies the method used to settle the credit transfer instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Used in element(s)

"SettlementMethod" on page 233

Restricts

"SettlementMethodCode" on page 313

6.118 SettlementMethodCode

Definition: Specifies the method used to settle the payment instruction.

Type: CodeSet

Code	Name	Definition
CLRG	ClearingSystem	Settlement is done through a payment clearing system.
COVE	CoverMethod	Settlement is done through a cover payment.
INDA	InstructedAgent	Settlement is done by the agent instructed to execute a payment instruction.
INGA	InstructingAgent	Settlement is done by the agent instructing and forwarding the payment to the next party in the payment chain.

Is restricted by

"SettlementMethod1Code" on page 313

6.119 TaxRecordPeriod1Code

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.

Code	Name	Definition
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Used in element(s)

"Type" on page 253

Restricts

"TaxRecordPeriodCode" on page 315

6.120 TaxRecordPeriodCode

Definition: Specifies the period related to the tax payment.

Type: CodeSet

Code	Name	Definition
HLF1	FirstHalf	Tax is related to the first half of the period.
HLF2	SecondHalf	Tax is related to the second half of the period.
MM01	FirstMonth	Tax is related to the second month of the period.
MM02	SecondMonth	Tax is related to the first month of the period.
MM03	ThirdMonth	Tax is related to the third month of the period.
MM04	FourthMonth	Tax is related to the fourth month of the period.
MM05	FifthMonth	Tax is related to the fifth month of the period.
MM06	SixthMonth	Tax is related to the sixth month of the period.
MM07	SeventhMonth	Tax is related to the seventh month of the period.
MM08	EighthMonth	Tax is related to the eighth month of the period.
MM09	NinthMonth	Tax is related to the ninth month of the period.

Code	Name	Definition
MM10	TenthMonth	Tax is related to the tenth month of the period.
MM11	EleventhMonth	Tax is related to the eleventh month of the period.
MM12	TwelfthMonth	Tax is related to the twelfth month of the period.
QTR1	FirstQuarter	Tax is related to the first quarter of the period.
QTR2	SecondQuarter	Tax is related to the second quarter of the period.
QTR3	ThirdQuarter	Tax is related to the third quarter of the period.
QTR4	FourthQuarter	Tax is related to the forth quarter of the period.

Is restricted by

"TaxRecordPeriod1Code" on page 314

6.121 TransactionIndividualStatus1Code

Definition: Specifies the status of a single payment transaction.

Type: CodeSet

Code	Name	Definition
ACCP	AcceptedCustomerProfile	Preceding check of technical validation was successful. Customer profile check was also successful.
ACCR	AcceptedCancellationRequest	Cancellation is accepted.
ACSC	AcceptedSettlementCompleted	Settlement on the debtor's account has been completed. Usage : this can be used by the first agent to report to the debtor that the transaction has been completed. Warning : this status is provided for transaction status reasons, not for financial information. It can only be used after bilateral agreement
ACSP	AcceptedSettlementInProgress	All preceding checks such as technical validation and customer profile were successful and therefore the payment initiation has been accepted for execution.
ACTC	AcceptedTechnicalValidation	Authentication and syntactical and semantical validation are successful.
ACWC	AcceptedWithChange	Instruction is accepted but a change will be made, such as date or remittance not sent.

Code	Name	Definition
PDNG	Pending	Payment initiation or individual transaction included in the payment initiation is pending. Further checks and status update will be performed.
RJCT	Rejected	Payment initiation or individual transaction included in the payment initiation has been rejected.

Used in element(s)

["DetailedStatus" on page 134](#)

Restricts

["PaymentStatusCode" on page 308](#)

6.122 TrueFalseIndicator

Definition: A flag indicating a True or False value.

Type: Indicator

Meaning When True: True

Meaning When False: False

Used in element(s)

["AmendmentIndicator" on page 128](#), ["EmployeeTerminationIndicator" on page 112](#), ["FamilyMedicalInsuranceIndicator" on page 112](#)

6.123 UUIDv4Identifier

Definition: Universally Unique Identifier (UUID) version 4, as described in IETF RFC 4122 "Universally Unique Identifier (UUID) URN Namespace".

Type: IdentifierSet

Format

pattern [a-f0-9]{8}-[a-f0-9]{4}-4[a-f0-9]{3}-[89ab][a-f0-9]{3}-[a-f0-9]{12}

Used in element(s)

["OriginalUETR" on page 195](#), ["OriginalUETR" on page 183](#), ["UETR" on page 78](#), ["UETR" on page 81](#), ["UETR" on page 189](#), ["UETR" on page 228](#), ["UETR" on page 237](#)

6.124 UnicodeChartsCode

Definition: codelist containing the names of the UNICODE code block name as specified on <http://unicode.org/Public/UNIDATA/Blocks.txt>.

Type: CodeSet

Rules

R2 ValidationByTable

Error handling: Undefined

Used in element(s)

"CharacterSet" on page 41

6.125 YesNoIndicator

Definition: Indicates a "Yes" or "No" type of answer for an element.

Type: Indicator

Meaning When True: Yes

Meaning When False: No

Used in element(s)

"AssignmentCancellationConfirmation" on page 125, "PossibleDuplicate" on page 44, "Reopen-CaseIndication" on page 51, "ReopenCaseIndication" on page 52

Legal Notices

Copyright

S.W.I.F.T. SC © 2026. All rights reserved.

This material is a component of MyStandards, the Swift collaborative Web application used to manage standards definitions and industry usage. It can only be used and distributed in accordance with MyStandards Terms of Use.

Unless otherwise agreed in writing with S.W.I.F.T. SC, you have no right to:

- authorise external end users to use this component for other purposes than their internal use.
- remove, alter, cover, obfuscate or cancel from view any copyright or other proprietary rights notices appearing in this physical medium.
- re-sell or authorise another party e.g. software and service providers, to re-sell this component.

Confidentiality

This publication may contain Swift or third-party confidential information. Only disclose it outside your organisation in accordance with MyStandards Terms of Use and your related license rights.

This component is provided 'AS IS'. Swift does not give and excludes any express or implied warranties with respect to this component such as but not limited to any guarantee as to its quality, supply or availability.

Any and all rights, including title, ownership rights, copyright, trademark, patents, and any other intellectual property rights of whatever nature in this component will remain the exclusive property of Swift or its licensors.

Trademarks and Patents

Swift is the trade name of S.W.I.F.T. SC. The following are registered trademarks of Swift: 3SKey, Innotribe, MyStandards, Sibos, Swift, SwiftNet, the Standards Forum logo, the Swift logo, Swift GPI with logo, the Swift GPI logo, and UETR. Other product, service, or company names in this publication are trade names, trademarks, or registered trademarks of their respective owners.