



Analysis of Computer Vision Methods for Counting Surgical Instruments

Surgical Innovation
2020, Vol. 0(0) 1–2
© The Author(s) 2020
Article reuse guidelines:
sagepub.com/journals-permissions
DOI: 10.1177/1553350620956425
journals.sagepub.com/home/sri


Gustavo Chavez, BA^{1,*} , **David Y. Zhao, MS^{2,*}**,
Albert Haque, MS^{2,*} , **Rahim Nazerali, MD³**,
and **Derek F. Amanatullah, MD, PhD¹**

Dear Editor,

The surgical count is the primary method to account for and manage surgical instruments, needles, and sponges during operative procedures.¹ However, a miscount, when there is a discrepancy between counted and deployed instruments, is estimated to occur in roughly 1 in 140 cases.¹ These events often result in significant costs to hospitals and patients per year due to lost operating room (OR) time and secondary imaging procedures.¹ An estimated 1 in 70 miscounts result in a retained surgical instrument, resulting in patient harm, as well as costly reoperation and litigation.¹ Given the high cost of OR time and the current burden of counting procedures, it is clear that a more accurate and less labor-intensive counting system is needed.

In recent years, there is tremendous growth in machine learning technology applied to healthcare. Computer vision techniques are now applied across many medical domains and are most visible in the context of minimally invasive surgery and endoscopic surgery. We conducted a literature search of computer vision studies on the detection or localization of surgical instruments outside of the surgical field. We are highlighting 4 studies that provide insight into both the feasibility and challenges of utilizing existing computer vision techniques to build a system that can perform the surgical count.

The 4 studies, summarized in [Table 1](#), implemented a wide range of computer vision techniques to localize different types of surgical items, with relatively high detection accuracies ranging from 89% to 95%.^{2–5} Various algorithms were tested, including: instrument barcoding with template matching,² random forest,⁵ and convolutional neural networks.³ Three studies presented their object detection models in the context of a robot manipulator which could pick up the detected instrument.^{2,4,5}

If computer vision is to have widespread adoption as a modality to perform the surgical count, the underlying object detection and tracking algorithms must be robust to the large number and types of surgical objects. The categories of objects present in an operative setting include soft disposables, such as laparotomy sponges, hard disposables, such as surgical needles, and instruments, such as hemostats. However, all 4 of the studies only considered object detection on a limited set of instruments and

hard disposables. In particular, none of the studies attempted detection of surgical sponges and needles, 2 of the most commonly miscounted items in the OR.¹

Data standardization and algorithmic benchmarking is another concern, as only 2 studies released their datasets publicly.^{4,5} Both datasets are limited in size (3200 and 3009 images, respectively), number of object categories, and types of objects, as Zhou and Wachs considered 5 instrument categories (scalpel, retractor, hemostat, scissors and babcock forceps),⁵ while Lavado considered 4 instrument categories (scalpel, straight dissection clamp, straight mayo scissor and curved mayo scissor).³ Furthermore, neither dataset contains annotations with object identifiers for tracking objects across a sequence of images. A collaborative effort between research groups should be established to create and publicly release a sufficiently large and varied dataset for detection and tracking. This would allow for a standardized process to evaluate the performance of computer vision algorithms at the surgical counting task.

Author Contributions

Critical revision of the manuscript: Gustavo Chavez, Albert Haque, David Y. Zhao, Rahim Nazerali, Derek F. Amanatullah

Study concept and design: Rahim Nazerali and Derek F. Amanatullah

Acquisition of data: Gustavo Chavez, David Y. Zhao, and Albert Haque

Study supervision: Derek F. Amanatullah

Analysis and interpretation: Gustavo Chavez, David Y. Zhao, and Albert Haque

¹Department of Orthopaedic Surgery, Stanford Medicine, Redwood City, CA, USA

²Department of Computer Science, Stanford University, CA, USA

³Division of Plastic and Reconstructive Surgery, Department of Surgery, Stanford Medicine, Palo Alto, CA, USA

* These authors contributed equally to this work.

Corresponding Author:

Derek F. Amanatullah, Department of Orthopaedic Surgery, Stanford Medicine, 450 Broadway Street, Pavillion C, Redwood City, CA, USA.
Email: dfa@stanford.edu

Table 1. Summary of Computer Vision Studies With Surgical Objects.

Study	Year	Task	Accuracy	Categories	Images	Setting	Algorithm
Carpintero et al ²	2010	Segmentation Localization	98%	7	— ^b	Lab	Template matching
Lavado ³	2018	Detection	91% ^a	4	3009	Lab	Convolutional neural network
Xu et al ⁴	2015	Detection Localization Pose estimation	95%	— ^b	421	Lab	Barcode Template matching
Zhou and Wachs ⁵	2017	Segmentation Pose estimation	96%	5	3200	Lab	Support vector machine Random forest AdaBoost

^aAuthors did not report accuracy, but reported a related metric: mean average precision.

^bValue unreported by authors.

Declaration of Conflicting Interests

The authors declare no potential conflicts of interest with respect to the research, authorship, and/or publication of this article.

Funding

The author(s) disclosed receipt of the following financial support for the research, authorship, and/or publication of this article: Dr. Amanatullah is supported by an NIH Career development grant KL2TR003143 and work related to this topic is supported by a Wallace H. Coulter Foundation grant.

ORCID iDs

Gustavo Chavez  <https://orcid.org/0000-0003-4990-8979>

Albert Haque  <https://orcid.org/0000-0001-6769-6370>

References

1. Egorova NN, Moskowitz A, Gelijns A, et al. Managing the prevention of retained surgical instruments. *Ann Surg*. 2008; 247(1):13-18.
2. Carpintero E, Pérez C, Morales R, García N, Candela A, Azorín J. Development of a robotic scrub nurse for the operating theatre. In: IEEE RAS EMBS international conference on biomedical robotics and biomechanics; 26-29 September, 2010; Tokyo, Japan: 504-509.
3. Lavado DM. *Sorting Surgical Tools from a Cluttered Tray - Object Detection and Occlusion Reasoning*. Silva JNCPd, Caramelo FJSFA, eds. Coimbra, Portugal: University of Coimbra; 2018. https://eg.uc.pt/bitstream/10316/86257/1/Tese-Diana_VersaoFinal.pdf
4. Xu Y, Mao Y, Tong X, et al. Robotic handling of surgical instruments in a cluttered tray. *IEEE Trans Autom Sci Eng*. 2015;12(2):775-780.
5. Zhou T, Wachs JP. Needle in a haystack: Interactive surgical instrument recognition through perception and manipulation. *Robot Autonom Syst*. 2017;97: 182-192.