

## Install Jenkins on rocky

<https://sysadminxpert.com/install-jenkins-on-rocky-linux-8-or-centos-8/>

# CI/CD Pipeline Using Jenkins, Git and Maven



[appfleet team](#)

Follow

[Mar 18, 2020](#) · 6 min read

### Step 1: Run Your First Jenkins Job

Once you are through with the installation and configuration of Jenkins, now let us create your first Jenkins Job. Login into Jenkins dashboard, find *New Item* as shown below:



New Item

1



People



Build History



Manage Jenkins



Lockable Resources



Credentials



New View

## Welcome to Jenkins!

Please **create new jobs** to get started.

### Build Queue



No builds in the queue.

### Build Executor Status



1 Idle

2 Idle

In the next page, enter the item name **My\_First\_Jenkins\_Job**, select *Freestyle project* and click on *OK*, as shown below:



1

## Enter an item name

» Required field

2



### Freestyle project

This is the central feature of Jenkins. Jenkins will build your project



### Pipeline

Orchestrates long-running activities that can span multiple build



### Multi-configuration project

Suitable for projects that need a large number of different configura



### Folder

Creates a container that stores nested items in it. Useful for group  
long as they are in different folders.



### GitHub Organization

Scans a GitHub organization (or user account) for all repositories



### Multibranch Pipeline

Creates a set of Pipeline projects according to detected branches

3

OK

Under `Jenkins > My_First_Jenkins_Job`, enter a short description into the text field for future reference. As of now, we are going to leave the *Source Code Management* field to *None*. Next, go to *Build* and select *Execute Shell* from the drop-down menu, as shown below:

- ☐ Build after other projects are built
- ☐ Build periodically
- ☐ GitHub hook trigger for GITScm polling
- ☐ Poll SCM

## Build Environment

- ☐ Delete workspace before build starts
- ☐ Use secret text(s) or file(s)
- ☐ Provide Configuration files
- ☐ Abort the build if it's stuck
- ☐ Add timestamps to the Console Output
- ☐ Inspect build log for published Gradle build scans
- ☐ Prepare SonarQube Scanner environment
- ☐ Provide Node & npm bin/ folder to PATH
- ☐ With Ant

## Build

1

Add build step ▾

2

- Execute NodeJS script
- Execute SonarQube Scanner
- Execute Windows batch command
- Execute shell**
- Invoke Ant
- Invoke Gradle script
- Invoke top-level Maven targets
- Provide Configuration files
- Run with timeout
- Set build status to "pending" on GitHub commit
- SonarScanner for MSBuild - Begin Analysis
- SonarScanner for MSBuild - End Analysis

Next, let us try to run simple Shell commands:

```
touch test-file.txt  
echo "Hello World" > test-file.txt  
cat test-file.txt
```

Enter the above-mentioned commands in the text box, and save the configuration, as shown in the figure:

- ☐ Provide Configuration files
- ☐ Abort the build if it's stuck
- ☐ Add timestamps to the Console Output
- ☐ Inspect build log for published Gradle build scans
- ☐ Prepare SonarQube Scanner environment
- ☐ Provide Node & npm bin/ folder to PATH
- ☐ With Ant

## Build

### Execute shell

Command `touch test-file.txt  
echo "Hello World" > test-file.txt  
cat test-file.txt`

See [the list of available environment variables](#)

Add build step ▾

## Post-build Actions


Add post-build action ▾

Save


Apply



It's time to build your project **My\_First\_Jenkins\_Job**. On the left-hand side menu, click the *Build Now* option as shown below:





To see the console output of your first build, follow the screenshot below:





# Jenkins


Jenkins > My\_First\_Jenkins\_Job >


 Back to Dashboard


 Status


 Changes

 Workspace

 Build Now

 Delete Project

 Configure

 Rename

Build History trend

#1 Jan 21, 2020 12:14 PM


Changes


Console Output

Edit Build Information

Delete build '#1'

## Project My\_First\_Jenkins\_Job

 [Workspace](#)

 [Recent Changes](#)

### Permalinks

- [Last build \(#1\), 19 hr ago](#)
- [Last stable build \(#1\), 19 hr ago](#)
- [Last successful build \(#1\), 19 hr ago](#)
- [Last completed build \(#1\), 19 hr ago](#)

On the next page, you will see the following output:

 **Jenkins**

Jenkins > My\_First\_Jenkins\_Job > #1

 Back to Project

 Status

 Changes

 **Console Output**

 View as plain text

 Edit Build Information

 Delete build '#1'

 **Console Output**

Started by user unknown or anonymous  
Running as SYSTEM  
Building in workspace /var/jenkins\_home/w  
[My\_First\_Jenkins\_Job] \$ /bin/sh -xe /tmp  
+ touch test-file.txt  
+ echo Hello World  
+ cat test-file.txt  
Hello World  
Finished: SUCCESS

You can see the executed command output, and in the last line, `Success` indicates that our job finished successfully. This is how you run a Jenkins job.