

March 2009

# Streaming with Project Capuchin

for Adobe Flash Lite™ developers



# Preface

## About this tutorial

---

This Project Capuchin tutorial illustrates how images stored in different locations can be accessed from within a Project Capuchin application.

## Sony Ericsson Developer World

---

At [www.sonyericsson.com/developer](http://www.sonyericsson.com/developer), developers find the latest technical documentation and development tools such as phone White papers, Developers guidelines for different technologies, Getting started tutorials, SDKs (Software Development Kits) and tool plugins. The Web site also features news articles, go-to-market advice, moderated discussion forums offering free technical support and a Wiki community sharing expertise and code examples.

For more information about these professional services, go to the Sony Ericsson Developer World Web site.

This Tutorial is published by:

Sony Ericsson Mobile Communications AB,  
SE-221 88 Lund, Sweden

[www.sonyericsson.com/](http://www.sonyericsson.com/)

© Sony Ericsson Mobile Communications AB,  
2009. All rights reserved. You are hereby granted  
a license to download and/or print a copy of this  
document.  
Any rights not expressly granted herein are  
reserved.

First edition (March 2009)  
Publication number: 1226-1252.1

This document is published by Sony Ericsson  
Mobile Communications AB, without any  
warranty\*. Improvements and changes to this  
text necessitated by typographical errors,  
inaccuracies of current information or  
improvements to programs and/or equipment,  
may be made by Sony Ericsson Mobile  
Communications AB at any time and without  
notice. Such changes will, however, be  
incorporated into new editions of this document.  
Printed versions are to be regarded as temporary  
reference copies only.

\*All implied warranties, including without  
limitation the implied warranties of  
merchantability or fitness for a particular  
purpose, are excluded. In no event shall  
Sony Ericsson or its licensors be liable for  
incidental or consequential damages of any  
nature, including but not limited to lost profits or  
commercial loss, arising out of the use of the  
information in this document.

# Typographical conventions

---

In this document code examples are written in Courier font:

```
loadMovie("res:///icon1.png");
```

# Trademarks and acknowledgements

---

Adobe Flash Lite and Adobe Flash are either trademarks or registered trademarks of Adobe Systems Incorporated in United States and/or other countries.

Java and all Java based trademarks and logos are trademarks or registered trademarks of Sun Microsystems, Inc, in the U.S. and other countries.

Other product and company names mentioned herein may be the trademarks of their respective owners.

# Document history

---

Change history		
2009-03-10	Doc. no. 1226-1252.1	First version published on Developer World

# Contents

<b>Introduction .....</b>	<b>5</b>
<b>Tutorial .....</b>	<b>6</b>
Protocols .....	6
Access files as MIDlet resources .....	6
MidletResource example .....	6
Access files on the Internet .....	6
HttpResource example .....	7
Access files on internal memory or memory card in the phone .....	7
FileSystemResource example .....	7
Application signing .....	8

# Introduction

This Project Capuchin tutorial provides an overview on how Capuchin applications can access images located either in the file system, a memory card, a MIDlet jar, or on the Internet. Images stored in different locations are accessed using different protocols, which are illustrated by three example files:

- `MidletResource fla`: Gives an example of how to access images put in the MIDlet resources folder.
- `HttpResource fla`: Shows how images on the Internet can be accessed.
- `FileSystemResource fla`: Shows how images from the file system of the phone are loaded.

# Tutorial

## Protocols

---

The Project Capuchin API provides access to images as external files (`file://`), Internet resources (`http://`) and MIDlet resources (`res://`). File paths must be absolute paths, that is, the paths should point to the same location on the file system regardless of the current work directory. An absolute path usually starts with the root directory, for example, `"c:/"` for the root directory of the internal phone memory.

## Access files as MIDlet resources

---

Capuchin applications can access files put in the MIDlet jar resources folder. This is done using the `res://` protocol followed by the path to the resource within the MIDlet.

### MidletResource example

---

The `MidletResource.fla` example shows how the `res://` protocol is used to load images from the resources folder. The images `icon1.png`, `icon2.png` and `icon3.png` are placed in the resources folder. To load the `icon1.png` image the following code is used:

```
loadMovie("res:///icon1.png");
```

`res://` means that the image file is placed in the resources folder, and `/icon1.png` is the path to the image within that folder.

## Access files on the Internet

---

To access files on the Internet, the `http://` protocol is used.

## HttpResource example

---

The `HttpResource.fla` example uses the `http://` protocol to load images from the Internet. The images `icon1.png`, `icon2.png` and `icon3.png` are located at `http://developer.sonyericsson.com/images/`. The following code loads the `icon1.png` image into Flash:

```
loadMovie("http://developer.sonyericsson.com/images/icon1.png");
```

## Access files on internal memory or memory card in the phone

---

To access image files residing in phone internal memory or on an inserted memory card, the `file://` protocol is used. However, all folders are not accessible from Java applications due to restrictions in the underlying file manager API. The following folders, subfolders and files are accessible from Capuchin:

- `<file:///c:/>` (internal memory file root)
- `<file:///c:/other>`
- `<file:///c:/pictures/>`
- `<file:///c:/sounds/>`
- `<file:///c:/videos/>`
- `<file:///c:/camera/>`
- `<file:///e:/>` (memory card file root)
- `<file:///e:/dcim/>` (camera pictures folder on memory card).

Which folders are accessible may differ between phone models. For more details about accessible folders, see Developers guidelines - Java ME™ CLDC (MIDP 2), found at <http://developer.sonyericsson.com/getDocument.do?docId=65067>.

## FileSystemResource example

---

The `FileSystemResource.fla` example shows how files residing in the `pictures` folder in the phone internal memory, are loaded with the `file://` protocol. For example, the `icon1.png` image is loaded with:

```
loadMovie("file:///c:/pictures/icon1.png");
```

`file://` indicates that the file is to be found in the file system, and `/c:/pictures/` is the path to the images.

# Application signing

---

Every time the application accesses the file system, the user gets a question whether to permit the access or not. In order to grant access to the file system without getting this question every time, the application needs to be signed. If the application is signed, the user will instead get a question with an extra option to approve the permission forever and never be asked again. For more information about MIDlet signing, see <http://developer.sonyericsson.com/docs/DOC-1640>.