

Cheat Sheet Commands for older RedHat/CentOS(6)

All commands run as root or via sudo

T.Weeks 2026-06-10

Port Scan From Outside Your Server (or from the server itself):

```
nmap -sS server # general /etc/services stealth port scan
nmap -sS -p 1-5000 server # specific port range scan (scans ports 1-5000)
```

Working with SysV-init Based Services (not systemd based systems):

```
#Check/list all services:
runlevel # list our previous and current run levels
chkconfig --list # list all configured services
chkconfig --list | grep 3:on # only list services "on" for runlevel 3
chkconfig --list | grep rpcbind # look for how one service is configured
service <servicename> [start|stop|status|restart] # ex: service httpd restart
init 2 # change to runlevel 2 (limited multiuser)
init 3 # change back to standard, headless runlevel
```

Examining/Working with Networking (from on your server):

```
ip address show # show configured IP addresses (the new way)
ifconfig # show configured IP addresses (the old way)
netstat -ant # see [a]ll [n]umerical [t]cp
netstat -antp # same as above + show process names bound to ports
netstat -antp|grep '0.0.0.0:[0-9]' # show any public port bindings
iptables -L # list human readable listing of iptables ACLs chains
/etc/sysconfig/iptables # edit the iptables ACL table/chain listings
service iptables restart # to restart (and reload config) of iptables
```

WARNING: It is very easy to lock yourself out with iptables. If you lock yourself out, restart your environment through the Cyber Range web interface.

Working with yum/rpm Packages (same as dnf/rpm):

```
rpm -qa # list all installed packages
yum list # list all packages available in the current package repositories
rpm -qi <package> # show info about a given installed packages from local package
yum info <package> # ^^ same as above ^^, but gets info from the repo metadata
rpm -ql <package> # list all files within a given packages
rpm -Uvh <package> # install/upgrade a local or remote(URL) rpm file (no autodeps)
yum install <pkg> # install package from repo & resolve dependencies
rpm -V <package> # verify a package (check file MD5 fingerprints) on disk vs dbase
rpm -Va # verify all package file fingerprints
rpm -Va | grep ^..5 # show files that have changed (fingerprint) since last install
rpm -qf <file> # list the package a file belongs to
yum reinstall <package> # reinstall same (clean) version of installed package
```

Process Listing & Manipulation:

```
ps -auxw # print processes, [a]ll, [u]users, [x]BSDish, [w]ide
kill <PID> # kill a specific process ID number
killall <process-name> # kill all processes with a given name
pkill <process-name> # kill all process names by regular-expression
```

Malware Sites/Tools

```
mkhunter --check # scan system and detect known rootkits and malware
chkrootkit # scan systems for signs of rootkits
https://www.joesandbox.com/analysis # Malware file and hash lookup tool
```

General Server Control:

```
reboot           # gracefully reboots the server
poweroff        # graceful power down
```

Multi-terminal **screen** Usage:

```
$ screen                # To start a screen session
^a (release) c          # c to create a new screen in region
^a n                    # Navigate to the next screen
^a a                    # Toggle between current/last screen
^a 2                    # Navigate to screen #2
^a S                    # Split upper/lower regions
^a Shift-|              # Shift pipe to do two split regions (newer ver)
^a TAB                  # Tab to flip to next region
^a d                    # Detach from screen session
^a ?                    # Show the help screen
$ echo $TERM            # Tells you if you're in screen or terminal
$ screen -r             # Rejoin a running screen session
```