

BIOS vs. UEFI Comparison

Part C – BIOS vs. UEFI Comparison Research

Category	BIOS	UEFI
Definition	Basic Input/Output System; traditional firmware interface used to initialize hardware and begin the operating-system boot process.	Unified Extensible Firmware Interface; a modern firmware interface that replaces the older BIOS model and provides a more extensible pre-boot environment.
Boot Process	Uses legacy firmware routines and normally looks for boot code in the boot sector of an MBR-partitioned disk.	Loads UEFI applications/bootloaders from an EFI System Partition and can use a boot manager with stored boot entries.
Maximum Disk Support	Traditional BIOS commonly uses MBR, whose addressing scheme creates a practical boot-disk limit of about 2.2 TB.	UEFI supports GPT, which uses 64-bit partition addresses and supports vastly larger disks; GPT can theoretically address up to about 9.4 ZB.
Partition Style	Primarily associated with MBR (Master Boot Record).	Primarily associated with GPT (GUID Partition Table), including an EFI System Partition for boot files.
Security Features	Limited native pre-boot security compared with UEFI; legacy BIOS does not provide UEFI Secure Boot.	Supports Secure Boot, which verifies trusted signatures for boot software and helps defend against bootkits/rootkits.
Speed	Generally slower startup and less efficient for modern hardware initialization.	Generally provides faster boot and resume times and is designed for modern hardware and operating systems.
Advantages	Simple, mature, widely supported on older systems, and useful for legacy operating systems and hardware.	Supports large drives, flexible partitioning, Secure Boot, modern boot management, and richer firmware capabilities.
Disadvantages	Legacy limitations include MBR capacity/partition constraints, fewer modern security features, and older firmware design.	Can require UEFI-compatible operating systems/drivers and may require firmware or disk configuration changes when moving from legacy BIOS/MBR.
Modern Usage	Mostly retained for legacy compatibility and older hardware/software.	Standard firmware approach on modern PCs; current Windows hardware requirements rely on UEFI features such as Secure Boot.

Research note: Disk limits depend on firmware, partitioning, and operating-system support. The figures above describe the traditional BIOS/MBR and modern UEFI/GPT models.

Why UEFI Has Largely Replaced BIOS

UEFI has largely replaced traditional BIOS because modern computers need a firmware environment that can handle larger storage devices, more flexible partitioning, stronger boot security, and newer hardware more effectively. BIOS was designed around an older PC architecture and is commonly paired with the Master Boot Record (MBR) partitioning scheme. MBR's addressing model creates a practical limit of about 2.2 TB for a boot disk, while GPT uses 64-bit partition addressing and can support dramatically larger storage. The UEFI Forum explains that GPT was designed to overcome important MBR limitations and can theoretically address disks up to about 9.4 zettabytes.

Another major reason for UEFI adoption is security. UEFI provides the foundation for Secure Boot, a feature that checks the digital signatures of boot components before allowing them to run. This helps prevent unauthorized bootloaders and some forms of bootkit or rootkit malware from taking control during the earliest stages of startup. Microsoft describes Secure Boot as part of the UEFI specification and explains that it verifies trusted boot software before the operating system is loaded.

UEFI also improves the boot experience. Microsoft identifies faster boot and resume times, support for drives larger than 2 TB, and support for more than four partitions among the benefits of UEFI firmware. Unlike the traditional BIOS approach, UEFI can load boot applications from an EFI System Partition and provides a more extensible firmware environment.

Compatibility with modern operating systems has further accelerated the transition. Current Windows platforms are designed around UEFI capabilities, and Microsoft hardware guidance uses UEFI-based configurations for modern security requirements. Microsoft also notes that TPM 2.0 is not supported in Legacy/CSM BIOS modes and that native UEFI is required for TPM 2.0 configurations.

Overall, BIOS remains useful when compatibility with older operating systems or hardware is required, but its limitations make it less suitable for current computers. UEFI provides a more flexible architecture, supports GPT and very large storage devices, enables Secure Boot and related security technologies, and offers a faster and more capable startup environment. For these reasons, UEFI has become the standard firmware approach on modern PCs, while legacy BIOS is increasingly maintained mainly for compatibility with older systems.

References

- Microsoft Learn — UEFI firmware requirements: <https://learn.microsoft.com/en-us/windows-hardware/design/device-experiences/oem-uefi>
- Microsoft Learn — Secure the Windows boot process:
<https://learn.microsoft.com/en-us/windows/security/information-protection/secure-the-windows-10-secure-boot-process>
- Unified Extensible Firmware Interface Forum — FAQ: Drive Partition Limits:
https://uefi.org/sites/default/files/resources/UEFI_Drive_Partition_Limits_Fact_Sheet.pdf
- Microsoft Learn — UEFI/GPT-based hard drive partitions:
<https://learn.microsoft.com/en-us/windows-hardware/manufacture/desktop/configure-uefigpt-based-hard-drive-partitions>
- Microsoft Learn — TPM recommendations: <https://learn.microsoft.com/en-us/windows/security/hardware-security/tpm/tpm-recommendations>