






KN KEWPUMP®

KDP

KDP dosing pump is a positive displacement, reciprocating pump with adjustable flow as process conditions require. It has a high level of repetitive accuracy and is capable of pumping a range of chemicals, including acid base, corrosive or viscous liquids. Models DOS 301/302 (simplex/duplex) are manufactured for easy operation, less space requirement, least maintenance with maximum efficiency.

Design and General Dimensions



Range

Maximum capacity:

Simplex - 30 L/Hr

Duplex - 60 L/Hr

Maximum pressure:

35 Kg/cm²

Maximum suction lift:

3m for water

Specifications

Motor - 0.75HP, 4 Poles Reducer - 1 : 20 Stroke per min - 72 Piston Diameter - 16mm Maximum Stroke - 13/4 in

Material of Construction


Casing - Stainless Steel
Piston Shaft - Stainless Steel
Fitting - Stainless Steel
Packing Set - Viton + Teflon
Valve Ball - Stainless Steel


Connections

Suction - 1/2" BSP Discharge - 1/2" BSP

Features


- Available in simplex, or duplex for multi chemical feed
- Materials of construction for metering chemicals for industrial and agricultural
- √ Output adjustable from zero to maximum capacity
- √ Completely self priming
- √ Double ball valve action for ease of priming
- √ Eccentric assembly has lifetime lubricated components
- √ Heavy duty worm gear reducer with oil sight gauge





PARTS LIST

KEWPUMP®



ltem No.	Part No.	Description	Quantity	Item No.	Part No.	Description	Quantity
1	KDP.1	Casing	2*	21	KDP.7	Bearing Cover	2*
2	-	Casing Bolt	8*	22		Bearing Cover Bolt	2*
3	1212	Packing	2*	23	KDP.8	Eccentric Shaft	2*
4	KDP.2	Grease Gland	2*	24	1	Bearing	2*
5	-	Coil Spring	2*	25	KDP.9	Bearing Cam	2*
6	(<u></u>	Casing Cap Plain Type Washer	2*	26	KDP.10	Stroke Scale Indicator	2*
7	KDP.3	Casing Cap	2*	27	KDP.11	Shaft Coupling	2*
8		Rod End Bearing	2*	28		Grooved Stud	8*
9		Rod End Bearing Nut	2*	29		Ext. Teeth Lock Washer	4*
10	KDP.4	Piston Shaft	2*	30		Shaft Coupling Bolt	4*
11	-	Grease Nipple	4 *	31	KDP.12	Reducer Shaft Key	2*
12	e ve e	Spring Clip	2*	32	KDP.13	Reducer Shaft	1
13	77	Valve Ball	8*	33		Worm Gear Reducer	1
14	KDP.6	Discharge Valve Body	4*	34		Worm Gear Reducer Bolt	4
15		Valve Body Plain Type Washer	8 *	35		Coupling Set	1
16		Cone Shape Coil Spring	2*	36	KDP.15	Reducer Support Spacer	4
17	KDP.17	Suction Valve Body	4*	37	KDP.16	Name Plate	1
18	KDP.5	Casing Support Stand	2*	38	KDP.14	Base Plate	1
19		Casing Support Stand Bolt	8*	39		Motor Bolt	4
20		Spring Pin	2*	40		Motor	1

All quantities based on duplex arrangment.
For simplex arrangement, all quantities marked * should be divided by 2, except for Item No. 28, which quantity for simplex arrangement is 6.