

```
MINGW64/c/[git-master]/grst
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gffm (main)
$ cd ..

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master] (main)
$ git init grst
Initialized empty Git repository in c:/[git-master]/grst/.git/

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master] (main)
$ cd grst

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ ehco 123 > h
bash: ehco: command not found

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git add h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git commit -m Numeric
[main (root-commit) e5f87b2] Numeric
1 file changed, 0 insertions(+), 0 deletions(-)
create mode 100644 h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ echo ABC >> h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git commit -am Alphabet
[main d1beb06] Alphabet
1 file changed, 1 insertion(+)

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ echo AB12 >> h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$
```

```
MINGW64/c/[git-master]/grst
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git commit -am Alphanumeric
[main fcb6889] Alphanumeric
1 file changed, 1 insertion(+)
g
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git add h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ echo '[1, 2]' >> h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git add h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ echo '{1, 2}' >> h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git status
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   h

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |
```

```
MINGW64:/c/[git-master]/grst
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git stash
Saved working directory and index state WIP on main: fcb6889 Alphan
umeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git stash list
stash@{0}: WIP on main: fcb6889 Alphanumeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git lgag1
* 80e9c4d (refs/stash) WIP on main: fcb6889 Alphanumeric
| \
| * ec444bb index on main: fcb6889 Alphanumeric
| /
* fcb6889 (HEAD -> main) Alphanumeric
* d1beb06 Alphabet
* e5f87b2 Numeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git status
On branch main
nothing to commit, working tree clean

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ cat h
ABC
AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git reset --hard ORIG_HEAD
HEAD is now at fcb6889 Alphanumeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ cat h
ABC
AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |
```

```
MINGW64:/c/[git-master]/grst
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git reset --hard ORIG_HEAD
HEAD is now at fcb6889 Alphanumeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git status
On branch main
nothing to commit, working tree clean

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ cat h
ABC
AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git log --oneline
fcb6889 (HEAD -> main) Alphanumeric
d1beb06 Alphabet
e5f87b2 Numeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git digg HEAD
git: 'digg' is not a git command. See 'git --help'.

The most similar command is
    diff

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff HEAD

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |
```

```

MINGW64:/c/[git-master]/grst
AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git log --ontline
fatal: unrecognized argument: --ontline

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git log --onnline
fatal: unrecognized argument: --onnline

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git log --oneline
d1beb06 (HEAD -> main) Alphabet
e5f87b2 Numeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff HEAD
diff --git a/h b/h
index 5da849b..157bc36 100644
--- a/h
+++ b/h
@@ -1,2 @@
   ABC
+AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff --staged
diff --git a/h b/h
index 5da849b..157bc36 100644
--- a/h
+++ b/h
@@ -1,2 @@
   ABC
+AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |

```

```

MINGW64:/c/[git-master]/grst
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git status
On branch main
nothing to commit, working tree clean

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ cat h
ABC
AB12

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git stash apply --index
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   h

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git status
On branch main
Changes to be committed:
  (use "git restore --staged <file>..." to unstage)
        modified:   h

Changes not staged for commit:
  (use "git add <file>..." to update what will be committed)
  (use "git restore <file>..." to discard changes in working directory)
        modified:   h

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |

```

```

MINGW64:/c/[git-master]/grst
d1beb06 Alphabet
e5f87b2 Numeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff
diff --git a/h b/h
index a681b06..a8a83f3 100644
--- a/h
+++ b/h
@@ -1,3 +1,4 @@
 ABC
 AB12
 [1, 2]
+{1, 2}

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff HEAD
diff --git a/h b/h
index 157bc36..a8a83f3 100644
--- a/h
+++ b/h
@@ -1,2 +1,4 @@
 ABC
 AB12
+[1, 2]
+{1, 2}

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ git diff --staged
diff --git a/h b/h
index 157bc36..a681b06 100644
--- a/h
+++ b/h
@@ -1,2 +1,3 @@
 ABC
 AB12
+[1, 2]

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |

```

```

MINGW64:/c/[git-master]/grst
$ git checkout HEAD~
Note: switching to 'HEAD~'.

You are in 'detached HEAD' state. You can look around, make exper
ental
changes and commit them, and you can discard any commits you make
n this
state without impacting any branches by switching back to a branch

If you want to create a new branch to retain commits you create,
u may
do so (now or later) by using -c with the switch command. Examplele

    git switch -c <new-branch-name>

or undo this operation with:

    git switch -

Turn off this advice by setting config variable advice.detachedHe
to false

HEAD is now at d1beb06 Alphabet

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst ((d1beb06...))
$ cat h
ABC

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst ((d1beb06...))
$ git log --oneline
d1beb06 (HEAD) Alphabet
e5f87b2 Numeric

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst ((d1beb06...))
$ git checkout main
Previous HEAD position was d1beb06 Alphabet
Switched to branch 'main'

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/grst (main)
$ |

```