

```
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master] (main)
$ git init gfile
Initialized empty Git repository in C:/[git-master]/gfile/.git/

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master] (main)
$ cd gfile

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ echo aaa > f

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git add f

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git commit -m A
[main (root-commit) 4e6cc6b] A
 1 file changed, 1 insertion(+)
 create mode 100644 f

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git log --oneline
4e6cc6b (HEAD -> main) A

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ |
```

```
qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ echo bbb >> f

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ cat f
aaa
bbb

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git status -s
M f

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git diff
diff --git a/f b/f
index 72943a1..dbec026 100644
--- a/f
+++ b/f
@@ -1,2 @@
   aaa
+bbb

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git diff --staged

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ git diff HEAD
diff --git a/f b/f
index 72943a1..dbec026 100644
--- a/f
+++ b/f
@@ -1,2 @@
   aaa
+bbb

qkrdl@DESKTOP-IO7MCK4 MINGW64 /c/[git-master]/gfile (main)
$ |
```