

```
class immbag.MultiRandBalBag (n_estimator=10, estimator=DecisionTreeClassifier(), k= 5)
```

Multi Random Balance Bagging (MultiRandBalBag)

MultiRandBalBag algorithm is a bagging ensemble algorithm for multi-class imbalance classification, in which a weight is assigned to each data class, drawn randomly from a uniform distribution over the interval [0, 1], and then scales these weights to sum to 1. These weights are subsequently used for sampling from the respective classes.

Source: Rodriguez, J. J., Diez-Pastor, J. F., Arnaiz-Gonzalez, A., & Kuncheva, L. I. (2020). Random balance ensembles for multiclass imbalance learning. Knowledge-Based Systems, 193, 105434.

Parameters : **n_estimator** : *int (default=10)*

The number of nearest neighbors to search for.

estimator : *object (default= DecisionTreeClassifier())*

An instance of a base classifier used in the ensemble

k: *int (default=2)*

The number of nearest neighbors used to generate synthetic samples.

Examples:

```
from sklearn.tree import DecisionTreeClassifier
from sklearn.model_selection import train_test_split
from ImbBag import MultiRandBalBag

dataframe = read_csv('dataset.csv')
data = dataframe.values
X = data[:, :-1]
Y = data[:, -1]

# split the dataset into training and test sets
X_train ,X_test ,y_train ,y_test = train_test_split (X, y,
test_size =0.2)
```

```
# instantiate the imbalance bagging classifier, training, prediction
cls = MultiRandBalBag(n_estimator = 10,
estimator=DecisionTreeClassifier())
clf.fit(X_train , y_train)
y_pred = clf.predict(X_test)
```

Methods

fit(self, X_train, y_train)	Fit the model.
predict(self, X)	Predict the class label for sample X
predict_proba(self, X)	Estimate the probability of X belonging to each class-labels.

fit(self, X_train, y_train)

Parameters X_train : *numpy.ndarray of shape (n_samples, n_features)*

The features to train the model.

y_train : *numpy.ndarray of shape (n_samples,)*

An array-like with the class labels of all samples in X_train.

Returns : self

predict(self, X):

Parameters X : *numpy.ndarray of shape (n_samples, n_features)*

All the samples we want to predict the label for.

Returns : *numpy.ndarray*

A 1D array of shape (, n_samples), containing the predicted class labels for all instances in X.

predict_proba(self, X):

Parameters X : *numpy.ndarray of shape (n_samples, n_features)*

All the samples we want to predict the label for.

Returns : *numpy.ndarray*

A 2D array of shape (n_samples, n_classes). Where each i-th row contains len(self.target_value) elements, representing the probability that the i-th sample of X belongs to a certain class label.