

CCNA 200-301

Chapter 15 - Router Basic Configuration

Lab Overview

- Two different LANs connected using one router.
- Devices on different IP networks cannot communicate without a router.
- Each router interface belongs to a different network.

Router Modes

- User Mode (>)
- Privileged Mode (#) using enable
- Global Configuration Mode using configure terminal or config t
- Use do before show commands while inside Configuration Mode.

Basic Configuration

- hostname <name> : Change router name.
- clock set : Configure date and time.
- copy running-config startup-config : Save configuration.
- wr : Shortcut for saving configuration.

Interface Configuration

- interface g0/0
- interface g0/1
- no shutdown
- ip address <IP> <Subnet Mask>

Verification Commands

- show ip interface brief (or do show ip interface brief)
- show ip route

Routing Table Notes

- C = Connected Network
- L = Local Interface Address
- Gateway of last resort is not set is normal because no default route exists.

Memory

- Running Configuration is stored in RAM.
- Save it to NVRAM using copy run start or wr.

Routing Protocols

- RIP, OSPF and EIGRP are used only when multiple routers exist.
- This lab contains one router, so routing protocols are not required.

Important Commands

- enable
- configure terminal
- hostname Cairo
- clock set
- interface g0/0
- interface g0/1
- ip address
- no shutdown
- do show ip interface brief
- show ip route
- copy running-config startup-config
- wr