TECHNICAL DATA SHEET

PORTABLE PNEUMATIC DIAPHRAGM PUMP • AQUEOUS UREA SERVICE

RFQ BASIS NEP01-512-GEN-OM-PO-025-Rev.0 One ship set / one pump	SUPPLIER Company: _____ Contact / Offer No.: _____
QUANTITY 1 pump for POS NEP01-512-GEN-OM-PO-025 (one ship set). This datasheet covers this pump only.	OFFER DATE / VALIDITY Date: _____ Validity: _____

5 m³/h	40 MTH	~7 bar	316L
Rated duty flow	Water-column head	Drive air pressure	Wetted metallic parts

BIDDER INSTRUCTION: Complete the Supplier Offer column and the compliance/deviation section. State all assumptions explicitly. Do not treat maximum free-flow capacity as proof of the specified duty point.

A. PROCESS & DUTY REQUIREMENTS

Parameter	Purchaser Requirement	Supplier Offer / Confirmation
Equipment / service	Urea pump for shipboard service. Portable pneumatic diaphragm pump.	Enter offered value / confirm
Pump configuration	Pneumatically driven diaphragm pump. Supplier shall state exact construction/type and model (e.g., AODD if applicable).	Enter offered value / confirm
Driver / electrical	Compressed-air operated. No electric motor or electrical equipment required per TCL.	Confirm: No electrical equipment included
Quantity	1 pump for this ship set, per NEP01-512-GEN-OM-PO-025. This datasheet covers one pump only.	Enter offered value / confirm
Rated flow	5 m³/h at the specified head.	Enter offered value / confirm
Rated head	40 MTH (40 m water column), per TCL. Supplier to confirm the duty point on its performance curve.	Enter offered value / confirm
Pumped liquid	Approximately 30% aqueous urea solution; no crystals reported. Concentration basis is not stated in the source documents.	State assumed basis: wt% / vol% / other
Liquid density	Approximately close to water (no exact value provided).	State design density and basis
Liquid viscosity	Approximately 1.5 times water (temperature not specified).	State viscosity and reference temperature
Suction lift / elevation	Up to 1.5 m above minimum liquid level, per TCL. Supplier to confirm at the specified duty and liquid conditions.	Enter offered value / confirm
Wetted metallic material	Corrosion-resistant stainless steel 316L for casing and other pump parts, per POS. List all wetted metal parts.	List material grades and provide evidence
Diaphragm / soft parts	Not specified by purchaser; supplier to select and certify chemical compatibility with the stated urea solution and temperature range.	State diaphragm, balls/valves, seats and seal materials

Basis: POS section 2 and TCL clarification image (six rows). The final operating temperature and concentration basis remain to be confirmed by Purchaser.

B. AIR, CONNECTIONS, TESTING & COMMERCIAL RETURN

Parameter	Purchaser Requirement	Supplier Offer / Confirmation
Drive-air supply pressure	Approximately 7 bar per TCL. Supplier to state allowable inlet pressure range and pressure required at duty.	Enter offered value / confirm
Air consumption	Not specified by Purchaser. Supplier shall state consumption at 5 m³/h @ 40 MTH and the basis/units.	Enter offered value / confirm
Air connection	Size and standard to be proposed by Supplier, subject to Purchaser approval.	Enter offered value / confirm
Suction / discharge connections	Sizes and standards to be proposed by Supplier and approved against ship piping. Provide a connection drawing.	Enter offered value / confirm
Performance data	Submit manufacturer performance curve clearly marking 5 m³/h @ 40 MTH and the drive-air conditions.	Attach curve / document No.
Suction capability / NPSH	POS includes a generic NPSH requirement; TCL specifies 1.5 m suction lift. Provide applicable self-priming/suction-lift data. If NPSH is not applicable, state N/A and provide equivalent data.	Enter offered value / confirm
Marine suitability / class	Suitable for marine/shipboard service. POS references Bureau Veritas or equivalent. State approvals/certificates available; do not assume approval.	Enter offered value / confirm
Shop inspection & testing	Submit ITP, proposed shop-test scope/procedure and test reports/certificates in line with POS and agreed project requirements.	Enter offered value / confirm
Documentation	English language; SI units. Submit datasheet, GA/connection drawings, BOM/materials, performance curve, ITP/test report, O&M; manual and recommended spares.	List document numbers / schedule
Accessories / portability	List standard accessories included. Define portable arrangement and state weight/dimensions. Quote trolley and hoses separately if offered.	Enter offered value / confirm
Warranty	POS general requirement: 18 months from ship delivery; repaired/replaced item extension 6 months, overall maximum 24 months. Confirm or state deviation.	Enter offered value / confirm

C. BIDDER COMPLIANCE & COMMERCIAL SUMMARY

Return Item	Supplier Response	Notes
Technical compliance	Comply / Deviate / N/A: _____	Attach clause-by-clause compliance statement and deviations.
Exact make / model	_____	
Unit price / currency	_____	State price for this pump.
Total price for 1 unit	_____	Show assumptions, taxes and exclusions.
Manufacturing / delivery lead time	_____	State from approved drawings / PO, as applicable.
Incoterm / delivery point	_____	Include packing, shipment dimensions and gross weight.
Country of origin	_____	
Recommended spare parts	_____	Quote separately; attach list and prices.
Commissioning assistance	Included / Optional / Excluded: _____	POS notes commissioning assistance as an option.

TECHNICAL HOLD POINTS: Confirm concentration basis and liquid temperature with Purchaser; verify available compressed-air capacity; approve connection sizes; confirm 316L wetted metallic parts and chemical compatibility; obtain current approved POS/TCL before purchase.

Supplier authorized representative	Purchaser review
Name / Title: _____ Signature / Date: _____	Reviewed by: _____ Status / Date: _____

Reference documents: POS NEP01-512-GEN-OM-PO-025, Rev.0; Purchaser TCL clarification image supplied with the inquiry. This RFQ data sheet covers one pump and does not replace the latest approved project documents.