

Lecture 3 – Xamarin.Forms Layouts

Mr. Yousif Garabet Arshak
Computer Science Department
University of Zakho
yousif.arshak@uoz.edu.krd

Outlines

- Xamarin.Forms Layouts
- Layouts with Single Content
 1. ContentView
 2. Frame
 3. ScrollView
 4. TemplatedView
 5. ContentPresenter
- Layouts with Multiple Children
 1. StackLayout
 2. Grid
 3. AbsoluteLayout
 4. RelativeLayout
 5. FlexLayout



Xamarin.Forms Layouts


- *Xamarin.Forms Layouts are used to compose user-interface controls into visual structures.*
- The `Layout` and `Layout<T>` classes in `Xamarin.Forms` are specialized subtypes of views that act as containers for views and other layouts.
- The `Layout` class itself derives from `View`.
- A `Layout` derivative typically contains logic to set the position and size of child elements in `Xamarin.Forms` applications.




Xamarin.Forms Layouts




ContentPresenter



ContentView




ScrollView




Frame




TemplatedView




StackLayout




AbsoluteLayout



RelativeLayout



Grid




FlexLayout

Layouts with Single Content

These classes derive from Layout, which defines Padding and IsClippedToBounds properties:

1. **ContentView:**
ContentView contains a single child that is set with the Content property. The Content property can be set to any View derivative, including other Layout derivatives. ContentView is mostly used as a structural element and serves as a base class to Frame.



Xaml Code


Note: You can download all the XAML code in the this link:

[Xamarin.Forms Layouts - Xamarin | Microsoft Docs](#)

```
<?xml version="1.0" encoding="utf-8" ?>
<ContentPage xmlns="http://xamarin.com/schemas/2014/forms"
    xmlns:x="http://schemas.microsoft.com/winfx/2009/xaml"
    x:Class="FormsGallery.XamlExamples.ContentViewDemoPage"
    Title="ContentView Demo">
    <StackLayout>
        <Label Text="ContentView"
            FontSize="50"
            FontAttributes="Bold"
            HorizontalOptions="Center" />
        <ContentView BackgroundColor="Aqua"
            Margin="10"
            Padding="25"
            HorizontalOptions="Fill"
            VerticalOptions="CenterAndExpand">
            <Label Text= "some text here"
                TextColor="Purple" />
        </ContentView>
    </StackLayout>
</ContentPage>
```



2. **Frame:** The Frame class derives from ContentView and displays a border, or frame, around its child. The Frame class has a default Padding value of 20, and also defines BorderColor, CornerRadius, and HasShadow properties.




Xaml Code

```
<?xml version="1.0" encoding="utf-8" ?>
<ContentPage xmlns="http://xamarin.com/schemas/2014/forms"
    xmlns:x="http://schemas.microsoft.com/winfx/2009/xaml"
    x:Class="FormsGallery.XamlExamples.FrameDemoPage"
    Title="Frame Demo">
    <StackLayout>
        <Label Text="Frame"
            FontSize="50"
            FontAttributes="Bold"
            HorizontalOptions="Center" />
        <Frame OutlineColor="Accent"
            HasShadow="True"
            HorizontalOptions="Center"
            VerticalOptions="CenterAndExpand">
            <Label Text="I've been framed!" />
        </Frame>
    </StackLayout>
</ContentPage>
```



3. **ScrollView**: is capable of scrolling its contents. Set the Content property to a view or layout too large to fit on the screen. (The content of a ScrollView is very often a StackLayout.) Set the Orientation property to indicate if scrolling should be vertical, horizontal, or both.



Xaml Code

```
<?xml version="1.0" encoding="utf-8" ?>
<ContentPage xmlns="http://xamarin.com/schemas/2014/forms"
    xmlns:x="http://schemas.microsoft.com/winfx/2009/xaml"
    x:Class="FormsGallery.XamlExamples.ScrollViewDemoPage"
    Title="ScrollView Demo">
    <StackLayout>
        <Label Text="ScrollView"
            FontSize="50"
            FontAttributes="Bold"
            HorizontalOptions="Center" />
        <ScrollView VerticalOptions="FillAndExpand"
            Margin="10">
            <Label Text=
                "Sometimes page content.... "
                FontSize="Large" />
        </ScrollView>
    </StackLayout>
</ContentPage>
```



4. TemplatedView: TemplatedView displays content with a control template, and is the base class for ContentView.




5. **ContentPresenter:** is a layout manager for templated views, used within a ControlTemplate to mark where the content that is to be presented appears.





Layouts with Multiple Children

These classes derive from
Layout<View>:


1. **StackLayout:** StackLayout positions child elements in a stack either horizontally or vertically based on the Orientation property. The Spacing property governs the spacing between the children, and has a default value of 6.





2. Grid: Grid positions its child elements in a grid of rows and columns. A child's position is indicated using the attached properties Row, Column, RowSpan, and ColumnSpan.




3. **RelativeLayout:**
RelativeLayout positions child elements at specific locations relative to its parent. A child's position is indicated using the attached properties `LayoutBounds` and `LayoutFlags`. An `RelativeLayout` is useful for animating the positions of views.



4. **RelativeLayout:** RelativeLayout positions child elements relative to the RelativeLayout itself or to their siblings. A child's position is indicated using the attached properties that are set to objects of type Constraint and BoundsConstraint.



5. FlexLayout: FlexLayout is based on the CSS Flexible Box Layout Module, commonly known as flex layout or flex-box. FlexLayout defines six bindable properties and five attached bindable properties that allow children to be stacked or wrapped with many alignment and orientation options.



Any Questions?

