- 1. Consider a dipole antenna with $a/\lambda = 0.006$ at 600 MHz.
 - a. Find its resonant length and resonant resistance using the plots. Plot R and X over 470-750 MHz using Tai's formula.




Fig. 7.13 Resonant Length versus Radius for Center-Fed Cylindrical Dipoles

$$\lambda_0 = \frac{c_0}{f_0} = \frac{299792458 \ m/s}{600 \ MHz} \approx 50 \ cm$$

$$\frac{2l_r}{\lambda} \approx 0.466 \to l_r \approx 11.64 \ cm$$

Dipole Length = 23.28 cm

Figure 1 Code

```
syms f
lambda = 3e8/f;
length = 0.233 * 3e8/600e6;
alpha = 0.806;
k(f) = (2*pi)/lambda;
R(f) = (2:6.5 - 204.1*k(f)*length + 110*(k(f)*length)^2;
X(f) = -1*(120*(log(2*length/alpha - 1) * cot(k(f)*length)) - 162.5 * 140*k(f)*length - 40*(k(f)*length)^2 );
X(f) = -1*(120*(log(2*length/alpha - 1) * cot(k(f)*length)) - 162.5 * 140*k(f)*length - 40*(k(f)*length)^2 );
F = figure;
F.Position = [0,0,800,600];
centerfig(F);
yaxis left
plot(f1./1e6, R(f1), "DisplayName", "Ohmic Resistance");
ylabel("R(f) \omega", "FontSize", 14);
hold on;
yyaxis right
ylabel("Y(f) \omega", "FontSize", 14)
plot(f1./1e6, X(f1), "DisplayName", "Reactance");
title("Plot of R(f) and X(f) from 470HHz to 750HHz", "FontSize", 18);
xlabel("Frequency (HHz)", "FontSize", 14);
grid on;
legend();

Figure 2 Code

F2 = figure;
F2.Position = [0,0,800,600];
centerfig(F2);
plot(f1/le6, k(f1).*length);
grid on;
title("kl factor from 470HHz to 750HHz", "FontSize", 18);
ylabel("kl factor");
xlabel("Rt factor from 470HHz to 750HHz", "FontSize", 18);
ylabel("kl factor");
xlabel("krequency (HHz)");
text(536, 1.8, {"Frequency range is mostly within the", "function domain of 1.3 <= kl <= 1.7"}, "FontSize", 15);
yline(1.3, ---, 'color', 'red', 'LineWidth', 2);
xline(532.8, '---', 'color', 'red', 'LineWidth', 2);
xline(532.8, '---', 'color', '#05319', 'LineWidth', 2);
ylane(.37, '---, 'color', '#05319', 'LineWidth', 2);
ylane(.37, '---,
```

