



Lab Report

CSE351, Computer Networking

Name: **Youssef Moustafa Elsayed** ID: **22P0047**
Lab No: (7) Experiment Title: Wireshark Lab: DHCP

Date: 14 / 12 /2025

Steps

1- In a command-line window we will enter the following command:

> ipconfig /release

This command will cause the PC to give up its IP address.

```
C:\Users\Youssef Moustafa>ipconfig /release

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 9 while it has its media disconnected.
No operation can be performed on Local Area Connection* 10 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::ceb4:5ecc:3c4e:b578%14
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 9:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 10:


    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::a29c:690b:4a23:7136%13
    Default Gateway . . . . . :

Ethernet adapter Bluetooth Network Connection:
```

2- Start up the Wireshark packet sniffer



3- In the command-line window enter the following command:

> ipconfig /renew

This will cause the DHCP protocol to request and receive an IP address and other information from a DHCP server.

```
C:\Users\Youssef Moustafa>ipconfig /renew

Windows IP Configuration

No operation can be performed on Ethernet while it has its media disconnected.
No operation can be performed on Local Area Connection* 9 while it has its media disconnected.
No operation can be performed on Local Area Connection* 10 while it has its media disconnected.
No operation can be performed on Bluetooth Network Connection while it has its media disconnected.

Ethernet adapter Ethernet:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::ceb4:5ecc:3c4e:b578%14
    IPv4 Address. . . . . : 192.168.56.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

Wireless LAN adapter Local Area Connection* 9:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Local Area Connection* 10:

    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Wireless LAN adapter Wi-Fi:

    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::a29c:690b:4a23:7136%13
    IPv4 Address. . . . . : 192.168.1.10
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.1.1

Ethernet adapter Bluetooth Network Connection:


    Media State . . . . . : Media disconnected
    Connection-specific DNS Suffix  . :

Ethernet adapter vEthernet (WSL (Hyper-V firewall)):
```

```
    Connection-specific DNS Suffix  . :
    Link-local IPv6 Address . . . . . : fe80::8c10:941f:6943:c0a6%60
    IPv4 Address. . . . . : 172.18.128.1
    Subnet Mask . . . . . : 255.255.240.0
    Default Gateway . . . . . :
```

4- After waiting for a few seconds, stop Wireshark capture.

5- After stopping Wireshark capture in step 4, we should peek into Wireshark window to make sure we captured the packets that we're looking for. Enter "dhcp" into the display filter field.



The screenshot shows the Wireshark interface with the display filter set to 'dhcp'. The packet list shows four packets: a DHCP Discover (No. 69), a DHCP Offer (No. 75), a DHCP Request (No. 76), and a DHCP ACK (No. 78). All packets have a source IP of 0.0.0.0 and a destination IP of 255.255.255.255, and they all belong to Transaction ID 0x51b2d6b.

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

Part 2: Answering Questions in textbook

1. Is this DHCP Discover message sent out using UDP or TCP as the underlying transport protocol?

UDP

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

```
> Frame 69: Packet, 342 bytes on wire (2736 bits), 342 bytes captured (2736 bits) on interface \Device\NPF_{A4CD95BD-AF85-4...}
> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)
v Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 328
    Identification: 0x33a9 (13225)
  > 000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 128
  Protocol: UDP (17)
  Header Checksum: 0x0000 [validation disabled]
  [Header checksum status: Unverified]
  Source Address: 0.0.0.0
  Destination Address: 255.255.255.255
```

2. What is the source IP address used in the IP datagram containing the Discover message? Is there anything special about this address? Explain.

0.0.0.0

Yes, there is something special as the client does not yet have an IP address

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 69: Packet, 342 bytes on wire (2736 bits), 342 bytes captured (2736 bits) on interface \Device\NPF_{A4CD95BD-AF85-408D-8000-000000000000}

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 328
Identification: 0x33a9 (13225)
> 000. = Flags: 0x0
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 128
Protocol: UDP (17)
Header Checksum: 0x0000 [validation disabled]
[Header checksum status: Unverified]
Source Address: 0.0.0.0
Destination Address: 255.255.255.255

3. What is the destination IP address used in the datagram containing the Discover message. Is there anything special about this address? Explain.

255.255.255.255

Yes, there is something special as this is the limited broadcast address.

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 69: Packet, 342 bytes on wire (2736 bits), 342 bytes captured (2736 bits) on interface \Device\NPF_{A4CD95BD-AF85-...}

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 328

Identification: 0x33a9 (13225)

> 000. = Flags: 0x0

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 128

Protocol: UDP (17)

Header Checksum: 0x0000 [validation disabled]

[Header checksum status: Unverified]

Source Address: 0.0.0.0

Destination Address: 255.255.255.255

4. What is the value in the transaction ID field of this DHCP Discover message?

Transaction ID: 0x051b2d6b

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 69: Packet, 342 bytes on wire (2736 bits), 342 bytes captured (2736 bits) on interface \Device\NPF_{A4CD95BD-AF85-...}

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

> User Datagram Protocol, Src Port: 68, Dst Port: 67

> Dynamic Host Configuration Protocol (Discover)

Message type: Boot Request (1)

Hardware type: Ethernet (0x01)

Hardware address length: 6

Hops: 0

Transaction ID: 0x051b2d6b

Seconds elapsed: 0

5. Now inspect the options field in the DHCP Discover message. What are five pieces of information (beyond an IP address) that the client is suggesting or requesting to receive from the DHCP server as part of this DHCP transaction?

- 1- **Client Identifier:** Used by the DHCP server to uniquely identify the client.
- 2- **Host Name:** The name of the client device requesting configuration.
- 3- **Vendor Class Identifier:** Identifies the client's operating system or vendor type.
- 4- **Parameter Request List:** specifies which configuration parameters the client wants from the server.
- 5- **Network configuration parameters** requested in the Parameter Request List, such as:
 - Subnet Mask
 - Router
 - DNS Server

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

Client IP address: 0.0.0.0
Your (client) IP address: 0.0.0.0
Next server IP address: 0.0.0.0
Relay agent IP address: 0.0.0.0
Client MAC address: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)
Client hardware address padding: 00000000000000000000
Server host name not given
Boot file name not given
Magic cookie: DHCP

- > Option: (53) DHCP Message Type (Discover)
- > Option: (61) Client identifier
- > Option: (50) Requested IP Address (192.168.1.10)
- > Option: (12) Host Name
- > Option: (60) Vendor class identifier
- ✓ Option: (55) Parameter Request List
 - Length: 14
 - Parameter Request List Item: (1) Subnet Mask
 - Parameter Request List Item: (3) Router
 - Parameter Request List Item: (6) Domain Name Server
 - Parameter Request List Item: (15) Domain Name
 - Parameter Request List Item: (31) Perform Router Discover
 - Parameter Request List Item: (33) Static Route
 - Parameter Request List Item: (43) Vendor-Specific Information
 - Parameter Request List Item: (44) NetBIOS over TCP/IP Name Server
 - Parameter Request List Item: (46) NetBIOS over TCP/IP Node Type
 - Parameter Request List Item: (47) NetBIOS over TCP/IP Scope
 - Parameter Request List Item: (119) Domain Search
 - Parameter Request List Item: (121) Classless Static Route
 - Parameter Request List Item: (249) Private/Classless Static Route (Microsoft)
 - Parameter Request List Item: (252) Private/Proxy autodiscovery
- > Option: (255) End

6. How do you know that this Offer message is being sent in response to the DHCP Discover message you studied in questions 1-5 above?

Its Transaction ID matches the discover message's Transaction ID equals 0x051b2d6b

Also, because it is the Offer message directly after the Discover message

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 75: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface \Device\NPF_{A4CD95BD-AF85}

> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)

> Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255

> User Datagram Protocol, Src Port: 67, Dst Port: 68

✓ Dynamic Host Configuration Protocol (Offer)

Message type: Boot Reply (2)

Hardware type: Ethernet (0x01)

Hardware address length: 6

Hops: 0

Transaction ID: 0x051b2d6b

Seconds elapsed: 0

7. What is the source IP address used in the IP datagram containing the Offer message? Is there anything special about this address? Explain.

192.168.1.1

Yes, there is something special as this is the server offering the IP address

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 75: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface \Device\NPF_{A4CD95BD-AF85}

> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)

✓ Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 310

Identification: 0x0000 (0)

> 000. = Flags: 0x0

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 64

Protocol: UDP (17)

Header Checksum: 0xb80e [validation disabled]

[Header checksum status: Unverified]

Source Address: 192.168.1.1

Destination Address: 255.255.255.255

8. What is the destination IP address used in the datagram containing the Offer message? Is there anything special about this address? Explain.

255.255.255.255

Yes, there is something special as Client still doesn't have an IP so, the Server broadcasts the offer

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

```
> Frame 75: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface \Device\NPF_{A4CD95BD-AF85-4A4C-8A4C-8A4C}
> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)
✓ Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255
  0100 .... = Version: 4
  .... 0101 = Header Length: 20 bytes (5)
  > Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
    Total Length: 310
    Identification: 0x0000 (0)
  > 000. .... = Flags: 0x0
    ...0 0000 0000 0000 = Fragment Offset: 0
    Time to Live: 64
    Protocol: UDP (17)
    Header Checksum: 0xb80e [validation disabled]
    [Header checksum status: Unverified]
    Source Address: 192.168.1.1
    Destination Address: 255.255.255.255
```

9. Now inspect the options field in the DHCP Offer message. What are five pieces of information that the DHCP server is providing to the DHCP client in the DHCP Offer message?

1- **Subnet Mask:** 255.255.255.0

2- **Router:** 192.168.1.1

3- **Domain Name Server (DNS)**

4- **DHCP Server Identifier:** 192.168.1.1 (The DHCP server is the router)

5- **IP Address Lease Time**

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

```
> Frame 75: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface \Device\NPF_{A4CD95BD-AF85-45B8-A021-3F31B0249F78}, id 0
> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)
> Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255
> User Datagram Protocol, Src Port: 67, Dst Port: 68
v Dynamic Host Configuration Protocol (Offer)
  Message type: Boot Reply (2)
  Hardware type: Ethernet (0x01)
  Hardware address length: 6
  Hops: 0
  Transaction ID: 0x051b2d6b
  Seconds elapsed: 0
> Bootp flags: 0x0000 (Unicast)
  Client IP address: 0.0.0.0
  Your (client) IP address: 192.168.1.10
  Next server IP address: 0.0.0.0
  Relay agent IP address: 0.0.0.0
  Client MAC address: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)
  Client hardware address padding: 00000000000000000000
  Server host name not given
  Boot file name not given
  Magic cookie: DHCP
> Option: (53) DHCP Message Type (Offer)
> Option: (1) Subnet Mask (255.255.255.0)
> Option: (3) Router
> Option: (6) Domain Name Server
> Option: (54) DHCP Server Identifier (192.168.1.1)
> Option: (51) IP Address Lease Time
> Option: (255) End
```

10. What is the UDP source port number in the IP datagram containing the first DHCP Request message in your trace? What is the UDP destination port number being used?

UDP Source port: 68

UDP Destination Port: 67

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 76: Packet, 360 bytes on wire (2880 bits), 360 bytes captured (2880 bits) on interface \Device\NPF_{A4CD95BD-AF85-45B8-A021-3F31B0249F78}, id 0

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

User Datagram Protocol, Src Port: 68, Dst Port: 67

Source Port: 68

Destination Port: 67

Length: 326

Checksum: 0x96e1 [unverified]

[Checksum Status: Unverified]

[Stream index: 13]

[Stream Packet Number: 2]

> [Timestamps]

UDP payload (318 bytes)

> Dynamic Host Configuration Protocol (Request)

11. What is the source IP address in the IP datagram containing this Request message? Is there anything special about this address? Explain.

0.0.0.0

Yes, there is something special as the client does not yet have an IP address

It would appear that once the DHCP Offer message is received, that the client may have all the information it needs to proceed. However, the client may have received OFFERS from multiple DHCP servers and so a second phase is needed, but client knows there is at least one DHCP server out there

That's why it is still not configured and haven't taken its IP address after the first 2 steps.

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 76: Packet, 360 bytes on wire (2880 bits), 360 bytes captured (2880 bits) on interface \Device\NPF_{A4CD95BD-AF85-45B8-A021-3F31B0249F78}, id 0

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 346

Identification: 0x33aa (13226)

> 000. = Flags: 0x0

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 128

Protocol: UDP (17)

Header Checksum: 0x0000 [validation disabled]

[Header checksum status: Unverified]

Source Address: 0.0.0.0

Destination Address: 255.255.255.255

12. What is the destination IP address used in the datagram containing this Request message. Is there anything special about this address? Explain.

255.255.255.255

Yes, there is something special as this is broadcasted message as for all DHCP servers to know which offer was accepted

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 76: Packet, 360 bytes on wire (2880 bits), 360 bytes captured (2880 bits) on interface \Device\NPF_{A4CD95BD-AF85-45B8-A021-3F31B0249F78}, id 0

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

0100 = Version: 4

.... 0101 = Header Length: 20 bytes (5)

> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)

Total Length: 346

Identification: 0x33aa (13226)

> 000. = Flags: 0x0

...0 0000 0000 0000 = Fragment Offset: 0

Time to Live: 128

Protocol: UDP (17)

Header Checksum: 0x0000 [validation disabled]

[Header checksum status: Unverified]

Source Address: 0.0.0.0

Destination Address: 255.255.255.255

13. What is the value in the transaction ID field of this DHCP Request message? Does it match the transaction IDs of the earlier Discover and Offer messages?

Transaction ID: 0x051b2d6b

Yes, its Transaction ID matches the discover message's & offer message's Transaction ID which equals 0x051b2d6b

That confirms it's the same DHCP session

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

> Frame 76: Packet, 360 bytes on wire (2880 bits), 360 bytes captured (2880 bits) on interface \Device\NPF_{A4CD95BD-AF85-45B8-A021-3F31B0249F78}, id 0

> Ethernet II, Src: Intel_2c:9c:b9 (90:09:df:2c:9c:b9), Dst: Broadcast (ff:ff:ff:ff:ff:ff)

> Internet Protocol Version 4, Src: 0.0.0.0, Dst: 255.255.255.255

> User Datagram Protocol, Src Port: 68, Dst Port: 67

> Dynamic Host Configuration Protocol (Request)

Message type: Boot Request (1)

Hardware type: Ethernet (0x01)

Hardware address length: 6

Hops: 0

Transaction ID: 0x051b2d6b

Seconds elapsed: 0

14. Now inspect the options field in the DHCP Discover message and take a close look at the “Parameter Request List”. The DHCP RFC notes that “The client can inform the server which configuration parameters the client is interested in by including the 'parameter request list' option. The data portion of this option explicitly lists the options requested by tag number.” What differences do you see between the entries in the ‘parameter request list’ option in this Request message and the same list option in the earlier Discover message?

In this trace, the Parameter Request List in the DHCP Request message is identical to the list in the earlier DHCP Discover message.

Parameter Request List in the DHCP Discover message:

No.	Time	Source	Destination	Protocol	Length	Info
69	7.559384	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover - Transaction ID 0x51b2d6b
75	9.641074	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer - Transaction ID 0x51b2d6b
76	9.644300	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request - Transaction ID 0x51b2d6b
78	9.844768	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK - Transaction ID 0x51b2d6b

Client IP address: 0.0.0.0
Your (client) IP address: 0.0.0.0
Next server IP address: 0.0.0.0
Relay agent IP address: 0.0.0.0
Client MAC address: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)
Client hardware address padding: 00000000000000000000
Server host name not given
Boot file name not given
Magic cookie: DHCP

- > Option: (53) DHCP Message Type (Discover)
- > Option: (61) Client identifier
- > Option: (50) Requested IP Address (192.168.1.10)
- > Option: (12) Host Name
- > Option: (60) Vendor class identifier
- ✓ Option: (55) Parameter Request List
 - Length: 14
 - Parameter Request List Item: (1) Subnet Mask
 - Parameter Request List Item: (3) Router
 - Parameter Request List Item: (6) Domain Name Server
 - Parameter Request List Item: (15) Domain Name
 - Parameter Request List Item: (31) Perform Router Discover
 - Parameter Request List Item: (33) Static Route
 - Parameter Request List Item: (43) Vendor-Specific Information
 - Parameter Request List Item: (44) NetBIOS over TCP/IP Name Server
 - Parameter Request List Item: (46) NetBIOS over TCP/IP Node Type
 - Parameter Request List Item: (47) NetBIOS over TCP/IP Scope
 - Parameter Request List Item: (119) Domain Search
 - Parameter Request List Item: (121) Classless Static Route
 - Parameter Request List Item: (249) Private/Classless Static Route (Microsoft)
 - Parameter Request List Item: (252) Private/Proxy autodiscovery
- > Option: (255) End

Parameter Request List in the DHCP Request message:

```

v Option: (55) Parameter Request List
  Length: 14
  Parameter Request List Item: (1) Subnet Mask
  Parameter Request List Item: (3) Router
  Parameter Request List Item: (6) Domain Name Server
  Parameter Request List Item: (15) Domain Name
  Parameter Request List Item: (31) Perform Router Discover
  Parameter Request List Item: (33) Static Route
  Parameter Request List Item: (43) Vendor-Specific Information
  Parameter Request List Item: (44) NetBIOS over TCP/IP Name Server
  Parameter Request List Item: (46) NetBIOS over TCP/IP Node Type
  Parameter Request List Item: (47) NetBIOS over TCP/IP Scope
  Parameter Request List Item: (119) Domain Search
  Parameter Request List Item: (121) Classless Static Route
  Parameter Request List Item: (249) Private/Classless Static Route (Microsoft)
  Parameter Request List Item: (252) Private/Proxy autodiscovery
> Option: (255) End
```

15. What is the source IP address in the IP datagram containing this ACK message? Is there anything special about this address? Explain.

192.168.1.1

Yes, there is something special as this is the DHCP server IP offering the IP address.

No.	Time	Source	Destination	Protocol	Length	Info
128	5.438150	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover
154	7.579455	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer
155	7.583112	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request
166	7.661916	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK

> Frame 166: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface

> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)

> Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255

0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 310
Identification: 0x0000 (0)
> 000. = Flags: 0x0
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 64
Protocol: UDP (17)
Header Checksum: 0xb80e [validation disabled]
[Header checksum status: Unverified]
Source Address: 192.168.1.1
Destination Address: 255.255.255.255

16. What is the destination IP address used in the datagram containing this ACK message. Is there anything special about this address? Explain.

255.255.255.255

Yes, there is something special as client may still not have IP configured at ACK time the Server broadcasts the offer

No.	Time	Source	Destination	Protocol	Length	Info
128	5.438150	0.0.0.0	255.255.255.255	DHCP	342	DHCP Discover
154	7.579455	192.168.1.1	255.255.255.255	DHCP	324	DHCP Offer
155	7.583112	0.0.0.0	255.255.255.255	DHCP	360	DHCP Request
166	7.661916	192.168.1.1	255.255.255.255	DHCP	324	DHCP ACK

> Frame 166: Packet, 324 bytes on wire (2592 bits), 324 bytes captured (2592 bits) on interface

> Ethernet II, Src: zte_50:17:20 (9c:e9:1c:50:17:20), Dst: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)

> Internet Protocol Version 4, Src: 192.168.1.1, Dst: 255.255.255.255

0100 = Version: 4
.... 0101 = Header Length: 20 bytes (5)
> Differentiated Services Field: 0x00 (DSCP: CS0, ECN: Not-ECT)
Total Length: 310
Identification: 0x0000 (0)
> 000. = Flags: 0x0
...0 0000 0000 0000 = Fragment Offset: 0
Time to Live: 64
Protocol: UDP (17)
Header Checksum: 0xb80e [validation disabled]
[Header checksum status: Unverified]
Source Address: 192.168.1.1
Destination Address: 255.255.255.255

17. What is the name of the field in the DHCP ACK message (as indicated in the Wireshark window) that contains the assigned client IP address?

Your (client) IP address

also called yiaddr

> Bootp flags: 0x0000 (Unicast)

Client IP address: 0.0.0.0

Your (client) IP address: 192.168.1.12

Next server IP address: 0.0.0.0

Relay agent IP address: 0.0.0.0

Client MAC address: Intel_2c:9c:b9 (90:09:df:2c:9c:b9)

18. For how long a time (the so-called “lease time”) has the DHCP server assigned this IP address to the client?

Lease Time: 1 day (86400 seconds)

```
> Option: (53) DHCP Message Type (ACK)
> Option: (1) Subnet Mask (255.255.255.0)
> Option: (3) Router
> Option: (6) Domain Name Server
> Option: (54) DHCP Server Identifier (192.168.1.1)
✓ Option: (51) IP Address Lease Time
    Length: 4
    IP Address Lease Time: 1 day (86400)
> Option: (255) End
```

19. What is the IP address (returned by the DHCP server to the DHCP client in this DHCP ACK message) of the first-hop router on the default path from the client to the rest of the Internet?

IP Address: 192.168.1.1

```
> Option: (53) DHCP Message Type (ACK)
> Option: (1) Subnet Mask (255.255.255.0)
✓ Option: (3) Router
    Length: 4
    Router: 192.168.1.1
```