

# Loading Gold Layer AS Views

```
/*
=====
DDL Script: Create Gold Views
=====
Script Purpose:
    This script creates views for the Gold layer in the data warehouse.
    The Gold layer represents the final dimension and fact tables (Star Schema)

    Each view performs transformations and combines data from the Silver layer
    to produce a clean, enriched, and business-ready dataset.

Usage:
    - These views can be queried directly for analytics and reporting.
=====
*/

-- =====
-- Create Dimension: gold.dim_customers
-- =====
IF OBJECT_ID('gold.dim_customers', 'V') IS NOT NULL
    DROP VIEW gold.dim_customers;
GO

CREATE VIEW gold.dim_customers AS
SELECT
    ROW_NUMBER() OVER (ORDER BY cst_id) AS customer_key, -- Surrogate key
    ci.cst_id AS customer_id,
    ci.cst_key AS customer_number,
    ci.cst_firstname AS first_name,
    ci.cst_lastname AS last_name,
    la.cntry AS country,
    ci.cst_marital_status AS marital_status,
    CASE
        WHEN ci.cst_gndr != 'n/a' THEN ci.cst_gndr -- CRM is the primary source for
gender
        ELSE COALESCE(ca.gen, 'n/a') -- Fallback to ERP data
    END AS gender,
    ca.bdate AS birthdate,
    ci.cst_create_date AS create_date
FROM silver.crm_cust_info ci
LEFT JOIN silver.erp_cust_az12 ca
    ON ci.cst_key = ca.cid
LEFT JOIN silver.erp_loc_a101 la
    ON ci.cst_key = la.cid;
GO

-- =====
-- Create Dimension: gold.dim_products
-- =====
IF OBJECT_ID('gold.dim_products', 'V') IS NOT NULL
    DROP VIEW gold.dim_products;
GO

CREATE VIEW gold.dim_products AS
SELECT
    ROW_NUMBER() OVER (ORDER BY pn.prd_start_dt, pn.prd_key) AS product_key, --
Surrogate key
    pn.prd_id AS product_id,
```

```

        pn.prđ_key      AS product_number,
        pn.prđ_nm       AS product_name,
        pn.cat_id       AS category_id,
        pc.cat          AS category,
        pc.subcat       AS subcategory,
        pc.maintenance  AS maintenance,
        pn.prđ_cost     AS cost,
        pn.prđ_line     AS product_line,
        pn.prđ_start_dt AS start_date
FROM silver.crm_prđ_info pn
LEFT JOIN silver.erp_px_cat_glv2 pc
    ON pn.cat_id = pc.id
WHERE pn.prđ_end_dt IS NULL; -- Filter out all historical data
GO

```

```

-- =====
-- Create Fact Table: gold.fact_sales
-- =====
IF OBJECT_ID('gold.fact_sales', 'V') IS NOT NULL
    DROP VIEW gold.fact_sales;
GO

```

```

CREATE VIEW gold.fact_sales AS
SELECT
    sd.sls_ord_num AS order_number,
    pr.product_key AS product_key,
    cu.customer_key AS customer_key,
    sd.sls_order_dt AS order_date,
    sd.sls_ship_dt AS shipping_date,
    sd.sls_due_dt AS due_date,
    sd.sls_sales AS sales_amount,
    sd.sls_quantity AS quantity,
    sd.sls_price AS price
FROM silver.crm_sales_details sd
LEFT JOIN gold.dim_products pr
    ON sd.sls_prđ_key = pr.product_number
LEFT JOIN gold.dim_customers cu
    ON sd.sls_cust_id = cu.customer_id;
GO

```

```

-- delete views
DROP VIEW IF EXISTS gold.dim_customers;
GO

DROP VIEW IF EXISTS gold.dim_products;
GO

DROP VIEW IF EXISTS gold.fact_sales;
GO

```