Assignment 8

Name: youssef mohamed yasser ID:

2305038

1. To socksify a web browser, you configure the browser to send its traffic through a SOCKS proxy server. This is usually done by going to the browser's network or proxy settings and entering the SOCKS proxy IP address and port number. Once configured, all browser traffic is routed securely through the SOCKS proxy.

2. Public proxy servers provide services such as hiding the user's IP address, enabling anonymous browsing, bypassing geographic restrictions, filtering content, caching web data to improve speed, and adding a layer of security by acting as intermediaries between the user and the destination server.

3. Privoxy can be installed by downloading it from the official repository of your operating system or from the Privoxy website. After installation, you edit the 'config' file—usually located in the Privoxy installation directory—to set parameters such as listen-address, allowed ports, and filtering rules. Once configured, you start the Privoxy service and set your browser to use Privoxy as an HTTP proxy.

4. To experiment with Tor, install the Tor Browser from the official Tor Project website. After launching the browser, open the 'Tor Network Settings' and choose to use a bridge. You can request a bridge from the Tor website or use built-in bridge options. After adding the bridge, Tor will route your traffic through bridge relays, helping bypass censorship and enabling anonymous communication.
Comment



1) update.php



2) delete.php



3) The vuln. endpoint



car_id: 1 - Model: Toyota Corolla - Used: 1 - Date: 2023-05-10 - Price: 15000.00



car_id: 1 - Model: Toyota Corolla - Used: 1 - Date: 2023-05-10 - Price: 15000.00
car_id: 2 - Model: Honda Civic - Used: 0 - Date: 2024-01-20 - Price: 20000.00
car_id: 3 - Model: BMW X5 - Used: 1 - Date: 2022-11-03 - Price: 45000.00
car_id: 4 - Model: Ford Focus - Used: 1 - Date: 2021-07-18 - Price: 10000.00

In the photo

The attack was successful by inserting (car_id=1OR1=1) aka Boolean flip while the code

show_vuln.php 4

show_vuln.php > ...

```php
<?php
include 'db.php';    Replace "include" with "include_once".

$car_id = $_GET['car_id'];  // ❌ UNSAFE – vulnerable to SQL injection

// Vulnerable query (no prepared statement)
$sql = "SELECT * FROM cars WHERE car_id = $car_id";

$result = $conn->query($sql);

if ($result->num_rows > 0) {
    while($row = $result->fetch_assoc()) {
        echo "car_id: " . $row["car_id"] .    Remove the useless trailing whitespaces at the end of this line.
        " - Model: " . $row["model"] .
        " - Used: " . $row["used"] .
        " - Date: " . $row["sale_date"] .
        " - Price: " . $row["price"] . "<br>";
    }
} else {
    echo "No results";
}
$conn->close();
?>    Remove this closing tag "?>".
```

The answer:

SELECT * FROM users WHERE username = ? AND password = ? ;