

ABC PHARMACY - SALESFORCE ENTRY ASSESSMENT

ABC Pharmacy REST API

Reference for the Ionic application developers

VERSION	1.0
DATE	13 September 2026
AUTHOR	Youssef Maged — prepared for Cloudastick Systems
STATUS	Issued

Contents

1. 1. Base URL

2. 2. Authentication

3. 3. The response envelope

4. 4. Error codes

5. 5. Endpoints

5.1 GET /abc/v1/products

5.2 POST /abc/v1/carts

5.3 GET /abc/v1/carts/{cartId}

5.4 POST /abc/v1/carts/{cartId}/items

5.5 POST /abc/v1/carts/{cartId}/checkout

6. 6. Notes for the client

Everything the Ionic app needs to browse the ABC catalogue and build a shopping cart. A Postman collection covering every call in this document is in `postman/`.

1. Base URL

```
https://orgfarm-ad027e59fe-dev-ed.develop.my.salesforce.com/services/apexrest
```

All paths below are relative to that. Use **your org's My Domain host** — not `login.salesforce.com`, which will not serve these endpoints.

Every request and response is `application/json; charset=UTF-8`.

2. Authentication

The API is registered as an External Client App called `abc_Ionic_App` using the OAuth 2.0 **client credentials** flow. Request a token, then send it as a bearer token.

Request

```
POST /services/oauth2/token HTTP/1.1
Host: orgfarm-ad027e59fe-dev-ed.develop.my.salesforce.com
Content-Type: application/x-www-form-urlencoded

grant_type=client_credentials
&client_id=<consumer key>
&client_secret=<consumer secret>
```

Response

```
{
  "access_token": "00Dg8000...!AQEAQJ3x...",
  "instance_url": "https://orgfarm-ad027e59fe-dev-ed.develop.my.salesforce.com",
  "token_type": "Bearer",
  "issued_at": "1789301234567"
}
```

Use it

```
GET /services/apexrest/abc/v1/products HTTP/1.1
Authorization: Bearer 00Dg8000...!AQEAQJ3x...
```

Tokens expire according to the org's session policy. Treat a `401` as "fetch a new token and retry once".

Production note. Client credentials authenticates the *application*, not the person using it: every order created this way is attributed to one shared integration user. It is used here because it keeps a reviewer's setup to a single call. A production Ionic app should use **Authorization Code with PKCE**, so each customer acts as themselves, or route calls through a backend that holds the secret. Never ship a client secret inside a mobile binary.

3. The response envelope

Every response uses the same four keys, whether it succeeded or failed. Parse one shape; never branch on the status code to find the payload.

```
{
  "success": true,
  "data": { },
  "errors": [],
  "requestId": "4Zx9KpQ2mN"
}
```

Key	Type	Notes
success	boolean	
data	object or null	Always present. null on failure.
errors	array	Always present. Empty on success.
errors[].code	string	Stable machine-readable code — branch on this, not on the message.
errors[].message	string	Human readable. Wording may change; the code will not.
errors[].field	string	Present only when one request field is at fault.
requestId	string	Correlation id, also stamped on every server-side log entry for this request.

Always log requestId . Quoting it in a support request lets the Salesforce team find the exact server-side log rows for that call.

A failure looks like this:

```
{
  "success": false,
  "data": null,
  "errors": [
    {
      "code": "INSUFFICIENT_STOCK",
      "message": "Only 2 unit(s) of \"Fingertip Pulse Oximeter\" are in stock; the cart would hold 5.",
      "field": "quantity"
    }
  ],
  "requestId": "4Zx9KpQ2mN"
}
```

4. Error codes

Code	HT TP	Meaning	What the app should do
<code>INVALID_INPUT</code>	400	A required value is missing, or a query parameter is not the right type.	Fix the request. Check <code>field</code> .
<code>MALFORMED_JSON</code>	400	The body is not valid JSON, has the wrong shape, or contains an attribute this endpoint does not define.	Fix the request. Usually a typo in a field name.
<code>VALIDATION_ERROR</code>	400	The request parsed, but a business rule rejected the values.	Show the message; check <code>field</code> .
<code>CART_NOT_FOUND</code>	404	No cart with that id.	Start a new cart.
<code>PRODUCT_NOT_FOUND</code>	404	No such product, or it is not sellable.	Refresh the catalogue.
<code>ROUTE_NOT_FOUND</code>	404	No endpoint at that path.	A client bug — the message lists the valid routes.
<code>CART_NOT_EDITABLE</code>	409	The cart has been checked out and its contents are frozen.	Start a new cart.
<code>INSUFFICIENT_STOCK</code>	409	The warehouse cannot supply that many units.	Show the message; offer the available quantity.
<code>INTERNAL_ERROR</code>	500	Something went wrong server-side.	Retry once; if it persists, report the <code>requestId</code> .

`INTERNAL_ERROR` never carries detail — the exception, message and stack trace are recorded server-side against the same `requestId`.

5. Endpoints

5.1 `GET /abc/v1/products`

The catalogue.

Query parameters — all optional.

Name	Type	Default	Notes
<code>search</code>	string	—	Substring, case-insensitive, matched against product name and product code.
<code>category</code>	string	—	One of <code>Medicine</code> , <code>Supplement</code> , <code>Personal Care</code> , <code>Medical Device</code> .
<code>includeOutOfStock</code>	boolean	<code>false</code>	Only <code>true</code> or <code>false</code> ; anything else is a 400.
<code>limit</code>	integer	<code>50</code>	1–200. Larger values are clamped to 200.
<code>offset</code>	integer	<code>0</code>	Rows to skip. Capped at 2000.

Example

```
GET /services/apexrest/abc/v1/products?category=Medicine&search=para&limit=2
Authorization: Bearer <token>
```

```
{
  "success": true,
  "data": {
    "items": [
      {
        "id": "01tg8000004xYzAAAU",
        "name": "Paracetamol 500mg Tablets (20)",
        "productCode": "ABC-MED-001",
        "description": "Analgesic and antipyretic tablets, blister pack of 20.",
        "category": "Medicine",
        "requiresPrescription": false,
        "stockQuantity": 500,
        "unitPrice": 12.50,
        "currencyIsoCode": "USD"
      }
    ],
    "count": 1,
    "limit": 2,
    "offset": 0
  },
  "errors": [],
  "requestId": "4Zx9KpQ2mN"
}
```

`count` is the number of items in **this page**, not the size of the catalogue. Page until a response returns fewer than `limit` items.

A product is only listed when it is active and has an active price in the standard price book. Out-of-stock products are hidden unless `includeOutOfStock=true`; use that on a "notify me" screen rather than the main list.

5.2 `POST /abc/v1/carts`

Opens a cart. A cart is a Draft order — it is a real record from the moment it is created, so the pharmacy can see abandoned carts.

The customer is matched by **email**. If a contact with that address exists it is reused; otherwise an account named `"First Last"` and its contact are created.

Body

Field	Type	Required	Notes
<code>customer.email</code>	string	yes	Must be a valid address. This is the customer's identity.
<code>customer.lastName</code>	string	yes	
<code>customer.firstName</code>	string	no	
<code>customer.phone</code>	string	no	
<code>items</code>	array	no	Up to 100 entries. Repeats of the same product are merged.
<code>items[].productId</code>	string	yes	Salesforce <code>Product2</code> id (18 characters, starts <code>01t</code>).
<code>items[].quantity</code>	number	yes	Whole number, 1–9999.

```
POST /services/apexrest/abc/v1/carts
Authorization: Bearer <token>
Content-Type: application/json

{
  "customer": {
    "email": "mona.hassan@example.com",
    "firstName": "Mona",
    "lastName": "Hassan",
    "phone": "+20 100 111 2222"
  },
  "items": [
    { "productId": "01tg8000004xYzAAAU", "quantity": 2 }
  ]
}
```

201 Created

```
{
  "success": true,
  "data": {
    "cartId": "801g8000003xAbCAAU",
    "orderNumber": "00000107",
    "status": "Draft",
    "customer": {
      "accountId": "001g8000012pQrSAAU",
      "contactId": "003g8000018tUvWAAQ",
      "email": "mona.hassan@example.com",
      "name": "Mona Hassan"
    },
    "items": [
      {
        "itemId": "802g8000002mNoPAAU",
        "productId": "01tg8000004xYzAAAAU",
        "productName": "Paracetamol 500mg Tablets (20)",
        "quantity": 2,
        "unitPrice": 12.50,
        "totalPrice": 25.00
      }
    ],
    "totalAmount": 25.00,
    "createdDate": "2026-09-13T05:48:11.000Z"
  },
  "errors": [],
  "requestId": "7Kp2QmX4Zb"
}
```

Every cart response uses this same `CartDto` shape.

Failures: `INVALID_INPUT` (missing or invalid email, missing last name), `PRODUCT_NOT_FOUND`, `VALIDATION_ERROR` (bad quantity), `INSUFFICIENT_STOCK`, `MALFORMED_JSON`.

5.3 `GET /abc/v1/carts/{cartId}`

Reads a cart. Returns 200 with the same `CartDto`.

```
GET /services/apexrest/abc/v1/carts/801g8000003xAbCAAU
Authorization: Bearer <token>
```

Failures: `CART_NOT_FOUND` (unknown, malformed, or an id belonging to another object).

5.4 `POST /abc/v1/carts/{cartId}/items`

Adds a product. If the product is already in the cart the existing line's quantity is increased — a cart always holds one line per product, so the app does not have to check first.

Body

Field	Type	Required	Notes
<code>productId</code>	string	yes	
<code>quantity</code>	number	yes	Whole number, 1–9999. This is the amount to add .

```
POST /services/apexrest/abc/v1/carts/801g80000003xAbCAAU/items
Authorization: Bearer <token>
Content-Type: application/json

{ "productId": "01tg80000004xYzAAAU", "quantity": 3 }
```

Returns **200** with the updated cart.

Stock is checked against what the cart would hold **after** the merge, so adding 2 then 4 of a product with 5 in stock fails on the second call.

Failures: `CART_NOT_FOUND`, `PRODUCT_NOT_FOUND`, `VALIDATION_ERROR`, `INSUFFICIENT_STOCK`, `CART_NOT_EDITABLE`, `MALFORMED_JSON`.

5.5 `POST /abc/v1/carts/{cartId}/checkout`

Places the order: the same record moves from `Draft` to `Activated`, and its order date is set to today. No body; anything sent is ignored, so a retry with a stale payload cannot change the order.

```
POST /services/apexrest/abc/v1/carts/801g80000003xAbCAAU/checkout
Authorization: Bearer <token>
```

Returns **200** with the cart, now `"status": "Activated"`.

After checkout the order is frozen — further `items` calls return `CART_NOT_EDITABLE`. From here the warehouse moves it to `In delivery` and then `Delivered`.

Failures: `CART_NOT_FOUND`, `CART_NOT_EDITABLE` (already checked out), `VALIDATION_ERROR` (the cart is empty).

6. Notes for the client

Strict bodies. Request bodies are parsed strictly: an attribute that is not part of the documented body is rejected with `MALFORMED_JSON`. This is deliberate — a misspelled field fails loudly at the call site instead of being read as absent and producing a confusing error later. Send exactly the fields documented above.

Ids. `cartId` is a Salesforce Order id (starts `801`), `productId` a `Product2` id (starts `01t`), `itemId` an `OrderItem` id (starts `802`). Treat them as opaque 18-character strings.

Quantities are whole numbers. `1.5` is rejected with `VALIDATION_ERROR`.

Money is returned as a JSON number with two decimal places, in the org's currency, given per product as `currencyIsoCode`.

Recommended flow

GET /abc/v1/products?limit=50&offset=0	browse, page as the user scrolls
POST /abc/v1/carts	on first add – keep the cartId
POST /abc/v1/carts/{cartId}/items	each subsequent add
GET /abc/v1/carts/{cartId}	to re-render the cart screen
POST /abc/v1/carts/{cartId}/checkout	place the order

Keep `cartId` for the life of the session. A cart left in Draft stays valid indefinitely and can be resumed.

Retries. `GET` calls are safe to retry. `POST /items` is **not** idempotent — retrying adds the quantity again — so retry it only after a network failure with no response, and re-read the cart afterwards to confirm. Checkout is safe to retry: a second call returns `CART_NOT_EDITABLE`, which tells you the first one succeeded.