DRAWING NO. Q36215-JFC2T4-02-PR-PID-00081

GENERAL NOTES:
1. CHANGES INDICATED UNDER ALL REVISION CLOUDS PERTAINS TO JFC 2&4 TSP ADAPTATION.
2. THE FACILITIES SHOWN IN THIS DRAWING ARE ENTIRELY NEW.


507A-PI-081
2050-DUCT-507A-T10-FRP
VENT
507A-PI-021
FROM 507AAS11
2200 - DUCT - 507A - T04 - FRP
10 BARG STEAM
507A-PI-045
FROM HEADER
20 - S10 - 507A - T91 - BB3 - HC
2050 - DUCT - 507A - T05 - FRP
VENT
507A-PI-030
507A-RB-023
100 - LL - 507A - T31 - BG1 - PP
100 - LL - 507A - T32 - BG1 - PP
100 - LL - 507A - T33 - BG1 - PP
100 - LL - 507A - T34 - BG1 - PP
100 - LL - 507A - T35 - BG1 - PP
100 - LL - 507A - T36 - BG1 - PP
507AAD06
SCRUBBER LIQUOR
507A-PI-032
FROM 507AAR02
DEFOAMER
507A-PI-041
FROM 507AAP06
25 - AM - 507A - T19 - BD2
SIGNAL
507A-PI-082
FROM DI-981
10 BARG STEAM
507A-PI-045
FROM HEADER
20 - S10 - 507A - T23 - BD2 - HC
20 - S10 - 507A -T20 - BB3 - HC
SCRUBBER LIQUOR
507A-PI-082
TO 507AAP12
507AKP12
600 - LL - 507A - T24 - BG1 - PP
500 - LL - 507A - T25 - BG1 - PP
ROD OUT
SCRUBBER LIQUOR
507A-PI-082
FROM 507AAP12/KP12
400 - LL - 507A - T29 - BG1 - PP
100 - LL - 507A - T27 - BG1 - PP
200 - LL - 507A - T28 - BG1 - PP
100 - LL - 507A - T26 - BG1 - PP
SELECTOR
507AAD06
DRYER
PRESCRUBBER
DAP/TSP 507A
PIPING & INSTRUMENTATION DIAGRAM
DRYER PRESCRUBBER
NONE
QU916204
507A-PI-081
2

NOTES:

1. LEGENDS AND ABBREVIATIONS REFER TO DWG. 500-PI-001/002/003.
2. ALL SCRUBBER LIQUOR AND PHOSPHORIC ACID PIPING TO BE FLANGED AT FITTING AND AT 6M MAX. INTERVALS.
3. ALL CLEAN-OUTS AND ACCESS HATCHES TO BE ACCESSIBLE FROM A PLATFORM.
4. PI SHALL BE VISIBLE FROM BUTTERFLY VALVE AND BOTH SHALL BE ACCESSIBLE FROM PLATFORM.
5. FLANGED ELBOW DROP SPOOL FOR REMOVAL OF EACH SPRAY NOZZLE (TYPICAL 8 PLACES).
6. ATTACH (BLACK ON YELLOW) SIGN TO SPRAY NOZZLE INSERT PIPE INDICATING "CAUTION HOT PIPE".
7. SCRUBBER VENDOR TO SUPPLY SPRAY INSERT PIPE AND TACK WELD SPRAY NOZZLE TO INSERT PIPE.
8. 100MM SPRAY BRANCHES SHALL BE MINIMUM LENGTH FROM 150MM OR 250MM HEADERS.
9. SPRAY INSERT/ NOZZLES C1 D1 THRU C6 D6 ARE AT SAME ELEVATION.
10. INSTRUMENTS ACCESSIBLE FROM PLATFORM.
11. TWIN HAND WHEEL.
12. COUNTERCURRENT SPRAY ORIENTATION WILL BE FINALIZED DURING START-UP.
13. INSTRUMENT TAG NUMBERS AND INTERLOCKS SHALL BE PREFIXED BY THE UNIT AND UNIT SUBDIVISION (I.E.507A) UNLESS SPECIFIED OTHERWISE.
14. ROUTE PIPING WITH MOST DIRECT ROUTING WITH MAXIMUM SLOPE AND MINIMUM ELBOWS. LINE SHALL DRAIN TO ORIGIN AND DESTINATION.
15. LEVEL INSTRUMENTATION NOZZLE P1 & P2 ARE AT SAME ELEVATION BELOW LIQUID LEVEL INSTRUMENT NOZZLE S1 & S2 ARE AT SAME ELEVATION.
16. HV PORT ARRANGEMENT: NORMAL (FAIL OPEN)= 1-3 AND STEAM PURGE (FAIL CLOSED)= 2-3.
17. REMOVABLE SPOOL FOR CLEANOUT, EXTREMITY OF SPOOL FROM HV-511, HV-514, TO (2) SETS OF BREAKOUT FLANGES AND INCLUDES SAMPLE VALVES P-5-1. (SEE P&ID 507A - PI - 029).
18. DELETED
19. EQUIPMENT TO BE LOCATED IN TILED/CURBED AREA WHICH IS SLOPED TOWARD THE SUMP.
20. FOR HYDRO VENT AND DRAIN REFER PIPING ISOMETRIC.
21. ALL PIPING SM ITEMS SHALL BE PREFIXED BY THE UNIT NUMBER.
22. WASH HEADERS END WITH SPRAY NOZZLES AND DIRECTED AT THE DAMPER.
23. FLANGED ELBOW DROP SPOOL FOR REMOVAL OF EACH SPRAY NOZZLES (TYPICAL 8 PLACES).
24. ATTACH (BLACK ON YELLOW) SIGN TO SPRAY NOZZLE INSERT PIPE INDICATING ``CAUTION HOT PIPE".
25. INSERT SPRAY PIPE TO BE SUPPLIED WITH PIPING AND SPRAYS (SP-12) TO BE TACK WELDED TO INSERT PIPE.
26. REFER TO DETAIL 'A'.
27. TEMPERATURE INSTRUMENT SHOULD SENSE THE BOTTOM OF THE PIPE TO MEASURE THE WASH WATER TEMPERATURE.

INSTRUMENT NUMBERING

LOOP NUMBERS RESERVED FOR THIS P&ID: 960-979.
LOOP NUMBERS NOT USED: 969 - 979

DETAIL 'A':

NOTE (25)(24)(23)

HOLDS:
1. CONTROL VALVE AND BYPASS SIZES.

This drawing was generated using AutoCAD and must not be altered manually. Do not Scale.

REFERENCE DRAWINGS Ref Drawing NO.	DESCRIPTION

REV	DESCRIPTION	BY	CKD	DATE	APPD	APPD
A	ISSUED FOR SQUAD CHECK	S.VIS	A.DAS	14 MAY 2024	Y.ELA	M.BOU
B	ISSUED FOR REVIEW (IFR)	S.VIS	A.DAS	31 MAY 2024	Y.ELA	M.BOU
C	ISSUED FOR DESIGN (IFD)	S.VIS	A.DAS	9 AUG 2024	Y.ELA	M.BOU

This drawing is the property of JESA Technologies. Neither this document nor any information herein shall be copied or reproduced in any manner, loaned or otherwise disposed of, or used for any purpose whatsoever without the prior written permission of JESA Technologies. If this document is loaned by or with the authority of JESA Technologies, the borrower in consideration of such loan, agrees to the foregoing conditions.

(seal)

APPROVED
ENGINEER DATE
APPROVED
DISCIPLINE APPROVAL DATE
APPROVED
PROJECT APPROVAL DATE

Proj. Approval: M.BOUZIANI
Discipline Approval: Y.EL ARFAOUI
Checked: A. DAS
Originator: S. VISHWAKARMA
Date: 9 AUG 2024
CAD File: Q36215-JFC2T4-02-PR-PID-00081

Groupe OCP JESA

PIPING & INSTRUMENTATION DIAGRAM
TSP ADAPTATION JFC 2&4
TSP PLANT 507A
DRYER PRESCRUBBER

SCALE	ORDER NO.	DRAWING NO.	REV.
NONE	Q36215	Q36215-JFC2T4-02-PR-PID-00081	C