## Report 1

# Jun Huang Gina Cody School of Engineering and Computer Science Concordia University Email: youyinnn@foxmail.com

Abstract—The abstract goes here.

Index Terms—1-bit Adder, Hybird Adder, CMOS Technology,

III. DESIGN B

IV. DESIGN C

V. DESIGN D

VI. DISCUSSION

VII. CONCLUSION

REFERENCES

#### I. INTRODUCTION

An XOR-XNOR-based hybrid full adder design has been proposed[1] which uses an XOR-XNOR module combined with the carry-generation module and the sum-generation module. As the designers discussed, it is a scalable and full-swing FA with some performance improvements compared with several existing state-of-the-art FAs.

in section 2, xxx will be discussed...

#### II. XOR-XNOR-BASED HYBRID FULL ADDER[1]

#### A. Background

The proposer of the design fist discussed how important ..

### B. Design

This FA design contains three modules to perform a 1-bit full adder operation. Firstly, an XOR-XNOR circuit will take original inputs A and B as its input and produce two signals, one is from the XNOR gate marked as  $S_{xnor\_out}$  and the other is from the XOR gate marked as  $S_{xor\_out}$ . Then, a TG-based circuit as the second module will take both signal and the input carry  $C_{in}$  to calculate the Sum while a third module will then use the  $C_{in}$  along with A and B and signals  $S_{xnor\_out}$  and  $S_{xor\_out}$  to generate the carry  $C_{out}$ .

Fig. 1 presents the block diagram of the design.




Fig. 1. Block diagram of the XOR-XNOR-based FA

#### 1) XOR-XNOR Circuit Design:

 M. Hasan, M. S. Hussain, M. Hossain, M. Hasan, H. U. Zaman, and S. Islam, "A high-speed and scalable xor-xnor-based hybrid full adder design," *Computers and Electrical Engineering*, vol. 93, 2021.