

# **HSG5 Analysis Framework for Run 2**

Kristian Gregersen

# Outline

- How the code is organised
- Calibration/Analysis tools in the framework
- Contents of the output file
- Technical details on I/O structure
- Configuration and running
- Performance numbers
- Mailing list and links

# Framework layout

- Based on **RootCore** (a C++ compilation framework which depends on ROOT).
- Uses **EventLoop** (EL) and **SampleHandler**.
- Currently there are 7 “RootCore” packages :

**CxAODMaker**

Contains the main code for processing the input xAOD files, applying the calibration tools (CP tools), and writing the output CxAOD (C for Calibrated).

**CxAODTools**

Contains tools that are shared outside of the main CxAODMaker work-flow, such as object and event selection.

**FrameworkExe**

Contains the code for the executables for running CxAODMaker, along with any associated configuration files.

**FrameworkSub**

Contains files related to defining datasets and information for tracking processing.

**CxAODReader**

Contains code to read CxAOD using the xAOD EDM. Implements plotting style used in HSG5.

**TupleMaker**


Contains example code for producing a compact flat TTree based tuple.

**TupleReader**

Contains the common TTree definition and example code to read a compact flat TTree.


# Framework layout

- Based on **RootCore** (a C++ compilation framework which depends on ROOT).
- Uses **EventLoop** (EL) and **SampleHandler**.
- Currently there are 7 “RootCore” packages :



Focus will be on these today

Work flow for processing (D)xAODs:



# CxAODMaker

- **List of Calibration/Analysis Tools in Framework**

- Jets :
  - JetCalibrationTool
  - JetCleaningTool
  - JERTool
  - JERSmearingTool
  - BTaggingEfficiencyTool
- Taus :
  - TauSmearingTool
  - TauSelectionTool
  - TauEfficiencyCorrectionsTool
- Photons :
  - EgammaCalibrationAndSmearingTool
  - AsgPhotonIsEMSelector
- Electrons :
  - EgammaCalibrationAndSmearingTool
  - AsgElectronLikelihoodTool
  - AsgElectronIsEMSelector
- Muons :
  - MuonCalibrationAndSmearingTool
  - MuonSelectionTool
  - MuonEfficiencyScaleFactors
- MET :
  - METRebuilder
- Overlap removal :
  - OverlapRemovalTool


# CxAODMaker

- **Contents of the output xAOD**

- We store as little as possible – which in practical terms implies a trade-off :
  - The output file is small and (fairly) well organised, without too many variables cluttering/creating confusion.
  - But, while developing the code, this will also result in important variables missing, and thus re-running of the code.
- For particle-type objects:
  - The 4-vector is always stored.
  - Other chosen quantities are explicitly added by hand (with 'decorators') and stored.  
(e.g. object scale factors, or flags which specify if an object passed some selection criteria).
- Event information:
  - Run number, event number, NVtx3Trks, MCEventWeight, ...
  - Eventually, also trigger information.
- Systematic variations are stored with the original collection name as “base” name and then the name of the variation appended to it (after 3 “\_”), so e.g “Muons\_\_\_\_Nominal” and “Muons\_\_\_\_someVariation”.

# CxAODMaker

## • Technical details on I/O structure



Calibration +  
Selection applied:  
Pass selection   
Fail selection

In this example, object 5  
doesn't pass the selection  
for nominal or any variation  
– it will not be stored!

### Summary:

- Shallow copies are made of the input (for nominal + systematic variations).
- These are calibrated and the object selection is applied.
- For the nominal output, new memory allocations are made based on selected objects (across variations).
- For the systematic variations, shallow copies are made of the nominal output.
- Properties are copied from calibrated shallow copies to output containers.

# CxAODMaker

- **Configuration**

- The configuration file is located here:

FrameworkExe/data/CxAODMaker-job.cfg

```

1 # This is a ConfigStore file, please see ConfigStore.cxx for info.
2
3 bool debug                = false
4
5 bool printObjectCounts    = false
6 bool printKnownVariations = false
7
8 bool applyObjectSelection = true
9 bool applyOverlapRemoval  = true
10
11 bool applyEventSelection  = true
12 string selectionName      = "1lep"
13 bool autoDetermineSelection = false
14
15 # note: container names can be commented out to disable their processing
16
17 string muonContainer       = Muons
18 string electronContainer   = ElectronCollection
19 # no taus in HIGGS5 derivations
20 #string tauContainer       = TauRecContainer
21 string photonContainer     = PhotonCollection
22 string jetContainer        = AntiKt4LCTopoJets
23 string jetAlgoName         = AntiKt4LCTopo
24 # JetUncertaintiesTool does not like AntiKt4TopoEM
25 #string jetSpectatorContainer = AntiKt4EMTopoJets
26 #string jetSpectatorAlgoName = AntiKt4TopoEM
27 string fatJetContainer     = CamKt12LCTopoJets
28 #string trackJetContainer   = AntiKt4ZTrackJets
29 string METContainer        = MET_Reffinal
30 string truthParticleContainer = TruthParticle
31 string truthVertexContainer = TruthVertex
32 string grl = $ROOTCOREBIN/data/CxAODMaker/data12_8TeV.periodAllYear_DetStatus-v61-pro14-02_DQDefects-00-01-00_PHYS_StandardGRL_All_Good.xml
33
34 # "Nominal" is always written
35 vector<string> variations = EG_SCALE ALL MUONS_SCALE MUONS_ID MUONS_MS
36 vector<string> weightVariations = MUONSFSYS
37 vector<string> variationsSymm = JetEResol
38 bool storeOriginal        = true

```

Note: By default the VHbb “1 lepton” selection is applied

Names of collections, used by MuonHandler, JetHandler,...

List of sys. variations



# TupleMaker

- Produces flat ntuples

- int, float and arrays
- An EventLoop algorithm, like AnalysisBase in CxAODMaker.
- Configured independent of CxAODMaker:

FrameworkExe/data/TupleMaker-job.cfg

```

Line
1 # This is a ConfigStore file, please see ConfigStore.cxx for info.
2
3 string TupleMaker.PhotonsIn      = PhotonCollection
4 string TupleMaker.MuonsIn        = Muons
5 string TupleMaker.ElectronsIn    = ElectronCollection
6 string TupleMaker.JetsIn         = AntiKt4LCTopoJets
7 string TupleMaker.FatJetsIn      = CamKt12LCTopoJets
8 string TupleMaker.MetIn          = MET_RefFinal
9 string TupleMaker.Label         = tuple
10
11 vector<string> TupleMaker.Variations = Original Nominal
12 string      TupleMaker.VariationMode = block
13 bool        TupleMaker.UseEventInfo = true

```

Names of collections (sys. variations are appended automatically)

List of sys. variations

- Run with : `hsg5frameworkTuple`
  - will run CxAODMaker followed by TupleMaker such that the output collections in TEvent from the CxAODMaker are read in by TupleMaker.
- The systematic variations can be written out in 3 different ways:
  - “file” : A separate file with one TTree for each variation
  - “tree” : One file with one TTree for each variation
  - “block” : One file with one tree where the variables have the variation appended to their name

# FrameworkExe

- The framework executables

- Contains the files that defines the “main()” methods which are compiled into executables
  - hsg5framework (runs CxAODMaker)
  - Hsg5frameworkTuple (runs CxAODMaker and TupleMaker in sequence)
  - Hsg5frameworkReader (runs CxAODMakerReader, which processes CxAODs)

- Configured in

FrameworkExe/data/framework-run.cfg

```

1 # This is a ConfigStore file, please see ConfigStore.cxx for info.
2
3 int maxEvents          = -1
4 string CxAODConfig      = data/FrameworkExe/CxAODMaker-job.cfg
5 string TupleConfig      = data/FrameworkExe/TupleMaker-job.cfg
6 string COMEnergy        = 13TeV
7
8 #####
9 # for grid only -> it is not affecting interactiv run
10 #####
11 # tag version
12 string vtag             = pl_141216
13 # test job
14 bool submit             = false
15 # exclude site
16 string excludedSite     = none
17 #string excludedSite    = ANALY_ARNES,ANALY_LUNARC,ANALY_SIGNET,ANALY_RAL_SL6,ANALY_BNL_SHORT,ANALY_DCSC,ANALY_NSC,ANALY_UIO
18 # lot of files per job
19 double nGBPerJob        = 8
20 double nFilesPerJob     = -1
21 # 1 file only per job
22 #double nGBPerJob       = -1
23 #double nFilesPerJob    = 1
24

```

Reads in the config files for CxAODMaker and TupleMaker from the previous 2 slides by default.

- Final note on runtime configuration:

- The steering file is distributed to all the Handlers in CxAODMaker, so modifying/adding configuration variables to a Handler is easy.

# Running CxAODMaker / TupleMaker

## Quick Start

For a quick setup of the framework please log into a clean lxplus session. Support for local machines is planned. Then you can copy&paste the following script to check out and compile the code:

```
# setup ATLAS environment
setupATLAS

# make some working direcorey
mkdir CxAODFramework
cd CxAODFramework/

# setup RootCore
rcSetup Base,2.0.23
# Note, from Base,2.0.16 and later there are a lot of compile time warnings concerning the boost lib
# which are due to a new compile flag in ROOT, -Wunused-local-typedefs

# check out CxAODFramework
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/CxAODMaker/trunk CxAODMaker
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/CxAODReader/trunk CxAODReader
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/CxAODTools/trunk CxAODTools
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/FrameworkExe/trunk FrameworkExe
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/FrameworkSub/trunk FrameworkSub
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/TupleMaker/trunk TupleMaker
svn co svn+ssh://svn.cern.ch/repos/atlasphys/Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework/TupleReader/trunk TupleReader

# scan packages and compile
rc find_packages
rc compile
```

A test job can be run with:

```
hsg5framework
```

# Performance

- **Sample specifics**
  - HIGG2D4 DxAOD (2 lepton filter),
  - 10000 ttbar events (2.3 Gb)  
(mc14\_8TeV.117050.PowhegPythia\_P2011C\_ttbar.merge.DAOD\_HIGG2D4.e1727\_s1933\_s1911\_r5591\_r5625\_p1784)
- **Reading/writing:**
  - ElectronCollection
  - Muons
  - AntiKt4LCTopoJets
  - CamKt12LCTopoJets
  - AntiKt4ZTrackJets
  - MET\_RefFinal
- **Configuration**
  - 10 systematic variations
  - VHbb “2 lepton” event selection
- **Processing time (CPU time):**
  - ~ 120 evt/sec
- **Disk space:**
  - Output CxAOD file size 3.5 Mb (reduction factor ~ 650)

# Mailing list and links

- HSG5 Framework mailing list:  
[atlas-phys-higgs-hsg5Framework](#)
- Framework TWiki:  
[CxAODFramework](#)
- Framework repository:  
[Physics/Higgs/HSG5/software/VHAnalysis/LHCRun2/CxAODFramework](#)

# Backup slides

# FrameworkExe

- **Grid running**

- This part of the framework is not covered here, please see the documentation provided on our TWiki:

<https://twiki.cern.ch/twiki/bin/viewauth/AtlasProtected/CxAODFramework>

## Grid running

For setting up the grid log into a clean lxplus session and run in your working direcorey:

```
setupATLAS
localSetupDQ2Client --skipConfirm # just for dq2-get -> no need for job submission
voms-proxy-init -voms atlas
localSetupPandaClient --noAthenaCheck
rcSetup
```

Find the list of samples in [FrameworkSub](#) /In, comment non-desired samples to run on and execute (for example) :

```
hsg5frameworkTuple FrameworkSub/In/list_sample_grid.*TeV.AOD.txt
```

# Modifying the code

- Adding a variable to the output
- Output variables are set in the method “setVariables()” which each handler has, e.g. **ElectronHandler**:

```

285 EL::StatusCode ElectronHandler::setVariables(xAOD::Electron * inElectron, xAOD::Electron * outElectron, bool isSysVar)
286 {
287
288     //TODO clean up
289     //TODO add check if variables changed due to calibrations?
290
291     // set four momentum
292     setP4( inElectron , outElectron );
293
294     //set isolation
295     outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::ptcone20),xAOD::Iso::ptcone20);
296     //outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::topoetcone30_corrected),xAOD::Iso::topoetcone30_corrected);
297     outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::topoetcone30),xAOD::Iso::topoetcone30);
298
299     // set something without having a pre-defined method
300     m_decorator.copy(inElectron, outElectron, ElecIntProps::isVeryTightLH);
301     m_decorator.copy(inElectron, outElectron, ElecIntProps::isVHLooseElectron);
302     m_decorator.copy(inElectron, outElectron, ElecIntProps::isZHSigElectron);
303     m_decorator.copy(inElectron, outElectron, ElecIntProps::isWHSigElectron);

```

- The I/O structure in the code is not entirely transparent – the “inElectron” is an object from a so-called “shallow copy” of the collection in the input file. This is the calibrated object which has additional “decorations” attached to it. The “outElectron” is the object which is written out. For the nominal calibration, this is a new memory allocation, while for sys. variations, it is a shallow copy of the nominal output object.



# Modifying the code

- Adding a variable to the output
- Output variables are set in the method “setVariables()” which each handler has, e.g. **ElectronHandler**:

```

285 EL::StatusCode ElectronHandler::setVariables(xAOD::Electron * inElectron, xAOD::Electron * outElectron, bool isSysVar)
286 {
287
288     //TODO clean up
289     //TODO add check if variables changed due to calibrations?
290
291     // set four momentum
292     setP4( inElectron , outElectron );
293
294     //set isolation
295     outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::ptcone20),xAOD::Iso::ptcone20);
296     //outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::topoetcone30_corrected),xAOD::Iso::topoetcone30_corrected);
297     outElectron->setIsolationValue(inElectron->isolationValue(xAOD::Iso::topoetcone30),xAOD::Iso::topoetcone30);
298
299     // set something without having a pre-defined method
300     m_decorator.copy(inElectron, outElectron, ElecIntProps::isVeryTightLH);
301     m_decorator.copy(inElectron, outElectron, ElecIntProps::isVHLooseElectron);
302     m_decorator.copy(inElectron, outElectron, ElecIntProps::isZHSigElectron);
303     m_decorator.copy(inElectron, outElectron, ElecIntProps::isWHSigElectron);

```

- So, what this method does is to copy properties from the calibrated object (“inElectron”) to the output object (“outElectron”).
- Thus, to add a variable to “outElectron”, a line must be put here copying the property.

# Modifying the code


- Adding a variable to the output
- In case **the variable is *not* a known property** to “inElectron”, it must first be calculated and added to this object, e.g. in the method `decorate()`:

```

107 EL::StatusCode ElectronHandler::decorate(xA0D::Electron * electron)
108 {
109     //selection tools
110     //-----
111     //retrieve decision from tools and decorate electron with it
112     //perform actual selection later
113     int isVeryLooseLH = static_cast<int>(m_checkVeryLooseLH->accept(electron));
114     int isVeryTightLH = static_cast<int>(m_checkVeryTightLH->accept(electron));
115     int isTightPP      = static_cast<int>(m_ElectronIsEMSelector->accept(electron));
116     m_decorator.set(electron, ElecIntProps::isVeryLooseLH, isVeryLooseLH);
117     m_decorator.set(electron, ElecIntProps::isVeryTightLH, isVeryTightLH);
118     m_decorator.set(electron, ElecIntProps::isTightPP, isTightPP);
119
120
121     return EL::StatusCode::SUCCESS;
122 }
123

```

This is the same object as “inElectron” on the previous slide



- There is more...

# Modifying the code

- Adding a variable to the output
- ... the property also needs to be added the object's decorator, which is defined in CxAODTools, e.g. for electrons: [CxAODTools/CxAODTools/ElectronDecorator.h](#)

```

1  #ifndef CxAODTools_ElectronDecorator_H
2  #define CxAODTools_ElectronDecorator_H
3
4  #include "ObjectDecorator.h"
5
6  enum class ElecBoolProps {
7      // OR tool
8      overlaps,
9      passPreSel,
10 };
11
12 enum class ElecIntProps {
13     // common stuff
14     partIndex,
15     passOR,
16     passORGlob,
17     // e-gamma ID
18     isVeryLooseLH,
19     isVeryTightLH,
20     isTightPP,
21     isMediumPP,
22     isLoosePP,
23     // analysis quality assignment
24     isVHLooseElectron,
25     isVHSignalElectron,
26     isZHSignalElectron,
27     isWHSignalElectron,
28     isTTLHOLElectron,
29     isTTLHDiLepVetoElectron,
30     isTTLHPreSelElectron,
31     isTTLHIsolElectron,
32     isTTLHSoftElectron,
33 };
34
35
36 enum class ElecFloatProps { IDEff, IDEffSys };
37

```

Boolean properties

Integer properties

Float properties

- That should do it 😊

