Doomscroll

Live Demo Script — Lab 4

Version 1.0
Prepared by: Project Team -- SC2006
Date: 18 October 2026

1. Setup (before the demo starts)

1. Laptop with a working webcam, normal indoor lighting, presenter seated at a normal desk distance from the screen.
2. Repository already cloned with its bundled face-landmark model and pretrained CNN present, dependencies installed (uv sync / pip install, including the optional 'cnn' extra if the CNN path will be shown).
3. A long-form reading document open in a second window behind the launcher (e.g. a long article or this report) to autoscroll through during the live segments.
4. On macOS: confirm camera permission has already been granted once beforehand, so the OS permission prompt does not interrupt the flow on stage.

2. Script

1. Launch: Run app.py. Show the Main Page: Quick Start, Record/train/calibrate, Calibrate only, and the Settings page link.

2. Quick Start (Math Model) calibration: Choose Quick Start, Trajectory protocol. Follow the moving dot (~40s) plus the short head-pose pass. Narrate: this fits a per-session ridge-regression model, no training data needed.

3. Calibration Checkpoint: Show the validation error printed to the Log and the Yes / No / Cancel dialog (Use Case 2.4). Choose Yes.

4. Autoscroll (tier 1): Read down the open document naturally; show Autoscroll firing once gaze dwells near the bottom of the window (tier 1, Use Case 4.2/5.1).

5. Attention Gate: Turn away from the screen for a couple of seconds; show Autoscroll pause automatically, then resume automatically on looking back (Use Case 5.2) -- no key press needed.

6. Content-aware tiers (macOS only): If on macOS, scroll to a point where little text remains below the gaze point and show tier 2/3 firing sooner than tier 1 would; narrate that this step is skipped/tier-1-only on Windows.

7. End session: Press 'q' to close the Autoscroll window and return to the Main Page (Use Case 5.3).

8. Settings page: Open Settings; show the Log, the Light/Dark appearance toggle (Use Case 6.1), and Clear all calibrations (Use Case 2.5) -- describe rather than actually clearing, to avoid having to recalibrate mid-demo.

9. CNN Model (optional, time permitting): Briefly show Calibrate only (CNN), explaining it fits a 9-point correction on top of an already-trained CNN rather than retraining from scratch; mention Record/train/calibrate as the long-form path that is impractical to run live.

3. Fallback if the webcam or lighting misbehaves on stage

Have a short screen recording of a successful Quick Start + Autoscroll session ready as backup, and narrate over it rather than re-attempting live calibration under poor conditions.