

# STUDENT VERSION (Backend Sprint-1 Week-2)

---



CLARUSWAY  
WAY TO REINVENT YOURSELF

## Meeting Agenda

---

- ▶ Icebreaking
- ▶ Questions
- ▶ Interview Questions
- ▶ Coding Challenge
- ▶ Video of the week
- ▶ Retro meeting
- ▶ Case study / project

# Teamwork Schedule

---

## Ice-breaking

5m

- Personal Questions (Stay at home & Corona, Study Environment, Kids etc.)
- Any challenges (Classes, Coding, studying, etc.)
- Ask how they're studying, give personal advice.
- Remind that practice makes perfect.

## Team work

5m

- Ask what exactly each student does for the team, if they know each other, if they care for each other, if they follow and talk with each other etc.

## Ask Questions

15m

### 1. What is the output of the following program?

```
L1 = []
L1.append([1, [2, 3], 4])
L1.extend([7, 8, 9])
print(L1[0][1][1] + L1[2])
```

- A. 12
- B. 11
- C. 13
- D. 10

### 2. Given the following three list, how would you create a new list that matches the desired output printed below in Python?

```
fruits = ['Apples', 'Oranges', 'Bananas']
quantities = [5, 3, 4]
prices = [1.50, 2.25, 0.89]
# Desired output
[('Apples', 5, 1.50),
 ('Oranges', 3, 2.25),
 ('Bananas', 4, 0.89)]
```

**A.**

```
fruits = ['Apples', 'Oranges', 'Bananas']
quantities = [5, 3, 4]
prices = [1.50, 2.25, 0.89]
output=[]

fruit_tuple_0 = (fruits[0], quantities[0], prices[0])
output.append(output)
fruit_tuple_1 = (fruits[1], quantities[1], prices[1])
output.append(output)
fruit_tuple_2 = (fruits[2], quantities[2], prices[2])
output.append(output)
print(fruit_tuple_0, fruit_tuple_1, fruit_tuple_2)
```

**B.**

```
fruits = ['Apples', 'Oranges', 'Bananas']
quantities = [5, 3, 4]
prices = [1.50, 2.25, 0.89]
i = 0
output = []
for fruit in fruits:
    temp_qty = quantities[i]
    temp_price = prices[i]
    output.append((fruit, temp_qty, temp_price))
    i += 1
print(output)
```

**C.**

```
fruits = ['Apples', 'Oranges', 'Bananas']
quantities = [5, 3, 4]
prices = [1.50, 2.25, 0.89]

groceries = zip(fruits, quantities, prices)
print(list(groceries))
```

**D.**

```
fruits = ['Apples', 'Oranges', 'Bananas']
quantities = [5, 3, 4]
prices = [1.50, 2.25, 0.89]
```

```

i = 0
output = []
for fruit in fruits:
    for qty in quantities:
        for price in prices:
            output.append((fruit, qty, price))
    i += 1
print(output)

```

**3. What will be the output of the following Python code?**

```

def printMax(a, b):
    if a > b:
        print(a, 'is maximum')
    elif a == b:
        print(a, 'is equal to', b)
    else:
        print(b, 'is maximum')
printMax(3, 4)

```

- A. 3
- B. 4
- C. 4 is maximum
- D. 3 is maximum

**4. What is the output of the following program?**

```

x = 50
def func(x):
    print('x is', x)
    x = 2
    print('Changed local x to', x)
func(x)
print('x is now', x)

```

**A.**

```

x is 50
Changed local x to 2
x is now 50

```

**B.**

```
x is 50  
Changed local x to 2  
x is now 2
```

**C.**

```
x is 50  
Changed local x to 2  
x is now 100
```

**D.** None of the mentioned

**5. What will be the output of the following Python code snippet?**

```
def function1(var1=5, var2=7):  
    var2=9  
    var1=3  
    print (var1, " ", var2)  
function1(10,12)
```

- A.** 5 7
- B.** 3 9
- C.** 10 12
- D.** error

**6.What will be the output of the following Python code?**

```
def san(x):  
    print(x+1)  
x=-2  
x=4  
san(12)
```

- A.** 13
- B.** 10

- C. 2
- D. 5

**7. What will be the output of the following Python code snippet?**

```
num = 2013
reversed_num = 0

while num != 0:
    digit = num % 10
    reversed_num = reversed_num * 10 + digit
    num //= 10

print(reversed_num)
```

- A. Error
- B. 2013
- C. 3102
- D. 2222

**8. Which of the following is not an exception handling keyword in Python?**

- A. try
- B. except
- C. accept
- D. finally

**9. What will be the output of the following Python code if we enter 10 as a number?**

```
valid = False
while not valid:
    try:
        n=int(input("Enter a number"))
        while n%2==0:
            print("Bye")
        valid = True
    except ValueError:
        print("Invalid")
```

- A. Bye (printed once)
- B. No output
- C. Invalid (printed once)
- D. Bye (printed infinite number of times)

**10. What will be the output of the following Python code snippet?**

```
f=lambda x:bool(x%2)
print(f(20), f(21))
```

- A. False True
- B. False False
- C. True True
- D. True False

**11. How can you filter duplicate data while retrieving records from a table in SQL?**

- A. DISTINCT
- B. WHERE
- C. LIMIT
- D. AS

**12. Which of the following is not a valid aggregate function?**

- A. COUNT
- B. COMPUTE
- C. SUM
- D. MAX

**13. Which data manipulation command is used to combines the records from one or more tables?**

- A. SELECT
- B. PROJECT
- C. JOIN
- D. PRODUCT

## Interview Questions

15m

**1. What is a lambda function in Python?**

**2. What is init??**

**3. What are decorators in Python?**

## Coding Challenge

35m

- [Code Challenge Run](#)

---

---

## Coffee Break

10m



---

---

## Video of the Week

10m

- [Fundamental Concepts of Object Oriented Programming](#)

## Retro Meeting on a personal and team level

5m

Ask the questions below:

- What went well?
- What went wrong?
- What is the improvement areas?

## Case study/Project

10m

### Python

- [Workshop 1 - Python Interview Challenge](#)

## Closing

5m

-Next week's plan



