Standard Operating Procedure

Yale School of Public Health

Data Science and Data Equity

The purpose of this document is to outline the contents of the Resource Navigation Tool

Authors Shelby Golden, M.S.

Date Effective April 24th, 2026

Date Updated N/A

Table of contents

File Structure 2

Updating Procedure 2

Create an Empty Remote Repository 2

Create a New Local Project 2

File Structure

```
dsde-workshops/
  |- start-local/
  |- JHU-CRC-Vaccinations/
  |- JHU-CRC-Cases-and-Deaths/
```

Updating Procedure

In this example, we will create a mock project folder from scratch, initialize Git, and link it to a remote repository on GitHub. We will then test the connection by adding "Hello World" to the `README.md` file on GitHub and pulling the changes to the local repository.

Create an Empty Remote Repository

1. Log in to your personal GitHub account.
2. In the top-right of the page navigation bar, select the
3. Fill out the following sections:
    a. Adjust the GitHub account owner as needed and create the name for the new repository.
    b. It is good practice to initially set the repository to "Private".
    c. Do **NOT** use a template or include a description, `README.md`, `.gitignore`, or license.

Create a New Local Project

1. Open the command-line application (i.e. Terminal for Macs and Git Bash for Windows) and navigate to the file location you want to temporarily store the repository copy [@local_hosted].

    Command-Line Interface

```
cd "~/dsde-workshops/"      # Go to workshop directory
mkdir "start-local"         # Create project folder
cd "start-local"            # Enter project folder
```

2. Confirm that Git has **NOT** yet been initialized by checking the project status. If the project is initialized, you should see that Git is present and tracking files.

Command-Line Interface

```
git status    # Show current status
```

Output

```
fatal: not a git repository (or any of the parent directories: .git
```