







Computer Networks

CMSC 417: Spring 2024



Topic: TCP Flow-control and Congestion-control (Textbook chapter 5 & 6)

Nirupam Roy

Tu-Th 2:00-3:15pm CSI 2117

March 14th, 2024











Stop-and-wait


Sender Receiver Packet ACK Time


Sliding Window




Sliding Window Protocol (recap)









Packet 1 is delivered




Packet 1 is delivered. Slide the window.




Packet 1 is delivered. Slide the window.







Packet 1 is delivered. Slide the window.

Should we advance the window in the following scenario?







Should we advance the window in the following scenario?



Should we advance the window in the following scenario?





Note that the window size is not changed!



Can you make sliding window behave like stop-and-wait?


Sliding Window Protocol (dealing packet loss)






(1) ARQ strategy 1: Retransmit all un-ACKed packets

(1) Go-back-N (Sender side)






(2) ARQ strategy 2: Retransmit only the lost packet

(2) Selective retransmit (Sender side)

Sliding Window: Lost Packet/ACK



Cumulative ACK:

ACK the largest in-sequence packet received.

What will be ACK sequence if the receive sequence is: 5, 7, 8, 6?


Cumulative ACK:

ACK the largest in-sequence packet received.


What will be ACK sequence if the receive sequence is: 5, 7, 8, 6?


ACK: 6, 6, 6, 9

(A more precise example)





Seq. #	234118
ACK flag	N/A
ACK#	N/A
Data Len	100 bytes
Seq. #	234218
ACK flag	N/A
ACK#	N/A
Data Len	50 bytes
Seq. #	234268
Seq. # ACK flag	234268 N/A
ACK flag	N/A
ACK flag	N/A N/A
ACK flag ACK # Data Len	N/A N/A 120 bytes
ACK flag ACK # Data Len Seq. #	N/A N/A 120 bytes 234388
ACK flag ACK # Data Len Seq. # ACK flag	N/A N/A 120 bytes 234388 N/A






	<u> </u>	• •	
Seq. #	234118	Sender	Receiver
ACK flag	N/A		
ACK#	N/A		
Data Len	100 bytes	234118	
Seq. #	234218		
ACK flag	N/A	234218 X	->
ACK#	N/A		
Data Len	50 bytes	234268	
Seq. #	234268		
ACK flag	N/A	22.4200	*
ACK#	N/A	234388	
Data Len	120 bytes	The state of the s	
Seq. #	234388	234218	***
ACK flag	N/A		· · · · · · · · · · · · · · · · · · ·
ACK#	N/A		
Data Len	100 bytes	•	*







Sender buffer:





Sender buffer:







Sender buffer:







Sender buffer:






Sender buffer:







Sender buffer:


234118	234218	234268	234388
100 bytes	50 bytes	120 bytes	100 bytes



Sender buffer:








Flow Control: TCP Sliding Window

Motivation: Maximum utilization of the resources without overwhelming the receiver.


Sliding Window




Receiver should have enough space to buffer/save the received data!!

Sliding Window: Implementation

 Allow a larger amount of data "in flight" for better channel utilization, but should not exceed receiver's capacity.






Receiver Buffering: Flow control


- Receive window size
 - Amount that can be sent without acknowledgment
 - Receiver must be able to store this amount of data
- Receiver tells the sender the window
 - Tells the sender the amount of free space left (i.e. sends an Advertised_Window size to the sender)

How to send the Advertised_Window size




TCP Header


Calculate Advertised_Window (Receiver side)




((NextByteExpected-1) - LastByteRead)

Sender buffer






Sender buffer



Receiver buffer



What if the AdvertisedWindow is zero?

>> Periodically send 1byte packets to break the deadlock. (uses the persist timer)

```
EffectiveWindow (calculated at the sender side)
= AdvertisedWindow - (LastByteSent - LastByteACKed)
```

Considering Maximum Segment Size (MSS)



What if...

- (1) Adv_window > MSS
- (2) Adv_window < MSS