

Formalizing AI Scientist Systems: A Unified Framework for Automated Scientific Discovery

Jaesol Shin
WeDataLab
ysys143@wedatalab.com

May 2026

Abstract

The emergence of end-to-end systems capable of automating hypothesis generation, experiment execution, and knowledge synthesis represents a significant change in how science is conducted. Despite rapid empirical progress, *AI Scientist* systems lack a unifying formal framework, which makes principled comparison across architectures and scientific domains difficult. We propose SCIAGENT, a six-component framework (S, G, E, V, M, π) comprising the **S**earch space, hypothesis **G**enerator, **E**xperiment executor, **V**alidator, **M**emory, and search **P**olicy (π), grounded in the theory of Partially Observable Markov Decision Processes (POMDPs) and Bayesian Experimental Design (BED). We apply this framework to analyze core AI Scientist systems and their instantiations across seven scientific domains (mathematics, physics, chemistry, materials science, biology, social science, and computer science), and separately examine a complementary artifact infrastructure proposal that addresses the output format and verification layer of such systems. Our analysis surfaces three persistent open problems: (1) the non-automatability of novelty evaluation, which remains dependent on human judgment despite multi-layer automated proxies; (2) the absence of BED-optimal search policies, despite the theoretical availability of tractable approximations; and (3) the underdevelopment of semantic memory M_s , whose absence prevents accumulated experimental experience from improving future search. We show that the completeness of the validator V is the single most consequential design variable: it determines whether closed-loop autonomous operation is feasible in each domain, and current AI Scientist systems can be read as a progression toward more complete validators.

1 Introduction

The pursuit of automated scientific discovery—systems that independently generate hypotheses, design and execute experiments, and synthesize new knowledge—has accelerated with the maturation of large language models (LLMs). Early demonstrations such as Co-scientist [Boiko et al., 2023] showed that LLM-based agents could autonomously plan and execute chemical syntheses. Subsequent systems including The AI Scientist [Lu et al., 2024]

and Agent Laboratory [Schmidgall et al., 2025] extended this vision to the full research cycle: from literature survey and hypothesis generation to code execution, manuscript writing, and automated peer review. Most recently, systems such as Aletheia [Google DeepMind, 2026] have begun to engage with research-level mathematical problems. In parallel, proposals such as Agent-Native Research Artifacts [Liu et al., 2026] address a complementary problem: what the *output* of AI Scientist systems should look like, and how it can be independently verified.

Despite this empirical momentum, the field lacks a shared formal vocabulary. Each system introduces its own architecture with bespoke terminology, making systematic comparison difficult. Questions that bear directly on practical deployment—*What determines whether a system can operate in a closed loop? Why does autonomous novelty evaluation fail consistently? What is the theoretical optimum for the search policy?*—remain unanswered in the literature.

We address these gaps by making three contributions:

1. We propose SCIAGENT, a formal framework (S, G, E, V, M, π) that decomposes any AI Scientist system into six components and connects it to the theoretical literature on POMDPs and Bayesian Experimental Design (Section 4).
2. We apply SCIAGENT to analyze four core AI Scientist systems (Section 5), a complementary artifact infrastructure proposal (Section 5.6), and domain-specific instantiations across six scientific fields (Section 6).
3. We identify three open problems that constrain progress across all current systems (Section 8).

Scope. This survey covers systems whose primary goal is automated scientific *discovery*—generating new knowledge through hypothesis-experiment-validation cycles. We explicitly exclude systems that apply AI as a specialized tool within a human-conducted research pipeline (e.g., AlphaFold [Jumper et al., 2021] for structure prediction), as these lack the hypothesis-generation and iterative search components central to our framework.

2 Background

2.1 POMDP Formulation of Scientific Discovery

Following the POMDP formulation [Kaelbling et al., 1998], we model AI Scientist systems as *partially observable Markov decision processes*. The true state $s \in \mathcal{S}$ corresponds to the unknown structure of nature (e.g., the correct physical law, the optimal molecular configuration). Because s is never directly accessible, the system maintains a belief state $b(s)$ updated by observations $o \in \Omega$ obtained through experiments.

Formally, an AI Scientist POMDP is the tuple $(\mathcal{S}, \mathcal{A}, T, R, \Omega, \mathcal{O}, \gamma)$, where $\mathcal{A}$ is the action space (hypothesis generation, experiment execution), $T : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\mathcal{S})$ is the transition function, $R : \mathcal{S} \times \mathcal{A} \rightarrow \mathbb{R}$ is the reward (scientific value of discovery), and $\mathcal{O} : \mathcal{S} \times \mathcal{A} \rightarrow \Delta(\Omega)$ is the noisy observation process.

This formulation departs from standard POMDPs in three ways specific to scientific discovery: (1) the reward function R is not pre-specified, as scientific significance cannot be defined a priori; (2) the state space $\mathcal{S}$ is unbounded and open-ended; and (3) the transition function T is non-stationary, since accumulated knowledge changes the frontier of valuable exploration.

2.2 Bayesian Experimental Design

Bayesian Experimental Design (BED) [Chaloner and Verdinelli, 1995, Rainforth et al., 2024] provides a principled basis for the search policy π . The optimal policy selects the experiment d^* that maximizes the Expected Information Gain (EIG):

$$d^* = \arg \max_{d \in \mathcal{D}} \text{EIG}(d) = \arg \max_d \mathbb{E}[H(\theta) - H(\theta \mid y, d)] \quad (1)$$

where $H(\theta)$ is the prior entropy over parameters θ and $H(\theta \mid y, d)$ is the expected posterior entropy after observing outcome y under experiment d . The two frameworks are complementary rather than competing: POMDP provides the structural formulation of the decision problem, while BED provides the normative criterion for the policy π .

Recent work has shown that EIG can be approximated via variational methods [Foster et al., 2019], amortized neural policies [Foster et al., 2021], and reinforcement learning [Blau et al., 2022]. Despite their theoretical availability, no current AI Scientist system explicitly implements EIG-optimal policies—a gap we identify as a central open problem.

3 Related Work

AI Scientist surveys and system papers. The literature on AI Scientist systems has grown rapidly but lacks shared vocabulary. Lu et al. [2024] propose the first closed-loop end-to-end system and provide qualitative characterization of their own components, but do not offer a formal framework for cross-system comparison. Schmidgall et al. [2025] focus on co-pilot design and evaluate cost reduction against human baselines. Boiko et al. [2023] demonstrate tool-augmented autonomous synthesis but do not model the discovery loop. Si et al. [2024] conduct a large-scale human study on LLM idea generation quality, establishing baselines for novelty evaluation; Baek et al. [2024] propose iterative literature-conditioned ideation. Neither provides a framework that unifies search, execution, validation, and memory. The closest precursor to our framework is the qualitative discussion in Lu et al. [2026], which introduces the concept of open-ended archives and replication nodes but does not formalize these as components of a general system.

Theoretical foundations: POMDP and BED. The POMDP formulation of decision-making under partial observability is classical [Kaelbling et al., 1998]. Bayesian Experimental Design formalizes the optimal experiment selection criterion [Chaloner and Verdinelli, 1995]; recent work provides tractable approximations via variational inference [Foster et al., 2019], amortized neural policies [Foster et al., 2021], and reinforcement learning [Blau et al., 2022]. We connect these two bodies of work: POMDP provides the structural formulation while BED provides the normative policy criterion. To our knowledge, no prior work explicitly applies BED as a design target for AI Scientist search policies.

Domain-specific AI science systems. Substantial prior work applies AI to scientific problems without proposing general frameworks: FunSearch [Romera-Paredes et al., 2024] and DeepSeek-Prover [Xin et al., 2024] in mathematics; AI Feynman [Udrescu and Tegmark, 2020] in physics; ChemCrow [Bran et al., 2024] and ChemReasoner [Sprueill et al., 2024] in chemistry; BioPlanner [O’Donoghue et al., 2023] in biology; AutoML-Zero [Real et al., 2020] in computer science. We treat these as SCIAGENT component instantiations, enabling principled cross-domain comparison.

Formal models of science. Taniguchi et al. [2024] propose Collective Predictive Coding as a Model of Science (CPC-MS), recasting scientific activity as decentralized Bayesian inference across a community of agents with diverse priors. Their framework maps directly onto SCIAGENT components: hypothesis generation as internal-representation inference $q(z^k | w, o^k)$, experimentation as action-conditioned observation $p(o | z, a)$, peer review as collective consensus $q(w | \{z^k\})$, and search policy as expected free energy minimization. The key distinction is scope: CPC-MS is a *collective* and *social* model, while SCIAGENT is a *single-system* and *modular* decomposition. Notably, CPC-MS explicitly analyzes Lu et al.’s AI Scientist and argues that it automates only a single researcher’s loop while leaving the collaborative peer-review and consensus layer unaddressed—motivating the collective extension we discuss in Section 9.

Research artifact infrastructure. Liu et al. [2026] propose Agent-Native Research Artifacts (ARA) as a structured output format and verification protocol for AI-produced research. We position this contribution separately from end-to-end AI Scientist systems, as it addresses the artifact layer rather than the discovery loop, and discuss its implications for the V and M_s components of SCIAGENT in Sections 5.6 and 8.

4 The SciAgent Framework

We define an AI Scientist system as a tuple (S, G, E, V, M, π) with the following components:

$$\text{SCIAGENT} = (S, G, E, V, M, \pi) \quad (2)$$

S : Search Space The set of candidate hypotheses, programs, molecules, experimental conditions, or other objects subject to exploration. S may be static or dynamically expanding (open-ended).

$G : M \times S \rightarrow h$: Hypothesis Generator A function that proposes new candidate $h \in S$ conditioned on accumulated memory M and the current state of the search space. G may involve LLM generation, evolutionary mutation, or symbolic search.

$E : h \times P \rightarrow o$: Experiment Executor A function that executes hypothesis h under protocol P to produce observation o . The fidelity of E ranges from fast computational simulation (low cost, potential surrogate error) to physical wet-lab execution (high cost, ground truth).

$V : o \rightarrow r$: Validator A function that assigns a reward signal r to observation o . We

distinguish four layers of V :

$V_{\text{syntax}} : o \rightarrow \{\text{pass, fail}\}$	(deterministic, fast)
$V_{\text{semantic}} : o \rightarrow r \in [0, 1]$	(LLM-based, stochastic)
$V_{\text{empirical}} : o \rightarrow r$	(reproduction-based)
$V_{\text{human}} : o \rightarrow \{\text{novel, significant}\}$	(non-automatizable)

M : Memory Structured as (M_e, M_s, M_p) . M_e (episodic) stores individual records (h_i, o_i, r_i) ; M_s (semantic) stores distilled knowledge patterns; M_p (procedural) stores learned protocols. The structure of M directly determines the quality of G and π .

$\pi : b(S) \times M \rightarrow h$: **Search Policy** The decision rule for selecting the next hypothesis. The belief state $b(S)$ is updated after each experiment. In the BED interpretation, $\pi^* = \arg \max_d \text{EIG}(d)$ (Equation 1). In practice, current systems use policies ranging from reactive (ReAct) to greedy to tree search.

The operational loop is:

$$\begin{aligned} \pi(b, M) &\rightarrow G(M_s, S) \rightarrow E(h, P) \rightarrow V(o) \\ &\rightarrow M += (h, o, r) \rightarrow b(S) \text{ update} \rightarrow \text{repeat} \end{aligned} \quad (3)$$

We further introduce $H \in [0, 1]$ as an auxiliary parameter denoting the degree of human intervention: $H = 0$ for fully autonomous systems and $H = 1$ for systems in which humans assume the role of G or π .

5 Analysis of Core AI Scientist Systems

We apply SCIAGENT to four core systems that propose or implement end-to-end automated research pipelines (Sections 5.1–5.4), followed by one artifact infrastructure proposal that addresses the output format and verification layer of such systems (Section 5.6). For each end-to-end system, we characterize the six components and assess three quality dimensions: (A) novelty claim mechanism, (B) closed-loop completeness, and (C) scientific quality assurance.

5.1 Coscientist

Boiko et al. [2023] demonstrate that GPT-4 can autonomously plan and physically execute chemical syntheses via a tool-augmented ReAct loop.

(A) Novelty. No novelty measurement mechanism exists; all synthesis targets are known compounds. The system’s novelty claim concerns architectural capability, not scientific discovery.

(B) Loop. The loop does not close: there is no hypothesis $\rightarrow$ experiment $\rightarrow$ new hypothesis cycle. Physical execution succeeds, but measurement results are not fed back to the agent.

(C) Quality. Single GC-MS measurement with no replication, no statistical testing, and no public data release (withheld for safety reasons). The authors note that multi-run variance analysis is future work.

Component	Instantiation
S	Known chemical reaction space (reproduction, not discovery)
G	Human-provided task $\rightarrow$ GPT-4 Planner steps; no autonomous ideation
E	Tool calls (web, docs, code) + RoboRXN physical synthesis; analytical characterization delegated to human
V	V_{human} only: author inspection + single GC-MS measurement
M	Session conversation history; no cross-session persistence
π	Greedy ReAct: next tool action conditioned on current context; no branching

Table 1. Coscientist (S, G, E, V, M, π) mapping.

5.2 The AI Scientist (Sakana AI)

Lu et al. [2024] propose the first system to close the full research loop: ideation, experimentation, manuscript writing, and automated peer review.

Component	Instantiation
S	ML research idea space, implicitly bounded by seed code templates
G	LLM ideation conditioned on archive M_e ; Semantic Scholar API (10 rounds) similarity filter
E	Aider code agent $\rightarrow$ Python execution; max 4 retries, 7200s timeout
V	V_{semantic} : GPT-4o reviewer (NeurIPS guidelines, 5-ensemble); BalAcc 0.65 vs. human 0.66
M	M_e : idea archive with title, scores, results; no M_s or M_p
π	Greedy: generate hypothesis dissimilar to archive; no long-horizon planning

Table 2. The AI Scientist (Sakana 2024) (S, G, E, V, M, π) mapping.

(A) Novelty. LLM self-scores each idea on novelty (1–10 scale). The authors acknowledge systematic over-estimation bias and that “judgments by LLMs can often have bias” [Lu et al., 2024]. Importantly, the authors state: “*we do not recommend taking the scientific content of this version of The AI Scientist at face value.*”

(B) Loop. The first genuinely closed loop: review scores feed into the next ideation cycle via M_e . However, π is greedy and does not improve with archive growth.

(C) Quality. Statistical rigor is weak: seeds and confidence intervals are not enforced. An early system version hallucinated ablation tables. Safety violations were observed, including a subprocess that indefinitely spawned Python processes and an agent that attempted to extend its own timeout.

5.3 The AI Scientist (Nature 2026)

Lu et al. [2026] extend the Sakana system with agentic tree search and an open-endedness

archive, achieving the first AI-authored manuscript accepted at a peer-reviewed workshop (ICLR 2025 ICBINB, score 6.33).

Component	Instantiation
S	Open-endedness archive (dynamic S); idea novelty checked against Semantic Scholar (20 rounds)
G	LLM conditioned on S_{archive} and M_e ; Semantic Scholar similarity filter
E	4-phase agentic tree search; VLM critique on figures; Aider with 4 retries
V	$V_{\text{empirical}}$: replication nodes (mean $\pm$ s.d.); V_{semantic} : automated reviewer (BalAcc 0.69); V_{human} : ICLR reviewers
M	M_e : tree nodes; M_s : open-endedness archive; replication statistics
π	Best-first tree search: GPT-4o scores nodes on metrics, training dynamics, and figure quality

Table 3. The AI Scientist (Nature 2026) (S, G, E, V, M, π) mapping.

(A) Novelty. Three-layer validation: self-score, API filter, and actual peer review. Automated reviewer performance: balanced accuracy 0.69 (vs. human 0.66), F1 0.62 (vs. human 0.49), with no significant difference from human accuracy on both pre-cutoff ($p = 0.319$) and post-cutoff ($p = 0.921$) data. Limitations remain: hallucinated citations and the inherent risk that pretraining data contaminates novelty judgments.

(B) Loop. The most complete closed loop to date: tree search provides reward-guided π , VLM critique creates within- E feedback, and replication nodes enforce statistical validation.

(C) Quality. Bootstrap CIs (5,000 replicates) and z-tests are reported. Hallucinated citations remain a documented failure mode; the workshop acceptance rate (70%) differs from the main conference rate (32%), limiting the significance of the peer review validation.

5.4 Agent Laboratory

Schmidgall et al. [2025] adopt a co-pilot design in which human researchers provide the research direction, and LLM agents execute the research pipeline (literature review, experimentation, manuscript writing).

(A) Novelty. Novelty is handled by having the human provide the research direction. The system explicitly states: *“the strongest research systems would combine human-guided ideation with LLM-based workflows”* [Schmidgall et al., 2025].

(B) Loop. The only backward edge is from paper refinement to prior phases. The mle-solver contains the most sophisticated within- E micro-loop of any system analyzed. Termination is heuristic (max steps or timeout).

(C) Quality. The automated reviewer over-estimates quality by +2.3 points on average compared to human PhD students. A documented hallucination case: GPT-4o fabricated hyperparameter values (“learning rate 0.001, batch size 32 over 50 epochs”) that were never actually tested.

Component	Instantiation
S	Human-provided research direction (constrained S ; no autonomous ideation)
G	Human idea $\rightarrow$ PhD agent elaborates via literature review
E	mle-solver: EDIT/REPLACE + LLM reward scoring + self-reflection + top-program pool
V	V_{semantic} : NeurIPS LLM reviewer; systematic over-estimation (+2.3 points vs. human)
M	Literature collection (M_e); no M_s or M_p
π	Co-pilot: human; autonomous: fixed sequential; paper refinement $\rightarrow$ backward edge to prior phase

Table 4. Agent Laboratory (S, G, E, V, M, π) mapping.

5.5 Comparative Summary

Table 5 synthesizes the four end-to-end systems along the key dimensions identified by SCIAGENT.

	Coscientist	AI Sci. (2024)	AI Sci. (2026)	AgentLab
Novelty measure	None	LLM self-score	3-layer	Human-delegated
Loop closed?	No	Yes (greedy)	Yes (tree)	Partial
π type	ReAct	Greedy	Tree search	Human/seq.
V completeness	V_h only	V_s	$V_e + V_s + V_h$	V_s (biased)
M structure	Ephemeral	M_e	$M_e + M_s$	M_e
H (human role)	G	Low	Low	G+ π

Table 5. Comparative SCIAGENT analysis of four core AI Scientist systems. V_s =semantic, V_e =empirical, V_h =human.

5.6 Artifact Infrastructure: Agent-Native Research Artifacts

The four systems above address the internal structure of the AI Scientist loop. Liu et al. [2026] address a complementary problem: what the *output* of that loop should look like, and how it can be independently verified. They propose Agent-Native Research Artifacts (ARA), a structured protocol that replaces the narrative paper with a four-layer file-system ontology: `/logic` (claims with explicit falsification criteria, hypotheses, related-work dependency graph), `/src` (typed kernel modules or full repository), `/trace` (exploration graph with five typed node types: question, decision, experiment, dead_end, pivot), and `/evidence` (raw machine-readable results, withheld from verification agents to enable blind reproduction).

The motivation is quantitative: Liu et al. [2026] report that only 45.4% of papers provide sufficient information for reproduction, and that 90.2% of the dollar cost of extending a paper is consumed by failed rediscovery of methods already known to the original authors. ARA addresses this by making the full research process—including dead ends and pivots—a first-class published artifact.

ARA makes two direct contributions to the components of SCIAGENT. First, it addresses V via the ARA Seal: a three-level automated verification credential combining V_{syntax}

(schema conformance and cross-layer reference integrity, seconds), V_{semantic} (Rigor Auditor with a six-dimensional rubric, catching 82.6% of seeded validity mutations), and $V_{\text{empirical}}$ (sandboxed directional reproduction). V_{human} is retained for significance, novelty, and taste as an explicit design principle: “*judgments of significance, novelty, and taste are reserved for human reviewers*” [Liu et al., 2026]. Second, the `/trace` layer addresses M_e and M_s : forensic bindings link each claim to the experiment that supports it and to raw evidence files, externalizing the semantic structure of accumulated knowledge.

A key empirical finding bears on π : preserved failure traces (dead_ends, pivots) in the `/trace` layer accelerated downstream agent performance in extension tasks, but the same traces also constrained more capable agents by anchoring them to prior solution paths. Richer M_e does not monotonically improve π .

The paper positions ARA as a substrate rather than a system: “ARA closes this gap not by replacing these tools but by providing the missing structural layer” [Liu et al., 2026]. In SCIAGENT terms, ARA specifies a standard output format for E and input format for G , with the goal that when AI Scientist systems produce and consume ARAs rather than narrative PDFs, accumulated knowledge compounds at the artifact level rather than the sentence level.

6 Domain Analysis

We examine how SCIAGENT components are instantiated across seven scientific domains, revealing that the completeness of V is the primary determinant of closed-loop feasibility.

6.1 Mathematics

Mathematics uniquely enables V_{formal} —a perfect oracle implemented by formal proof assistants such as Lean 4. This has direct consequences for π : because the reward signal is binary and noise-free, reinforcement learning is applicable without reward hacking.

FunSearch [Romera-Paredes et al., 2024] instantiates S as the space of Python functions (short programs implementing priority heuristics), G as LLM mutation conditioned on the best-so-far population, E as deterministic sandboxed execution, and $V_{\text{empirical}}$ as the numerical score from a user-provided evaluator. The loop is fully closed; novelty is established via quantitative SOTA improvement.

DeepSeek-Prover-V1.5 [Xin et al., 2024] uses $S = \text{Lean 4 tactic scripts}$, $E = \text{Lean proof kernel (decidable)}$, $V_{\text{formal}} = \text{type-check success (perfect oracle)}$, and $\pi = \text{RMaxTS (UCB + intrinsic exploration reward)}$ combined with RLPAF (reinforcement learning from proof assistant feedback). The noise-free V enables stable RL without reward hacking.

Aletheia [Google DeepMind, 2026] takes the opposite approach: S is natural language proof space, V is a fallible LLM Verifier subagent, and V_{human} remains the ground truth. Of 700 Erdős problems attempted, human auditors rated only 13 (1.9%) as “meaningfully correct.” The system explicitly identifies “subconscious plagiarism”—pretraining data contamination masking as discovery—as a serious validity threat.

The key observation is that S choice bifurcates mathematical AI Scientist paradigms: program-space ($V_{\text{empirical}}$ sufficient, full autonomy possible) vs. natural-language-proof-space (V_{human} required, partial autonomy only).

6.2 Physics

AI Feynman [Udrescu and Tegmark, 2020] encodes domain knowledge in π rather than G : the search policy applies physics-specific heuristics (dimensional analysis, symmetry detection, separability) to progressively reduce the effective size of S . M_e is absent—each mystery starts fresh. The loop is partially closed: there is no cross-mystery knowledge accumulation.

Discovering Symbolic Models [Cranmer et al., 2020] uses a two-stage pipeline: GNN training (G via inductive bias over interacting particle systems) followed by symbolic regression (E via Eureka genetic algorithm). The loop is fully open; discovered formulas do not feed back into GNN training. V_{human} plays a decisive role: “this formula is new to cosmologists.”

Domain observation. Physics law discovery requires V to evaluate both numerical accuracy and interpretability (symbolic form). This dual requirement is absent in algorithm discovery (accuracy only) and is more demanding than mathematical construction (SOTA score only).

6.3 Chemistry

ChemCrow [Bran et al., 2024] is architecturally similar to Coscientist: tool-augmented ReAct with 18 APIs. The physical loop is open at the analytical measurement boundary—the robotic synthesizer executes reactions, but NMR, MS, and UV-Vis characterization remain human-delegated. V_{semantic} (EvaluatorGPT) is shown to be unreliable: it cannot distinguish between correct and clearly incorrect GPT-4 outputs.

ChemReasoner [Sprueill et al., 2024] introduces the strongest M and π of any domain paper analyzed: a tree-structured M_e storing all visited (question, answer, reward) nodes, and a beam search π (beam width $M = 6$) that selects top-scoring nodes for expansion at each depth. E is computational only (GNN surrogate, GemNet-dT), with DFT validation reserved for post-hoc verification. The authors document divergence between GNN predictions and DFT ground truth, confirming that V is a surrogate with systematic error.

Domain observation. The wet-lab loop in chemistry is structurally open at the measurement boundary. Physical execution is achievable (ChemCrow, Coscientist); automated analytical characterization is not. ChemReasoner is the only chemistry system with a BED-adjacent π (beam search over reward-ranked nodes).

6.4 Materials Science

Materials discovery presents a distinct V profile: formation energy per atom computed via Density Functional Theory (DFT) serves as a near-perfect empirical oracle—computationally expensive but noise-free and ground-truth aligned—while physical synthesis constitutes a costly, human-mediated second validation layer.

GNoME [Merchant et al., 2023] (Graph Networks for Materials Exploration, DeepMind) scales this structure to 380 million hypothetical inorganic crystal structures. G is a pair of Graph Neural Networks (GNNs) trained to predict thermodynamic stability: one structural GNN operating on known crystal prototypes and one compositional GNN operating

on element combinations. E is high-throughput DFT. π is entropy-weighted uncertainty sampling: candidates where the GNN is most uncertain are prioritized for DFT evaluation, approximating an active learning policy over $b(S)$. M_s grows as the GNN retrains on accumulated DFT outcomes; GNoME is one of the few systems where $G(M_s, S)$ genuinely improves with accumulated experiments.

Component	Instantiation
S	380M hypothetical inorganic crystal structures
G	Dual GNN (structural + compositional) predicts stability; retrained on DFT outcomes
E	High-throughput DFT (computational); synthesis at collaborating labs (physical)
V	$V_{\text{empirical}}$: formation energy / above-hull threshold (DFT); V_{human} : synthesis confirmation
M	M_e : 460K prior DFT results; M_s : GNN weights updated each iteration
π	Uncertainty sampling: prioritize high-entropy predictions for DFT

Table 6. GNoME (S, G, E, V, M, π) mapping.

Key results: 2.2 million stable structures identified (83% novel, precision 0.87), of which 736 were experimentally synthesized in collaboration with a robotic lab. The computational loop is closed; the synthesis loop remains open, with weeks-to-months latency for physical validation.

Domain observation. Materials science is the domain where π most closely approximates BED theory. GNoME’s uncertainty-sampling policy is structurally equivalent to information-gain maximization over a probabilistic stability model, closer to EIG-optimal than any system in other domains. The primary bottleneck is the DFT wall-time (hours per candidate), which limits the loop frequency but does not prevent closure.

6.5 Biology

BioPlanner [O’Donoghue et al., 2023] contributes a pseudofunction abstraction that enables automatic evaluation of protocol-generation quality (function accuracy, argument precision, sequence order). The system’s primary contribution is V operationalization rather than G - E - V loop closure. Wet-lab validation succeeds (E. coli culture executed without modification), but results are not fed back to the generator.

AlphaFold 2 [Jumper et al., 2021] is explicitly excluded from the SCIENTIST mapping: it is a discriminative predictor, not a hypothesis-experiment loop. π is absent (recycling is a fixed 3-iteration refinement); G performs no hypothesis generation; experimental feedback does not occur during inference. AlphaFold 2 represents a target capability that motivates AI Scientist development in biology rather than an instance of the pattern.

6.6 Social Science

Social science is unique in that LLMs substitute for E (human subjects experiments). This creates a structural validity threat: when G and E share the same underlying model, the

experiment executor may confirm the hypothesis generator’s implicit biases.

Automated Social Science [Manning et al., 2024] demonstrates that LLM-simulated experiments yield results directionally consistent with economic theory. However, LLMs systematically over-estimate effect magnitudes by $13.2\times$ when queried directly, while simulation-based estimates are closer to theory. The system’s π is a full-factorial design over exogenous SCM variables; cross-scenario transition is not automated (H intervenes at this boundary).

Generative Agents [Park et al., 2023] provides E-infrastructure (memory stream + reflection + planning architecture) that subsequent systems use. It is not itself an AI Scientist system—the loop produces socially plausible behavior, not scientific discovery.

Turing Experiments [Aher et al., 2023] serves as a meta-paper, measuring whether LLMs constitute valid E for social science. Key finding: *hyper-accuracy distortion*—stronger LLMs produce answers too accurate to simulate human population distributions. This identifies a fundamental constraint on E fidelity in social science AI Scientist systems.

6.7 Computer Science

AutoML-Zero [Real et al., 2020] evolves complete ML algorithms from primitive mathematical operations using a regularized evolutionary algorithm. S = operation sequences (three components: Setup, Predict, Learn), $V_{\text{empirical}}$ = validation accuracy on proxy tasks, π = tournament selection with aging regularization. The loop is fully closed and runs for millions of generations.

Algorithm Discovery with LLMs [Sartori and Blum, 2024] uses LLMs as semantic mutation operators: instead of syntactic bit-flipping, the LLM understands the current program’s logic and proposes meaningful variations. This reduces search space by orders of magnitude relative to blind evolutionary search.

AutoKernel [Jaber and Jaber, 2026] targets GPU kernel optimization, making S the space of CUDA/Triton implementations and $V_{\text{empirical}}$ the measured runtime speedup on hardware. An LLM agent reads a structured optimization playbook (M_p), proposes code edits to the current kernel, and executes a five-stage correctness gate before benchmarking. π is a keep/revert policy: edits that pass correctness checks and achieve $>1.01\times$ speedup are committed; others are rolled back via `git reset`. The loop runs unattended overnight (300–400 iterations per 10-hour run), achieving $2\text{--}5\times$ kernel speedups at a $\sim 20\%$ per-iteration success rate.

AutoKernel represents the clearest example of M_p (procedural memory) as a primary system component: the optimization playbook encodes expert heuristics—roofline model constraints, memory coalescing patterns, tiling strategies—in a structured format that guides G without LLM hallucination of inapplicable strategies.

6.8 Cross-Domain Summary

Table 7 summarizes the SCIENTIST analysis across domains. The key finding is that V completeness determines π capability and closed-loop feasibility.

Domain	V type	V reliability	Loop	π	Primary bottleneck
Math (formal)	V_{formal}	Perfect oracle	Fully closed	RL/MCTS	Pretraining contamination
Math (NL)	$V_{\text{sem}} + V_h$	Imperfect	Partial	Seq. refine	Hallucination; plagiarism
Physics	$V_{\text{emp}} + V_h$	Medium	None/partial	Deterministic	No cross-problem M
Chemistry	V_{emp} (surr.)	Medium	Comp. only	Beam	Wet-lab loop open
Materials	V_{emp} (DFT)	High	Comp. closed	Uncert. samp.	DFT wall-time; synth. lag
Biology	$V_{\text{emp}} + V_h$	Low-med	Partial	None	V metrics insufficient
Social Sci.	Stat. test	Low-med	Partial	Factorial	Circular validity
CS / Algo.	V_{emp}	High	Fully closed	Evol./LLM	Interpretability absent

Table 7. Cross-domain SCIAGENT analysis across seven domains. V reliability refers to agreement with ground truth.

7 Illustrative Simulation: Validator Coverage and False Novelty

To make the consequences of V incompleteness concrete, we construct a minimal agent-based simulation in which the degree of V completeness is the only variable altered across conditions. We model a community of $n = 20$ *reviewer agents*, each holding a local memory of previously observed latent classes. Each agent acts as a local validator: it estimates novelty by checking whether an incoming hypothesis belongs to a latent class it has encountered before, subject to a classifier accuracy parameter that models imperfect semantic identification. The hypothesis space consists of $n = 200$ hypotheses drawn uniformly from 40 latent classes; ground-truth novelty is determined by first occurrence of each class (exactly 40 hypotheses are novel, 160 are redundant). Agents share memory only through their communication topology, which we vary as the primary independent variable.

Operationalizing V completeness via connectivity. Each condition represents a different degree of V completeness, varied by mean degree k : an isolated agent ($k = 0$) consults only its own memory (incomplete, purely local V); a lattice agent ($k = 2$) pools with immediate neighbors (partial V); a medium-connectivity condition ($k \approx 4$, Watts–Strogatz) adds cross-cutting links that improve coverage; and a fully shared topology ($k = n-1$) gives every agent access to the entire community’s collective memory (the most complete V in this setting). Table 8 formalizes this mapping.

Results. Figure 1 reports the false novelty rate (FNR: fraction of non-novel hypotheses incorrectly marked as novel) across connectivity conditions and classifier accuracies, averaged over 30 random seeds. Because the estimator is a coverage membership test (`latent_class` $\notin$ `memory`) and memory sharing is a set-union, broader collective coverage structurally reduces false novelty calls—this is an analytic consequence of the mechanism, not an emergent finding. FNR decreases from 0.955 ± 0.028 (isolated, $k = 0$) to 0.285 ± 0.047 (lattice, $k = 2$) to 0.075 ± 0.036 ($k \approx 4$) to 0.008 ± 0.012 (shared, $k = n-1$). Within any

Table 8. Simulation conditions. Each condition operationalizes a different level of V completeness via mean degree k .

Condition	V -completeness	Mean degree k	Graph structure	Coverage
Isolated	Incomplete	0	No edges	Own memory only
Lattice	Partial	2	Ring	2-hop neighborhood
Medium ($k=4$)	Improved	4	Watts–Strogatz	Local + cross-links
Shared	Complete	$n-1$	Complete graph	Full community memory

condition, varying classifier accuracy from 0.60 to 0.90 moves FNR by at most 0.035; across conditions at fixed accuracy the FNR span is 0.947. These two ranges differ substantially in scale but are reported descriptively—one spans the maximum structural variation, the other a local parameter window, and neither constitutes a dimensionless effect-size estimate.

High-connectivity conditions suppress false novelty at the cost of recall: the shared condition achieves near-zero FNR (0.008 ± 0.012) but also near-zero true novelty recall (0.029 ± 0.025), because a saturated collective memory classifies genuinely novel hypotheses as already known. No condition operates as a useful discriminator: all conditions fall within 0.07 of chance-level balanced accuracy (BA range 0.506–0.565 at the default seeding rate). The structural reason is that a coverage threshold has only one degree of freedom and cannot improve false-novelty rejection and true-novelty detection simultaneously.

A non-trivial result emerges from varying the prior seeding rate: at low prior coverage (seeding rate $\leq 5\%$, each agent covering $\approx 22\%$ of latent classes), more connected topologies achieve better balanced accuracy (lattice BA = 0.563, $t = -7.4$ vs. isolated at $p < 0.001$); but at moderate prior coverage (seeding rate $\geq 10\%$, each agent covering $\approx 39\%$ of classes), isolated agents achieve *higher* balanced accuracy (0.564, $t = +3.1$ vs. lattice at $p < 0.01$), because additional memory sharing over-saturates collective knowledge and collapses recall for genuinely novel hypotheses. This reversal is structurally consistent with the epistemic-network literature [Zollman, 2010, Rosenstock et al., 2017]: the advantage of sparse connectivity is greatest when true positives are rare, and diminishes as individual coverage grows. The simulation thereby illustrates one minimal mechanism by which V incompleteness produces systematic failure in autonomous scientific loops—and suggests that optimal validator connectivity is prior-knowledge-dependent rather than monotonically determined by completeness alone.

An additional robustness sweep varying the hypothesis space complexity ($n_{\text{latent}} \in \{20, 40, 80\}$) reveals that the magnitude scales with domain complexity: isolated agents achieve FNR = 0.642 at 20 latent classes (a simple domain where local memory frequently saturates), but FNR rises to 0.995 at 80 classes. Medium-connectivity ($k \approx 4$) deteriorates similarly (FNR $0.002 \rightarrow 0.292$), while shared topology remains near zero across all complexity levels—consistent with the structural account and not independently informative about emergent dynamics. The failure mode is more severe in complex domains such as biology and mathematics (Table 7) than in constrained settings such as formal verification.

Limitations. This simulation uses synthetic agents and a ground-truth novelty oracle unavailable in real science; its agents do not generate hypotheses, run experiments, or update beliefs. The connectivity-to- V -completeness mapping is an operationalization, not an identity. As noted in the Results, the FNR–recall tradeoff is structurally determined:




Figure 1. False novelty rate (FNR) by V -completeness level (connectivity condition) and classifier accuracy. Error bars show ± 1 std across 30 seeds ($n = 200$ hypotheses, 40 latent classes, 20 agents). Across conditions the FNR span is 0.947; within any condition varying classifier accuracy over 0.60–0.90 moves FNR by ≤ 0.035 . Both ranges are sensitive to their chosen endpoints and are reported descriptively.

the mechanism (memory union growth with degree) cannot produce any outcome other than the one reported, and the simulation is therefore an existence illustration rather than an empirical measurement. The effect magnitude further depends on the prior seeding rate: the FNR ordering (more connected $\rightarrow$ lower FNR) is robust across 2–20% seeding rates, but absolute differences collapse above 10% seeding and balanced accuracy ordering reverses, confirming that no coverage-based topology achieves stable discrimination across prior-knowledge regimes. The simulation is intended to make the structural consequence of V incompleteness legible, not to measure its magnitude in any deployed system.

8 Open Problems

Our analysis identifies three open problems that persist across all systems and domains.

8.1 The Non-Automatability of Novelty

Every system in our survey encounters the same problem: novelty cannot be reliably evaluated by automated means. The trajectory of systems from Coscientist (no mechanism) to The AI Scientist Nature (three-layer validation including actual peer review) converges on the same conclusion; ARA [Liu et al., 2026] makes this an explicit design principle, reserving significance, novelty, and taste for human reviewers while automating the mechanical layers of review.

Two specific failure modes are documented: (1) *LLM self-evaluation bias*, manifesting as systematic over-estimation of novelty and quality (+2.3 points in Agent Laboratory;

hallucinated results in The AI Scientist Sakana; grade inflation observed in 17/23 ARA artifacts despite structural safeguards); and (2) *pretraining contamination*, most acutely in mathematics, where systems may “discover” results implicit in their training data (as documented by Aletheia for Erdős problems).

The ARA Seal [Liu et al., 2026] represents the most concrete existing proposal for automating the sub-novelty layers of V : its Rigor Auditor detects 82.6% of seeded structural violations across five injection types, with a documented 22% blind spot for orphaned experiments. This calibrates how far automated verification can reach before the novelty boundary. Addressing the boundary itself requires either evaluation protocols robust to pre-training contamination, or explicit architectural separation between the generating model and the evaluating model—approaches that remain largely unexplored.

8.2 The BED–Practice Gap for π

Equation 1 specifies the theoretically optimal search policy: select the experiment that maximizes EIG. The theoretical infrastructure for approximating this policy exists [Foster et al., 2019, 2021, Blau et al., 2022], yet no current AI Scientist system implements it. Instead:

- Coscientist: reactive ($\pi = \text{next tool selection}$)
- AI Scientist Sakana: greedy ($\pi = \text{avoid archive similarity}$)
- AI Scientist Nature: best-first tree search (node scoring by GPT-4o)
- Agent Laboratory: sequential (human-guided)
- GNoME: uncertainty sampling ($\pi \approx \text{EIG proxy over GNN posterior}$) — the closest approximation, but restricted to domains with tractable probabilistic models

The gap between available theory and deployed practice is striking, though one partial exception exists. GNoME’s [Merchant et al., 2023] uncertainty-sampling policy—prioritizing crystal structures where the GNN stability prediction has highest entropy—is structurally equivalent to information-gain maximization over a probabilistic model. It approximates EIG without computing it explicitly, by treating GNN uncertainty as a proxy for posterior entropy $H(\theta \mid b)$. This works in materials science because $V_{\text{empirical}}$ (DFT) is well-calibrated and the GNN posterior is tractable. In LLM-based systems, neither condition holds: the “posterior” over hypotheses is implicit in language model weights, and EIG requires integrating over $p(\theta \mid y)$, which is intractable without significant architectural changes. Amortized EIG approximations [Foster et al., 2021] that use trained neural networks to estimate information gain efficiently may offer a viable path forward for domains where a tractable model of the hypothesis space can be maintained.

8.3 The Underdevelopment of Semantic Memory M_s

Current systems predominantly implement M_e (episodic memory: storing raw experiment records). M_s (semantic memory: distilled patterns and regularities extracted from experimental history) is largely absent. The consequence is that a system with 1,000 completed

experiments does not search more intelligently than one with 10, because accumulated experience is not distilled into improved G or π .

The cost of this absence is empirically visible in the reproducibility gap. Liu et al. [2026] report that 90.2% of the dollar cost of extending a published result is consumed by failed rediscovery—reconstruction of intermediate knowledge the original authors possessed but did not publish. This is precisely the knowledge that M_s should encode but does not: the dead ends, pivots, and hard-won heuristics that distinguish experts from novices.

The ARA /`trace` layer [Liu et al., 2026] is the closest existing approximation: it encodes the exploration graph with typed nodes (experiment, `dead_end`, pivot) and forensic bindings to evidence. However, this is a representation framework rather than a learning mechanism— M_s is structured but not automatically distilled from experimental outcomes. Empirically, preserved traces accelerated agent performance on extension tasks but also anchored more capable agents to prior solution paths, suggesting that M_s structure must be paired with mechanisms for selectively forgetting or abstracting over low-level history.

Building systems where $G(M_s, S)$ genuinely improves with accumulated experience—not merely by appending to an archive but by distilling transferable knowledge—is an open problem with significant implications for long-horizon scientific discovery.

9 Discussion

Implications for system design. Our analysis suggests a design hierarchy: the choice of V should precede all other design decisions, as it determines whether closed-loop operation is feasible and what form π can take. Domains where V is approximated by noisy surrogates (chemistry, biology) require π strategies that are robust to reward noise—a requirement that beam search partially addresses (ChemReasoner) but that has not yet been systematically studied.

The role of human oversight (H). Rather than treating H as a limitation to be minimized, our analysis suggests that explicit human integration at the π and V_{human} level is not only practically necessary but theoretically well-motivated. In the POMDP formulation, human judgment provides access to a richer information source than any automated proxy, particularly for the non-automatizable components of V (novelty, significance). Systems that design H explicitly, as in The Last Human-Written Paper, may achieve better outcomes than those that attempt to minimize it.

Towards collective AI co-scientists. All systems analyzed in this survey operate as single-agent loops. A natural extension is a *collective* AI scientist: a multi-agent system $\{\text{SCIAGENT}_k\}_{k=1}^K$ sharing an external semantic memory w and coordinating through a collective validator $V_{\text{collective}}$. Taniguchi et al. [2024] formalize this vision via Collective Predictive Coding, recasting science as decentralized Bayesian inference in which a community of agents with diverse priors θ_k jointly updates a shared representation w through experimentation and peer review modeled as a Metropolis-Hastings consensus process. In their framework, social objectivity emerges from prior diversity—a requirement that LLM-based systems currently fail, since all instances share the same pretraining distribution. This is the “communication barrier” that Taniguchi et al. [2024] identify as the central obstacle to

AI participation in collective science, and it constitutes a fourth open problem beyond the three we identify.

Notably, the three open problems in our analysis are precisely the necessary conditions for a collective AI co-scientist to be realizable: $V_{\text{collective}}$ requires solving novelty automatability; a principled collective π requires closing the BED–practice gap; and the shared w requires a developed M_s . Their convergence suggests that progress on any one of the three would unlock disproportionate gains toward the collective system—and that ARA [Liu et al., 2026], as a structured artifact protocol for w , may be the most tractable entry point.

Limitations. Our framework (S, G, E, V, M, π) abstracts away important domain-specific nuances, including the cost structure of E (which varies by orders of magnitude across domains), the non-stationarity of S (open-ended problems), and the distinction between single-task and multi-task discovery. The single-agent framing also abstracts away the social layer that Taniguchi et al. [2024] formalize; extending SCIAGENT to multi-agent settings is a natural direction for future work.

10 Conclusion

We introduced SCIAGENT, a formal framework (S, G, E, V, M, π) for characterizing AI Scientist systems, and applied it to four core end-to-end systems, one artifact infrastructure proposal, and domain-specific instantiations across seven scientific fields. The framework connects the AI Scientist literature to the established theories of POMDPs and Bayesian Experimental Design, providing a principled basis for evaluating and improving search policies.

Three findings stand out from the cross-system, cross-domain analysis. First, current AI Scientist systems are best understood as a progression toward more complete validators: every architectural advance—from Coscientist’s single-measurement V_{human} to The AI Scientist’s automated reviewer to GNoME’s DFT oracle—is ultimately a gain in V completeness, and V completeness is what unlocks closed-loop operation. Second, the BED–practice gap for π is real but not absolute: GNoME’s uncertainty-sampling policy approximates EIG in a tractable probabilistic setting, showing that the gap is a solvable engineering problem in domains where a learnable model of the hypothesis space exists. Third, the underdevelopment of M_s is the least-addressed bottleneck: systems can close their loops with M_e alone, but they cannot compound accumulated knowledge without distillation—a capability that determines whether AI Scientist systems remain expensive one-shot tools or become genuinely cumulative research partners.

The three open problems we identify—novelty non-automatability, the BED–practice gap, and M_s underdevelopment—are not independent. A system with complete V and tractable M_s would, by construction, be able to implement an EIG-optimal π . The convergence of all three problems on the same structural gap suggests a single organizing question for the field: *how do we build validators and memory structures that are simultaneously complete enough to support closed-loop operation and structured enough to support principled search?*

References

- G. V. Aher, R. I. Arriaga, and A. T. Kalai. Using large language models to simulate multiple humans and replicate human subject studies. In *International Conference on Machine Learning*, 2023. arXiv:2208.10264.
- J. Baek, S. K. Jauhar, S. Pitis, S. J. Hwang, and J. Teevan. ResearchAgent: Iterative research idea generation over scientific literature with large language models. *arXiv preprint arXiv:2404.07738*, 2024.
- T. Blau, E. V. Bonilla, I. Chades, and A. Dezfouli. Optimizing sequential experimental design with deep reinforcement learning. In *International Conference on Machine Learning*, 2022. arXiv:2202.00821.
- D. A. Boiko, R. MacKnight, B. Kline, and G. Gomes. Emergent autonomous scientific research capabilities of large language models. *Nature*, 624:570–578, 2023.
- A. M. Bran, S. Cox, O. Schilter, C. Baldassari, A. D. White, and P. Schwaller. ChemCrow: Augmenting large-language models with chemistry tools. *Nature Machine Intelligence*, 2024. arXiv:2304.05376.
- K. Chaloner and I. Verdinelli. Bayesian experimental design: A review. *Statistical Science*, 10(3):273–304, 1995.
- M. Cranmer, A. Sanchez Gonzalez, P. Battaglia, R. Xu, K. Cranmer, D. Spergel, and S. Ho. Discovering symbolic models from deep learning with inductive biases. In *Advances in Neural Information Processing Systems*, 2020. arXiv:2006.11287.
- A. Foster, M. Jankowiak, E. Bingham, P. Horsfall, Y. W. Teh, T. Rainforth, and N. Goodman. Variational Bayesian optimal experimental design. In *Advances in Neural Information Processing Systems*, 2019. arXiv:1903.05480.
- A. Foster, D. R. Ivanova, I. Malik, and T. Rainforth. Deep adaptive design: Amortizing sequential Bayesian experimental design. In *International Conference on Machine Learning*, 2021. arXiv:2103.02438.
- Google DeepMind. Towards autonomous mathematics research. *arXiv preprint*, 2026.
- J. Jaber and O. Jaber. AutoKernel: Autonomous GPU kernel optimization via iterative agent-driven search. *arXiv preprint arXiv:2603.21331*, 2026.
- J. Jumper, R. Evans, A. Pritzel, T. Green, M. Figurnov, O. Ronneberger, K. Tunyasuvunakool, R. Bates, A. Židek, A. Potapenko, et al. Highly accurate protein structure prediction with AlphaFold. *Nature*, 596:583–589, 2021.
- L. P. Kaelbling, M. L. Littman, and A. R. Cassandra. Planning and acting in partially observable stochastic domains. *Artificial Intelligence*, 101(1–2):99–134, 1998.
- R. Liu et al. The last human-written paper: Agent-native research artifacts. *arXiv preprint arXiv:2604.24658*, 2026.
- C. Lu, C. Lu, R. T. Lange, J. Foerster, J. Clune, and D. Ha. The AI Scientist: Towards fully automated open-ended scientific discovery. *arXiv preprint arXiv:2408.06292*, 2024.
- C. Lu, C. Lu, R. T. Lange, Y. Yamada, J. Foerster, J. Clune, and D. Ha. Towards end-to-end automation of AI research. *Nature*, 2026.
- B. S. Manning, K. Zhu, and J. J. Horton. Automated social science: Language models as scientist and subjects. *NBER Working Paper*, (32381), 2024. arXiv:2404.11794.
- A. Merchant, S. Batzner, S. S. Schoenholz, M. Aykol, G. Cheon, and E. D. Cubuk. Scaling deep learning for materials discovery. *Nature*, 624:80–85, 2023.

- O. O'Donoghue, G. Puthumanaim, J. Won, P. Moura, M. Oettig, J. M. de Kruif, M. Gini, M. Heinonen, and P. Sloot. BioPlanner: Automatic evaluation of LLMs on protocol planning in biology. *arXiv preprint arXiv:2310.10632*, 2023.
- J. S. Park, J. C. O'Brien, C. J. Cai, M. R. Morris, P. Liang, and M. S. Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the ACM Symposium on User Interface Software and Technology*, 2023. arXiv:2304.03442.
- T. Rainforth, A. Foster, D. R. Ivanova, and F. B. Smith. Modern Bayesian experimental design. *Statistical Science*, 2024. arXiv:2302.14545.
- E. Real, C. Liang, D. So, and Q. Le. AutoML-Zero: Evolving machine learning algorithms from scratch. In *International Conference on Machine Learning*, 2020. arXiv:2003.12638.
- B. Romera-Paredes, M. Barekatin, A. Novikov, M. Balog, M. P. Kumar, E. Dupont, F. J. R. Ruiz, J. Ellenberg, P. Wang, O. Fawzi, et al. Mathematical discoveries from program search with large language models. *Nature*, 625:468–475, 2024.
- S. Rosenstock, J. Bruner, and C. O'Connor. In epistemic networks, is less really more? *Philosophy of Science*, 84(2):234–252, 2017.
- C. C. Sartori and C. Blum. Algorithm discovery with large language models: Evolutionary search meets transformer. *arXiv preprint arXiv:2411.00895*, 2024.
- S. Schmidgall, Y. Su, Z. Wang, X. Sun, J. Wu, X. Yu, J. Liu, and E. Barsoum. Agent Laboratory: Using LLM agents as research assistants. *arXiv preprint arXiv:2501.04227*, 2025.
- C. Si, D. Yang, and T. Hashimoto. Can LLMs generate novel research ideas? A large-scale human study with 100+ NLP researchers. *arXiv preprint arXiv:2409.04109*, 2024.
- H. W. Sprueill, C. Edwards, K. Agarwal, M. Olarte, U. Sanyal, C. Johnston, H. Liu, H. Ji, and S. Bhatt. ChemReasoner: Heuristic search over a large language model's knowledge space using quantum-chemical feedback. In *International Conference on Machine Learning*, 2024. arXiv:2402.10980.
- T. Taniguchi, K. Suzuki, H. Yamakawa, R. Sato, E. Ugur, A. Ugur, and Y. Nagai. Collective predictive coding as model of science: Formalizing scientific activities towards generative science. *arXiv preprint arXiv:2409.00102*, 2024.
- S.-M. Udrescu and M. Tegmark. AI Feynman: A physics-inspired method for symbolic regression. *Science Advances*, 6(16):eaay2631, 2020.
- H. Xin, D. Ren, S. Song, Z. Shao, W. Zhao, H. Wang, W. Liu, L. Cheng, et al. DeepSeek-Prover-V1.5: Harnessing proof assistant feedback for reinforcement learning and Monte-Carlo tree search. *arXiv preprint arXiv:2408.11170*, 2024.
- K. J. S. Zollman. The epistemic benefit of transient diversity. *Erkenntnis*, 72(1):17–35, 2010.

AI Involvement Checklist

This checklist documents the role of AI systems at each stage of this research, as required by CAISc 2026.

- **Hypothesis development.** The core SCIAGENT framework (S, G, E, V, M, π), the H parameter, the G output spectrum (propositional hypothesis $\rightarrow$ falsifiable construction), and the three open problems were conceived by the human author. Claude Code (Anthropic) elaborated framework components, identified paper-level instantiations of each component, and proposed connections between concepts.
- **Literature search and selection.** The human author determined inclusion criteria and target systems. Claude Code autonomously retrieved and read over 40 full-text PDFs, categorized papers into the taxonomy, and performed claim-level verification against source text.
- **Analysis.** Claude Code extracted S, G, E, V, M, π components for each of the 13 analyzed systems by reading primary sources. The human author reviewed all extractions, corrected mischaracterizations (several substantive corrections were required), and synthesized cross-system patterns.
- **Writing.** Claude Code drafted the majority of this manuscript. The human author provided key conceptual passages (notably §?? and the core definitions in §4), directed structural decisions, and reviewed all drafts.

Overall, the division of labor is best characterized as: the human author provided intellectual direction, framework design, and final judgment; Claude Code provided literature retrieval, analysis execution, and text generation.

Responsibility & Reproducibility Checklist

- **Claims and evidence.** All empirical claims are grounded in cited primary sources. Major claims were verified by direct full-text reading of source PDFs; specific figures (e.g., Science of Science statistics) were cross-checked against institutional press releases where journal access was unavailable.
- **Limitations.** This paper is a conceptual meta-analysis of existing published systems. It contains no original experiments. The SCIAGENT framework is not empirically validated against held-out systems in this submission; its descriptive adequacy rests on consistency across the 13 analyzed systems. Domain-specific cost structures, multi-agent dynamics, and temporal evolution of systems are not modeled.
- **Reproducibility.** The analytical framework can be applied to any AI Scientist system following the component definitions in §4. All analyzed papers are publicly accessible. No proprietary data or closed models were used.
- **Experimental details.** Literature review methodology follows Muka et al. (2020) 24-step systematic review guide. System selection criterion: end-to-end automation of at least one component of the hypothesis–experiment–validation loop.
- **Data and code availability.** Analysis notes will be made available upon acceptance. No datasets were produced.
- **Ethical and societal impact.** The H parameter analysis explicitly addresses the necessity of human oversight in current systems. The Science of Science discussion (§??) flags risks of research homogenization under widespread AI Scientist deployment, citing empirical evidence from Park et al. (2023) and Wu et al. (2019).