

COEN 11- Practice I

Solutions on Wednesday

1. What is printed?

```
int main ( )
{
    printf ("%d\n", a(5));
    return 0;
}

int a (int x)
{
    int    y;

    y = b (x) + b (++x) + b (x++);
    return (y + x);
}

int b (int z)
{
    return (z * 10);
}
```

2. What is printed?

```
int main ( )
{
    int    i;
    int    x[5] = {0, 1, 2, 3, 4};
    int    *p = x;
    int    a = 0;
    int    b = 10;

    x[0] += f (a, &b, x);
    printf ("%d, %d\n", a, b);
    for (i = 0; i < 5; i++)
        printf ("%d\n", x[i]);
    return 0;
}

int f (int x, int *y, int *z)
{
    x += 100;
    *y += 200;
    z[2] += 300;
    return (x);
}
```

3. Write a function to return the sum of all the elements in a 2D array of size `NROWSxNCOLS`. The prototype of the function is:
`int sum (int[][NCOLS]);`

4. Write a function to initialize 2D array `x` (size `MxM`) with the following pattern (shown for a 5x5 array):

```
1  0  0  0  1
0  1  0  1  0
0  0  1  0  0
0  1  0  1  0
1  0  0  0  1
```

5. Write a function to return the number of sub-strings (sequence of characters with no spaces, tabs, or newlines) in string `str` received as argument. The prototype of the function is:
`int count_strings (char *);`
6. Write a function to return the length of the longest string in an array of strings (size `NROWSxNCOLS`) received as argument. Do not use `strlen`! The prototype of the function is:
`int largest_size (char[][NCOLS]);`