

JavaScript Conditions

COEN 161

Comparison Operators

- Apart from `==`, `>`, and `<`, JavaScript has additional operators for more complex comparisons

Operator	Description	Comparing	Returns
<code>!=</code>	not equal	<code>x != 8</code>	true
<code>>=</code>	greater than or equal to	<code>x >= 8</code>	false
<code><=</code>	less than or equal to	<code>x <= 8</code>	true

*** `x = 5`**

Comparison Operators

- JavaScript has one unusual, quirky operator: ===
- “Triple Equals” not only compares two values, it compares types as well

Operator	Description	Comparing	Returns
==	equal to	x == 5	true
		x == "5"	true
===	equal value and equal type	x === 5	true
* x = 5		x === "5"	false

Comparison Operators

- The inverse operation of “triple equals” is `!==`

Operator	Description	Comparing	Returns
<code>!=</code>	not equal	<code>x != 8</code>	true
<code>!==</code>	not equal value or not equal type	<code>x !== 5</code>	false
		<code>x !== "5"</code>	true
<code>* x = 5</code>		<code>x !== 8</code>	true

Logical Operators

- You can combine comparisons using logical operators
- Here **x = 6** and **y = 3**

Operator	Description	Example
&&	and	(x < 10 && y > 1) is true
	or	(x == 5 y == 5) is false
!	not	!(x == y) is true

Comparing Different Types

- When comparing with a number, JavaScript will try to convert a string to a number to do the comparison
- An empty string is 0 and anything non-numeric is NaN, which is always false

Case	Value	Case	Value
2 < 12	true	2 == "John"	false
2 < "12"	true	"2" < "12"	false
2 < "John"	false	"2" > "12"	true
2 > "John"	false	"2" == "12"	false

Conditional Statements

- JavaScript supports the following conditional statements
 - if - executes the block of code if the condition is true
 - else - executes the block of code if the condition is false
 - else if - tests a new condition if the previous condition was false
 - switch - specifies many alternative blocks of code to run

The if Statement

- If the condition is true, the block of code is run
 - If there is no block { } then only the first line after the if is run

```
if (condition) {  
    block of code to be executed if the condition is true  
}
```


The else Statement

- Must follow an if statement, and only runs if the if condition is false
 - Like the if, if there is no block after an else, only the first line is run

```
if (condition) {  
    block of code to be executed if the condition is true  
} else {  
    block of code to be executed if the condition is false  
}
```

The else if Statement

- This specifies a new condition to check if the previous condition is false
 - Must be after an if statement, but can follow another else if statement
 - Like if and else, if there is no block, only the first line after the else if is run

```
if (condition1) {  
    block of code to be executed if condition1 is true  
} else if (condition2) {  
    block of code to be executed if the condition1 is false  
    and condition2 is true  
} else {  
    block of code to be executed if the condition1 is false and  
    condition2 is false  
}
```

Conditional (Ternary) Operator

- This operator assigns a value based on a condition
- Syntax: `variablename = (condition) ? value1:value2`
- Example:

```
var voteable = (age < 18) ? "Too young":"Old enough";
```

The switch Statement

- A switch evaluates an expression and has *cases* for different conditions

```
switch(expression) {  
    case n:  
        code block  
        break;  
    case n:  
        code block  
        break;  
    default:  
        code block  
}
```

The break Keyword

- In a switch, the keyword break exits a block and stops executing the rest of the switch
- Break statements should be at the end of each case block otherwise the switch will continue to check each case condition

```
switch (new Date().getDay()) {  
    case 6:  
        text = "Today is Saturday";  
        break;  
    case 0:  
        text = "Today is Sunday";  
        break;  
    default:  
        text = "Looking forward to the Weekend";  
}
```

The default Keyword

- The default case is executed if there is no other match for the expression
- It doesn't have to be the last case in the switch statement

```
switch (new Date().getDay()) {  
    default:  
        text = "Looking forward to the Weekend";  
        break;  
    case 6:  
        text = "Today is Saturday";  
        break;  
    case 0:  
        text = "Today is Sunday";  
}
```

Common Code Blocks

- Case blocks can/should only have one value
- If you have multiple cases for one block of code you can use the following

```
switch (new Date().getDay()) {  
    case 4:  
    case 5:  
        text = "Soon it is Weekend";  
        break;  
    case 0:  
    case 6:  
        text = "It is Weekend";  
        break;  
    default:  
        text = "Looking forward to the Weekend";  
}
```

Resources

https://www.w3schools.com/js/js_comparisons.asp

https://www.w3schools.com/js/js_if_else.asp

https://www.w3schools.com/js/js_switch.asp