Who controls the failover?



Sovereign global traffic management with Kubernetes

- **TRAFFIC MANAGEMENT**
- **DNS STEERING**
- **MULTI-REGION RESILIENCE**

Yury Tsarev · Creator & Project Lead, k8gb

24 October 2026 · Saarbrücken

From node resilience to cluster failover

Spread replicas, then widen the failure boundary.

01 NODES

One Kubernetes cluster




Spread replicas

Survive a worker failure.

02 AVAILABILITY ZONES

One Kubernetes cluster




Spread across zones

Survive a zone failure.

03 CLUSTERS

Independent clusters



Steer across clusters

Keep one application hostname.

When an entire cluster is unavailable, who steers the next request?

k8gb in one minute

Two or more clusters. No fixed cluster-count limit in k8gb.



CNCF INCUBATING

Kubernetes-native

Readiness becomes DNS eligibility.

Decentralized

A control loop at each participating cluster.

Declarative

Review traffic steering in Git.

Global application resilience across Kubernetes clusters.

From Absa production to CNCF incubation

An operational need grew into a community project.

PRODUCTION ORIGINS

Born at Absa

Multiple on-prem datacenters, then hybrid deployments

30 MAR 2021

CNCF Sandbox

Contributed to the cloud native community

PUBLIC ADOPTION

Beyond Absa

Millennium bcp
Open Systems
PagBank


18 JUL 2026

CNCF Incubating

A new milestone for the project and its community

Born from a production problem. Built with the community.

Independent clusters, shared DNS contract



Peer health is learned through DNS

One direction shown; each controller queries peer CoreDNS.

Three components. Three distinct jobs.



k8gb controller

Readiness + strategy
→ eligible targets



CoreDNS

Delegated zone
→ DNS answers




ExternalDNS

Delegation state
→ parent DNS updates


Decide locally. Answer authoritatively. Delegate explicitly.

Two k8gb reconciliation loops feed DNS



Membership refresh and application reconciliation run separately.


DNS selects an address. The client connects.



DNS is outside the application data path.

Delegation is the authority boundary

Parent DNS delegates the zone. CoreDNS answers application lookups.



A app.gslb.example.com → Eligible application IPs


Own the name, the delegation, and DNS recovery.

Choose how eligible clusters are used

Illustrative DNS selections across Kubernetes clusters.

FAILOVER


Prefer primary



Return to primary on recovery

ROUND ROBIN


Use healthy clusters



Active / active DNS answers

WEIGHTED ROUND ROBIN


Express preference



Request shares are approximate

GEOIP

Map client subnets



Needs GeoIP data + ECS

All modes change DNS answers, not existing connections.

Traffic steering with a declarative manifest

Gslb is a Kubernetes custom resource.


gslb.yaml — KUBERNETES CUSTOM RESOURCE

```yaml
apiVersion: k8gb.io/v1beta1
kind: Gslb
metadata:
  name: test-gslb-failover
  namespace: test-gslb
spec:
  resourceRef:
    apiVersion: gateway.networking.k8s.io/v1
    kind: HTTPRoute
    name: payments
  strategy:
    type: failover
    primaryGeoTag: eu
```

Prefer A · eu

While it has eligible targets.

Deploy per cluster



Each cluster observes health locally.

The route, zone, and matching geotags are prerequisites.

Kubernetes and DNS integrations

Run on-prem, in the cloud, or across both.

Conformant Kubernetes

NATIVE RESOURCE INTEGRATIONS

- Gateway API
- Ingress
- Istio VirtualService
- LoadBalancer Service

AUTOMATED PARENT-ZONE DELEGATION

- AWS Route 53
- Azure Public DNS
- Google Cloud DNS
- NS1
- Infoblox
- Cloudflare

RFC 2136
DNS updates

BIND9 · Windows DNS
TSIG / GSS-TSIG authentication

Choose your parent DNS. Keep your Gslb traffic strategy.

You define what a “region” means

Global traffic management can follow your own topology.

ILLUSTRATIVE clusterGeoTag VALUES



REGION

`eu-west`



DATACENTER

`dc-1`




RACK

`rack-a`



SERVER

`server-01`



CUSTOM

`sovereign-a`




Each tag identifies a k8gb cluster.

Rack or server boundaries use independent clusters, including single-node clusters.

Choose boundaries that match your sovereignty model.

One hostname. Two clusters.


All local. Two application clusters represent different locations.



Observe A → remove A's ready targets → watch B → restore A

Normal operation: both authorities prefer A

Both applications are ready. Cluster A is the preferred target.




Each k8gb controller queries peer CoreDNS.

Both authorities agree after reconciliation; client caches may lag.

A loses ready targets: publish B

A’s application is unready; its DNS authority is still available.




Each k8gb controller queries peer CoreDNS.

Both authorities agree after reconciliation; client caches may lag.

A recovers: the strategy returns to A

A’s application is ready again. The primary preference returns.



Each k8gb controller queries peer CoreDNS.

Both authorities agree after reconciliation; client caches may lag.

A new DNS answer is not an instant switch

Detection, DNS publication and client recovery happen at different times.



TIMING VARIES

Readiness · reconciliation · caches · retries

New DNS answer ≠ recovered clients

Measure recovery at the resolver and application.

Readiness must reflect the real operation

Kubernetes runs Pod probes. k8gb consumes EndpointSlice readiness.

`readinessProbe`
Application-defined check

→

Pod Ready
Kubernetes condition

→

EndpointSlice
Service endpoint readiness

→

Gslb targets
Readiness + traffic strategy

HEALTH ENDPOINT

`GET /healthz`

HTTP 200

The shallow check passes.

REAL REQUEST

Payment cannot be saved

Payment API
`POST /payments`

WRITE ✕


Database
READ-ONLY

Replication and safe writer ownership belong to the application.

k8gb steers traffic. The application must be ready to serve.

A partition can create two correct-looking answers

Both applications are ready. Clients can still reach both DNS authorities.



B cannot obtain A's peer-health answer.

A failed health query does not prove the application is down.

Traffic recovery is one part of availability

DNS failover, data recovery, and sessions need separate plans.

k8gb · TRAFFIC STEERING

FAILURE	DNS RESPONSE
APPLICATION Readiness lost	→ **Exclude unready targets**
CLUSTER / REGION Cluster unavailable	→ **Publish healthy cluster targets**

APPLICATION RESPONSIBILITY

STATEFUL DATA

Replication, fencing,
and recovery are yours.

Plan session recovery too.

Traffic recovery ≠ data recovery ≠ session continuity.

Test your traffic strategy in your environment



Define expectations	Expected routing for each scenario.
Rehearse scenarios	Failures and recovery in your environment.
Verify the result	DNS answers, real requests and timing.
Automate and repeat	Run the checks after changes.

Validate failover, failback, and every Gslb strategy you rely on.

The community behind k8gb

Public users, shared maintenance, open participation.



CNCF

Incubating

Since July 2026

7

public adopters

46

contributors

1,335

☆ **GitHub stars**

PUBLIC ADOPTERS

absa · Millennium bcp · eficode · Opensystems · 20 ANOS PagBank · DAREDE à nuvem · ENVIO

CNCF / GitHub · checked 23 October 2026

Meet the community Every other Wednesday · everyone welcome

Resilience in production

Millennium bcp · Results reported in a CNCF case study

DNS INCIDENT RESPONSE

70%

shorter response times

for DNS-related incidents

5

regions

Two cloud providers
+ on-premises

Zero downtime

Reported during regional failover tests

CNCF case study · 16 September 2025

cncf.io/case-studies/millennium-bcp

Published results from Millennium bcp’s deployment.

Questions?

Try k8gb, meet the maintainers, share your deployment.

Try k8gb



k8gb.io

STAR & CONTRIBUTE

github.com/k8gb-io/k8gb

JOIN THE CONVERSATION

#k8gb · CNCF Slack

Community meetings

SHARE YOUR DEPLOYMENT

Add your organization to ADOPTERS.md

Yury Tsarev

Creator & Project Lead · k8gb

linkedin.com/in/yurytsarev