

Data Wrangling

with pandas Cheat Sheet

<http://pandas.pydata.org>

[Pandas API Reference](#) [Pandas User Guide](#)

Creating DataFrames

	a	b	c
1	4	7	10
2	5	8	11
3	6	9	12

```
df = pd.DataFrame(  
    {"a" : [4, 5, 6],  
     "b" : [7, 8, 9],  
     "c" : [10, 11, 12]},  
    index = [1, 2, 3])
```

Specify values for each column.

```
df = pd.DataFrame(  
    [[4, 7, 10],  
     [5, 8, 11],  
     [6, 9, 12]],  
    index=[1, 2, 3],  
    columns=['a', 'b', 'c'])
```

Specify values for each row.

		a	b	c
N	v			
D	1	4	7	10
	2	5	8	11
e	2	6	9	12

```
df = pd.DataFrame(  
    {"a" : [4, 5, 6],  
     "b" : [7, 8, 9],  
     "c" : [10, 11, 12]},  
    index = pd.MultiIndex.from_tuples(  
        [('d', 1), ('d', 2),  
         ('e', 2)], names=['n', 'v']))
```

Create DataFrame with a MultiIndex

Method Chaining

Most pandas methods return a DataFrame so that another pandas method can be applied to the result. This improves readability of code.

```
df = (pd.melt(df)  
      .rename(columns={  
          'variable': 'var',  
          'value': 'val'})  
      .query('val >= 200'))
```

Tidy Data – A foundation for wrangling in pandas

In a tidy data set:




Each **variable** is saved in its own **column**

&



Each **observation** is saved in its own **row**

Tidy data complements pandas's **vectorized operations**. pandas will automatically preserve observations as you manipulate variables. No other format works as intuitively with pandas.



M * A

Reshaping Data – Change layout, sorting, reindexing, renaming



`pd.melt(df)`
Gather columns into rows.



`df.pivot(columns='var', values='val')`
Spread rows into columns.



`pd.concat([df1, df2])`
Append rows of DataFrames



`pd.concat([df1, df2], axis=1)`
Append columns of DataFrames

`df.sort_values('mpg')`
Order rows by values of a column (low to high).

`df.sort_values('mpg', ascending=False)`
Order rows by values of a column (high to low).

`df.rename(columns = {'y': 'year'})`
Rename the columns of a DataFrame

`df.sort_index()`
Sort the index of a DataFrame

`df.reset_index()`
Reset index of DataFrame to row numbers, moving index to columns.

`df.drop(columns=['Length', 'Height'])`
Drop columns from DataFrame

Subset Observations - rows



`df[df.Length > 7]`
Extract rows that meet logical criteria.

`df.drop_duplicates()`
Remove duplicate rows (only considers columns).

`df.sample(frac=0.5)`
Randomly select fraction of rows.

`df.sample(n=10)` Randomly select n rows.

`df.nlargest(n, 'value')`
Select and order top n entries.

`df.nsmallest(n, 'value')`
Select and order bottom n entries.

`df.head(n)`
Select first n rows.

`df.tail(n)`
Select last n rows.

Subset Variables - columns



`df[['width', 'length', 'species']]`
Select multiple columns with specific names.

`df['width']` or `df.width`
Select single column with specific name.

`df.filter(regex='regex')`
Select columns whose name matches regular expression *regex*.

Using query

`query()` allows Boolean expressions for filtering rows.

`df.query('Length > 7')`

`df.query('Length > 7 and Width < 8')`

`df.query('Name.str.startswith("abc")', engine="python")`

Subsets - rows and columns

Use `df.loc[]` and `df.iloc[]` to select only rows, only columns or both.

Use `df.at[]` and `df.iat[]` to access a single value by row and column.

First index selects rows, second index columns.

`df.iloc[10:20]`
Select rows 10-20.

`df.iloc[:, [1, 2, 5]]`
Select columns in positions 1, 2 and 5 (first column is 0).

`df.loc[:, 'x2': 'x4']`
Select all columns between x2 and x4 (inclusive).

`df.loc[df['a'] > 10, ['a', 'c']]`
Select rows meeting logical condition, and only the specific columns.

`df.iat[1, 2]` Access single value by index

`df.at[4, 'A']` Access single value by label

Logic in Python (and pandas)			
<	Less than	<code>!=</code>	Not equal to
>	Greater than	<code>df.column.isin(values)</code>	Group membership
==	Equals	<code>pd.isnull(obj)</code>	Is NaN
<=	Less than or equals	<code>pd.notnull(obj)</code>	Is not NaN
>=	Greater than or equals	<code>&, , ~, ^, df.any(), df.all()</code>	Logical and, or, not, xor, any, all

regex (Regular Expressions) Examples	
<code>'\.'</code>	Matches strings containing a period '.'
<code>'Length\$'</code>	Matches strings ending with word 'Length'
<code>'^Sepal'</code>	Matches strings beginning with the word 'Sepal'
<code>'^x[1-5]\$'</code>	Matches strings beginning with 'x' and ending with 1,2,3,4,5
<code>'^(?!Species\$).*\$'</code>	Matches strings except the string 'Species'

Summarize Data

`df['w'].value_counts()`

Count number of rows with each unique value of variable

`len(df)`

of rows in DataFrame.

`df.shape`


Tuple of # of rows, # of columns in DataFrame.

`df['w'].nunique()`

of distinct values in a column.

`df.describe()`

Basic descriptive and statistics for each column (or GroupBy).



pandas provides a large set of [summary functions](#) that operate on different kinds of pandas objects (DataFrame columns, Series, GroupBy, Expanding and Rolling (see below)) and produce single values for each of the groups. When applied to a DataFrame, the result is returned as a pandas Series for each column. Examples:

`sum()`

Sum values of each object.

`count()`

Count non-NA/null values of each object.

`median()`

Median value of each object.

`quantile([0.25, 0.75])`

Quantiles of each object.

`apply(function)`

Apply function to each object.

`min()`

Minimum value in each object.

`max()`

Maximum value in each object.

`mean()`

Mean value of each object.

`var()`

Variance of each object.

`std()`

Standard deviation of each object.

Group Data



`df.groupby(by="col")`

Return a GroupBy object, grouped by values in column named "col".

`df.groupby(level="ind")`

Return a GroupBy object, grouped by values in index level named "ind".

All of the summary functions listed above can be applied to a group. Additional GroupBy functions:

`size()`

Size of each group.

`agg(function)`

Aggregate group using function.

Windows

`df.expanding()`

Return an Expanding object allowing summary functions to be applied cumulatively.

`df.rolling(n)`

Return a Rolling object allowing summary functions to be applied to windows of length n.

Handling Missing Data


`df.dropna()`

Drop rows with any column having NA/null data.

`df.fillna(value)`

Replace all NA/null data with value.

Make New Columns



`df.assign(Area=lambda df: df.Length*df.Height)`

Compute and append one or more new columns.

`df['Volume'] = df.Length*df.Height*df.Depth`

Add single column.

`pd.qcut(df.col, n, labels=False)`

Bin column into n buckets.



pandas provides a large set of **vector functions** that operate on all columns of a DataFrame or a single selected column (a pandas Series). These functions produce vectors of values for each of the columns, or a single Series for the individual Series. Examples:

`max(axis=1)`

Element-wise max.

`min(axis=1)`

Element-wise min.

`clip(lower=-10, upper=10)`

Trim values at input thresholds

`abs()`

Absolute value.

The examples below can also be applied to groups. In this case, the function is applied on a per-group basis, and the returned vectors are of the length of the original DataFrame.

`shift(1)`

Copy with values shifted by 1.

`rank(method='dense')`

Ranks with no gaps.

`rank(method='min')`

Ranks. Ties get min rank.

`rank(pct=True)`

Ranks rescaled to interval [0, 1].

`rank(method='first')`

Ranks. Ties go to first value.

`shift(-1)`

Copy with values lagged by 1.

`cumsum()`

Cumulative sum.

`cummax()`

Cumulative max.

`cummin()`

Cumulative min.


`cumprod()`

Cumulative product.

Plotting


`df.plot.hist()`

Histogram for each column



`df.plot.scatter(x='w', y='h')`

Scatter chart using pairs of points



Combine Data Sets

adf

x1	x2
A	1
B	2
C	3

bdf

x1	x3
A	T
B	F
D	T



Standard Joins

x1	x2	x3
A	1	T
B	2	F
C	3	NaN

`pd.merge(adf, bdf, how='left', on='x1')`
Join matching rows from bdf to adf.

x1	x2	x3
A	1.0	T
B	2.0	F
D	NaN	T

`pd.merge(adf, bdf, how='right', on='x1')`
Join matching rows from adf to bdf.

x1	x2	x3
A	1	T
B	2	F

`pd.merge(adf, bdf, how='inner', on='x1')`
Join data. Retain only rows in both sets.

x1	x2	x3
A	1	T
B	2	F
C	3	NaN
D	NaN	T

`pd.merge(adf, bdf, how='outer', on='x1')`
Join data. Retain all values, all rows.

Filtering Joins

x1	x2
A	1
B	2

`adf[adf.x1.isin(bdf.x1)]`
All rows in adf that have a match in bdf.

x1	x2
C	3

`adf[~adf.x1.isin(bdf.x1)]`
All rows in adf that do not have a match in bdf.

ydf

x1	x2
A	1
B	2
C	3

zdf

x1	x2
B	2
C	3
D	4



Set-like Operations

x1	x2
B	2
C	3

`pd.merge(ydf, zdf)`
Rows that appear in both ydf and zdf (Intersection).

x1	x2
A	1
B	2
C	3
D	4

`pd.merge(ydf, zdf, how='outer')`
Rows that appear in either or both ydf and zdf (Union).

x1	x2
A	1

`pd.merge(ydf, zdf, how='outer', indicator=True)`
`.query('_merge == "left_only"')`
`.drop(columns=['_merge'])`
Rows that appear in ydf but not zdf (Setdiff).



Data Science Cheat Sheet

NumPy

KEY

*We'll use shorthand in this cheat sheet***arr** - A numpy Array object

IMPORTS

*Import these to start***import numpy as np**

IMPORTING/EXPORTING

np.loadtxt('file.txt') - From a text file**np.genfromtxt('file.csv', delimiter=',')**
- From a CSV file**np.savetxt('file.txt', arr, delimiter=' ')**
- Writes to a text file**np.savetxt('file.csv', arr, delimiter=',')**
- Writes to a CSV file

CREATING ARRAYS

np.array([1,2,3]) - One dimensional array**np.array([(1,2,3), (4,5,6)])** - Two dimensional array**np.zeros(3)** - 1D array of length 3 all values 0**np.ones((3,4))** - 3x4 array with all values 1**np.eye(5)** - 5x5 array of 0 with 1 on diagonal (Identity matrix)**np.linspace(0,100,6)** - Array of 6 evenly divided values from 0 to 100**np.arange(0,10,3)** - Array of values from 0 to less than 10 with step 3 (eg [0,3,6,9])**np.full((2,3),8)** - 2x3 array with all values 8**np.random.rand(4,5)** - 4x5 array of random floats between 0-1**np.random.rand(6,7)*100** - 6x7 array of random floats between 0-100**np.random.randint(5, size=(2,3))** - 2x3 array with random ints between 0-4

INSPECTING PROPERTIES

arr.size - Returns number of elements in **arr****arr.shape** - Returns dimensions of **arr** (rows, columns)**arr.dtype** - Returns type of elements in **arr****arr.astype(dtype)** - Convert **arr** elements to type **dtype****arr.tolist()** - Convert **arr** to a Python list**np.info(np.eye)** - View documentation for **np.eye**

COPYING/SORTING/RESHAPING

np.copy(arr) - Copies **arr** to new memory**arr.view(dtype)** - Creates view of **arr** elements with type **dtype****arr.sort()** - Sorts **arr****arr.sort(axis=0)** - Sorts specific axis of **arr****two_d_arr.flatten()** - Flattens 2D array **two_d_arr** to 1D**arr.T** - Transposes **arr** (rows become columns and vice versa)**arr.reshape(3,4)** - Reshapes **arr** to 3 rows, 4 columns without changing data**arr.resize((5,6))** - Changes **arr** shape to 5x6 and fills new values with 0

ADDING/REMOVING ELEMENTS

np.append(arr, values) - Appends **values** to end of **arr****np.insert(arr, 2, values)** - Inserts **values** into **arr** before index 2**np.delete(arr, 3, axis=0)** - Deletes row on index 3 of **arr****np.delete(arr, 4, axis=1)** - Deletes column on index 4 of **arr**

COMBINING/SPLITTING

np.concatenate((arr1, arr2), axis=0) - Adds **arr2** as rows to the end of **arr1****np.concatenate((arr1, arr2), axis=1)** - Adds **arr2** as columns to end of **arr1****np.split(arr, 3)** - Splits **arr** into 3 sub-arrays**np.hsplit(arr, 5)** - Splits **arr** horizontally on the 5th index

INDEXING/SLICING/SUBSETTING

arr[5] - Returns the element at index 5**arr[2,5]** - Returns the 2D array element on index [2][5]**arr[1]=4** - Assigns array element on index 1 the value 4**arr[1,3]=10** - Assigns array element on index [1][3] the value 10**arr[0:3]** - Returns the elements at indices 0,1,2 (On a 2D array: returns rows 0,1,2)**arr[0:3,4]** - Returns the elements on rows 0,1,2 at column 4**arr[:2]** - Returns the elements at indices 0,1 (On a 2D array: returns rows 0,1)**arr[:,1]** - Returns the elements at index 1 on all rows**arr<5** - Returns an array with boolean values (**arr1<3** & **arr2>5**) - Returns an array with boolean values**~arr** - Inverts a boolean array**arr[arr<5]** - Returns array elements smaller than 5

SCALAR MATH

np.add(arr,1) - Add 1 to each array element**np.subtract(arr,2)** - Subtract 2 from each array element**np.multiply(arr,3)** - Multiply each array element by 3**np.divide(arr,4)** - Divide each array element by 4 (returns **np.nan** for division by zero)**np.power(arr,5)** - Raise each array element to the 5th power

VECTOR MATH

np.add(arr1, arr2) - Elementwise add **arr2** to **arr1****np.subtract(arr1, arr2)** - Elementwise subtract **arr2** from **arr1****np.multiply(arr1, arr2)** - Elementwise multiply **arr1** by **arr2****np.divide(arr1, arr2)** - Elementwise divide **arr1** by **arr2****np.power(arr1, arr2)** - Elementwise raise **arr1** raised to the power of **arr2****np.array_equal(arr1, arr2)** - Returns **True** if the arrays have the same elements and shape**np.sqrt(arr)** - Square root of each element in the array**np.sin(arr)** - Sine of each element in the array**np.log(arr)** - Natural log of each element in the array**np.abs(arr)** - Absolute value of each element in the array**np.ceil(arr)** - Rounds up to the nearest int**np.floor(arr)** - Rounds down to the nearest int**np.round(arr)** - Rounds to the nearest int

STATISTICS

np.mean(arr, axis=0) - Returns mean along specific axis**arr.sum()** - Returns sum of **arr****arr.min()** - Returns minimum value of **arr****arr.max(axis=0)** - Returns maximum value of specific axis**np.var(arr)** - Returns the variance of array**np.std(arr, axis=1)** - Returns the standard deviation of specific axis**arr.corrcoef()** - Returns correlation coefficient of array

Python For Data Science Cheat Sheet

NumPy Basics

Learn Python for Data Science Interactively at [www.DataCamp.com](https://www.datacamp.com)



NumPy

The NumPy library is the core library for scientific computing in Python. It provides a high-performance multidimensional array object, and tools for working with these arrays.

Use the following import convention:



```
>>> import numpy as np
```

NumPy Arrays

1D array

```
1 2 3
```

2D array

axis 1
axis 0

```
1.5 2 3  
4 5 6
```

3D array

axis 2
axis 1
axis 0

Creating Arrays

```
>>> a = np.array([1,2,3])  
>>> b = np.array([(1.5,2,3), (4,5,6)], dtype = float)  
>>> c = np.array([(1.5,2,3), (4,5,6)], [(3,2,1), (4,5,6)]],  
                dtype = float)
```

Initial Placeholders

```
>>> np.zeros((3,4))  
>>> np.ones((2,3,4),dtype=np.int16)  
>>> d = np.arange(10,25,5)  
  
>>> np.linspace(0,2,9)  
  
>>> e = np.full((2,2),7)  
>>> f = np.eye(2)  
>>> np.random.random((2,2))  
>>> np.empty((3,2))
```

Create an array of zeros
Create an array of ones
Create an array of evenly spaced values (step value)
Create an array of evenly spaced values (number of samples)
Create a constant array
Create a 2X2 identity matrix
Create an array with random values
Create an empty array

I/O

Saving & Loading On Disk

```
>>> np.save('my_array', a)  
>>> np.savez('array.npz', a, b)  
>>> np.load('my_array.npy')
```

Saving & Loading Text Files

```
>>> np.loadtxt("myfile.txt")  
>>> np.genfromtxt("my_file.csv", delimiter=',')  
>>> np.savetxt("myarray.txt", a, delimiter=" ")
```

Data Types

```
>>> np.int64  
>>> np.float32  
>>> np.complex  
>>> np.bool  
>>> np.object  
>>> np.string_  
>>> np.unicode_
```

Signed 64-bit integer types
Standard double-precision floating point
Complex numbers represented by 128 floats
Boolean type storing TRUE and FALSE values
Python object type
Fixed-length string type
Fixed-length unicode type

Inspecting Your Array

```
>>> a.shape  
>>> len(a)  
>>> b.ndim  
>>> e.size  
>>> b.dtype  
>>> b.dtype.name  
>>> b.astype(int)
```

Array dimensions
Length of array
Number of array dimensions
Number of array elements
Data type of array elements
Name of data type
Convert an array to a different type

Asking For Help

```
>>> np.info(np.ndarray.dtype)
```

Array Mathematics

Arithmetic Operations

```
>>> g = a - b  
array([[ -0.5,  0. ,  0. ],  
       [ -3. , -3. , -3. ]])  
>>> np.subtract(a,b)  
>>> b + a  
array([[ 2.5,  4. ,  6. ],  
       [ 5. ,  7. ,  9. ]])  
>>> np.add(b,a)  
>>> a / b  
array([[ 0.66666667,  1. ,  1. ],  
       [ 0.25 ,  0.4 ,  0.5 ]])  
>>> np.divide(a,b)  
>>> a * b  
array([[ 1.5,  4. ,  9. ],  
       [ 4. , 10. , 18. ]])  
>>> np.multiply(a,b)  
>>> np.exp(b)  
>>> np.sqrt(b)  
>>> np.sin(a)  
>>> np.cos(b)  
>>> np.log(a)  
>>> e.dot(f)  
array([[ 7. ,  7. ],  
       [ 7. ,  7.]])
```

Subtraction
Subtraction
Addition
Addition
Division
Division
Multiplication
Multiplication
Exponentiation
Square root
Print sines of an array
Element-wise cosine
Element-wise natural logarithm
Dot product

Comparison

```
>>> a == b  
array([[False,  True,  True],  
       [False, False, False]], dtype=bool)  
>>> a < 2  
array([[True, False, False], dtype=bool)  
>>> np.array_equal(a, b)
```

Element-wise comparison
Element-wise comparison
Array-wise comparison

Aggregate Functions

```
>>> a.sum()  
>>> a.min()  
>>> b.max(axis=0)  
>>> b.cumsum(axis=1)  
>>> a.mean()  
>>> b.median()  
>>> a.corrcoef()  
>>> np.std(b)
```

Array-wise sum
Array-wise minimum value
Maximum value of an array row
Cumulative sum of the elements
Mean
Median
Correlation coefficient
Standard deviation

Copying Arrays

```
>>> h = a.view()  
>>> np.copy(a)  
>>> h = a.copy()
```

Create a view of the array with the same data
Create a copy of the array
Create a deep copy of the array

Sorting Arrays

```
>>> a.sort()  
>>> c.sort(axis=0)
```

Sort an array
Sort the elements of an array's axis

Subsetting, Slicing, Indexing

Also see Lists

Subsetting

```
>>> a[2]  
3  
>>> b[1,2]  
6.0
```

Select the element at the 2nd index
Select the element at row 1 column 2 (equivalent to b[1][2])

Slicing

```
>>> a[0:2]  
array([1, 2])  
>>> b[0:2,1]  
array([ 2.,  5.])  
>>> b[:1]  
array([[1.5, 2., 3.]])  
>>> c[1,...]  
array([[ 3.,  2.,  1.],  
       [ 4.,  5.,  6.]])
```

Select items at index 0 and 1
Select items at rows 0 and 1 in column 1
Select all items at row 0 (equivalent to b[0:1, :])
Same as [1, :, :]

Boolean Indexing

```
>>> a[a<2]  
array([1])
```

Reversed array a
Select elements from a less than 2

Fancy Indexing

```
>>> b[[1, 0, 1, 0], [0, 1, 2, 0]]  
array([ 4. ,  2. ,  6. , 1.5])  
>>> b[[1, 0, 1, 0]][:, [0,1,2,0]]  
array([[ 4. ,  5. ,  6. ,  4. ],  
       [ 1.5,  2. ,  3. , 1.5],  
       [ 4. ,  5. ,  6. ,  4. ],  
       [ 1.5,  2. ,  3. , 1.5]])
```

Select elements (1,0), (0,1), (1,2) and (0,0)
Select a subset of the matrix's rows and columns

Array Manipulation

Transposing Array

```
>>> i = np.transpose(b)  
>>> i.T
```

Permute array dimensions
Permute array dimensions

Changing Array Shape

```
>>> b.ravel()  
>>> g.reshape(3,-2)
```

Flatten the array
Reshape, but don't change data

Adding/Removing Elements

```
>>> h.resize((2,6))  
>>> np.append(h,g)  
>>> np.insert(a, 1, 5)  
>>> np.delete(a, [1])
```

Return a new array with shape (2,6)
Append items to an array
Insert items in an array
Delete items from an array

Combining Arrays

```
>>> np.concatenate((a,d),axis=0)  
array([ 1,  2,  3, 10, 15, 20])  
>>> np.vstack((a,b))  
array([[ 1. ,  2. ,  3. ],  
       [ 1.5,  2. ,  3. ],  
       [ 4. ,  5. ,  6. ]])  
>>> np.r_[e,f]  
>>> np.hstack((e,f))  
array([[ 7.,  7.,  1.,  0.],  
       [ 7.,  7.,  0.,  1.]])  
>>> np.column_stack((a,d))  
array([[ 1, 10],  
       [ 2, 15],  
       [ 3, 20]])  
>>> np.c_[a,d]
```

Concatenate arrays
Stack arrays vertically (row-wise)
Stack arrays vertically (row-wise)
Stack arrays horizontally (column-wise)
Create stacked column-wise arrays
Create stacked column-wise arrays

Splitting Arrays

```
>>> np.hsplit(a,3)  
[array([1]),array([2]),array([3])]  
>>> np.vsplit(c,2)  
[array([[ 1.5,  2. ,  1. ],  
       [ 4. ,  5. ,  6. ]]),  
 array([[ 3.,  2.,  3.],  
       [ 4. ,  5. ,  6.]])]
```

Split the array horizontally at the 3rd index
Split the array vertically at the 2nd index

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

Matplotlib

Learn Python Interactively at [www.DataCamp.com](https://www.datacamp.com)



Matplotlib

Matplotlib is a Python 2D plotting library which produces publication-quality figures in a variety of hardcopy formats and interactive environments across platforms.



1 Prepare The Data

Also see [Lists & NumPy](#)

1D Data

```
>>> import numpy as np
>>> x = np.linspace(0, 10, 100)
>>> y = np.cos(x)
>>> z = np.sin(x)
```

2D Data or Images

```
>>> data = 2 * np.random.random((10, 10))
>>> data2 = 3 * np.random.random((10, 10))
>>> Y, X = np.mgrid[-3:3:100j, -3:3:100j]
>>> U = -1 - X**2 + Y
>>> V = 1 + X - Y**2
>>> from matplotlib.cbook import get_sample_data
>>> img = np.load(get_sample_data('axes_grid/bivariate_normal.npy'))
```

2 Create Plot

```
>>> import matplotlib.pyplot as plt
```

Figure

```
>>> fig = plt.figure()
>>> fig2 = plt.figure(figsize=plt.figaspect(2.0))
```

Axes

All plotting is done with respect to an Axes. In most cases, a subplot will fit your needs. A subplot is an axes on a grid system.

```
>>> fig.add_axes()
>>> ax1 = fig.add_subplot(221) # row-col-num
>>> ax3 = fig.add_subplot(212)
>>> fig3, axes = plt.subplots(nrows=2,ncols=2)
>>> fig4, axes2 = plt.subplots(ncols=3)
```

3 Plotting Routines

1D Data

<pre>>>> lines = ax.plot(x,y) >>> ax.scatter(x,y) >>> axes[0,0].bar([1,2,3],[3,4,5]) >>> axes[1,0].barh([0.5,1,2.5],[0,1,2]) >>> axes[1,1].axhline(0.45) >>> axes[0,1].axvline(0.65) >>> ax.fill(x,y,color='blue') >>> ax.fill_between(x,y,color='yellow')</pre>	<p>Draw points with lines or markers connecting them</p> <p>Draw unconnected points, scaled or colored</p> <p>Plot vertical rectangles (constant width)</p> <p>Plot horizontal rectangles (constant height)</p> <p>Draw a horizontal line across axes</p> <p>Draw a vertical line across axes</p> <p>Draw filled polygons</p> <p>Fill between y-values and 0</p>
--	--

2D Data or Images

<pre>>>> fig, ax = plt.subplots() >>> im = ax.imshow(img, cmap='gist_earth', interpolation='nearest', vmin=-2, vmax=2)</pre>	Colormapped or RGB arrays
--	---------------------------

Vector Fields

<pre>>>> axes[0,1].arrow(0,0,0.5,0.5) >>> axes[1,1].quiver(y,z) >>> axes[0,1].streamplot(X,Y,U,V)</pre>	<p>Add an arrow to the axes</p> <p>Plot a 2D field of arrows</p> <p>Plot 2D vector fields</p>
--	---


Data Distributions

<pre>>>> ax1.hist(y) >>> ax3.boxplot(y) >>> ax3.violinplot(z)</pre>	<p>Plot a histogram</p> <p>Make a box and whisker plot</p> <p>Make a violin plot</p>
--	--

<pre>>>> axes2[0].pcolor(data2) >>> axes2[0].pcolormesh(data) >>> CS = plt.contour(Y,X,U) >>> axes2[2].contourf(data1) >>> axes2[2] = ax.clabel(CS)</pre>	<p>Pseudocolor plot of 2D array</p> <p>Pseudocolor plot of 2D array</p> <p>Plot contours</p> <p>Plot filled contours</p> <p>Label a contour plot</p>
--	--

Plot Anatomy & Workflow

Plot Anatomy



Workflow

The basic steps to creating plots with matplotlib are:

- 1 Prepare data
- 2 Create plot
- 3 Plot
- 4 Customize plot
- 5 Save plot
- 6 Show plot

```
>>> import matplotlib.pyplot as plt
>>> x = [1,2,3,4]
>>> y = [10,20,25,30]
>>> fig = plt.figure()
>>> ax = fig.add_subplot(111)
>>> ax.plot(x, y, color='lightblue', linewidth=3)
>>> ax.scatter([2,4,6],
    [5,15,25],
    color='darkgreen',
    marker='^')
>>> ax.set_xlim(1, 6.5)
>>> plt.savefig('foo.png')
>>> plt.show()
```

4 Customize Plot

Colors, Color Bars & Color Maps

```
>>> plt.plot(x, x, x, x**2, x, x**3)
>>> ax.plot(x, y, alpha = 0.4)
>>> ax.plot(x, y, c='k')
>>> fig.colorbar(im, orientation='horizontal')
>>> im = ax.imshow(img,
    cmap='seismic')
```

Markers

```
>>> fig, ax = plt.subplots()
>>> ax.scatter(x,y,marker=".")
>>> ax.plot(x,y,marker="o")
```

Linestyles

```
>>> plt.plot(x,y,linewidth=4.0)
>>> plt.plot(x,y,ls='solid')
>>> plt.plot(x,y,ls='--')
>>> plt.plot(x,y,'--',x**2,y**2,'-.')
>>> plt.setp(lines,color='r',linewidth=4.0)
```

Text & Annotations

```
>>> ax.text(1,
    -2.1,
    'Example Graph',
    style='italic')
>>> ax.annotate("Sine",
    xy=(8, 0),
    xycoords='data',
    xytext=(10.5, 0),
    textcoords='data',
    arrowprops=dict(arrowstyle="->",
        connectionstyle="arc3"),)
```

Mathtext

```
>>> plt.title(r'$\sigma_i=15$', fontsize=20)
```

Limits, Legends & Layouts

Limits & Autoscaling

```
>>> ax.margins(x=0.0,y=0.1)
>>> ax.axis('equal')
>>> ax.set(xlim=[0,10.5],ylim=[-1.5,1.5])
>>> ax.set_xlim(0,10.5)
```

Legends

```
>>> ax.set(title='An Example Axes',
    ylabel='Y-Axis',
    xlabel='X-Axis')
>>> ax.legend(loc='best')
```

Ticks

```
>>> ax.xaxis.set(ticks=range(1,5),
    ticklabels=[3,100,-12,"foo"])
>>> ax.tick_params(axis='y',
    direction='inout',
    length=10)
```

Subplot Spacing

```
>>> fig3.subplots_adjust(wspace=0.5,
    hspace=0.3,
    left=0.125,
    right=0.9,
    top=0.9,
    bottom=0.1)
```

```
>>> fig.tight_layout()
```

Axis Spines

```
>>> ax1.spines['top'].set_visible(False)
>>> ax1.spines['bottom'].set_position(('outward',10))
```

Add padding to a plot

Set the aspect ratio of the plot to 1

Set limits for x-and y-axis

Set limits for x-axis

Set a title and x-and y-axis labels

No overlapping plot elements

Manually set x-ticks

Make y-ticks longer and go in and out

Adjust the spacing between subplots

Fit subplot(s) in to the figure area

Make the top axis line for a plot invisible

Move the bottom axis line outward

5 Save Plot

Save figures

```
>>> plt.savefig('foo.png')
```

Save transparent figures

```
>>> plt.savefig('foo.png', transparent=True)
```

6 Show Plot

```
>>> plt.show()
```

Close & Clear

```
>>> plt.cla()
>>> plt.clf()
>>> plt.close()
```

DataCamp

Learn Python for Data Science Interactively



Python For Data Science Cheat Sheet

Scikit-Learn

Learn Python for data science [Interactively](#) at [www.DataCamp.com](#)



Scikit-learn

Scikit-learn is an open source Python library that implements a range of machine learning, preprocessing, cross-validation and visualization algorithms using a unified interface.



A Basic Example

```
>>> from sklearn import neighbors, datasets, preprocessing
>>> from sklearn.model_selection import train_test_split
>>> from sklearn.metrics import accuracy_score
>>> iris = datasets.load_iris()
>>> X, y = iris.data[:, :2], iris.target
>>> X_train, X_test, y_train, y_test = train_test_split(X, y, random_state=33)
>>> scaler = preprocessing.StandardScaler().fit(X_train)
>>> X_train = scaler.transform(X_train)
>>> X_test = scaler.transform(X_test)
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
>>> knn.fit(X_train, y_train)
>>> y_pred = knn.predict(X_test)
>>> accuracy_score(y_test, y_pred)
```

Loading The Data

Also see NumPy & Pandas

Your data needs to be numeric and stored as NumPy arrays or SciPy sparse matrices. Other types that are convertible to numeric arrays, such as Pandas DataFrame, are also acceptable.

```
>>> import numpy as np
>>> X = np.random.random((10,5))
>>> y = np.array(['M', 'M', 'F', 'F', 'M', 'F', 'M', 'F', 'F', 'F'])
>>> X[X < 0.7] = 0
```

Training And Test Data

```
>>> from sklearn.model_selection import train_test_split
>>> X_train, X_test, y_train, y_test = train_test_split(X,
                                                    y,
                                                    random_state=0)
```

Preprocessing The Data

Standardization

```
>>> from sklearn.preprocessing import StandardScaler
>>> scaler = StandardScaler().fit(X_train)
>>> standardized_X = scaler.transform(X_train)
>>> standardized_X_test = scaler.transform(X_test)
```

Normalization

```
>>> from sklearn.preprocessing import Normalizer
>>> scaler = Normalizer().fit(X_train)
>>> normalized_X = scaler.transform(X_train)
>>> normalized_X_test = scaler.transform(X_test)
```

Binarization

```
>>> from sklearn.preprocessing import Binarizer
>>> binarizer = Binarizer(threshold=0.0).fit(X)
>>> binary_X = binarizer.transform(X)
```

Create Your Model

Supervised Learning Estimators

```
Linear Regression
>>> from sklearn.linear_model import LinearRegression
>>> lr = LinearRegression(normalize=True)

Support Vector Machines (SVM)
>>> from sklearn.svm import SVC
>>> svc = SVC(kernel='linear')

Naïve Bayes
>>> from sklearn.naive_bayes import GaussianNB
>>> gnb = GaussianNB()

KNN
>>> from sklearn import neighbors
>>> knn = neighbors.KNeighborsClassifier(n_neighbors=5)
```

Unsupervised Learning Estimators

```
Principal Component Analysis (PCA)
>>> from sklearn.decomposition import PCA
>>> pca = PCA(n_components=0.95)

K Means
>>> from sklearn.cluster import KMeans
>>> k_means = KMeans(n_clusters=3, random_state=0)
```

Model Fitting

Supervised learning	Fit the model to the data
<pre>>>> lr.fit(X, y) >>> knn.fit(X_train, y_train) >>> svc.fit(X_train, y_train)</pre>	
Unsupervised Learning	Fit the model to the data
<pre>>>> k_means.fit(X_train) >>> pca_model = pca.fit_transform(X_train)</pre>	Fit to data, then transform it

Prediction

Supervised Estimators	Predict labels
<pre>>>> y_pred = svc.predict(np.random.random((2,5))) >>> y_pred = lr.predict(X_test) >>> y_pred = knn.predict_proba(X_test)</pre>	Predict labels
Unsupervised Estimators	Estimate probability of a label
<pre>>>> y_pred = k_means.predict(X_test)</pre>	Predict labels in clustering algos

Evaluate Your Model's Performance

Classification Metrics

Accuracy Score	Estimator score method
<pre>>>> knn.score(X_test, y_test) >>> from sklearn.metrics import accuracy_score >>> accuracy_score(y_test, y_pred)</pre>	Metric scoring functions
Classification Report	Precision, recall, f1-score and support
<pre>>>> from sklearn.metrics import classification_report >>> print(classification_report(y_test, y_pred))</pre>	
Confusion Matrix	
<pre>>>> from sklearn.metrics import confusion_matrix >>> print(confusion_matrix(y_test, y_pred))</pre>	

Regression Metrics

Mean Absolute Error
<pre>>>> from sklearn.metrics import mean_absolute_error >>> y_true = [3, -0.5, 2] >>> mean_absolute_error(y_true, y_pred)</pre>
Mean Squared Error
<pre>>>> from sklearn.metrics import mean_squared_error >>> mean_squared_error(y_true, y_pred)</pre>
R² Score
<pre>>>> from sklearn.metrics import r2_score >>> r2_score(y_true, y_pred)</pre>

Clustering Metrics

Adjusted Rand Index
<pre>>>> from sklearn.metrics import adjusted_rand_score >>> adjusted_rand_score(y_true, y_pred)</pre>
Homogeneity
<pre>>>> from sklearn.metrics import homogeneity_score >>> homogeneity_score(y_true, y_pred)</pre>
V-measure
<pre>>>> from sklearn.metrics import v_measure_score >>> metrics.v_measure_score(y_true, y_pred)</pre>

Cross-Validation

```
>>> from sklearn.cross_validation import cross_val_score
>>> print(cross_val_score(knn, X_train, y_train, cv=4))
>>> print(cross_val_score(lr, X, y, cv=2))
```

Tune Your Model

Grid Search

```
>>> from sklearn.grid_search import GridSearchCV
>>> params = {"n_neighbors": np.arange(1,5),
            "metric": ["euclidean", "cityblock"]}
>>> grid = GridSearchCV(estimator=knn,
                      param_grid=params)
>>> grid.fit(X_train, y_train)
>>> print(grid.best_score_)
>>> print(grid.best_estimator_.n_neighbors)
```

Randomized Parameter Optimization

```
>>> from sklearn.grid_search import RandomizedSearchCV
>>> params = {"n_neighbors": range(1,5),
            "weights": ["uniform", "distance"]}
>>> rsearch = RandomizedSearchCV(estimator=knn,
                               param_distributions=params,
                               cv=4,
                               n_iter=8,
                               random_state=5)
>>> rsearch.fit(X_train, y_train)
>>> print(rsearch.best_score_)
```

Encoding Categorical Features

```
>>> from sklearn.preprocessing import LabelEncoder
>>> enc = LabelEncoder()
>>> y = enc.fit_transform(y)
```

Imputing Missing Values

```
>>> from sklearn.preprocessing import Imputer
>>> imp = Imputer(missing_values=0, strategy='mean', axis=0)
>>> imp.fit_transform(X_train)
```

Generating Polynomial Features

```
>>> from sklearn.preprocessing import PolynomialFeatures
>>> poly = PolynomialFeatures(5)
>>> poly.fit_transform(X)
```



scikit-learn
algorithm cheat-sheet