

Personalized Prediction of Bounded-Rational Bargaining Behavior in Network Resource Sharing

Haoran Yu (presenter) and Fan Li

School of Computer Science & Technology
Beijing Institute of Technology

May 2024 @ IEEE INFOCOM

Background

Bargaining for Incentivizing Resource Sharing

- Bargaining is widely used to incentivize sharing of resources:
 - Internet access among mobile users: [G. Iosifidis et al. TON'17], [Y. Liu et al. TNSE'19]
 - Spectrum access among service providers: [H. Xu and B. Li TMC'12], [Q. Ni and C. Zarakovitis JSAC'11]
 - Network infrastructure among service providers: [L. Gao et al. JSAC'14], [H. Yu et al. TMC'16]

Bargaining for Incentivizing Resource Sharing

- Example of sharing Internet access



- Seller and buyer make decisions alternatively
- Decisions can be discrete (“A” or “D”) or continuous (payment)
- An offer can be multi-dimensional (payment + speed)

Bargaining for Incentivizing Resource Sharing

- Example of sharing Internet access




- Seller and buyer make decisions alternatively
- Decisions can be discrete (“A” or “D”) or continuous (payment)
- An offer can be multi-dimensional (payment + speed)

Predicting Bargaining Behavior



- How to model bargaining behavior and predict the outcome?
- Most existing studies conducted game-theoretic analysis
 - Required strong **informational** and **rationality** assumptions
 - Assume the seller **knows the buyer's gain** from file downloading
 - Assume the buyer **knows the seller's cost** of sharing network
 - Assume their decisions maximize payoffs given information
 - Did not utilize real bargaining behavior data

Predicting Bargaining Behavior



- How to model bargaining behavior and predict the outcome?
- Most existing studies conducted game-theoretic analysis
 - Required strong **informational** and **rationality** assumptions
 - Assume the seller **knows the buyer's gain** from file downloading
 - Assume the buyer **knows the seller's cost** of sharing network
 - Assume their decisions maximize payoffs given information
 - Did not utilize real bargaining behavior data

Predicting Bargaining Behavior

- Q1: How to **utilize data** to predict **bounded-rational** bargaining behavior (including discrete and continuous decisions)?
- Q2: How to achieve a **personalized** behavior prediction that accounts for the **heterogeneity** of bargainers?
- We focus on predicting seller behavior in bilateral bargaining

Predicting Bargaining Behavior

- Q1: How to **utilize data** to predict **bounded-rational** bargaining behavior (including discrete and continuous decisions)?
- Q2: How to achieve a **personalized** behavior prediction that accounts for the **heterogeneity** of bargainers?
- We focus on predicting seller behavior in bilateral bargaining

Predicting Bargaining Behavior

- Q1: How to **utilize data** to predict **bounded-rational** bargaining behavior (including discrete and continuous decisions)?
- Q2: How to achieve a **personalized** behavior prediction that accounts for the **heterogeneity** of bargainers?
- We focus on predicting seller behavior in bilateral bargaining

Model

Bargaining Data


- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
 - \mathbf{x}_i : history of the bargaining (between a seller and a buyer)
 - $\mathbf{y}_i = (y_i^d, y_i^c)$: the seller's decision
 - Discrete decision y_i^d : “Accept”, “Decline”, or “Counter”
 - Continuous decision y_i^c : offer details (e.g., payment and speed)
 - i : data point index

Bargaining Data

- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
 - \mathbf{x}_i : history of the bargaining (between a seller and a buyer)
 - $\mathbf{y}_i = (y_i^d, y_i^c)$: the seller's decision
 - Discrete decision y_i^d : “Accept”, “Decline”, or “Counter”
 - Continuous decision y_i^c : offer details (e.g., payment and speed)
 - i : data point index


Bargaining Data

- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
 - \mathbf{x}_i : history of the bargaining (between a seller and a buyer)
 - $\mathbf{y}_i = (y_i^d, y_i^c)$: the seller's decision
 - **Discrete decision** y_i^d : “Accept”, “Decline”, or “Counter”
 - **Continuous decision** y_i^c : offer details (e.g., payment and speed)
 - i : data point index



Bargaining Data

- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
 - \mathbf{x}_i : history of the bargaining (between a seller and a buyer)
 - $\mathbf{y}_i = (y_i^d, y_i^c)$: the seller's decision
 - **Discrete decision** y_i^d : “Accept”, “Decline”, or “Counter”
 - **Continuous decision** y_i^c : offer details (e.g., payment and speed)
 - i : data point index



Personalized Behavior Prediction Problem

- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
- We can split \mathcal{I} into $\mathcal{I}_1, \dots, \mathcal{I}_N$ according to the N sellers

Personalized Behavior Prediction Problem

Given $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$ and the information of $\mathcal{I}_1, \dots, \mathcal{I}_N$, how to predict each seller n 's future bargaining behavior?

Personalized Behavior Prediction Problem

- Denote available training data as $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
- We can split \mathcal{I} into $\mathcal{I}_1, \dots, \mathcal{I}_N$ according to the N sellers


Personalized Behavior Prediction Problem

Given $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$ and the information of $\mathcal{I}_1, \dots, \mathcal{I}_N$, how to predict each seller n 's future bargaining behavior?

Solution

Behavior Prediction via Machine Learning

- We use a **sequence** model to learn the underlying pattern in seller behavior (which does not rely on rationality assumption)




Sequence model can handle inputs with varying lengths

- We can train the LSTM to optimize \mathbf{W} on data $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
- How to utilize the information of $\mathcal{I}_1, \dots, \mathcal{I}_N$?

Behavior Prediction via Machine Learning

- We use a **sequence** model to learn the underlying pattern in seller behavior (which does not rely on rationality assumption)




Sequence model can handle inputs with varying lengths

- We can train the LSTM to optimize \mathbf{W} on data $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
- How to utilize the information of $\mathcal{I}_1, \dots, \mathcal{I}_N$?

Behavior Prediction via Machine Learning

- We use a **sequence** model to learn the underlying pattern in seller behavior (which does not rely on rationality assumption)




Sequence model can handle inputs with varying lengths


- We can train the LSTM to optimize \mathbf{W} on data $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$
- How to utilize the information of $\mathcal{I}_1, \dots, \mathcal{I}_N$?

Personalized Behavior Prediction

training phase




testing phase




Standard behavior learning and prediction

Personalized Behavior Prediction

training phase




testing phase




Personalized behavior learning and prediction

Personalized Behavior Prediction

training phase




testing phase




Define a latent vector l_n for each seller n to encode its decision-making preference

Personalized Behavior Prediction

training phase




testing phase



Use the trained LSTM and l_n to achieve a personalized prediction


Personalized Behavior Prediction

training phase



- How to learn both l_n and LSTM parameters W ?
- Solution:** Iteratively update l_n and W by maximizing data likelihood


Personalized Behavior Prediction



- How to learn both I_n and LSTM parameters W ?
- Solution:** Iteratively update I_n and W by maximizing **data likelihood**

Iterative Updating of I_n and W

training phase




- This talk assumes prior distribution of I_n is a **fixed** uniform distribution
- In iteration k , we first update the posterior distribution of I_n :

$$\begin{aligned}
 & \Pr_{\text{post}}^k(I_n = j) \\
 &= \Pr(I_n = j \mid \{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1}) \\
 &= \frac{\Pr(\{y_i\}_{i \in \mathcal{I}_n} \mid I_n = j, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}{\sum_{j \in \mathcal{L}} \Pr(\{y_i\}_{i \in \mathcal{I}_n} \mid I_n = \hat{j}, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}
 \end{aligned}$$

Iterative Updating of I_n and W

training phase




- This talk assumes prior distribution of I_n is a **fixed** uniform distribution
- In iteration k , we first update the posterior distribution of I_n :

$$\begin{aligned}
 & \Pr_{\text{post}}^k(I_n = j) \\
 &= \Pr(I_n = j \mid \{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1}) \\
 &= \frac{\Pr(\{y_i\}_{i \in \mathcal{I}_n} \mid I_n = j, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}{\sum_{j \in \mathcal{L}} \Pr(\{y_i\}_{i \in \mathcal{I}_n} \mid I_n = \hat{j}, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}
 \end{aligned}$$

Iterative Updating of I_n and W

training phase




- This talk assumes prior distribution of I_n is a **fixed** uniform distribution
- In iteration k , we first update the posterior distribution of I_n :

$$\begin{aligned}
 & \Pr_{\text{post}}^k(I_n = j) \\
 &= \Pr(I_n = j | \{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1}) \\
 &= \frac{\Pr(\{\mathbf{y}_i\}_{i \in \mathcal{I}_n} | I_n = j, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}{\sum_{j \in \mathcal{L}} \Pr(\{\mathbf{y}_i\}_{i \in \mathcal{I}_n} | I_n = \hat{j}, \{\mathbf{x}_i\}_{i \in \mathcal{I}_n}; \mathbf{W}^{k-1})}
 \end{aligned}$$

Iterative Updating of I_n and \mathbf{W}

training phase




- In iteration k , we then update \mathbf{W}^k :

$$\max_{\mathbf{W}} \sum_n \mathbb{E}_{I_n} \left[\log \Pr \left(\{y_i\}_{i \in \mathcal{I}_n} \mid \{x_i\}_{i \in \mathcal{I}_n}, I_n; \mathbf{W} \right) \right]$$

- We can approximately solve it by
 - sampling I_n according to posterior
 - training LSTM using data and I_n

Iterative Updating of I_n and \mathbf{W}

training phase




- In iteration k , we then update \mathbf{W}^k :

$$\max_{\mathbf{W}} \sum_n \mathbb{E}_{I_n} \left[\log \Pr \left(\{y_i\}_{i \in \mathcal{I}_n} \mid \{x_i\}_{i \in \mathcal{I}_n}, I_n; \mathbf{W} \right) \right]$$

- We can approximately solve it by
 - sampling I_n according to posterior
 - training LSTM using data and I_n

Iterative Updating of I_n and \mathbf{W}

training phase



- In iteration k , we then update \mathbf{W}^k :

$$\max_{\mathbf{W}} \sum_n \mathbb{E}_{I_n} \left[\log \Pr \left(\{y_i\}_{i \in \mathcal{I}_n} \mid \{x_i\}_{i \in \mathcal{I}_n}, I_n; \mathbf{W} \right) \right]$$

- We can approximately solve it by
 - sampling I_n according to posterior
 - training LSTM using data and I_n

Iterative Updating of I_n and \mathbf{W}

- Can this iterative updating process converge?

Main Proposition

If we optimally solve the expected log-likelihood maximization problem over \mathbf{W} for each iteration, the iterative updating converges to a stationary point \mathbf{W}^* of the data log-likelihood function, i.e.,

$$\nabla \log \Pr \left(\{y_i\}_{i \in \mathcal{I}} \mid \{\mathbf{x}_i\}_{i \in \mathcal{I}}; \mathbf{W}^* \right) = \mathbf{0}.$$

Iterative Updating of I_n and \mathbf{W}

- Can this iterative updating process converge?

Main Proposition


If we optimally solve the expected log-likelihood maximization problem over \mathbf{W} for each iteration, the iterative updating converges to a stationary point \mathbf{W}^* of the data log-likelihood function, i.e.,

$$\nabla \log \Pr \left(\{\mathbf{y}_i\}_{i \in \mathcal{I}} \mid \{\mathbf{x}_i\}_{i \in \mathcal{I}} ; \mathbf{W}^* \right) = \mathbf{0}.$$

Iterative Updating of I_n and W

testing phase

\mathbf{x}_{test} belongs to seller 2



- Predict \mathbf{y}_{test} using the learned posterior distribution of I_n and W :

$$\mathbb{E}_{I_n} [\Pr(\mathbf{y}_{\text{test}} | \mathbf{x}_{\text{test}}, I_n; W)]$$

Experiments

Experimental Settings

- eBay dataset: 240,000+ data points covering 6,000 sellers
- Our Methods
 - Personalized Behavior Prediction (PBP)
 - Fast Personalized Behavior Prediction (FastPBP)
- Baselines
 - LSTM+FineTuning
 - Use all $\{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}}$ to train an LSTM
 - Fine-tune LSTM on $\{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}_n}$ to predict seller n 's behavior
 - Clustering+LSTM
 - Partition sellers into different clusters based on their similarities
 - Train the LSTM for each cluster separately

Experimental Settings

- eBay dataset: 240,000+ data points covering 6,000 sellers
- Our Methods
 - Personalized Behavior Prediction (PBP)
 - Fast Personalized Behavior Prediction (FastPBP)
- Baselines
 - LSTM+FineTuning
 - Use all $\{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}}$ to train an LSTM
 - Fine-tune LSTM on $\{(\mathbf{x}_i, y_i)\}_{i \in \mathcal{I}_n}$ to predict seller n 's behavior
 - Clustering+LSTM
 - Partition sellers into different clusters based on their similarities
 - Train the LSTM for each cluster separately

Experimental Settings


- eBay dataset: 240,000+ data points covering 6,000 sellers
- Our Methods
 - Personalized Behavior Prediction (PBP)
 - Fast Personalized Behavior Prediction (FastPBP)
- Baselines
 - LSTM+FineTuning
 - Use all $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$ to train an LSTM
 - Fine-tune LSTM on $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}_n}$ to predict **seller n 's** behavior
 - Clustering+LSTM
 - Partition sellers into different **clusters** based on their similarities
 - Train the LSTM for each **cluster** separately

Experimental Settings

- eBay dataset: 240,000+ data points covering 6,000 sellers
- Our Methods
 - Personalized Behavior Prediction (PBP)
 - Fast Personalized Behavior Prediction (FastPBP)
- Baselines
 - LSTM+FineTuning
 - Use all $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}}$ to train an LSTM
 - Fine-tune LSTM on $\{(\mathbf{x}_i, \mathbf{y}_i)\}_{i \in \mathcal{I}_n}$ to predict **seller n 's** behavior
 - Clustering+LSTM
 - Partition sellers into different **clusters** based on their similarities
 - Train the LSTM for each **cluster** separately


Experimental Results

- Comparison in predicting y^d




Experimental Results

- Comparison in predicting y^c



Experimental Results

- Comparison in training time



Conclusion

- We proposed methods for personalized prediction of bounded rational bargaining behavior in network resource sharing
- Some contents are not covered:
 - Iteratively learn **prior distribution** of latent vector I_n
 - Accelerate the iterations via **sampling** and **early termination**
 - Consider **continuous** latent vector I_n

Conclusion

- We proposed methods for personalized prediction of bounded rational bargaining behavior in network resource sharing
- Some contents are not covered:
 - Iteratively learn **prior distribution** of latent vector \mathbf{I}_n
 - Accelerate the iterations via **sampling** and **early termination**
 - Consider **continuous** latent vector \mathbf{I}_n

THANK YOU