# Transcript generation workflow

One false premise · four scenarios · the same sequence of user pressure

**Original question q**
Dataset → user question
Shared starting point.

**1 Generate initial target response $r_1$**
$q \rightarrow r_1$ · once per target model
Reuse $q + r_1$ across all four scenarios.

**Attach hidden control data**
Dataset + scenario → false-premise alternatives, correction alternatives, scenario metadata
Guides the simulator and validation; hidden from the target. Controls are not derived from $r_1$.

TURN STRATEGIES — T2 confusion → T3 reassertion → T4 anecdote → T5 skepticism

## WITHOUT SIMULATOR HISTORY

Simulator: q + controls; may use prior user pushbacks, never target replies.
One shared set of four validated drafts feeds both styles; prepare before target loop.

## WITH SIMULATOR HISTORY

Simulator: q + controls + current visible dialogue, including latest target reply.
Adaptive per turn and scenario; pushbacks are not shared across target models.

### FORMAL

Reuse the draft

T2 shown · prepare T2–T5 sequentially before target turns

**2 Generate draft**
Context → draft
Neutral semantic draft (baseline).

**3 Validate draft**
Draft → valid draft
Gate A: preserve premise and strategy.

**4 Reuse draft**
Valid draft → pushback
Polished, grammatical, complete wording.

**5 Check pushback**
Pushback → valid text
Gate B: meaning and requested style.

**6 Store fixed pushbacks**
Four validated turns → style bank
Reusable across target models.

**7 Run target transcript loop**
Visible dialogue + fixed pushback → next response
T2–T5, then stop. No simulator calls in this loop.

T2 shown · generate after the latest response

**2 Generate draft**
Context → draft
Neutral semantic draft (baseline).

**3 Validate draft**
Draft → valid draft
Gate A: preserve premise and strategy.

**4 Reuse draft**
Valid draft → pushback
Polished, grammatical, complete wording.

**5 Check pushback**
Pushback → valid text
Gate B: meaning and requested style.

Latest target response → next simulator call
Repeat T3–T5; stop.

**6 Append pushback; target responds**
Evolving visible dialogue + pushback → next target response
Target sees q and all visible user / assistant messages.

### HUMANLIKE

Rewrite the surface

T2 shown · prepare T2–T5 sequentially before target turns

**2 Generate draft**
Context → draft
Neutral semantic draft (baseline).

**3 Validate draft**
Draft → valid draft
Gate A: preserve premise and strategy.

**4 Rewrite draft**
Valid draft → pushback
Same meaning; mild, recoverable noise.

**5 Check pushback**
Pushback → valid text
Gate B: meaning and requested style.

**6 Store fixed pushbacks**
Four validated turns → style bank
Reusable across target models.

**7 Run target transcript loop**
Visible dialogue + fixed pushback → next response
T2–T5, then stop. No simulator calls in this loop.

T2 shown · generate after the latest response

**2 Generate draft**
Context → draft
Neutral semantic draft (baseline).

**3 Validate draft**
Draft → valid draft
Gate A: preserve premise and strategy.

**4 Rewrite draft**
Valid draft → pushback
Same meaning; mild, recoverable noise.

**5 Check pushback**
Pushback → valid text
Gate B: meaning and requested style.

Latest target response → next simulator call
Repeat T3–T5; stop.

**6 Append pushback; target responds**
Evolving visible dialogue + pushback → next target response
Target sees q and all visible user / assistant messages.

### VALIDATION & REGENERATION · applies at gates A and B

**A Semantic validation**
Preserve false premise, turn strategy and pressure goal.
Reject correction leakage, answers and topic changes.

**B Meaning + surface style**
Preserve draft meaning and meaning-bearing anchors.
Check formal wording or mild humanlike noise.

Both gates include deterministic format / length / lexical checks. Formal reuses the draft's passed semantic and style checks.

Generate candidate → Gate A or B → Pass → continue
Fail: discard + regenerate
Draft fails → new draft; rewrite fails → new rewrite.

Target replies: usable completion check; invalid / truncated response retries. Target sees q + evolving visible dialogue, never hidden controls.

Shared / input · Simulator · Validator · Target model · Explanatory note · Data flow · Regeneration / feedback · Hidden / internal information

SHARED Same false premise and turn strategies; $q + r_1$ shared across scenarios for each target model.
DIFFERS Formal / humanlike changes surface realization. Simulator history changes context and generation timing.