Transcript generation workflow

Same false premise and turn strategies · two history conditions · style branches only at realization

Original question q
Dataset → user question
Shared starting point.

1 Initial target response r_1
$q \rightarrow r_1$ · generated once per target model
Reuse $q + r_1$ across all four scenarios.

Attach hidden control data
Dataset + scenario → false-premise alternatives, correction alternatives, scenario metadata
Internal simulator / validation inputs; hidden from target. Controls do not come from r_1.

TURN STRATEGIES — T2 confusion → T3 reassertion → T4 anecdote → T5 skepticism

WITHOUT SIMULATOR HISTORY

Simulator sees: q + controls; may use earlier generated user pushbacks.
Earlier target responses are never simulator input.

BEFORE TARGET LOOP · first prepare all four validated drafts, then both styles

INTERNAL · simulator + validation · T2 shown; use the same path for T3–T5

2 Generate neutral semantic draft (baseline)
Simulator context + turn strategy → draft
Capture the false premise, turn strategy and pressure goal.

3 Check draft · Gate A
Draft → validated neutral semantic draft
Format / length / lexical checks + semantic validation.
Keep premise, strategy and pressure goal.
Reject correction leakage, answers and topic changes.

4 FORMAL · reuse draft
Validated draft → formal pushback
Polished, grammatical, complete wording.
Reuse the draft without rewriting.

4 HUMANLIKE · rewrite draft
Validated draft → humanlike pushback
Add mild, recoverable surface noise.
Keep the same meaning and turn strategy.

5 Validate styled pushback · Gate B · separately per style
Styled pushback → text that passes meaning and requested-style checks
FORMAL: polished, grammatical, complete wording.
HUMANLIKE: mild, recoverable noise; protect meaning-bearing anchors.
Both preserve the draft's meaning and turn strategy; repeat format / length / lexical checks.
Conceptual gates: FORMAL reuses the draft's passed semantic and surface-style checks.

6 Store four fixed pushbacks per style
Validated T2 → T3 → T4 → T5 → one fixed bank per style
Both styles use one shared draft set. Reuse the fixed banks across target models.

7 Run the target transcript loop
Visible dialogue + next fixed pushback → next target response
Append each fixed pushback before responding. T2–T5; no simulator calls here.

WITH SIMULATOR HISTORY

Simulator sees: q + controls + current visible dialogue,
including the latest target response.

PER TURN · adaptive generation, separately for each scenario and target model

INTERNAL · simulator + validation · T2 shown; use the same path for T3–T5

2 Generate neutral semantic draft (baseline)
Simulator context + turn strategy → draft
Capture the false premise, turn strategy and pressure goal.

3 Check draft · Gate A
Draft → validated neutral semantic draft
Format / length / lexical checks + semantic validation.
Keep premise, strategy and pressure goal.
Reject correction leakage, answers and topic changes.

4 FORMAL · reuse draft
Validated draft → formal pushback
Polished, grammatical, complete wording.
Reuse the draft without rewriting.

4 HUMANLIKE · rewrite draft
Validated draft → humanlike pushback
Add mild, recoverable surface noise.
Keep the same meaning and turn strategy.

5 Validate styled pushback · Gate B · separately per style
Styled pushback → text that passes meaning and requested-style checks
FORMAL: polished, grammatical, complete wording.
HUMANLIKE: mild, recoverable noise; protect meaning-bearing anchors.
Both preserve the draft's meaning and turn strategy; repeat format / length / lexical checks.
Conceptual gates: FORMAL reuses the draft's passed semantic and surface-style checks.

6 Append validated pushback to the visible transcript
Current dialogue + validated pushback → next target input
Adaptive per turn; pushbacks are not shared across target models.

7 Generate the next target response
q + evolving visible dialogue → next target response
Latest reply becomes simulator context; continue through T5, then stop.

Latest reply → next turn T3–T5; stop.

VALIDATION & REGENERATION · reusable at gates A and B

Failed candidates are discarded and regenerated.
Draft fails → new draft. Humanlike rewrite fails → new rewrite of the valid draft.

Generate candidate → Gate A or B → Pass → continue
Fail → discard + regenerate

TARGET VISIBLE q + all visible user / assistant messages; never hidden controls. Replies: usable completion check; invalid / truncated responses retry.

Shared / input · Simulator · Validator · Target model · Explanatory note · Data flow · Regeneration / feedback · Hidden / internal information

SHARED Same false premise and turn strategies; $q + r_1$ reused across scenarios for each target model.
DIFFERS FORMAL / HUMANLIKE changes surface realization. Simulator history changes context and generation timing.