

IE 522 HW07

Q1

10 Points

The file ZMTSLA.csv contains daily prices of ZM. Compute ZM's daily log returns. Assume that ZM's daily log returns are i.i.d. Assume that one trading day equals $t = 1/252$ year.

Q1.1

1 Point

Fit a Black-Scholes-Merton model to ZM's daily log returns. Report the MLEs for μ , σ and the corresponding value of the log likelihood function.

[Choose Files](#) No file chosen


BSM_mu = 1.3340069

BSM_sigma = 0.7362867

loglikelihoodBSM = 588.0812

CURRENTLY UPLOADED FILES

▸ Q1-1.R

[Download](#) [Remove](#) Please select file(s)

Select file(s)

[Save Answer](#)Last saved on **Oct 13 at 1:43 AM**

Q1.2


1 Point

Fit a NIG model to ZM's daily log returns. Report the MLEs for α , β , δ , μ and the corresponding value of the log likelihood function.

```
(NIGalpha, NIGbeta, NIGdelta, NIGmu, loglikelihoodNIG) =  
(16.4540784598237, 2.34990357077191, 8.50804955093113, 0.106341984286513,  
627.465930520146)
```

CURRENTLY UPLOADED FILES

▶ Q1-2.R

[Download](#) [Remove](#) Please select file(s)[Select file\(s\)](#)[Save Answer](#)Last saved on **Oct 13 at 1:43 AM**[Choose Files](#)

No file chosen

Q1.3



1 Point

Compute the sample mean, variance, skewness and kurtosis of ZM's daily log returns.

```
(logrt_ZM_mu, logrt_ZM_Var, logrt_ZM_Skew, logrt_ZM_kurt) =  
(0.00529367809296, 0.00215731473159484, 1.19896749416696, 11.7050223772246)
```

CURRENTLY UPLOADED FILES

▸ Q1-3.R

 Download  Remove

 Please select file(s)

Select file(s)

Save Answer

Last saved on **Oct 13 at 1:43 AM**

Q1.4



1 Point

Fit the NIG model using moment matching. Report the parameters you obtain.

alpha = 15.3997719, beta= 4.0914736, delta = 7.5013727, mu = -0.7332863

CURRENTLY UPLOADED FILES

▸ Q1-4.R

 Download  Remove

Choose Files

No file(s) chosen

Select file(s)

Save Answer

Last saved on **Oct 13 at 1:43 AM**

Q1.5

1 Point

What's the value of the log likelihood function when moment matching estimates are used? Do the moment matching estimates maximize the log likelihood function?

625.9847, does not reach the maximum log likelihood function.

CURRENTLY UPLOADED FILES

▶ Q1-5.R

Download Remove

Please select file(s)

Select file(s)

Save Answer

Last saved on Oct 13 at 1:43 AM

Q1.6

1 Point

\$counts in the output of the function optim in R reports the number of times the objective function is called and evaluated. Smaller counts mean faster convergence. In question 1.2, is the convergence faster if you use moment matching estimates as the initial value?

Yes, the outcome is smaller than that of 1.2.

Choose Files

No file chosen

CURRENTLY UPLOADED FILES

▼ Q1-6.R


Download Remove

```
1 #Q1-6
2 #Data Preparation
3 ZMTSLA = read.csv("/Users/yu-chingliao/Library/CloudStorage/GoogleDrive-
  josephliao0127@gmail.com/My Drive/Note/UIUC/Fall_2022/Statistical Methods in
  Finance/Assignment 06/ZMTSLA.csv")
4 m = nrow(ZMTSLA)
```

```

5 logrt_ZM = log(ZMTSLA$ZM[2:m]/ZMTSLA$ZM[1:m-1])
6 t = 1/252
7
8 library(moments)
9
10 #NIG Model_fitting
11 initialvalueNIG_star = MMestimates
12 NIG_star = function(x, theta)
13   {theta[1]*theta[3]*t/pi*besselK(theta[1]*sqrt(theta[3]^2*t^2+(x-theta[4]*t)^2),
14   1)/(sqrt(theta[3]^2*t^2+(x-theta[4]*t)^2))*exp(theta[3]*sqrt(theta[1]^2-
15   theta[2]^2)*t+theta[2]*(x-theta[4]*t))}
13 resultNIG_star = optim(initialvalueNIG_star, fn=function(theta){-
14   sum(log(NIG_star(logrt_ZM, theta)))}, method = "L-BFGS-B")
15 resultNIG_star

```

 Please select file(s)

Select file(s)

Save Answer

Last saved on **Oct 13 at 1:43 AM**

Q1.7

Choose Files

No file chosen

Fit the daily log returns using a Laplace distribution with density $p(x) = \frac{1}{2b}e^{-|x-\mu|/b}$, $b > 0$. Report the MLEs for μ and b and the corresponding value of the log likelihood function. In this problem, optim won't succeed unless the initial values are appropriately chosen. use moment matching (matching mean and standard deviation) to find good initial values that work.

mu = 0.002637152, b = 0.031774552 maximum log likelihood = 625.2951

CURRENTLY UPLOADED FILES

▼ Q1-7.R

[Download](#) [Remove](#)

```

1 #Q1-7
2 #Data Preparation
3 ZMTSLA = read.csv("/Users/yu-chingliao/Library/CloudStorage/GoogleDrive-
  josephliao0127@gmail.com/My Drive/Note/UIUC/Fall_2022/Statistical Methods in
  Finance/Assignment 06/ZMTSLA.csv")
4 m = nrow(ZMTSLA)
5 logrt_ZM = log(ZMTSLA$ZM[2:m]/ZMTSLA$ZM[1:m-1])
6 t = 1/252
7
8 library(moments)
9
10 #Moment Matching to generate the initial solution.
11 lap_mu = mean(logrt_ZM)
12 lap_b = sqrt((m-1)/(2*m))*sd(logrt_ZM)
13
14
15 #Laplace Model_fitting
16 initialvalueLaplace = c(lap_mu, lap_b)
17 Laplace = function(x, theta){exp(-abs(x-theta[1])/theta[2])/(2*theta[2])}
18 resultLaplace = optim(initialvalueLaplace, fn=function(theta){-
  sum(log(Laplace(logrt_ZM, theta)))}, method = "BFGS")

```


20

▼ Moment Matching Estimators for Laplace Dist. .png

[Download](#) [Remove](#)

$$\hat{\mu} = \bar{X}_n, \hat{b} = \frac{1}{\sqrt{2}} \sqrt{\frac{1}{n} \sum_{i=1}^n X_i^2 - \bar{X}_n^2} = \frac{1}{\sqrt{2}} \sqrt{\frac{1}{n} \sum_{i=1}^n (X_i - \bar{X}_n)^2} = \sqrt{\frac{n-1}{2n}} S_n,$$

 Please select file(s)

Select file(s)

Save Answer

Last saved on **Oct 14 at 6:41 PM**

Q1.8

1 Point

Derive and compute the theoretical maximum likelihood estimates for the Laplace distribution. Are they close to what you get in problem 1.7? Is the value of the log likelihood the same (to 4 digits after the decimal point)? It's okay for you to search online for this question.

```
T_lap_mu = median(logrt_ZM)
T_lap_b = mean(abs(logrt_ZM - T_lap_mu))
```

theoretical mean = 0.002542841, theoretical b = 0.031758523, it is somewhat close to 1.7.
log-likelihood is 625.2951, which is same as 1.7.

CURRENTLY UPLOADED FILES

Choose Files

No file chosen

 Download  Remove



```
1 #Q1-8
2 #Data Preparation
3 ZMTSLA = read.csv("/Users/yu-chingliao/Library/CloudStorage/GoogleDrive-
  josephliao0127@gmail.com/My Drive/Note/UIUC/Fall_2022/Statistical Methods in
  Finance/Assignment 06/ZMTSLA.csv")
4 m = nrow(ZMTSLA)
5 logrt_ZM = log(ZMTSLA$ZM[2:m]/ZMTSLA$ZM[1:m-1])
6 t = 1/252
7
8 library(moments)
9
```

```

10 T_lap_mu = median(logrt_ZM)
11 T_lap_b = mean(abs(logrt_ZM - T_lap_mu))
12 theoretical = c(T_lap_mu, T_lap_b)
13 theoretical
14
15 loglikelihoodLaplace = sum(log(Laplace(logrt_ZM, theoretical)))
16 loglikelihoodLaplace
17

```

▼ Theoretical Estimators for Laplace Dist..png


 Download  Remove

Given n independent and identically distributed samples x_1, x_2, \dots, x_n , the [maximum likelihood](#) (MLE) estimator of μ is the sample [median](#),^[4]

$$\hat{\mu} = \text{med}(x).$$

The MLE estimator of b is the [mean absolute deviation](#) from the median,^[citation needed]

$$\hat{b} = \frac{1}{N} \sum_{i=1}^n |x_i - \hat{\mu}|.$$

 Please select file(s)

Select file(s)

Save Answer

Last saved on **Oct 14 at 6:40 PM**

Choose Files

No file chosen

Q1.9

1 Point

Compute AIC for all three cases. In terms of AIC, which model is fitting the data the best?

(AIC_BSM, AIC_NIG, AIC_Laplace) =
 (-1172.16237122154 -1246.93186104029 -1246.5901445823)
 the NIG provide the best estimation.

CURRENTLY UPLOADED FILES

▼ Q1-9.R

[Download](#) [Remove](#)

```
1 #Q1-9
2 #Data Preparation
3 ZMTSLA = read.csv("/Users/yu-chingliao/Library/CloudStorage/GoogleDrive-
  josephliao0127@gmail.com/My Drive/Note/UIUC/Fall_2022/Statistical Methods in
  Finance/Assignment 06/ZMTSLA.csv")
4 m = nrow(ZMTSLA)
5 logrt_ZM = log(ZMTSLA$ZM[2:m]/ZMTSLA$ZM[1:m-1])
6 t = 1/252
7
8 library(moments)
9
10 AIC_BSM = -2*(-resultBSM$value-2)
11 AIC_NIG = -2*(-resultNIG$value-4)
12 AIC_Laplace= -2*(-resultLaplace$value-2)
13
14 print(paste(AIC_BSM, AIC_NIG, AIC_Laplace))
15
16
```

 Please select file(s)

Last saved on Oct 13 at 7:09 PM

No file chosen

Q1.10


1 Point

Construct the histogram (density) of ZM's daily log returns, and add your BSM, NIG, Laplace fits to the histogram. Graphically, which model provides the worst fit?

BSM provides the worst fit.

CURRENTLY UPLOADED FILES

▼ Q1-10.png


[Download](#) [Remove](#)

▼ Q1-10.R

[Download](#) [Remove](#)

```
1 #Q1-10
2 #Data Preparation
3 ZMTSLA = read.csv("/Users/yu-chingliao/Library/CloudStorage/GoogleDrive-
  josephliao0127@gmail.com/My Drive/Note/UIUC/Fall_2022/Statistical Methods in
  Finance/Assignment 06/ZMTSLA.csv")
4 m = nrow(ZMTSLA)
5 logrt_ZM = log(ZMTSLA$ZM[2:m]/ZMTSLA$ZM[1:m-1])
6 t = 1/252
7
```

```
8 library(moments)
9
10 hist(logrt_ZM, breaks = 30, prob = TRUE, ylim = c(0, 16))
11 thetaNIG = resultNIG$par
12 thetaBSM = resultBSM$par
13 thetaLaplace = resultLaplace$par
14
15 curve(NIG(x, thetaNIG), add = TRUE, col = "blue", lwd = 2, lty = 2)
16 curve(BSM(x, thetaBSM), add = TRUE, col = "red", lwd = 2, lty = 1)
17 curve(Laplace(x, thetaLaplace), add = TRUE, col = "black", lwd = 2, lty = 1)
18
19
```

 Please select file(s)

Select file(s)

Save Answer

Last saved on **Oct 13 at 1:43 AM**

Save All Answers

Submit & View Submission >