AI INFRASTRUCTURE / TECHNICAL REPORT

Candidate-Conditioned Teacher Scoring

Systems context, probability contract, prior art and evaluation design

---

Author	Jiacheng Yu

Edition	29 October 2026; English
Document status	Author reviewed the c1ab1f4 report; AI assisted
Research status	Technical hypothesis under review; no project optimization implemented
Measurements	At the reviewed snapshot, CPU numerical, gradient, GPU, HTTP and training experiments not run

Scope. This report studies a possible per-position candidate scoring contract for teacher inference. It records upstream behavior and mathematical limitations, not a measured speedup or a novel kernel claim. Experimental-status statements describe the reviewed c1ab1f4 snapshot; subsequent results are recorded separately.

The reported code observations refer to frozen upstream revisions. Third-party results are not project measurements.

Abstract

A post-training consumer may request teacher scores for different token sets at different causal positions. Whether a compact, candidate-conditioned path is useful depends on the consumer's exact loss, existing API semantics, causal alignment, and end-to-end costs. SGLang already offers per-item scoring and position selection; an open branch-specific pull request implements per-position IDs with full-vocabulary normalization. vLLM has merged a per-row interface, and IndexedLogits supplies an existing selected-logit primitive. Conditional reverse KL is not full-vocabulary KL, and the inspected Rethinking OPD implementation is not a drop-in consumer of conditional-only scores. These observations narrow rather than establish the potential contribution. No project numerical, GPU, service or training result was available at the reviewed snapshot.

Contents

1 Problem and research boundary **2**

2 Prior work and source snapshots **2**

3 Mathematical contract **2**

4 Consumer and causal alignment **3**

5 Architecture and potential change **3**

6 Analytical cost model **3**

7 Evaluation design **5**

8 Limitations and decision criteria **5**

9 Document reproduction **6**

1 Problem and research boundary

On-policy distillation (OPD) can require teacher information on a student's trajectory. A sampled-token objective, teacher-top-k loss, and student-top-k conditional objective require different outputs. The request for student-top-k renormalized reverse KL in verl is a concrete demand signal, not evidence that every training system needs this contract.[13–15]

Let R be the number of selected causal rows and C_t the candidate IDs for row t. An API forced to use the union $U = \bigcup_t C_t$ may return $R|U|$ scores instead of $\sum_t |C_t|$. With uniform K and little overlap, $|U| \leq \min(V, RK)$. This is an output-count model for that particular interface, not a measured byte reduction or a claim about every SGLang route.

Position selection, per-row candidate selection and normalization are separate concerns. Reducing returned scores alone does not establish reduced projection work; selected logits alone cannot reconstruct a full-vocabulary normalizer. A complete RL training benefit requires an actual, matched training measurement.

2 Prior work and source snapshots

At SGLang revision `4517a5ff1bbd1f944d6bde1819300ed14af7b698`, generic prefill logprob handling applies a request-level list across relevant rows. Its separate `/score` path accepts per-item label IDs and can renormalize over them; selected-position scoring also exists but still invokes dense readout. These are distinct mechanisms, so a blanket claim that SGLang lacks candidate or position selection would be false.[9–12]

As observed on 29 October 2026, SGLang PR #38119 is open against `sglang-miles`, not merged into the audited main revision, and preserves full-vocabulary normalization. vLLM PR #56984 was merged on 3 October 2026 and already implements a per-row candidate interface. Both are prior art.[8, 16]

OmniLens and its IndexedLogits implementation already calculate selected per-row logits without a full gathered-weight intermediate. The primitive is not claimed as an invention here. The related Subset-KL implementation has different support and KL direction; a shared primitive does not make objectives equivalent.[4–6]

Rethinking OPD studies student-top-k behavior, Sparse Logit Sampling studies a different distillation setting, and Tail-Aware Top-k OPD considers discarded probability mass. Their results are third-party observations and cannot be transferred as project benchmark results.[1–3]

3 Mathematical contract

For row t, let $h_t \in \mathbb{R}^d$, $W \in \mathbb{R}^{V \times d}$, $b \in \mathbb{R}^V$, and a nonempty set of unique IDs $C_t \subseteq \mathcal{V}$. An actual model may add scaling, softcaps or adaptation; those transformations must be preserved. The score definitions are:

$$z_{t,i} = h_t^{\mathsf{T}} W_i + b_i, \tag{1}$$

$$\ell_{t,i}^{\text{full}} = z_{t,i} - \text{LSE}_{j \in \mathcal{V}}\, z_{t,j}, \tag{2}$$

$$\ell_{t,i}^{C} = z_{t,i} - \text{LSE}_{j \in C_t}\, z_{t,j} = \ell_{t,i}^{\text{full}} - \log Q_t(C_t). \tag{3}$$

Here $Q_t(C_t)$ is teacher probability mass on the support. Exact full log-probabilities can be renormalized over C_t because the common full normalizer cancels. Conversely, omitted logits can change full probabilities while selected logits remain unchanged.

For fixed support C, positive temperatures τ_S, τ_T and a detached teacher, define student p^C and teacher q^C:

$$p_i^C = \frac{e^{z_i^S/\tau_S}}{\sum_{j\in C} e^{z_j^S/\tau_S}}, \qquad q_i^C = \frac{e^{z_i^T/\tau_T}}{\sum_{j\in C} e^{z_j^T/\tau_T}}, \tag{4}$$

$$L_C = \sum_{i\in C} p_i^C \log \frac{p_i^C}{q_i^C}, \tag{5}$$

$$\frac{\partial L_C}{\partial z_j^S} = \frac{p_j^C}{\tau_S}\left(\log \frac{p_j^C}{q_j^C} - L_C\right), \quad j \in C. \tag{6}$$

The derivative follows from the softmax Jacobian, $\partial p_i/\partial a_j = p_i(\mathbf{1}_{i=j} - p_j)$. Unselected local logits have zero derivative under fixed support. Candidate selection itself is discrete; ties and support changes are outside this local derivative. Tied input/output weights and nonlinear readout introduce additional gradient paths.

Let $\alpha = P(C)$ and $\beta = Q(C)$, both strictly between zero and one. The exact decomposition is:

$$D_{\mathrm{KL}}(P\|Q) = D_{\mathrm{Ber}}(\alpha\|\beta) + \alpha D_{\mathrm{KL}}(P^C\|Q^C) + (1-\alpha)D_{\mathrm{KL}}(P^{\bar{C}}\|Q^{\bar{C}}). \tag{7}$$

Conditional KL omits support-mass mismatch and tail structure. A concrete counterexample is:

$$P = (0.49, 0.49, 0.02), \quad Q = (0.005, 0.005, 0.99), \quad C = \{0, 1\}. \tag{8}$$

Both conditional distributions are $(1/2, 1/2)$, so conditional KL is zero, while full KL is positive. At $K = 1$ the conditional loss and local gradient are identically zero; at $K = V$ the conditional and full objectives coincide. These are analytical statements, not numerical test results.

4 Consumer and causal alignment

At Rethinking OPD author-code revision `ac26e38d6f1572eb027597b48a9f4e01f6915ef8`, the inspected route uses full-normalized student and teacher log-probabilities for a log-ratio reward, normalizes support weights, and applies detached advantages through a PPO surrogate. A conditional-only teacher output changes that reward; it is not a loss-preserving substitute. The observation describes current inspected code, not the historical provenance of a paper figure.[3, 7]

A practical integration must specify which policy generates C_t, when the IDs become available, tokenization and model revisions, and the next-token shift. Rollout-recorded support, a student prepass and reordered execution have different staleness and cost. At the reviewed snapshot, an actual consumer of the proposed direct conditional reverse KL had not been established.

5 Architecture and potential change

Figure 1 separates observed upstream operations, proposed components and existing prior art. A candidate branch would start before dense LM-head projection and provide an explicitly conditional output contract. A dense reference and any candidate implementation must agree on positions, ordered IDs, masks, normalization, transformations and error behavior. A full-normalized path remains distinct.

6 Analytical cost model

For uniform K, ignoring bias and other transformations, the approximate operation counts are $2RVd$ and $2RKd$. Effective time depends on achieved compute, memory traffic, launch, validation




Figure 1: Shared topology with English labels. Dashed proposed paths are not implemented.

and packing. If an optimizable part takes fraction f of a baseline request and is accelerated by factor s, Amdahl's relation gives the last expression:

$$F_{\text{dense}} \approx 2RVd, \qquad F_{\text{selected}} \approx 2RKd, \tag{9}$$

$$T \gtrsim \max(F/P_{\text{eff}}, B/\text{BW}_{\text{eff}}) + T_{\text{launch}} + T_{\text{validate}} + T_{\text{pack}}, \tag{10}$$

$$S_{\text{request}} = \frac{1}{(1-f) + f/s}. \tag{11}$$

A FLOP ratio is not a latency prediction: dense matrix multiplication can reuse weights efficiently, while irregular gathers can waste bandwidth and incur launches. Existing model weights generally remain resident. Candidate overlap, batching and shape can change the preferred implementation.

Analytical illustration only. With $R = 128$, $d = 1024$, $V = 131072$, $K = 32$ and two-byte elements, head weights occupy 256 MiB, dense logits 32 MiB, an eager gathered-weight tensor 8 MiB and selected logits 8 KiB. These are tensor-size identities, not measured peak GPU memory. At hypothetical $f = 0.1$, eliminating the affected part entirely bounds request speedup by 1/0.9; actual f is unknown.

7 Evaluation design

At the reviewed snapshot, all experiments below were proposed and **not run**. Compare a native full-normalized path only as context; for the same conditional contract compare dense projection plus gather, chunked dense, eager indexed gather and the existing IndexedLogits implementation when compatible. A future candidate must beat strong correct baselines on relevant workloads, rather than only the slowest baseline.

Start with CPU FP64 references for logits, normalization, loss and student gradients. Test $K = 1$, $K = V$, permutations, invalid or duplicate IDs, ragged rows, masks, omitted-logit changes and causal off-by-one cases. Declare tolerances and quantized input values before comparing implementations. Teacher values must be detached. Unsupported LoRA, quantization or tensor-parallel modes need explicit rejection or a semantics-preserving, measured fallback.

For performance, freeze hardware, driver, framework, model and tokenizer revisions, traces, dtype, masks, batching and timing boundaries. Include low/high candidate overlap, representative row counts and prompt lengths, feasible concurrency, and OOM/fallback cases. Establish stable A/A controls before randomized paired A/B blocks; preserve failures and negative outcomes. Measure kernel and complete HTTP request latency separately, including p50/p95, throughput, memory, payload bytes and error rates. Profile outside headline timing. A teacher-only replay is not a full training run.

8 Limitations and decision criteria

At the reviewed snapshot, the exact real consumer and any remaining gap relative to the cited APIs and kernels were unresolved. No project CPU numerical, gradient, GPU, HTTP or real training experiment had been performed. There was no evidence of project speedup, memory saving, training quality benefit or a novel selected-logit primitive. A gap is credible only with a concrete consumer, fixed semantics and a reproducible comparison against relevant existing paths. Record an inconclusive or negative result when those conditions fail.

The author reviewed both report editions at repository revision `c1ab1f4308c2ac1aecf47e222f210a16d0a5a898`. AI assisted the original draft. Substantive later technical revisions require a new author review. Its source survey is bounded to the cited snapshots, not an exhaustive novelty search. Upstream source and papers remain attributed to their authors; no third-party implementation is

vendored here. The inspected IndexedLogits repository did not declare a license in the reviewed files, so later reuse requires separate permission analysis.

9 Document reproduction

From the repository root, install XeLaTeX, BibTeX, Poppler, Python and Pillow, and use the bundled font subset as documented in the README. Run `bashscripts/build_assets.sh` and `python3scripts/verify_assets.py`. This rebuilds document assets only; it does not execute SGLang or benchmark the research hypothesis.

References

[1] Anshumann, Mohd Abbas Zaidi, Akhil Kedia, Jinwoo Ahn, Taehwak Kwon, Kangwook Lee, Haejun Lee, and Joohyung Lee. Sparse Logit Sampling: Accelerating Knowledge Distillation in LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar, editors, *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 18085–18108, Vienna, Austria, July 2025. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.885. URL `https://aclanthology.org/2025.acl-long.885/`.

[2] Huipeng Huang and Hongxin Wei. Tail-Aware Top-k On-Policy Distillation, 2026. URL `https://arxiv.org/abs/2608.14728v1`. Audited version 2608.14728v1; relevant methods and experimental sections read, not reproduced. Retrieved 2026-10-28.

[3] Yaxuan Li, Yuxin Zuo, Bingxiang He, Jinqian Zhang, Chaojun Xiao, Cheng Qian, Tianyu Yu, Huan-ang Gao, Wenkai Yang, Zhiyuan Liu, and Ning Ding. Rethinking On-Policy Distillation of Large Language Models: Phenomenology, Mechanism, and Recipe, 2026. URL `https://arxiv.org/abs/2604.13016v2`. Audited version 2604.13016v2; relevant methods and experimental sections read, not reproduced. Retrieved 2026-10-28.

[4] Jordan Pettyjohn. IndexedLogits: indexed selected-logit CUDA implementation, 2026. URL `https://github.com/pettyjohnjn/indexed_logits/tree/6020cb446cde8cb2b74a8fdf90db905a320936c3`. Source inspected 2026-10-28; no project runtime reproduction.

[5] Jordan Pettyjohn. Subset-KL: subset objective implementation, 2026. URL `https://github.com/pettyjohnjn/subset-kl/tree/69a813ce2233bdf243a39e7d76926ece8af76ed4`. Source inspected 2026-10-28; no project runtime reproduction.

[6] Jordan Pettyjohn, Mansi Sakarvadia, Nathaniel Hudson, Daniel McKenzie, Kyle Chard, and Ian Foster. Interpreting Language Model Hidden States at Scale, 2026. URL `https://arxiv.org/abs/2608.10260v1`. Audited version 2608.10260v1; relevant methods and experimental sections read, not reproduced. Retrieved 2026-10-28.

[7] Rethinking OPD contributors. Current author implementation: rewards and actor update contract, 2026. URL `https://github.com/Thinking-Space/Rethinking-OPD/tree/ac26e38d6f1572eb027597b48a9f4e01f6915ef8`. Source inspected 2026-10-28; no project runtime reproduction.

[8] SGLang contributors. PR 38119: Add sparse per-position requested-token scoring, 2026. URL `https://github.com/sgl-project/sglang/pull/38119`. Source inspected 2026-10-28; no project runtime reproduction.

[9] SGLang contributors. SGLang request data structures, 2026. URL https://github.com/sgl-project/sglang/blob/4517a5ff1bbd1f944d6bde1819300ed14af7b698/python/sglang/srt/managers/io_struct.py. Source inspected 2026-10-28; no project runtime reproduction.

[10] SGLang contributors. SGLang logits processor and LM-head dispatch, 2026. URL https://github.com/sgl-project/sglang/blob/4517a5ff1bbd1f944d6bde1819300ed14af7b698/python/sglang/srt/layers/logits_processor.py. Source inspected 2026-10-28; no project runtime reproduction.

[11] SGLang contributors. SGLang input logprob processing and requested-token gather, 2026. URL https://github.com/sgl-project/sglang/blob/4517a5ff1bbd1f944d6bde1819300ed14af7b698/python/sglang/srt/layers/logprob_processor.py. Source inspected 2026-10-28; no project runtime reproduction.

[12] SGLang contributors. SGLang scoring mixin: per-item labels and score normalization, 2026. URL https://github.com/sgl-project/sglang/blob/4517a5ff1bbd1f944d6bde1819300ed14af7b698/python/sglang/srt/managers/tokenizer_manager_score_mixin.py. Source inspected 2026-10-28; no project runtime reproduction.

[13] verl contributors. Issue 6676: Student-top-k renormalized reverse-KL OPD, 2026. URL https://github.com/verl-project/verl/issues/6676. Source inspected 2026-10-28; no project runtime reproduction.

[14] verl contributors. Distillation losses: supported objective families, 2026. URL https://github.com/verl-project/verl/blob/2ab35292039a51175a4b3d3b3b2d76e951a0d3e4/verl/trainer/distillation/losses.py. Source inspected 2026-10-28; no project runtime reproduction.

[15] verl contributors. Teacher manager: inference request contract, 2026. URL https://github.com/verl-project/verl/blob/2ab35292039a51175a4b3d3b3b2d76e951a0d3e4/verl/experimental/teacher_loop/teacher_manager.py. Source inspected 2026-10-28; no project runtime reproduction.

[16] vLLM contributors. PR 56984: Per-row candidate IDs for prefill token scoring, 2026. URL https://github.com/vllm-project/vllm/pull/56984. Source inspected 2026-10-28; no project runtime reproduction.